

RF Exposure Evaluation Report

Product : Wio RP2040 Module
Trade mark : Seeed Studio
Model/Type reference : WIORP2040-A
Serial Number : N/A
Report Number : EED32N80423302
FCC ID : Z4T-WIORP2040-A
Date of Issue : Jul. 13, 2021
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Test result : PASS

Prepared for:

Seeed Technology Co., Ltd.

**9F, G3 Building, TCL International E City, Zhongshanyuan Road,
Nanshan District, Shenzhen, Guangdong Province, P.R.C**

Prepared by:

Centre Testing International Group Co., Ltd.

**Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Vito He

Approved by:

David Wang

Reviewed by:

Aaron Ma

Date:

Jul. 13, 2021



Check No.:3143310521

2 Version

Version No.	Date	Description
00	Jul. 13, 2021	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Seeed Technology Co., Ltd.
Address of Applicant:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C
Manufacturer:	Seeed Technology Co., Ltd.
Address of Manufacturer:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C
Factory:	Shenzhen Xinxian Technology Co
Address of Factory:	Limited / F5, Building B17, Hengfeng Industrial City, No. 739 Zhoushi Rd, Baoan District, Shenzhen, Guangdong, P.R.C.

4.2 General Description of EUT

Product Name:	Wio RP2040 Module
Model No.:	WIORP2040-A
Test model:	WIORP2040-A
Trade Mark:	Seeed Studio
EUT Supports Radios application:	WIFI: 2412MHz~2462MHz

4.3 Product Specification subjective to this standard

Frequency Range:	WIFI: 2412MHz~2462MHz
Modulation Type:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM,QPSK,BPSK)
Test Power Grade:	Default
Test Software of EUT:	EspRFTTestTool_v2.6_Manual
Antenna Type:	PCB antenna
Antenna Gain:	-8.62dBi
Power Supply:	DC 5V
Max Conducted Peak Output Power:	11.62dBm The Max Conducted Peak Output Power data refer to the report EED32N80423301
Sample Received Date:	May. 31, 2021
Sample tested Date:	Jun. 16, 2021 to Jul. 07, 2021
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. N/A ¹⁾ The Product is powered battery. Model No.: WIORP2040-A	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

WIFI:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
1	2412	14.521	0.1374	20	0.0004	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32N80423301 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***