

Appendix B

Detailed Test Results

WIFI 2.4G for Back side
WIFI 2.4G for Next to the mouth
LTE Band 2 for Back side
LTE Band 2 for Next to the mouth
LTE Band 4 for Back side
LTE Band 4 for Next to the mouth
LTE Band 5 for Back side
LTE Band 5 for Next to the mouth
LTE Band 12 for Back side
LTE Band 12 for Next to the mouth
LTE Band 17 for Back side
LTE Band 17 for Next to the mouth
LTE Band 66 for Back side
LTE Band 66 for Next to the mouth



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-SAR Lab Date: 2024-11-07

NoveeWatch WIFI 2.4G 802.11b 1CH Back side 0mm

NoveeWatch

Communication System: WLAN 2.4GHz; Frequency: 2412.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 2412.000$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 39.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(7.95, 7.95, 7.95); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (72.0 mm x 72.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.24 W/kg; SAR (10g) = 0.582 W/kg;


Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm

Power Drift = -0.16 dB

SAR (1g) = 1.27 W/kg; SAR (10g) = 0.614 W/kg;

M2/M1 [%]=52.6

Dist 3dB Peak [mm]=10.2



SGS-SAR Lab Date: 2024-11-07

NoveeWatch WIFI 2.4G 802.11b 1CH Next to the mouth 10mm

NoveeWatch

Communication System: WLAN 2.4GHz; Frequency: 2412.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 2412.000$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 39.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(7.95, 7.95, 7.95); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (72.0 mm x 72.0 mm): Measurement Grid: 12.0 mm x 12.0 mm

SAR (1g) = 0.372 W/kg; SAR (10g) = 0.210 W/kg;


Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm

Power Drift = -0.15 dB

SAR (1g) = 0.365 W/kg; SAR (10g) = 0.213 W/kg;

M2/M1 [%]=57.5

Dist 3dB Peak [mm]=16.2



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 2 20M QPSK 1RB50 19100CH Back side 0mm

NoveeWatch

Communication System: Band 2; Frequency: 1900.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1900.000$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 38.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.51, 8.51, 8.51); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.57 W/kg; SAR (10g) = 0.865 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.07 dB

SAR (1g) = 1.49 W/kg; SAR (10g) = 0.817 W/kg;

M2/M1 [%]=61.0

Dist 3dB Peak [mm]=12.8



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 2 20M QPSK 1RB50 19100CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 2; Frequency: 1900.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1900.000$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 38.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.51, 8.51, 8.51); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.756 W/kg; SAR (10g) = 0.445 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.08 dB

SAR (1g) = 0.677 W/kg; SAR (10g) = 0.411 W/kg;

M2/M1 [%]=59.6

Dist 3dB Peak [mm]=18.2



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 4 20M QPSK 1RB50 20300CH Back side 0mm

NoveeWatch

Communication System: Band 4; Frequency: 1745.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1745.000$ MHz; $\sigma = 1.31$ S/m; $\epsilon_r = 39.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.85, 8.85, 8.85); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.57 W/kg; SAR (10g) = 0.898 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.00 dB

SAR (1g) = 1.78 W/kg; SAR (10g) = 0.982 W/kg;

M2/M1 [%]=62.1

Dist 3dB Peak [mm]=13.7



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 4 20M QPSK 1RB50 20300CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 4; Frequency: 1745.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1745.000$ MHz; $\sigma = 1.31$ S/m; $\epsilon_r = 39.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.85, 8.85, 8.85); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.787 W/kg; SAR (10g) = 0.457 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = 0.02 dB

SAR (1g) = 0.830 W/kg; SAR (10g) = 0.482 W/kg;

M2/M1 [%]=61.0

Dist 3dB Peak [mm]=14.4



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 5 10M QPSK 1RB25 20525CH Back side 0mm

NoveeWatch

Communication System: Band 5; Frequency: 836.500

Medium: Head Simulating Liquid. Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.910$ S/m; $\epsilon_r = 41.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.36, 10.36, 10.36); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.247 W/kg; SAR (10g) = 0.163 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = 0.15 dB

SAR (1g) = 0.310 W/kg; SAR (10g) = 0.147 W/kg;

M2/M1 [%]=36.9

Dist 3dB Peak [mm]=6.6



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 5 10M QPSK 1RB25 20525CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 5; Frequency: 836.500

Medium: Head Simulating Liquid. Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.910$ S/m; $\epsilon_r = 41.6$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.36, 10.36, 10.36); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.072 W/kg; SAR (10g) = 0.047 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.36 dB

SAR (1g) = 0.074 W/kg; SAR (10g) = 0.044 W/kg;

M2/M1 [%]=57.4

Dist 3dB Peak [mm]=14.4



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 12 10M QPSK 1RB49 23060CH Back side 0mm

NoveeWatch

Communication System: Band 12; Frequency: 704.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 704.000$ MHz; $\sigma = 0.887$ S/m; $\epsilon_r = 42.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.65, 10.65, 10.65); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.49 W/kg; SAR (10g) = 0.930 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = 0.02 dB

SAR (1g) = 1.56 W/kg; SAR (10g) = 0.760 W/kg;

M2/M1 [%]=29.8

Dist 3dB Peak [mm]=5.8



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 12 10M QPSK 1RB49 23060CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 12; Frequency: 704.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 704.000$ MHz; $\sigma = 0.887$ S/m; $\epsilon_r = 42.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.65, 10.65, 10.65); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.200 W/kg; SAR (10g) = 0.134 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.01 dB

SAR (1g) = 0.207 W/kg; SAR (10g) = 0.131 W/kg;

M2/M1 [%]=60.1

Dist 3dB Peak [mm]=18.3



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 17 10M QPSK 1RB0 23790CH Back side 0mm

NoveeWatch

Communication System: Band 17; Frequency: 710.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 710.000$ MHz; $\sigma = 0.887$ S/m; $\epsilon_r = 42.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.65, 10.65, 10.65); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.23 W/kg; SAR (10g) = 0.823 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.02 dB

SAR (1g) = 1.41 W/kg; SAR (10g) = 0.728 W/kg;

M2/M1 [%]=30.5

Dist 3dB Peak [mm]=8.0



SGS-SAR Lab Date: 2024-12-07

NoveeWatch LTE Band 17 10M QPSK 25RB13 23790CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 17; Frequency: 710.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 710.000$ MHz; $\sigma = 0.887$ S/m; $\epsilon_r = 42.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(10.65, 10.65, 10.65); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.176 W/kg; SAR (10g) = 0.117 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.14 dB

SAR (1g) = 0.183 W/kg; SAR (10g) = 0.115 W/kg;

M2/M1 [%]=61.1

Dist 3dB Peak [mm]=18.3



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 66 20M QPSK 1RB0 132072CH Back side 0mm

NoveeWatch

Communication System: Band 66; Frequency: 1720.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1720.000$ MHz; $\sigma = 1.28$ S/m; $\epsilon_r = 39.3$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.85, 8.85, 8.85); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 1.68 W/kg; SAR (10g) = 0.967 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.02 dB

SAR (1g) = 1.85 W/kg; SAR (10g) = 1.04 W/kg;

M2/M1 [%]=62.4

Dist 3dB Peak [mm]=14.5



SGS-SAR Lab Date: 2024-12-23

NoveeWatch LTE Band 66 20M QPSK 1RB0 132072CH Next to the mouth 10mm

NoveeWatch

Communication System: Band 66; Frequency: 1720.000

Medium: Head Simulating Liquid. Medium parameters used: $f = 1720.000$ MHz; $\sigma = 1.28$ S/m; $\epsilon_r = 39.3$

DASY8 Configuration:

- Probe: EX3DV4 - SN7636; ConvF(8.85, 8.85, 8.85); Calibrated: 2024-07-17
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1803; Calibrated: 2024-08-08
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2156
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (75.0 mm x 75.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.986 W/kg; SAR (10g) = 0.569 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm

Power Drift = -0.06 dB

SAR (1g) = 1.02 W/kg; SAR (10g) = 0.593 W/kg;

M2/M1 [%]=60.4

Dist 3dB Peak [mm]=14.4

