



**CFR 47 FCC PART 15 SUBPART E**  
**CERTIFICATION TEST REPORT**

*For*

**WIFI Module**

**MODEL NUMBER: WC5EM2601F**

**FCC ID: 2AC23-WC5E**

**REPORT NUMBER: 4790105656.2-2**

**ISSUE DATE: October 29, 2021**

*Prepared for*

**Hui Zhou Gaoshengda Technology Co.,LTD**  
**NO.75 Zhongkai Development Area, Huizhou, Guangdong China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	10/29/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6dB/26dB Bandwidth	FCC 15.407 (a)&(e)	PASS
2	Conducted Output Power	FCC 15.407 (a)	PASS
3	Power Spectral Density	FCC 15.407 (a)	PASS
4	Radiated Bandedge and Spurious Emission	FCC 15.407 (b) FCC 15.209 FCC 15.205	PASS
5	Conducted Emission Test for AC Power Port	FCC 15.207	PASS
6	Frequency Stability	FCC 15.407 (g)	PASS
7	Dynamic Frequency Selection	FCC 15.407 (h)	PASS
8	Antenna Requirement	FCC 15.203	PASS
<b>Note:</b> 1.This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART E > when <Accuracy Method> decision rule is applied.			



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>7</b>
<b>2. TEST METHODOLOGY .....</b>	<b>8</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>8</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>9</b>
4.1. MEASURING INSTRUMENT CALIBRATION .....	9
4.2. MEASUREMENT UNCERTAINTY .....	9
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>10</b>
5.1. DESCRIPTION OF EUT .....	10
5.2. MAXIMUM OUTPUT POWER .....	11
5.3. CHANNEL LIST .....	12
5.4. DESCRIPTION OF AVAILABLE ANTENNAS .....	13
5.5. THE WORSE CASE POWER SETTING PARAMETER .....	14
5.6. TEST CHANNEL CONFIGURATION .....	16
5.7. THE WORSE CASE CONFIGURATIONS .....	18
5.8. DESCRIPTION OF TEST SETUP .....	19
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b>	<b>20</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>22</b>
7.1. ON TIME AND DUTY CYCLE .....	22
7.2. 6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH .....	23
7.3. CONDUCTED OUTPUT POWER .....	25
7.4. POWER SPECTRAL DENSITY .....	28
<b>8. RADIATED TEST RESULTS .....</b>	<b>30</b>
8.1. RESTRICTED BANDEDGE .....	36
8.1.1. 802.11a 20 SISO MODE .....	36
UNII-1 BAND .....	36
UNII-2A BAND .....	40
UNII-2C BAND .....	42
UNII-3 BAND .....	45
8.1.2. 802.11n HT20 MIMO MODE .....	47
UNII-1 BAND .....	47
UNII-2A BAND .....	49
UNII-2C BAND .....	51
UNII-3 BAND .....	54
8.1.3. 802.11n HT40 MIMO MODE .....	56
UNII-1 BAND .....	56
UNII-2A BAND .....	58



UNII-2C BAND .....	60
UNII-3 BAND .....	63
8.1.4. 802.11ac VHT80 MIMO MODE .....	65
UNII-1 BAND .....	65
UNII-2A BAND .....	67
UNII-2C BAND .....	69
UNII-3 BAND .....	72
8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz) .....	73
8.2.1. 802.11a 20 SISO MODE .....	73
UNII-1 BAND .....	73
UNII-2A BAND .....	79
UNII-2C BAND .....	85
STRADDLE CHANNEL 144 .....	91
UNII-3 BAND .....	93
8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz) .....	99
8.3.1. 802.11a 20 SISO MODE .....	99
UNII-1 BAND .....	99
UNII-2A BAND .....	105
UNII-2C BAND .....	111
STRADDLE CHANNEL 144 .....	117
UNII-3 BAND .....	119
8.3.2. 802.11n HT20 MIMO MODE .....	125
UNII-1 BAND .....	125
UNII-2A BAND .....	131
UNII-2C BAND .....	137
STRADDLE CHANNEL 144 .....	143
UNII-3 BAND .....	145
8.3.3. 802.11n HT40 MIMO MODE .....	151
UNII-1 BAND .....	151
UNII-2A BAND .....	155
UNII-2C BAND .....	159
STRADDLE CHANNEL 142 .....	165
UNII-3 BAND .....	167
8.3.4. 802.11ac VHT80 MIMO MODE .....	171
UNII-1 BAND .....	171
UNII-2A BAND .....	173
UNII-2C BAND .....	175
STRADDLE CHANNEL 138 .....	179
UNII-3 BAND .....	181
8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz) .....	183
8.4.1. 802.11a 20 SISO MODE .....	183
8.5. SPURIOUS EMISSIONS (26 GHz ~ 40 GHz) .....	185
8.5.1. 802.11a 20 SISO MODE .....	185
8.6. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz) .....	187
8.6.1. 802.11a 20 SISO MODE .....	187
8.7. SPURIOUS EMISSIONS BELOW 30 MHz .....	189
8.7.1. 802.11a 20 SISO MODE .....	189
<b>9. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>192</b>



9.1.1.	802.11a 20 SISO MODE.....	193
<b>10.</b>	<b>FREQUENCY STABILITY.....</b>	<b>195</b>
<b>11.</b>	<b>DYNAMIC FREQUENCY SELECTION .....</b>	<b>197</b>
<b>12.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>201</b>
12.1.	<i>Appendix A1: Emission Bandwidth .....</i>	<i>202</i>
12.1.1.	Test Result.....	202
12.1.2.	Test Graphs .....	204
12.2.	<i>Appendix A2: Occupied Channel Bandwidth .....</i>	<i>232</i>
12.2.1.	Test Result.....	232
12.2.2.	Test Graphs .....	234
12.3.	<i>Appendix A3: Min Emission Bandwidth .....</i>	<i>262</i>
12.3.1.	Test Result.....	262
12.3.2.	Test Graphs .....	263
12.4.	<i>Appendix B: Maximum Average Conducted Output Power.....</i>	<i>272</i>
12.4.1.	Test Result.....	272
12.5.	<i>Appendix C: Maximum power spectral density .....</i>	<i>274</i>
12.5.1.	Test Result.....	274
12.5.2.	Test Graphs .....	276
12.6.	<i>Appendix D: Duty Cycle.....</i>	<i>307</i>
12.6.1.	Test Result.....	307
12.6.2.	Test Graphs .....	308
12.7.	<i>Appendix E: Frequency Stability.....</i>	<i>310</i>
	Test Result.....	310
12.8.	<i>Appendix F: Dynamic Frequency Selection .....</i>	<i>312</i>



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD  
Address: NO.75 Zhongkai Development Area, Huizhou, Guangdong China

### Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD  
Address: NO.75 Zhongkai Development Area, Huizhou, Guangdong China

### EUT Information

EUT Name: WIFI Module  
Model: WC5EM2601F  
Brand: GSD  
Sample Received Date: September 22, 2021  
Sample Status: Normal  
Sample ID: 4245286  
Date of Tested: September 24, 2021 ~ October 25, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E	PASS

Prepared By:

Denny Huang  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, CFR 47 FCC Part 2, CFR 47 FCC Part 15, KDB 789033 D02 v02r01, KDB414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02, KDB 905462 D03 UNII clients without radar detection New Rules v01r02, KDB 905462 D04 Operational Modes for DFS Testing New Rules v01 and KDB 905462 D06 802 11 Channel Plans New Rules v02.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.





## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz-18 GHz)
	5.23dB (18 GHz-26 GHz)
	5.64 dB (26 GHz-40 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	WIFI Module
Model	WC5EM2601F
Radio Technology	WLAN (IEEE 802.11a 20/n HT20/n HT40/ac VHT20/VHT 40/VHT 80)
Operation frequency	UNII-1: 5150 ~ 5250 MHz UNII-2A: 5250 ~ 5350 MHz UNII-2C: 5470 ~ 5725 MHz UNII-3: 5725 ~ 5850 MHz
Modulation	IEEE 802.11a 20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT20: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT40: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT80: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Power Supply	DC 3.3 V

## 5.2. MAXIMUM OUTPUT POWER

### UNII-1 BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a 20	5150 ~ 5250	19.80	22.80
n HT20		18.32	21.32
n HT40		18.76	21.76
ac VHT 80		17.76	20.76

### UNII-2A BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)
a 20	5250 ~ 5350	19.65
n HT20		18.25
n HT40		18.45
ac VHT 80		18.08

### UNII-2C BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)
a 20	5470 ~ 5725	14.68
n HT20		15.34
n HT40		15.88
ac VHT 80		16.96

### UNII-3 BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)
a 20	5725 ~ 5850	19.95
n HT20		19.84
n HT40		19.62
ac VHT 80		19.88

### 5.3. CHANNEL LIST

UNII-1 (For Bandwidth=20MHz)		UNII-1 (For Bandwidth=40MHz)		UNII-1 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A (For Bandwidth=20MHz)		UNII-2A (For Bandwidth=40MHz)		UNII-2A (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2C (For Bandwidth=20MHz)		UNII-2C (For Bandwidth=40MHz)		UNII-2C (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	5600	142	5710		
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				
144	5720				

UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

#### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency Band	Antenna Type	Max Antenna Gain (dBi)
1	5180 ~ 5825	PIFA	3
2	5180 ~ 5825	PIFA	3

The EUT support Cyclic Shift Diversity (CDD), Space Time Coding (STBC), Spatial Division Multiplexing (SDM) modes.

According to KDB 662911 D01:

The Directional Gain was calculated as the following method:

For CDD mode:

For output power measurements:

Directional gain=  $G_{ANT} + \text{Array Gain} = 3 \text{ dBi}$

$G_{ANT}$ : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain=  $G_{ANT} + \text{Array Gain} = 6 \text{ dBi}$

Array Gain =  $10 \log (N_{ANT}/N_{SS}) \text{ dB}$ .

$N_{ANT}$ : number of transmit antennas

$N_{SS}$ : number of spatial streams, the worst case directional gain will occur when  $N_{SS} = 1$

For STBC and SDM mode:

For output power measurements and power spectral density (PSD) measurements

Directional gain =  $G_{ANT} = 3 \text{ dBi}$

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a 20	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11n HT20	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11n HT40	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT20	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT40	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT80	☒2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.

Note:

1.WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter	
Test Software	QA tool

### UNII-1

IEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a 20	6M	36	23	23
		40	25	25
		48	25	25
n HT20	MCS0	36	1E	1E
		40	1E	1E
		48	1E	1E
n HT40	MCS0	38	1E	1E
		46	1E	1E
ac HT 80	MCS0	42	1C	1E

### UNII-2A

IEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a 20	6M	52	25	25
		60	25	25
		64	21	21
n HT20	MCS0	52	1E	1E
		60	1E	1E
		64	1E	1E
n HT40	MCS0	54	1E	1E
		62	1E	1E
ac VHT80	MCS0	58	1C	1E

### UNII-2C

IEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a 20	6M	100	19	19
		120	19	19
		140	19	19
n HT20	MCS0	100	18	18
		120	18	18
		140	18	18
n HT40	MCS0	102	18	18
		118	18	18
		134	18	18
ac VHT80	MCS0	106	18	1A
		122	18	1A



## UNII-3

IEE Std. 802.11	Rate	Channel	Soft set value	
			ANT 1	ANT 2
a 20	6M	149	25	25
		157	25	25
		165	25	25
n HT20	MCS0	149	22	22
		157	22	22
		165	22	22
n HT40	MCS0	151	20	20
		159	20	20
ac VHT80	MCS0	155	20	21

## 5.6. TEST CHANNEL CONFIGURATION

UNII-1 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11ac VHT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT80	CH 42(Low Channel)	5210 MHz
/	/	/

UNII-2A Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11ac VHT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT80	CH 58(Low Channel)	5290 MHz

UNII-2C Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500 MHz, 5600 MHz, 5700 MHz
802.11n VHT20	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500 MHz, 5600 MHz, 5700 MHz
802.11n VHT40	CH 102(Low Channel), CH 118(MID Channel), CH 134(High Channel)	5510 MHz, 5590 MHz, 5670 MHz
802.11ac VHT20	CH 100(Low Channel), CH 120(MID Channel), CH 140(High Channel)	5500MHz, 5600 MHz, 5700MHz
802.11ac VHT40	CH 102(Low Channel), CH 118(MID Channel), CH 134(High Channel)	5510 MHz, 5590 MHz, 5670 MHz
802.11ac VHT80	CH 106(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz
/	/	/





UNII-3 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ac VHT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11ac VHT40	CH 151(Low Channel), CH 159(High Channel)	5755 MHz, 5795 MHz
802.11ac VHT80	CH 155(Low Channel)	5775 MHz

## 5.7. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.6.

Worst case Data Rates declared by the customer:

802.11a 20 mode: 6 Mbps  
802.11n HT20 mode: MCS0  
802.11n HT40 mode: MCS0  
802.11ac VHT20 mode: MCS0  
802.11ac VHT40 mode: MCS0  
802.11ac VHT80 mode: MCS0

802.11ac VHT20 and VHT40 mode are different from 802.11nHT20 and HT40 only in control messages, so for these 4 modes, only 802.11n HT20 and 802.11n HT40 worst case power modes radiated emission test data are recorded in the report.

802.11ac&n SISO mode and MIMO mode have the same power setting, so only the worst case power mode (MIMO) will be record in the report.

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 1 and Core 2 correspond to antenna 1 and antenna 2 respectively.

Antenna 1 and Antenna 2 have the same power setting, but the power test data are different. (Declared by customer.)

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

The EUT support Cyclic Shift Diversity (CDD), Space Time Coding (STBC), Spartial Division Multiplexing (SDM) modes. They use the same conducted power per chain in any given mode, CDD mode have the maximum power setting, so we only chose the worst case mode CDD for final testing.

## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	XIAOXIN 5000	/
2	AC Adapter	Lenovo	42T4434	Input: AC 100 ~ 240 V, 1.5 A, 50-60 Hz Output: DC 20 V, 4.5 A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	0.3	/

### ACCESSORIES


Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

Note: The cable is provided by customer.

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS



## 6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 02, 2021	Aug. 01, 2024
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	TDK	PA-02-3	TRS-308-00002	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Nov. 12, 2020	Nov. 11, 2021



Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Nov. 12, 2020	Nov. 11, 2021
Software					
Description		Manufacturer		Name	Version
Test Software for Radiated Emissions		Farad		EZ-EMC	Ver. UL-3A1

Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Nov.20,2020	Nov.19,2021
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Nov.20,2020	Nov.19,2021
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Nov.20,2020	Nov.19,2021
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Nov.20,2020	Nov.19,2021
DC power supply	Keysight	E3642A	MY55159130	Nov.24,2020	Nov.23,2021
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2021
Software					
Description		Manufacturer		Name	Version
Tonsend SRD Test System		Tonsend		JS1120-3 RF Test System	2.6.77.0518

Other Instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power sensor, Power Meter	R&S	OSP120	100921	Mar.23,2021	Mar.22,2022



## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE

#### LIMITS


None; for reporting purposes only.

#### PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set  $RBW \geq EBW$  if possible; otherwise, set RBW to the largest available value. Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$ , where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	26.2 °C	Relative Humidity	56.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

#### RESULTS

Please refer to appendix D.



## 7.2. 6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15, Subpart E ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725 (For FCC) 5470 ~ 5600 (For ISED) 5650 ~ 5725 (For ISED)
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

### TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $> 3 \times \text{RBW}$ For 99 % Bandwidth: $> 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

- Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

### Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

99 % Bandwidth of UNII-2C Band Portion =  $(5725 - (5720 - (21.00/2))) = 15.50$  MHz

99 % Bandwidth of UNII-3 Band Portion =  $(5720 + (21.00/2) - 5725) = 5.50$  MHz

### Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion =  $5725 - 5710.16 = 14.84$  MHz

### Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz


FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion =  $5728.2 - 5725 = 3.2$  MHz

### TEST SETUP



### TEST ENVIRONMENT

Temperature	26.2 °C	Relative Humidity	56.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

### RESULTS

Please refer to Appendix A1&A2&A3.





### 7.3. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	<input type="checkbox"/> Outdoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Indoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Fixed Point-To-Point Access Points: 1 W (30 dBm) <input checked="" type="checkbox"/> Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

**Note:**

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

## **TEST PROCEDURE**

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

### **Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep):**

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW  $\geq$  3 MHz.
- (iv) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle  $< 98\%$ , use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98\%$ , and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."
- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

### **Method PM (Measurement using an RF average power meter):**

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
  - a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
  - b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
  - c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle,  $x$ , of the transmitter output signal as described in II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding  $10 \log (1/x)$  where  $x$  is the duty cycle (e.g.,  $10 \log (1/0.25)$  if the duty cycle is 25 %).


### **Method PM-G (Measurement using a gated RF average power meter):**

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Straddle channel power was measured using spectrum analyzer.



### TEST SETUP



### TEST ENVIRONMENT

Temperature	26.2 °C	Relative Humidity	56.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

### RESULTS

Please refer to Appendix B.



## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	<input type="checkbox"/> Outdoor Access Point: 17 dBm/MHz <input type="checkbox"/> Indoor Access Point: 17 dBm/MHz <input type="checkbox"/> Fixed Point-To-Point Access Points: 17 dBm/MHz <input checked="" type="checkbox"/> Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

**Note:**

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.  
If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.



Connect the EUT to the spectrum analyser and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto


For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow trace to fully stabilize and Use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

## **TEST SETUP**



## **TEST ENVIRONMENT**

Temperature	26.2 °C	Relative Humidity	56.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

## **RESULTS**

Please refer to Appendix C.



## 8. RADIATED TEST RESULTS

### LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.


<sup>2</sup>Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISSED RSS-247 6.2.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

## TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 ohm; For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.



Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

#### **TEST ENVIRONMENT**

Temperature	24.3 °C	Relative Humidity	61 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.3 V

#### **RESULTS**



## 8.1. RESTRICTED BANDEDGE


### 8.1.1. 802.11a 20 SISO MODE

#### UNII-1 BAND

#### ANTENNA 2 TEST RESULTS (WORST CASE)

#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	23.27	41.19	64.46	74.00	-9.54	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	7.27	41.19	48.46	54.00	-5.54	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)


## PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	18.84	41.19	60.03	74.00	-13.97	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	4.96	41.19	46.15	54.00	-7.85	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**UNII-2A BAND****ANTENNA 1 TEST RESULTS (WORST CASE)****RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	19.65	41.20	60.85	74.00	-13.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	5.27	41.20	46.47	54.00	-7.53	AVG


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
 4. For the transmitting duration, please refer to clause 7.1.  
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**UNII-2C BAND****ANTENNA 1 TEST RESULTS (WORST CASE)****RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	15.91	41.82	57.73	68.20	-10.47	peak
2	5470.000	16.00	41.87	57.87	68.20	-10.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	4.05	41.82	45.87	54.00	-8.13	AVG
2	5470.000	4.58	41.87	46.45	/	/	/

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	22.69	41.67	64.36	68.20	-3.84	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# UNII-3 BAND

## ANTENNA 1 TEST RESULTS (WORST CASE)

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5642.880	17.11	41.65	58.76	68.20	-9.44	peak
2	5697.760	18.92	41.56	60.48	103.55	-43.07	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5892.715	20.89	42.96	63.85	92.06	-28.21	peak
2	5950.980	18.10	42.79	60.89	68.20	-7.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) and Antennas had been tested, only the worst data was recorded in the report.




## 8.1.2. 802.11n HT20 MIMO MODE

UNII-1 BANDRESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.34	41.19	56.53	74.00	-17.47	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	3.54	41.19	44.73	54.00	-9.27	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.






**UNII-2A BAND**

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	19.43	41.20	60.63	74.00	-13.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	5.69	41.20	46.89	54.00	-7.11	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## UNII-2C BAND

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)


#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	15.85	41.82	57.67	68.20	-10.53	peak
2	5470.000	15.38	41.87	57.25	68.20	-10.95	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	3.39	41.82	45.21	54.00	-8.79	AVG
2	5470.000	3.58	41.87	45.45	/	/	/

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	22.09	41.67	63.76	68.20	-4.44	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## UNII-3 BAND

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5630.880	17.25	41.68	58.93	68.20	-9.27	peak
2	5698.720	26.52	41.55	68.07	104.26	-36.19	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5889.275	20.57	42.92	63.49	94.60	-31.11	peak
2	5953.130	18.66	42.78	61.44	68.20	-6.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.

### 8.1.3. 802.11n HT40 MIMO MODE

#### UNII-1 BAND

#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	20.52	41.19	61.71	74.00	-12.29	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.





**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	6.59	41.19	47.78	54.00	-6.22	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## UNII-2A BAND


### RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	26.91	41.20	68.11	74.00	-5.89	peak
2	5350.920	29.87	41.21	71.08	74.00	-2.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	9.97	41.20	51.17	54.00	-2.83	AVG
2	5350.920	9.77	41.21	50.98	54.00	-3.02	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**UNII-2C BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	16.00	41.82	57.82	68.20	-10.38	peak
2	5470.000	16.66	41.87	58.53	68.20	-9.67	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	3.68	41.82	45.50	54.00	-8.50	AVG
2	5470.000	4.86	41.87	46.73	/	/	/

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	16.86	41.67	58.53	68.20	-9.67	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## UNII-3 BAND

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5605.940	17.65	41.72	59.37	68.20	-8.83	peak
2	5717.900	42.06	41.63	83.69	110.21	-26.52	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5851.420	30.26	42.54	72.80	118.96	-46.16	peak
2	5936.290	18.17	42.86	61.03	68.20	-7.17	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.



# 8.1.4. 802.11ac VHT80 MIMO MODE

## UNII-1 BAND


### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL) PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.720	31.60	39.72	71.32	74.00	-2.68	peak
2	5150.000	28.54	39.91	68.45	74.00	-5.55	peak
3	5350.000	16.80	40.08	56.88	74.00	-17.12	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.720	9.61	39.72	49.33	54.00	-4.67	AVG
2	5150.000	10.12	39.91	50.03	54.00	-3.97	AVG
3	5350.000	3.13	40.08	43.21	54.00	-10.79	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: All the polarities (Vertical & Horizontal) and Antennas had been tested, only the worst data was recorded in the report.

**UNII-2A BAND****RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.040	20.11	39.87	59.98	74.00	-14.02	peak
2	5150.000	16.38	39.91	56.29	74.00	-17.71	peak
3	5350.000	27.70	40.08	67.78	74.00	-6.22	peak
4	5357.280	30.45	40.13	70.58	74.00	-3.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.040	4.12	39.87	43.99	54.00	-10.01	AVG
2	5150.000	4.06	39.91	43.97	54.00	-10.03	AVG
3	5350.000	12.05	40.08	52.13	54.00	-1.87	AVG
4	5357.280	10.73	40.13	50.86	54.00	-3.14	AVG


- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) and Antennas had been tested, only the worst data was recorded in the report.

**UNII-2C BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	23.65	40.79	64.44	68.20	-3.76	peak
2	5470.000	24.42	40.85	65.27	68.20	-2.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	8.21	40.79	49.00	54.00	-5.00	AVG
2	5470.000	10.30	40.85	51.15	/	/	/

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
4. For the transmitting duration, please refer to clause 7.1.  
5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

# RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

## PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	24.17	40.63	64.80	68.20	-3.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) and Antennas had been tested, only the worst data was recorded in the report.

## UNII-3 BAND

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5645.600	25.20	40.62	65.82	68.20	-2.38	peak
2	5723.200	47.79	40.61	88.40	118.10	-29.70	peak
3	5850.800	40.85	41.46	82.31	120.38	-38.07	peak
4	5927.200	21.99	41.82	63.81	68.20	-4.39	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities (Vertical & Horizontal) had been tested, only the worst data was recorded in the report.




## 8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz)

### 8.2.1. 802.11a 20 SISO MODE

#### UNII-1 BAND

#### ANTENNA 2 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	47.04	-11.02	36.02	74.00	-37.98	peak
2	4213.000	40.67	-2.73	37.94	74.00	-36.06	peak
3	4828.000	40.59	-0.63	39.96	74.00	-34.04	peak
4	5110.750	44.36	0.25	44.61	74.00	-29.39	peak
5	5863.000	39.28	1.68	40.96	74.00	-33.04	peak
6	6631.000	35.53	4.52	40.05	74.00	-33.95	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3850.000	41.35	-4.45	36.90	74.00	-37.10	peak
2	4220.500	40.53	-2.75	37.78	74.00	-36.22	peak
3	4666.750	41.41	-1.31	40.10	74.00	-33.90	peak
4	5116.000	41.40	0.29	41.69	74.00	-32.31	peak
5	5995.750	38.96	2.19	41.15	74.00	-32.85	peak
6	6838.000	36.00	4.69	40.69	74.00	-33.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	46.62	-11.02	35.60	74.00	-38.40	peak
2	4675.000	40.46	-1.27	39.19	74.00	-34.81	peak
3	5110.000	43.87	0.24	44.11	74.00	-29.89	peak
4	5669.500	38.21	1.44	39.65	74.00	-34.35	peak
5	6013.000	37.61	2.20	39.81	74.00	-34.19	peak
6	6655.750	35.71	4.52	40.23	74.00	-33.77	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2784.250	43.89	-7.77	36.12	74.00	-37.88	peak
2	4423.750	41.53	-2.73	38.80	74.00	-35.20	peak
3	5114.500	39.77	0.29	40.06	74.00	-33.94	peak
4	5489.500	38.54	1.13	39.67	74.00	-34.33	peak
5	5954.500	37.96	2.03	39.99	74.00	-34.01	peak
6	6658.000	35.87	4.51	40.38	74.00	-33.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	47.32	-11.02	36.30	74.00	-37.70	peak
2	4669.000	41.48	-1.30	40.18	74.00	-33.82	peak
3	5119.750	41.81	0.32	42.13	74.00	-31.87	peak
4	5635.750	38.93	1.45	40.38	74.00	-33.62	peak
5	5890.000	37.98	1.79	39.77	74.00	-34.23	peak
6	6778.000	36.88	4.56	41.44	74.00	-32.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1921.000	45.61	-11.02	34.59	74.00	-39.41	peak
2	3496.750	42.09	-5.83	36.26	74.00	-37.74	peak
3	4774.750	39.84	-0.79	39.05	74.00	-34.95	peak
4	5111.500	39.63	0.25	39.88	74.00	-34.12	peak
5	5974.750	37.88	2.10	39.98	74.00	-34.02	peak
6	6619.750	35.77	4.51	40.28	74.00	-33.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-2A BAND

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4734.250	39.72	-0.97	38.75	74.00	-35.25	peak
2	5097.250	42.50	0.16	42.66	74.00	-31.34	peak
3	5398.000	40.37	0.80	41.17	74.00	-32.83	peak
4	5668.000	38.76	1.44	40.20	74.00	-33.80	peak
5	6374.500	36.46	3.20	39.66	74.00	-34.34	peak
6	6657.250	36.04	4.52	40.56	74.00	-33.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3617.500	42.22	-5.21	37.01	74.00	-36.99	peak
2	4557.250	40.97	-1.89	39.08	74.00	-34.92	peak
3	5131.000	39.32	0.39	39.71	74.00	-34.29	peak
4	5519.500	39.32	1.22	40.54	74.00	-33.46	peak
5	5859.250	38.28	1.68	39.96	74.00	-34.04	peak
6	6623.500	36.05	4.50	40.55	74.00	-33.45	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




## HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	47.30	-11.02	36.28	74.00	-37.72	peak
2	4783.000	40.11	-0.74	39.37	74.00	-34.63	peak
3	5122.750	42.97	0.34	43.31	74.00	-30.69	peak
4	5410.000	42.33	0.83	43.16	74.00	-30.84	peak
5	5656.000	39.69	1.44	41.13	74.00	-32.87	peak
6	6654.250	36.32	4.52	40.84	74.00	-33.16	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4127.500	41.94	-3.45	38.49	74.00	-35.51	peak
2	4852.750	39.54	-0.62	38.92	74.00	-35.08	peak
3	5122.000	39.49	0.33	39.82	74.00	-34.18	peak
4	5282.500	40.19	0.84	41.03	74.00	-32.97	peak
5	6011.500	37.85	2.20	40.05	74.00	-33.95	peak
6	6790.000	35.51	4.57	40.08	74.00	-33.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	46.94	-11.02	35.92	74.00	-38.08	peak
2	4271.500	40.45	-2.79	37.66	74.00	-36.34	peak
3	5119.750	41.80	0.32	42.12	74.00	-31.88	peak
4	5403.250	46.14	0.81	46.95	74.00	-27.05	peak
5	5672.500	38.97	1.44	40.41	74.00	-33.59	peak
6	6658.750	36.00	4.52	40.52	74.00	-33.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3616.000	42.46	-5.22	37.24	74.00	-36.76	peak
2	4297.000	41.46	-2.81	38.65	74.00	-35.35	peak
3	4706.500	40.06	-1.12	38.94	74.00	-35.06	peak
4	5399.500	40.08	0.79	40.87	74.00	-33.13	peak
5	5818.750	38.65	1.52	40.17	74.00	-33.83	peak
6	6655.750	35.71	4.52	40.23	74.00	-33.77	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-2C BAND

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	47.42	-11.02	36.40	74.00	-37.60	peak
2	4783.000	40.03	-0.74	39.29	74.00	-34.71	peak
3	5336.500	41.62	0.81	42.43	74.00	-31.57	peak
4	5664.250	38.64	1.44	40.08	74.00	-33.92	peak
5	5881.750	37.30	1.75	39.05	74.00	-34.95	peak
6	6627.250	36.33	4.51	40.84	74.00	-33.16	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	45.52	-11.02	34.50	74.00	-39.50	peak
2	2813.500	42.22	-7.66	34.56	74.00	-39.44	peak
3	3775.000	41.12	-4.47	36.65	74.00	-37.35	peak
4	4705.750	41.24	-1.12	40.12	74.00	-33.88	peak
5	5953.000	38.29	2.02	40.31	74.00	-33.69	peak
6	6657.250	35.93	4.52	40.45	74.00	-33.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	48.09	-11.02	37.07	74.00	-36.93	peak
2	4270.750	40.12	-2.78	37.34	74.00	-36.66	peak
3	4750.750	40.41	-0.90	39.51	74.00	-34.49	peak
4	5361.250	38.70	0.80	39.50	74.00	-34.50	peak
5	5662.000	39.57	1.44	41.01	74.00	-32.99	peak
6	6658.000	35.94	4.51	40.45	74.00	-33.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	45.26	-11.02	34.24	74.00	-39.76	peak
2	2077.000	45.57	-10.69	34.88	74.00	-39.12	peak
3	3842.500	41.27	-4.44	36.83	74.00	-37.17	peak
4	4666.750	40.64	-1.31	39.33	74.00	-34.67	peak
5	5860.750	38.30	1.68	39.98	74.00	-34.02	peak
6	6779.500	36.39	4.56	40.95	74.00	-33.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1726.000	43.85	-11.22	32.63	74.00	-41.37	peak
2	3622.000	42.38	-5.19	37.19	74.00	-36.81	peak
3	4783.000	40.29	-0.74	39.55	74.00	-34.45	peak
4	5368.000	38.71	0.80	39.51	74.00	-34.49	peak
5	5860.000	39.67	1.68	41.35	74.00	-32.65	peak
6	6784.000	35.88	4.56	40.44	74.00	-33.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	45.90	-11.02	34.88	74.00	-39.12	peak
2	3036.250	42.32	-7.00	35.32	74.00	-38.68	peak
3	4222.000	41.21	-2.75	38.46	74.00	-35.54	peak
4	4906.750	39.92	-0.57	39.35	74.00	-34.65	peak
5	5973.250	38.71	2.09	40.80	74.00	-33.20	peak
6	6652.000	35.37	4.52	39.89	74.00	-34.11	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## STRADDLE CHANNEL 144

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2458.750	42.41	-8.93	33.48	74.00	-40.52	peak
2	4189.000	41.59	-2.83	38.76	74.00	-35.24	peak
3	4556.500	41.77	-1.90	39.87	74.00	-34.13	peak
4	4868.500	39.91	-0.60	39.31	74.00	-34.69	peak
5	5768.500	41.84	1.45	43.29	74.00	-30.71	peak
6	6664.750	36.32	4.53	40.85	74.00	-33.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	46.12	-11.02	35.10	74.00	-38.90	peak
2	3536.500	41.16	-5.63	35.53	74.00	-38.47	peak
3	4247.500	40.99	-2.76	38.23	74.00	-35.77	peak
4	4874.500	39.85	-0.60	39.25	74.00	-34.75	peak
5	5756.500	39.41	1.44	40.85	74.00	-33.15	peak
6	6718.750	35.70	4.54	40.24	74.00	-33.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-3 BAND

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4273.000	41.41	-2.78	38.63	74.00	-35.37	peak
2	4840.000	40.74	-0.62	40.12	74.00	-33.88	peak
3	5689.000	43.88	1.44	45.32	74.00	-28.68	peak
4	5746.000	51.74	1.45	53.19	74.00	-20.81	peak
5	5926.000	39.60	1.93	41.53	74.00	-32.47	peak
6	6658.000	36.63	4.51	41.14	74.00	-32.86	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4264.000	41.79	-2.78	39.01	74.00	-34.99	peak
2	4558.000	42.05	-1.89	40.16	74.00	-33.84	peak
3	5668.000	42.89	1.44	44.33	74.00	-29.67	peak
4	5745.000	49.09	1.45	50.54	74.00	-23.46	peak
5	5887.000	39.80	1.77	41.57	74.00	-32.43	peak
6	6655.000	37.05	4.52	41.57	74.00	-32.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1918.000	48.75	-11.02	37.73	74.00	-36.27	peak
2	4873.000	41.13	-0.60	40.53	74.00	-33.47	peak
3	5662.000	42.78	1.44	44.22	74.00	-29.78	peak
4	5788.000	49.29	1.44	50.73	74.00	-23.27	peak
5	5884.000	39.96	1.76	41.72	74.00	-32.28	peak
6	6658.000	36.68	4.51	41.19	74.00	-32.81	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


## HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4841.500	39.85	-0.62	39.23	74.00	-34.77	peak
2	5152.750	38.76	0.55	39.31	74.00	-34.69	peak
3	5691.250	39.96	1.44	41.40	74.00	-32.60	peak
4	5782.000	46.25	1.44	47.69	74.00	-26.31	peak
5	6657.250	35.79	4.52	40.31	74.00	-33.69	peak
6	6871.750	36.23	4.78	41.01	74.00	-32.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1920.250	47.46	-11.02	36.44	74.00	-37.56	peak
2	4780.000	40.14	-0.75	39.39	74.00	-34.61	peak
3	5099.500	39.89	0.18	40.07	74.00	-33.93	peak
4	5828.500	46.83	1.56	48.39	74.00	-25.61	peak
5	6381.250	36.04	3.25	39.29	74.00	-34.71	peak
6	6661.750	35.50	4.52	40.02	74.00	-33.98	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3610.000	42.14	-5.24	36.90	74.00	-37.10	peak
2	4594.750	41.31	-1.68	39.63	74.00	-34.37	peak
3	5668.000	39.23	1.44	40.67	74.00	-33.33	peak
4	5828.500	45.21	1.56	46.77	74.00	-27.23	peak
5	5892.250	39.32	1.80	41.12	74.00	-32.88	peak
6	6749.500	35.36	4.55	39.91	74.00	-34.09	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

Note: All the modes, bands and antennas had been tested, but only the worst data was recorded in the report.


### 8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz)

#### 8.3.1. 802.11a 20 SISO MODE

##### UNII-1 BAND

##### ANTENNA 2 TEST RESULTS (WORST CASE)

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8984.125	38.28	11.57	49.85	74.00	-24.15	peak
2	9388.375	37.19	11.39	48.58	74.00	-25.42	peak
3	11786.375	34.84	16.64	51.48	74.00	-22.52	peak
4	12585.250	35.20	16.81	52.01	74.00	-21.99	peak
5	14734.375	33.68	17.74	51.42	74.00	-22.58	peak
6	17173.625	29.53	22.33	51.86	74.00	-22.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9345.750	37.18	11.21	48.39	74.00	-25.61	peak
2	10352.250	37.63	12.41	50.04	74.00	-23.96	peak
3	12638.875	35.13	16.82	51.95	74.00	-22.05	peak
4	14818.250	33.76	17.82	51.58	74.00	-22.42	peak
5	16713.000	30.60	20.90	51.50	74.00	-22.50	peak
6	17181.875	29.71	22.37	52.08	74.00	-21.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11354.625	35.75	15.31	51.06	74.00	-22.94	peak
2	11732.750	35.17	16.39	51.56	74.00	-22.44	peak
3	12651.250	35.41	16.81	52.22	74.00	-21.78	peak
4	13525.750	33.68	17.47	51.15	74.00	-22.85	peak
5	15978.750	33.76	18.45	52.21	74.00	-21.79	peak
6	17224.500	29.66	22.39	52.05	74.00	-21.95	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8735.250	38.41	9.75	48.16	74.00	-25.84	peak
2	10367.375	37.54	12.49	50.03	74.00	-23.97	peak
3	11808.375	34.89	16.70	51.59	74.00	-22.41	peak
4	13419.875	33.97	17.42	51.39	74.00	-22.61	peak
5	14745.375	33.78	17.75	51.53	74.00	-22.47	peak
6	16684.125	31.09	20.87	51.96	74.00	-22.04	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7889.625	38.29	9.24	47.53	74.00	-26.47	peak
2	9028.125	36.65	11.56	48.21	74.00	-25.79	peak
3	11868.875	35.68	16.64	52.32	74.00	-21.68	peak
4	12724.125	35.09	16.81	51.90	74.00	-22.10	peak
5	13909.375	33.20	17.99	51.19	74.00	-22.81	peak
6	17080.125	29.85	21.81	51.66	74.00	-22.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9200.000	37.31	10.57	47.88	74.00	-26.12	peak
2	10474.625	39.12	12.97	52.09	74.00	-21.91	peak
3	11747.875	34.99	16.47	51.46	74.00	-22.54	peak
4	12610.000	35.26	16.82	52.08	74.00	-21.92	peak
5	15930.625	33.18	18.29	51.47	74.00	-22.53	peak
6	17114.500	29.69	22.00	51.69	74.00	-22.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



## UNII-2A BAND

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8611.500	37.77	9.71	47.48	74.00	-26.52	peak
2	9384.250	36.80	11.37	48.17	74.00	-25.83	peak
3	10381.125	35.90	12.54	48.44	74.00	-25.56	peak
4	11884.000	34.94	16.62	51.56	74.00	-22.44	peak
5	13921.750	33.30	17.97	51.27	74.00	-22.73	peak
6	16436.625	31.45	19.98	51.43	74.00	-22.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8115.125	37.23	9.87	47.10	74.00	-26.90	peak
2	9352.625	37.07	11.23	48.30	74.00	-25.70	peak
3	11826.250	34.16	16.68	50.84	74.00	-23.16	peak
4	14811.375	32.24	17.82	50.06	74.00	-23.94	peak
5	17004.500	29.52	21.39	50.91	74.00	-23.09	peak
6	17947.750	27.11	24.00	51.11	74.00	-22.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8219.625	37.53	10.46	47.99	74.00	-26.01	peak
2	9076.250	36.81	11.28	48.09	74.00	-25.91	peak
3	11405.500	35.34	15.43	50.77	74.00	-23.23	peak
4	11827.625	35.37	16.68	52.05	74.00	-21.95	peak
5	13425.375	34.77	17.43	52.20	74.00	-21.80	peak
6	16781.750	31.67	20.99	52.66	74.00	-21.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8333.750	38.69	10.05	48.74	74.00	-25.26	peak
2	9360.875	37.20	11.27	48.47	74.00	-25.53	peak
3	10562.625	38.34	13.32	51.66	74.00	-22.34	peak
4	12633.375	34.65	16.82	51.47	74.00	-22.53	peak
5	13945.125	33.27	17.95	51.22	74.00	-22.78	peak
6	17223.125	29.29	22.40	51.69	74.00	-22.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7886.875	37.56	9.24	46.80	74.00	-27.20	peak
2	9304.500	37.35	11.02	48.37	74.00	-25.63	peak
3	11812.500	34.74	16.69	51.43	74.00	-22.57	peak
4	12652.625	35.23	16.81	52.04	74.00	-21.96	peak
5	15963.625	33.22	18.40	51.62	74.00	-22.38	peak
6	17957.375	27.51	24.00	51.51	74.00	-22.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8122.000	37.72	9.92	47.64	74.00	-26.36	peak
2	9026.750	36.69	11.57	48.26	74.00	-25.74	peak
3	11742.375	35.00	16.44	51.44	74.00	-22.56	peak
4	12590.750	34.87	16.81	51.68	74.00	-22.32	peak
5	14818.250	33.13	17.82	50.95	74.00	-23.05	peak
6	17228.625	29.10	22.38	51.48	74.00	-22.52	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-2C BAND


### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9080.375	37.46	11.25	48.71	74.00	-25.29	peak
2	11879.875	34.74	16.62	51.36	74.00	-22.64	peak
3	12643.000	35.52	16.82	52.34	74.00	-21.66	peak
4	13463.875	34.39	17.45	51.84	74.00	-22.16	peak
5	16607.125	30.42	20.80	51.22	74.00	-22.78	peak
6	17711.250	28.79	23.33	52.12	74.00	-21.88	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8227.875	36.84	10.43	47.27	74.00	-26.73	peak
2	9131.250	37.35	10.95	48.30	74.00	-25.70	peak
3	11813.875	34.84	16.68	51.52	74.00	-22.48	peak
4	12714.500	34.84	16.80	51.64	74.00	-22.36	peak
5	13516.125	34.21	17.46	51.67	74.00	-22.33	peak
6	17544.875	29.79	22.30	52.09	74.00	-21.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7848.375	38.35	9.35	47.70	74.00	-26.30	peak
2	9068.000	36.84	11.32	48.16	74.00	-25.84	peak
3	11866.125	35.01	16.63	51.64	74.00	-22.36	peak
4	12603.125	35.26	16.83	52.09	74.00	-21.91	peak
5	13974.000	33.20	17.90	51.10	74.00	-22.90	peak
6	17188.750	29.79	22.41	52.20	74.00	-21.80	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8230.625	37.29	10.42	47.71	74.00	-26.29	peak
2	9655.125	36.75	11.74	48.49	74.00	-25.51	peak
3	11087.875	34.75	14.64	49.39	74.00	-24.61	peak
4	12589.375	35.56	16.81	52.37	74.00	-21.63	peak
5	14782.500	33.45	17.80	51.25	74.00	-22.75	peak
6	16678.625	31.37	20.87	52.24	74.00	-21.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8984.125	36.62	11.57	48.19	74.00	-25.81	peak
2	11721.750	35.77	16.34	52.11	74.00	-21.89	peak
3	12654.000	34.79	16.81	51.60	74.00	-22.40	peak
4	14723.375	33.19	17.73	50.92	74.00	-23.08	peak
5	15989.750	32.51	18.49	51.00	74.00	-23.00	peak
6	17146.125	29.74	22.18	51.92	74.00	-22.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8218.250	36.85	10.47	47.32	74.00	-26.68	peak
2	9118.875	37.07	11.03	48.10	74.00	-25.90	peak
3	11842.750	35.00	16.66	51.66	74.00	-22.34	peak
4	12704.875	34.91	16.81	51.72	74.00	-22.28	peak
5	13919.000	33.92	17.97	51.89	74.00	-22.11	peak
6	17936.750	28.21	24.00	52.21	74.00	-21.79	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**STRADDLE CHANNEL 144****ANTENNA 1 TEST RESULTS (WORST CASE)****HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11818.000	35.34	16.68	52.02	74.00	-21.98	peak
2	12215.375	35.67	16.40	52.07	74.00	-21.93	peak
3	12700.750	35.97	16.81	52.78	74.00	-21.22	peak
4	13894.250	33.19	18.00	51.19	74.00	-22.81	peak
5	16611.250	30.98	20.80	51.78	74.00	-22.22	peak
6	17711.250	28.54	23.33	51.87	74.00	-22.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8226.500	37.17	10.43	47.60	74.00	-26.40	peak
2	9352.625	37.19	11.23	48.42	74.00	-25.58	peak
3	11868.875	35.10	16.64	51.74	74.00	-22.26	peak
4	12667.750	35.06	16.82	51.88	74.00	-22.12	peak
5	14749.500	33.37	17.76	51.13	74.00	-22.87	peak
6	17421.125	29.94	21.89	51.83	74.00	-22.17	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-3 BAND

### ANTENNA 1 TEST RESULTS (WORST CASE)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8266.375	37.13	10.29	47.42	74.00	-26.58	peak
2	8967.625	37.08	11.40	48.48	74.00	-25.52	peak
3	11483.875	37.61	15.58	53.19	74.00	-20.81	peak
4	12619.625	34.99	16.83	51.82	74.00	-22.18	peak
5	13954.750	33.33	17.93	51.26	74.00	-22.74	peak
6	17994.500	28.39	24.02	52.41	74.00	-21.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9191.750	39.44	10.61	50.05	74.00	-23.95	peak
2	11492.125	38.62	15.59	54.21	74.00	-19.79	peak
3	11492.125	27.27	15.59	42.86	54.00	-11.14	AVG
4	12637.500	35.17	16.82	51.99	74.00	-22.01	peak
5	13949.250	33.31	17.94	51.25	74.00	-22.75	peak
6	14797.625	33.48	17.82	51.30	74.00	-22.70	peak
7	17297.375	29.58	22.17	51.75	74.00	-22.25	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9183.500	37.69	10.67	48.36	74.00	-25.64	peak
2	11570.500	38.48	15.74	54.22	74.00	-19.78	peak
3	11570.500	27.73	15.74	43.47	54.00	-10.53	AVG
4	12656.750	35.27	16.82	52.09	74.00	-21.91	peak
5	14727.500	33.51	17.73	51.24	74.00	-22.76	peak
6	16802.375	30.69	21.01	51.70	74.00	-22.30	peak
7	17173.625	29.63	22.33	51.96	74.00	-22.04	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9256.375	37.95	10.82	48.77	74.00	-25.23	peak
2	11569.125	39.67	15.73	55.40	74.00	-18.60	peak
3	11569.125	27.92	15.73	43.65	54.00	-10.35	AVG
4	11830.375	35.73	16.67	52.40	74.00	-21.60	peak
5	12696.625	34.73	16.81	51.54	74.00	-22.46	peak
6	13967.125	33.53	17.91	51.44	74.00	-22.56	peak
7	16684.125	32.87	20.87	53.74	74.00	-20.26	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9347.125	37.33	11.21	48.54	74.00	-25.46	peak
2	11650.250	40.49	16.03	56.52	74.00	-17.48	peak
3	11650.250	28.25	16.03	44.28	54.00	-9.72	AVG
4	12666.375	35.29	16.82	52.11	74.00	-21.89	peak
5	13913.500	32.87	17.98	50.85	74.00	-23.15	peak
6	15966.375	31.83	18.41	50.24	74.00	-23.76	peak
7	17175.000	29.11	22.33	51.44	74.00	-22.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9319.625	38.11	11.09	49.20	74.00	-24.80	peak
2	11650.250	39.12	16.03	55.15	74.00	-18.85	peak
3	11650.250	27.65	16.03	43.68	54.00	-10.32	AVG
4	12658.125	35.10	16.82	51.92	74.00	-22.08	peak
5	13938.250	33.11	17.95	51.06	74.00	-22.94	peak
6	16605.750	30.72	20.79	51.51	74.00	-22.49	peak
7	17210.750	29.60	22.44	52.04	74.00	-21.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### 8.3.2. 802.11n HT20 MIMO MODE


#### UNII-1 BAND

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8113.750	38.27	9.86	48.13	74.00	-25.87	peak
2	8988.250	36.67	11.60	48.27	74.00	-25.73	peak
3	11827.625	35.06	16.68	51.74	74.00	-22.26	peak
4	12590.750	35.04	16.81	51.85	74.00	-22.15	peak
5	13921.750	33.04	17.97	51.01	74.00	-22.99	peak
6	17214.875	32.56	22.42	54.98	74.00	-19.02	peak
7	17214.875	17.61	22.42	40.03	54.00	-13.97	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7893.750	37.56	9.24	46.80	74.00	-27.20	peak
2	9136.750	37.43	10.94	48.37	74.00	-25.63	peak
3	11831.750	35.35	16.67	52.02	74.00	-21.98	peak
4	12689.750	34.83	16.82	51.65	74.00	-22.35	peak
5	13875.000	33.10	18.04	51.14	74.00	-22.86	peak
6	16689.625	31.68	20.88	52.56	74.00	-21.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8219.625	37.26	10.46	47.72	74.00	-26.28	peak
2	9197.250	38.03	10.58	48.61	74.00	-25.39	peak
3	11886.750	35.12	16.62	51.74	74.00	-22.26	peak
4	13466.625	33.96	17.45	51.41	74.00	-22.59	peak
5	16648.375	30.79	20.84	51.63	74.00	-22.37	peak
6	17560.000	29.90	22.37	52.27	74.00	-21.73	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8787.500	37.34	9.77	47.11	74.00	-26.89	peak
2	9371.875	36.68	11.32	48.00	74.00	-26.00	peak
3	11728.625	35.18	16.38	51.56	74.00	-22.44	peak
4	12619.625	34.52	16.83	51.35	74.00	-22.65	peak
5	13872.250	33.13	18.03	51.16	74.00	-22.84	peak
6	16842.250	31.27	21.08	52.35	74.00	-21.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8227.875	36.70	10.43	47.13	74.00	-26.87	peak
2	8986.875	36.89	11.59	48.48	74.00	-25.52	peak
3	11736.875	34.90	16.42	51.32	74.00	-22.68	peak
4	12544.000	35.03	16.77	51.80	74.00	-22.20	peak
5	14431.875	33.88	17.88	51.76	74.00	-22.24	peak
6	17230.000	29.58	22.37	51.95	74.00	-22.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9021.250	36.61	11.60	48.21	74.00	-25.79	peak
2	11794.625	34.48	16.67	51.15	74.00	-22.85	peak
3	12240.125	34.82	16.44	51.26	74.00	-22.74	peak
4	12570.125	35.06	16.80	51.86	74.00	-22.14	peak
5	13466.625	34.01	17.45	51.46	74.00	-22.54	peak
6	17221.750	29.76	22.40	52.16	74.00	-21.84	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-2A BAND

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8119.250	37.18	9.90	47.08	74.00	-26.92	peak
2	9601.500	36.24	11.94	48.18	74.00	-25.82	peak
3	11837.250	35.23	16.67	51.90	74.00	-22.10	peak
4	12557.750	34.52	16.79	51.31	74.00	-22.69	peak
5	13954.750	33.66	17.93	51.59	74.00	-22.41	peak
6	17221.750	29.85	22.40	52.25	74.00	-21.75	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8233.375	37.17	10.41	47.58	74.00	-26.42	peak
2	9301.750	37.30	11.01	48.31	74.00	-25.69	peak
3	11727.250	34.69	16.38	51.07	74.00	-22.93	peak
4	12641.625	35.08	16.82	51.90	74.00	-22.10	peak
5	13446.000	33.81	17.45	51.26	74.00	-22.74	peak
6	16400.875	32.20	19.79	51.99	74.00	-22.01	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8225.125	36.72	10.43	47.15	74.00	-26.85	peak
2	9084.500	37.39	11.23	48.62	74.00	-25.38	peak
3	11757.500	35.34	16.51	51.85	74.00	-22.15	peak
4	12567.375	34.71	16.79	51.50	74.00	-22.50	peak
5	13921.750	33.39	17.97	51.36	74.00	-22.64	peak
6	17091.125	30.51	21.87	52.38	74.00	-21.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7873.125	37.53	9.29	46.82	74.00	-27.18	peak
2	9369.125	36.78	11.31	48.09	74.00	-25.91	peak
3	11834.500	35.07	16.66	51.73	74.00	-22.27	peak
4	12594.875	35.17	16.83	52.00	74.00	-22.00	peak
5	13925.875	33.16	17.97	51.13	74.00	-22.87	peak
6	16395.375	32.07	19.77	51.84	74.00	-22.16	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8112.375	38.48	9.84	48.32	74.00	-25.68	peak
2	8955.250	36.77	11.28	48.05	74.00	-25.95	peak
3	11837.250	35.42	16.67	52.09	74.00	-21.91	peak
4	12517.875	34.38	16.74	51.12	74.00	-22.88	peak
5	13857.125	33.73	18.05	51.78	74.00	-22.22	peak
6	17181.875	30.24	22.37	52.61	74.00	-21.39	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8230.625	37.58	10.42	48.00	74.00	-26.00	peak
2	8982.750	36.87	11.56	48.43	74.00	-25.57	peak
3	11837.250	34.71	16.67	51.38	74.00	-22.62	peak
4	12630.625	34.47	16.81	51.28	74.00	-22.72	peak
5	13950.625	34.39	17.94	52.33	74.00	-21.67	peak
6	17396.375	30.53	21.85	52.38	74.00	-21.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



## UNII-2C BAND

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7897.875	37.91	9.22	47.13	74.00	-26.87	peak
2	8973.125	37.35	11.46	48.81	74.00	-25.19	peak
3	11813.875	35.45	16.68	52.13	74.00	-21.87	peak
4	13861.250	33.07	18.04	51.11	74.00	-22.89	peak
5	16684.125	31.46	20.87	52.33	74.00	-21.67	peak
6	17716.750	29.26	23.36	52.62	74.00	-21.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8218.250	37.39	10.47	47.86	74.00	-26.14	peak
2	8742.125	38.70	9.75	48.45	74.00	-25.55	peak
3	11838.625	34.73	16.67	51.40	74.00	-22.60	peak
4	12626.500	35.52	16.83	52.35	74.00	-21.65	peak
5	16688.250	31.02	20.88	51.90	74.00	-22.10	peak
6	17235.500	29.76	22.36	52.12	74.00	-21.88	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	37.03	10.41	47.44	74.00	-26.56	peak
2	8991.000	36.87	11.63	48.50	74.00	-25.50	peak
3	11862.000	35.23	16.64	51.87	74.00	-22.13	peak
4	12581.125	35.02	16.81	51.83	74.00	-22.17	peak
5	13949.250	33.41	17.94	51.35	74.00	-22.65	peak
6	16857.375	31.66	21.11	52.77	74.00	-21.23	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8017.500	38.71	9.10	47.81	74.00	-26.19	peak
2	8947.000	37.23	11.21	48.44	74.00	-25.56	peak
3	11346.375	35.94	15.29	51.23	74.00	-22.77	peak
4	11811.125	35.22	16.69	51.91	74.00	-22.09	peak
5	12549.500	35.16	16.77	51.93	74.00	-22.07	peak
6	17672.750	29.56	23.06	52.62	74.00	-21.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8227.875	36.87	10.43	47.30	74.00	-26.70	peak
2	9442.000	36.46	11.57	48.03	74.00	-25.97	peak
3	11745.125	35.77	16.46	52.23	74.00	-21.77	peak
4	12544.000	34.70	16.77	51.47	74.00	-22.53	peak
5	13532.625	34.15	17.46	51.61	74.00	-22.39	peak
6	17707.125	29.22	23.30	52.52	74.00	-21.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8123.375	37.55	9.93	47.48	74.00	-26.52	peak
2	9120.250	38.35	11.03	49.38	74.00	-24.62	peak
3	11833.125	35.20	16.66	51.86	74.00	-22.14	peak
4	12659.500	35.24	16.82	52.06	74.00	-21.94	peak
5	13424.000	33.95	17.43	51.38	74.00	-22.62	peak
6	16846.375	31.18	21.08	52.26	74.00	-21.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## STRADDLE CHANNEL 144

### HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9065.250	37.57	11.34	48.91	74.00	-25.09	peak
2	11862.000	35.51	16.64	52.15	74.00	-21.85	peak
3	12549.500	35.03	16.77	51.80	74.00	-22.20	peak
4	13861.250	33.30	18.04	51.34	74.00	-22.66	peak
5	16726.750	30.50	20.91	51.41	74.00	-22.59	peak
6	17252.000	29.93	22.31	52.24	74.00	-21.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7754.875	38.09	9.31	47.40	74.00	-26.60	peak
2	9151.875	37.67	10.85	48.52	74.00	-25.48	peak
3	11761.625	34.78	16.53	51.31	74.00	-22.69	peak
4	12688.375	34.88	16.82	51.70	74.00	-22.30	peak
5	13913.500	33.50	17.98	51.48	74.00	-22.52	peak
6	17731.875	29.01	23.46	52.47	74.00	-21.53	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-3 BAND****HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	36.93	10.41	47.34	74.00	-26.66	peak
2	9591.875	36.24	11.93	48.17	74.00	-25.83	peak
3	11490.750	36.99	15.58	52.57	74.00	-21.43	peak
4	12535.750	35.13	16.76	51.89	74.00	-22.11	peak
5	13858.500	33.23	18.04	51.27	74.00	-22.73	peak
6	16849.125	31.54	21.09	52.63	74.00	-21.37	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8981.375	36.31	11.54	47.85	74.00	-26.15	peak
2	9191.750	39.46	10.61	50.07	74.00	-23.93	peak
3	11490.750	37.58	15.58	53.16	74.00	-20.84	peak
4	12581.125	34.66	16.81	51.47	74.00	-22.53	peak
5	14770.125	33.05	17.79	50.84	74.00	-23.16	peak
6	16790.000	30.86	20.99	51.85	74.00	-22.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8934.625	37.03	11.08	48.11	74.00	-25.89	peak
2	11576.000	36.98	15.75	52.73	74.00	-21.27	peak
3	12607.250	35.68	16.83	52.51	74.00	-21.49	peak
4	13858.500	33.07	18.04	51.11	74.00	-22.89	peak
5	16428.375	31.97	19.93	51.90	74.00	-22.10	peak
6	17714.000	29.18	23.34	52.52	74.00	-21.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8086.250	37.29	9.63	46.92	74.00	-27.08	peak
2	9256.375	38.26	10.82	49.08	74.00	-24.92	peak
3	11569.125	36.89	15.73	52.62	74.00	-21.38	peak
4	12634.750	34.70	16.82	51.52	74.00	-22.48	peak
5	14805.875	33.68	17.82	51.50	74.00	-22.50	peak
6	17219.000	30.00	22.41	52.41	74.00	-21.59	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7814.000	38.00	9.44	47.44	74.00	-26.56	peak
2	8981.375	36.81	11.54	48.35	74.00	-25.65	peak
3	11651.625	38.06	16.03	54.09	74.00	-19.91	peak
4	11651.625	24.29	16.03	40.32	54.00	-13.68	AVG
5	12621.000	35.22	16.83	52.05	74.00	-21.95	peak
6	13862.625	33.71	18.04	51.75	74.00	-22.25	peak
7	16850.500	31.56	21.09	52.65	74.00	-21.35	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8247.125	36.72	10.36	47.08	74.00	-26.92	peak
2	9319.625	38.59	11.09	49.68	74.00	-24.32	peak
3	11644.750	36.59	15.99	52.58	74.00	-21.42	peak
4	12534.375	35.19	16.76	51.95	74.00	-22.05	peak
5	17260.250	29.93	22.29	52.22	74.00	-21.78	peak
6	17582.000	30.18	22.48	52.66	74.00	-21.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### 8.3.3. 802.11n HT40 MIMO MODE

#### UNII-1 BAND

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8981.375	37.67	11.54	49.21	74.00	-24.79	peak
2	11419.250	35.72	15.47	51.19	74.00	-22.81	peak
3	11723.125	36.42	16.35	52.77	74.00	-21.23	peak
4	12607.250	36.31	16.83	53.14	74.00	-20.86	peak
5	13941.000	34.03	17.95	51.98	74.00	-22.02	peak
6	16406.375	32.73	19.83	52.56	74.00	-21.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8225.125	37.73	10.43	48.16	74.00	-25.84	peak
2	9000.625	37.36	11.72	49.08	74.00	-24.92	peak
3	11812.500	35.34	16.69	52.03	74.00	-21.97	peak
4	12647.125	35.36	16.83	52.19	74.00	-21.81	peak
5	13916.250	34.06	17.98	52.04	74.00	-21.96	peak
6	17917.500	28.29	23.99	52.28	74.00	-21.72	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9289.375	38.05	10.95	49.00	74.00	-25.00	peak
2	11342.250	36.29	15.28	51.57	74.00	-22.43	peak
3	11695.625	35.78	16.24	52.02	74.00	-21.98	peak
4	12601.750	35.28	16.83	52.11	74.00	-21.89	peak
5	13947.875	34.26	17.95	52.21	74.00	-21.79	peak
6	16744.625	31.70	20.94	52.64	74.00	-21.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8982.750	37.48	11.56	49.04	74.00	-24.96	peak
2	11360.125	36.21	15.33	51.54	74.00	-22.46	peak
3	11746.500	35.57	16.46	52.03	74.00	-21.97	peak
4	12611.375	35.06	16.82	51.88	74.00	-22.12	peak
5	17236.875	30.65	22.35	53.00	74.00	-21.00	peak
6	17692.000	30.30	23.19	53.49	74.00	-20.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

## UNII-2A BAND

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9389.750	37.07	10.07	47.14	74.00	-26.86	peak
2	11833.125	34.47	17.30	51.77	74.00	-22.23	peak
3	12706.250	34.97	16.87	51.84	74.00	-22.16	peak
4	13505.125	33.33	18.41	51.74	74.00	-22.26	peak
5	17047.125	31.49	18.81	50.30	74.00	-23.70	peak
6	17961.500	28.09	23.27	51.36	74.00	-22.64	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8223.750	37.08	8.62	45.70	74.00	-28.30	peak
2	9575.375	36.37	10.47	46.84	74.00	-27.16	peak
3	11796.000	34.29	17.33	51.62	74.00	-22.38	peak
4	12427.125	34.83	16.83	51.66	74.00	-22.34	peak
5	13506.500	33.43	18.41	51.84	74.00	-22.16	peak
6	17942.250	27.87	23.22	51.09	74.00	-22.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.