

RF Exposure Evaluation

E.U.T. : Transmitter

Model Number : 171XPR


Applicant : Nutek Corporation

Address : No.167, Lane 235, Bauchiau Rd., Xindian District,
New Taipei City 23145, Taiwan


Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,
Taiwan 244, R.O.C.

Report Issued : 2017/07/11

Project Engineer : 

Elli Chang

Approved: 

Jerry Liu

1 RF Exposure Evaluation

Portable Device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498_D01_V06 4.3.1(a) SAR exclusion thresholds by:
[max. power of channel, including tune-up tolerance, mW]/(min, test separation distances, mm)]* $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Maximum measured transmitter power

Frequency Range (MHz)	Maximum measured transmitter power (dBm)	Tune-up power tolerance (dB)	Total Maximum power (dBm)	Total Maximum power (mW)
909.6	1.15	(±)2	3.15	2.065
913.8	1.08	(±)2	3.08	2.032
918.0	1.12	(±)2	3.12	2.051

$$(2.065/5)*(\sqrt{0.9096})=0.394 \leq 7.5$$

Conclusion:

No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A