

## Maximum Permissible Exposure Report

### 1. Product Information

FCC ID:	2AUIUWSHB1
Product name	WYZE Sense Hub
Test Model	WSHB1
Model List No.	WSHB1
Power Supply	DC 5V/1A Adapter parameters: Input: AC 100-240V 50/60Hz 0.25A Output: DC 5V/1A
Bluetooth	2402-2480MHz
Channel Number	40 channels for Bluetooth V5.0 (BT LE)
Channel Spacing	2MHz for Bluetooth V5.0 (BT LE)
Modulation Type	GFSK for V5.0 (BT LE)
WIFI(2.4G Band)	2412MHz-2462MHz
Channel Spacing	5MHz
Channel Number	11 channels for 20MHz bandwidth (2412~2462MHz) 7 channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	IEEE 802.11b: DSSS (CCK,DQPSK,DBPSK); IEEE 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
906.8	906.8 MHz
Modulation Type	ASK
Antenne Description	Antenna 3: External Antenna for 906.8, 1.3 dBi; Antenna 1: External Antenna for 2.4G WIFI, 1.3 dBi Antenna 2: Internal Antenna for Bluetooth, 1.3 dBi
Hardware version	GW3U-P1.0-V1.8
Software version	4.32.2.62
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Fixed Equipment

### 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

#### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

WSHB1 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 2	Internal antenna	2402 MHz – 2480 MHz	1.3 dBi
Antenna 1	External antenna	2412 MHz – 2462 MHz	1.3 dBi
Antenna 3	External antenna	906.8 MHz	1.3 dBi

## 6. Conducted Power

### BT LE

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	18.394
	12	2426	18.305
	39	2480	18.027

### 2.4G WLAN

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)
IEEE 802.11b	1	2412	17.21
	6	2437	17.14
	11	2462	18.01
IEEE 802.11g	1	2412	19.13
	6	2437	19.82
	11	2462	18.9
IEEE 802.11n HT20	1	2412	18.48
	6	2437	18.52
	11	2462	18.23
IEEE 802.11n HT40	3	2422	17.98
	6	2437	18.32
	9	2452	18.16

## 7. Manufacturing Tolerance

### BT LE

GFSK (Peak)			
Channel	Channel 0	Channel 12	Channel 39
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### WIFI(2.4G Band)

IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	19.0	19.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

## 8. Measurement Results

### 8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
GFSK	19.00	79.4328	1.3	1.35	100%	0.0213	1.0000
IEEE 802.11b	19.00	79.4328	1.3	1.35	100%	0.0213	1.0000
IEEE 802.11g	20.00	100.0000	1.3	1.35	100%	0.0269	1.0000
IEEE 802.11n HT20	19.00	79.4328	1.3	1.35	100%	0.0213	1.0000
IEEE 802.11n HT40	19.00	79.4328	1.3	1.35	100%	0.0213	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

### 8.2 Simultaneous Transmission MPE

The sample support 906.8, Bluetooth and 2.4G WLAN modular, 906.8, Bluetooth and 2.4G WLAN share different antenna, need consider simultaneous transmission;

Maximum Simultaneous transmission SAR Ratio for BT and 2.4G WLAN;

MPE Ratio <sub>BT</sub>	MPE Ratio <sub>2.4GWIFI</sub>	ΣMPE ratios	Limit	Results
< 0.0213	< 0.0269	< 0.0482	1.0	PASS

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----