



FCC PART 15 TEST REPORT No.I20Z62284-IOT04

for

TCL Communication Ltd.

HSUPA/HSDPA/UMTS 7 Bands/GSM Quad Bands/LTE 13 bands

mobile phone

T782P

With

FCC ID: 2ACCJN051

Hardware Version: 03

Software Version: 5EID

Issued Date: 2021-01-15

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I20Z62284-IOT04	Rev.0	1st edition	2021-01-15

CONTENTS

CONTENTS	3
1. TEST LATORATORY.....	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATE	5
1.5. SIGNATURE	6
2. CLIENT INFORMATION.....	7
2.1 APPLICANT INFORMATION	7
2.2 MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARYEQUIPMENT(AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
3.4. GENERAL DESCRIPTION.....	9
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	9
4. REFERENCE DOCUMENTS	9
4.1. DOCUMENTS SUPPLIED BY APPLICANT	9
4.2. REFERENCE DOCUMENTS FOR TESTING.....	9
5. LABORATORY ENVIRONMENT.....	10
6. SUMMARY OF TEST RESULTS	10
6.1. SUMMARY OF TEST RESULTS.....	10
6.2. STATEMENTS.....	10
6.3. TEST CONDITIONS	10
7. TEST EQUIPMENTS UTILIZED	11
8. MEASUREMENT UNCERTAINTY	12
8.1 TRANSMITTER OUTPUT POWER.....	12
8.2 PEAK POWER SPECTRAL DENSITY	12
8.3 OCCUPIED CHANNEL BANDWIDTH	12
8.4 BAND EDGES COMPLIANCE	12
8.5 SPURIOUS EMISSIONS	12
8.6 AC POWER-LINE CONDUCTED EMISSION	12
ANNEX A: EUT PARAMETERS.....	12
ANNEX B: MEASUREMENT RESULTS.....	13
B.1. MEASUREMENT METHOD	13

B.2. MAXIMUM OUTPUT POWER.....	14
B.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	16
B.4. OCCUPIED 26DB BANDWIDTH(CONDUCTED).....	17
B.5. BAND EDGES COMPLIANCE	33
B.5.1 BAND EDGES - RADIATED	33
B.6. TRANSMITTER SPURIOUS EMISSION.....	46
B.7. AC POWERLINE CONDUCTED EMISSION (150kHz- 30MHz)	87
B.8. 99% OCCUPIED BANDWIDTH	90
B.9. POWER CONTROL	95
ANNEX C: ACCREDITATION CERTIFICATE	96

1. TEST LATORATORY

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Location 2: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

1.3. Testing Environment

Normal Temperature: 15-35℃


Relative Humidity: 20-75%

1.4. Project date


Testing Start Date: 2020-12-22

Testing End Date: 2021-01-15


1.5. Signature



Xie Xiuzhen
(Prepared this test report)



Zheng Wei
(Reviewed this test report)



Hu Xiaoyu
(Approved this test report)

2. CLIENT INFORMATION

2.1 Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

2.2 Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: 0086-755-36611722
Fax: 0086-755-36612000-81722

3. EQUIPMENT UNDER TEST (EUT) AND

ANCILLARY EQUIPMENT (AE)

3.1. About EUT

Description	HSUPA/HSDPA/UMTS 7 Bands/GSM Quad Bands/LTE 14 bands mobile phone
Model name	T782P
FCC ID	2ACCJN051
WLAN Frequency Band	ISM Bands: -5150MHz~5250MHz -5250MHz~5350MHz -5470MHz~5725MHz
Type of modulation	OFDM
Antenna	Integral Antenna
Voltage	3.85V

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	352430520005383	03	5EID
EUT2	352430520005862	03	5EID

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Charger	/
AE2	USB cable	/
AE3	Battery	/
AE1		
Model	S008ACM0500200	
Manufacturer	TENPAO	
Length of cable	/	
AE2		
Model	CDA0000123C2	
Manufacturer	Shenghua	
Length of cable	/	
AE3		
Model	TLp043D1	
Manufacturer	BYD	
Capacitance	4360mAh	
Nominal voltage	3.85v	

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of HSUPA/HSDPA/UMTS 7 Bands/GSM Quad Bands/LTE 14 bands mobile phone with integrated antenna and inbuilt battery.

It has Bluetooth (EDR)function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2018
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	P
Peak Power Spectral Density	15.407	/	P
Occupied 26dB Bandwidth	15.403	/	P
Band edge compliance (Radiated)	15.209	/	P
Transmitter spurious emissions (Radiated)	15.407	/	P
AC Powerline Conducted Emission (150kHz- 30MHz)	15.407	/	P
99% Occupied bandwidth	/	/	P
Transmit Power Control	15.407	/	NA

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.85V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-06
2	LISN	ENV216	101200	R&S	1 year	2021-02-26
3	Test Receiver	ESCI	100344	R&S	1 year	2021-05-19
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2021-03-03
2	BiLog Antenna	VULB9163	9163-1223	Schwarzbeck	1 year	2021-03-18
3	Dual-Ridge Waveguide Horn Antenna	3115	6914	ETS-Lindgren	1 year	2021-01-14
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2021-08-05

8. Measurement Uncertainty

8.1 Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2 Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3 Occupied Channel Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4 Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5 Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.16
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.44
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.28

8.6 AC Power-line Conducted Emission

8.7 Measurement Uncertainty : 3.08dB,k=2

ANNEX A: EUT parameters


Disclaimer: the power worse case provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX B: MEASUREMENT RESULTS

B.1. Measurement Method

B.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




B.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

B.2. Maximum output Power

Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm
	5250MHz~5350MHz	24dBm or 11+10logB
	5470MHz~5725MHz	24dBm or 11+10logB

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-2 is made according to KDB 789033

Measurement Results:

Duty Cycle

Mode	802.11a	802.11n-HT20	802.11ac-HT20	802.11n-HT40	802.11ac-HT40	802.11ac-HT80
Duty Cycle	98%	98%	98%	98%	98%	98%

802.11a mode

Mode	Data Rate	Test Result (dBm)								
		Frequency (MHz)								
		5180	5200	5240	5260	5280	5320	5500	5580	5700
802.11a	6Mbps	15.62	15.77	16.21	16.45	16.56	16.02	16.58	15.35	16.63

The data rate 6Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate	Test Result (dBm)								
		Frequency (MHz)								
		5180	5200	5240	5260	5280	5320	5500	5580	5700
802.11n-HT20	MCS0	14.29	14.44	14.98	15.25	15.38	14.98	15.38	14.18	15.40

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT20 mode

Mode	Data Rate	Test Result (dBm)								
		Frequency (MHz)								
		5180	5200	5240	5260	5280	5320	5500	5580	5700
802.11ac-HT20	MCS0	13.99	14.01	14.51	14.72	14.92	14.47	14.97	13.77	15.06

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate	Test Result (dBm)						
		Frequency (MHz)						
		5190	5230	5270	5310	5510	5550	5670
802.11n(HT40)	MCS0	15.25	14.87	15.20	15.11	14.52	14.74	14.97

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT40 mode

Mode	Data Rate	Test Result (dBm)						
		Frequency (MHz)						
		5190	5230	5270	5310	5510	5550	5670
802.11n(HT40)	MCS0	14.43	14.78	15.30	15.30	15.40	14.84	14.77

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

802.11ac-HT80 mode

Mode	Rate	Test Result (dBm)			
		Frequency (MHz)			
		5210	5290	5530	5610
802.11ac(HT80)	MCS0	14.31	14.38	13.87	13.96

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

B.3. Peak Power Spectral Density (conducted)

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11
	5250MHz~5350MHz	11
	5470MHz~5725MHz	11

The output power measurement method Section F is made according to KDB 789033

Measurement Results:

Mode	Frequency	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	4.58	P
	5200 MHz	5.44	P
	5240 MHz	4.80	P
	5260 MHz	6.05	P
	5280 MHz	4.06	P
	5320 MHz	4.54	P
	5500 MHz	4.30	P
	5580 MHz	4.65	P
	5700 MHz	4.73	P
802.11n HT20	5180 MHz	3.83	P
	5200 MHz	3.92	P
	5240 MHz	2.61	P
	5260 MHz	3.53	P
	5280 MHz	3.28	P
	5320 MHz	3.11	P
	5500 MHz	2.82	P
	5580 MHz	3.11	P
	5700 MHz	3.21	P
802.11ac HT40	5190 MHz	0.77	P
	5230 MHz	0.28	P
	5270 MHz	0.47	P
	5310 MHz	0.31	P
	5510 MHz	-0.26	P
	5550 MHz	-0.15	P
	5670 MHz	0.19	P
802.11ac HT80	5210MHz	-3.30	P
	5290MHz	-2.68	P
	5530MHz	-2.82	P
	5610MHz	-2.98	P

Conclusion: PASS

B.4. Occupied 26dB Bandwidth(conducted)

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Frequency	Occupied 26dB Bandwidth (MHz)		conclusion
802.11a	5180 MHz	Fig.1	24.30	P
	5200 MHz	Fig.2	23.35	P
	5240 MHz	Fig.3	23.75	P
	5260 MHz	Fig.4	23.45	P
	5280 MHz	Fig.5	23.50	P
	5320 MHz	Fig.6	23.90	P
	5500 MHz	Fig.7	23.80	P
	5580 MHz	Fig.8	23.45	P
	5700 MHz	Fig.9	23.55	P
802.11n HT20	5180 MHz	Fig.10	25.55	P
	5200 MHz	Fig.11	24.55	P
	5240 MHz	Fig.12	25.10	P
	5260 MHz	Fig.13	24.10	P
	5280 MHz	Fig.14	24.50	P
	5320 MHz	Fig.15	24.15	P
	5500 MHz	Fig.16	24.00	P
	5580 MHz	Fig.17	24.00	P
	5700 MHz	Fig.18	24.10	P

802.11ac HT40	5190 MHz	Fig.19	41.44	P
	5230 MHz	Fig.20	41.68	P
	5270 MHz	Fig.21	41.52	P
	5310 MHz	Fig.22	41.68	P
	5510 MHz	Fig.23	41.52	P
	5550 MHz	Fig.24	41.60	P
	5670 MHz	Fig.25	41.76	P

802.11ac HT80	5210MHz	Fig.26	83.84	P
	5290MHz	Fig.27	84.48	P
	5530MHz	Fig.28	83.84	P

	5610MHz	Fig.29	84.16	P
--	---------	--------	-------	---

Conclusion: PASS

Test graphs as below:



Fig.1 Occupied 26dB Bandwidth (802.11a, 5180MHz)




Fig.2 Occupied 26dB Bandwidth (802.11a, 5200MHz)




Fig.3 Occupied 26dB Bandwidth (802.11a, 5240MHz)



Fig.4 Occupied 26dB Bandwidth (802.11a, 5260MHz)




Fig.5 Occupied 26dB Bandwidth (802.11a, 5280MHz)



Fig.6 Occupied 26dB Bandwidth (802.11a, 5320MHz)




Fig.7 Occupied 26dB Bandwidth (802.11a, 5500MHz)




Fig.8 Occupied 26dB Bandwidth (802.11a, 5580MHz)




Fig.9 Occupied 26dB Bandwidth (802.11a, 5700MHz)




Fig.10 Occupied 26dB Bandwidth (802.11n-HT20, 5180MHz)




Fig.11 Occupied 26dB Bandwidth (802.11n-HT20, 5200MHz)




Fig.12 Occupied 26dB Bandwidth (802.11n-HT20, 5240MHz)




Fig.13 Occupied 26dB Bandwidth (802.11n-HT20, 5260MHz)




Fig.14 Occupied 26dB Bandwidth (802.11n-HT20, 5280MHz)




Fig.15 Occupied 26dB Bandwidth (802.11n-HT20, 5320MHz)




Fig.16 Occupied 26dB Bandwidth (802. 11n-HT20, 5500MHz)




Fig.17 Occupied 26dB Bandwidth (802. 11n-HT20, 5580MHz)




Fig.18 Occupied 26dB Bandwidth (802. 11n-HT20, 5700MHz)




Fig.19 Occupied 26dB Bandwidth (802.11ac-HT40, 5190MHz)




Fig.20 Occupied 26dB Bandwidth (802.11ac-HT40, 5230MHz)




Fig.21 Occupied 26dB Bandwidth (802.11ac-HT40, 5270MHz)




Fig.22 Occupied 26dB Bandwidth (802.11ac-HT40, 5310MHz)




Fig.23 Occupied 26dB Bandwidth (802. 11ac-HT40, 5510MHz)




Fig.24 Occupied 26dB Bandwidth (802. 11ac-HT40, 5550MHz)




Fig.25 Occupied 26dB Bandwidth (802. 11ac-HT40, 5670MHz)




Fig.26 Occupied 26dB Bandwidth (802. 11ac-HT80, 5210MHz)




Fig.27 Occupied 26dB Bandwidth (802. 11ac-HT80, 5290MHz)




Fig.28 Occupied 26dB Bandwidth (802. 11ac-HT80, 5530MHz)




Fig.29 Occupied 26dB Bandwidth (802. 11ac-HT80, 5610MHz)

B.5. Band Edges Compliance

B.5.1 Band Edges - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)	Measurement distance(m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The measurement is made according to ANSI C63.10-2013 and KDB 789033

Measurement Result:

Mode	Channel	Test Results	Conclusion
802.11a	5180 MHz	Fig.30	P
	5320 MHz	Fig.31	P
	5500 MHz	Fig.32	P
	5700 MHz	Fig.33	P
802.11n HT20	5180 MHz	Fig.34	P
	5320 MHz	Fig.35	P
	5500 MHz	Fig.36	P
	5700 MHz	Fig.37	P
802.11n HT40	5190 MHz	Fig.38	P
	5310 MHz	Fig.39	P
	5510 MHz	Fig.40	P
	5670 MHz	Fig.41	P
802.11ac HT20	5180 MHz	Fig.42	P
	5320 MHz	Fig.43	P
	5500 MHz	Fig.44	P
	5700 MHz	Fig.45	P
802.11ac HT40	5190 MHz	Fig.46	P
	5310 MHz	Fig.47	P
	5510 MHz	Fig.48	P
	5670 MHz	Fig.49	P
802.11ac HT80	5210 MHz	Fig.50	P
	5290 MHz	Fig.51	P
	5530 MHz	Fig.52	P

Conclusion: PASS
Test graphs as below:




Fig.30 Band Edges (802.11a, 5180MHz)




Fig.31 Band Edges (802.11a, 5320MHz)




Fig.32 Band Edges (802.11a, 5500MHz)




Fig.33 Band Edges (802.11a, 5700MHz)

Full Spectrum




Fig.34 Band Edges (802.11n-HT20, 5180MHz)

Full Spectrum




Fig.35 Band Edges (802.11n-HT20, 5320MHz)




Fig.36 Band Edges (802.11n-HT20, 5500MHz)




Fig.37 Band Edges (802.11n-HT20, 5700MHz)

Full Spectrum




Fig.38 Band Edges (802.11n-HT40, 5190MHz)

Full Spectrum




Fig.39 Band Edges (802.11n-HT40, 5310MHz)

Full Spectrum




Fig.40 Band Edges (802.11n-HT40, 5510MHz)

Full Spectrum




Fig.41 Band Edges (802.11n-HT40, 5670MHz)

Full Spectrum




Fig.42 Band Edges (802.11ac-HT20, 5180MHz)

Full Spectrum




Fig.43 Band Edges (802.11ac-HT20, 5320MHz)




Fig.44 Band Edges (802.11ac-HT20, 5500MHz)




Fig.45 Band Edges (802.11ac-HT20, 5700MHz)




Fig.46 Band Edges (802.11ac-HT40, 5190MHz)




Fig.47 Band Edges (802.11ac-HT40, 5310MHz)




Fig.48 Band Edges (802.11ac-HT40, 5510MHz)




Fig.49 Band Edges (802.11ac-HT40, 5670MHz)

Full Spectrum




Fig.50 Band Edges (802.11ac-HT80, 5210MHz)

Full Spectrum




Fig.51 Band Edges (802.11ac-HT80, 5290MHz)

Full Spectrum




Fig.52 Band Edges (802.11ac-HT80, 5530MHz)

B.6. Transmitter Spurious Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)	Measurement distance(m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The measurement is made according to ANSI C63.10-2013 and KDB 789033

Measurement Results:

802.11a mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11a	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n -HT20	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	38(5190MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	46(5230MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	54(5270MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	62(5310MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	102(5510MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	118(5590MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	134(5670MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	142(5710MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac -HT20	36(5180MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	40(5200MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	48(5240MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	52(5260MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	56(5280MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	64(5320MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	100(5500MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	120(5600MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	140(5700MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	144(5720MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT40	38(5190MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	46(5230MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	54(5270MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	62(5310MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	102(5510MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	118(5590MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	134(5670MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	142(5710MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

802.11ac-HT80 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac -HT80	42(5210MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	58(5290MHz)	30 MHz ~1 GHz	---	P
		1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
		18 GHz ~ 26.5 GHz	---	P
		26.5 GHz ~ 40 GHz	---	P
	106(5530MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P
	138(5690MHz)	1 GHz ~ 3 GHz	---	P
		3 GHz ~ 7 GHz	---	P
		7 GHz ~ 18 GHz	---	P

Conclusion: PASS

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea}+A_{Rpl}= P_{Mea}+Cable\ Loss+Antenna\ Factor$

AVERAGE Results:
802.11a
Channel 36

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17985.2	46.9	-25.5	46.7	25.7	54	7.1	V
17989.5	46.8	-25.5	46.7	25.6	54	7.2	V
17974.2	46.7	-25.5	46.7	25.5	54	7.3	V
17967.5	46.6	-25.5	46.7	25.4	54	7.4	V
17981.8	46.6	-25.5	46.7	25.4	54	7.4	V
5149.8	40.7	-27.6	33.7	34.6	54	13.3	H

Channel 40

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17978.5	46.7	-25.5	46.7	25.5	54	7.3	V
17983	46.7	-25.5	46.7	25.5	54	7.3	V
17991.2	46.7	-25.5	46.7	25.5	54	7.3	V
17961.5	46.6	-25.5	46.7	25.4	54	7.4	V
17985.7	46.6	-25.5	46.7	25.4	54	7.4	V
17989	46.6	-25.5	46.7	25.4	54	7.4	V

Channel 48

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17962	46.7	-25.5	46.7	25.5	54	7.3	V
17956.5	46.6	-25.5	46.7	25.4	54	7.4	V
17972.5	46.6	-25.5	46.7	25.4	54	7.4	V
17985.2	46.6	-25.5	46.7	25.4	54	7.4	V
17994	46.6	-25.5	46.7	25.4	54	7.4	V
17958.8	46.5	-25.5	46.7	25.3	54	7.5	V

Channel 52

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.8	46.4	-25.5	46.7	25.2	54	7.6	V
17977.5	46.3	-25.5	46.7	25.1	54	7.7	V
17956	46.2	-25.5	46.7	25	54	7.8	V
17971.4	46.2	-25.5	46.7	25	54	7.8	V
17988.5	46.2	-25.5	46.7	25	54	7.8	V
17991.2	46.2	-25.5	46.7	25	54	7.8	V

Channel 56

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17951.6	46.5	-25.5	46.7	25.3	54	7.5	V
17969.2	46.4	-25.5	46.7	25.2	54	7.6	V
17983	46.4	-25.5	46.7	25.2	54	7.6	V
17992.8	46.4	-25.5	46.7	25.2	54	7.6	V
17957.1	46.3	-25.5	46.7	25.1	54	7.7	V
17978.5	46.3	-25.5	46.7	25.1	54	7.7	V

Channel 64

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17994	46.4	-25.5	46.7	25.2	54	7.6	V
17971.4	46.3	-25.5	46.7	25.1	54	7.7	V
17978	46.3	-25.5	46.7	25.1	54	7.7	V
17979.7	46.3	-25.5	46.7	25.1	54	7.7	V
17990.1	46.3	-25.5	46.7	25.1	54	7.7	V
5350	42.5	-27.4	34	35.9	54	11.5	V

Channel 100

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17968.1	46.7	-25.5	46.7	25.5	54	7.3	V
17972.5	46.5	-25.5	46.7	25.3	54	7.5	V
17987.9	46.5	-25.5	46.7	25.3	54	7.5	V
17977.5	46.4	-25.5	46.7	25.2	54	7.6	V
17989	46.4	-25.5	46.7	25.2	54	7.6	V
5459.6	42.6	-27.2	34.2	35.6	54	11.4	V

Channel 120

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17981.8	46.6	-25.5	46.7	25.4	54	7.4	V
17949.4	46.5	-25.5	46.7	25.3	54	7.5	V
17976.9	46.5	-25.5	46.7	25.3	54	7.5	V
17948.3	46.4	-25.5	46.7	25.2	54	7.6	V
17997.2	46.4	-25.5	46.7	25.2	54	7.6	V
17998.9	46.4	-25.5	46.7	25.2	54	7.6	V

Channel 140

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17954.9	46.5	-25.5	46.7	25.3	54	7.5	V
17972	46.5	-25.5	46.7	25.3	54	7.5	V
17969.2	46.4	-25.5	46.7	25.2	54	7.6	V
17983	46.4	-25.5	46.7	25.2	54	7.6	V
17988.5	46.4	-25.5	46.7	25.2	54	7.6	V
5725.2	42.9	-27.1	34.3	35.7	54	11.1	V

Channel 144

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17978.5	46.7	-25.5	46.7	25.5	54	7.3	V
17983	46.6	-25.5	46.7	25.4	54	7.4	V
17956	46.5	-25.5	46.7	25.3	54	7.5	V
17979.7	46.5	-25.5	46.7	25.3	54	7.5	V
17991.2	46.5	-25.5	46.7	25.3	54	7.5	V
17984.6	46.4	-25.5	46.7	25.2	54	7.6	V

802.11n-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17969.8	46.8	-25.5	46.7	25.6	54	7.2	V
17968.7	46.7	-25.5	46.7	25.5	54	7.3	V
17965.9	46.6	-25.5	46.7	25.4	54	7.4	V
17967.5	46.6	-25.5	46.7	25.4	54	7.4	V
17978.5	46.6	-25.5	46.7	25.4	54	7.4	V
5137.1	39.9	-27.6	33.7	33.8	54	14.1	H

Channel 40

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17973	46.8	-25.5	46.7	25.6	54	7.2	V
17985.2	46.8	-25.5	46.7	25.6	54	7.2	V
17992.3	46.7	-25.5	46.7	25.5	54	7.3	V
17950	46.6	-25.5	46.7	25.4	54	7.4	V
17948.3	46.5	-25.5	46.7	25.3	54	7.5	V
17949.4	46.5	-25.5	46.7	25.3	54	7.5	V