	URI BUREAU VERITAS
	FCC Test Report
Report No.:	RFCCOG-WTW-P22060454-2
FCC ID:	2AH7L-UPSB
Test Model:	PAS600L
Series Model:	PAS600T, PAS600
Received Date:	Jun. 15, 2022
Test Date:	Sep. 15, 2022
Issued Date:	Oct. 28, 2022
Applicant:	Schneider Electric Industries SAS
Address:	Electropole Site - 38EQ1, 31 rue Pierre Mendes France, Eybens - 38050 Grenoble cedex 9
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
	Lin Kou Laboratories
Lab Address:	No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location:	No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration / Designation Number:	788550 / TW0003

TAF Testing Laboratory 2021

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance or the isonator or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

Re	Release Control Record				
1	Cer	tificate of Conformity	4		
2	Sur	nmary of Test Results	5		
	2.1	Modification Record	5		
3	Ger	neral Information	6		
	3.1	General Description of EUT	6		
	3.2	Description of Test Modes	7		
	0	3.2.1 Test Mode Applicability and Tested Channel Detail	8		
	3.3	Duty Cycle of Test Signal	8		
	3.4	Description of Support Units	9		
		3.4.1 Configuration of System under Test	9		
	3.5	General Description of Applied Standards and References	9		
4	Tes	t Types and Results	. 10		
			40		
	4.1	6 dB Bandwidth Measurement	10		
		4.1.1 Limits of 6 dB Bandwidth Measurement	10		
		4.1.2 Test Setup	10		
		4.1.5 Test Instruments	10		
		4.1.5 Deviation from Test Standard	10		
		4.1.6 EUT Operating Conditions	10		
		4.1.7 Test Result	11		
	4.2	Conducted Output Power Measurement	12		
		4.2.1 Limits of Conducted Output Power Measurement	. 12		
		4.2.2 Test Setup	. 12		
		4.2.3 Test Instruments	. 12		
		4.2.4 Test Procedures	12		
		4.2.5 Deviation from Test Standard	12		
		4.2.6 EUT Operating Conditions	12		
		4.2.7 Test Results	12		
	4.3	Power Spectral Density Measurement	. 13		
		4.3.1 Limits of Power Spectral Density Measurement	.13		
		4.3.2 Test Setup	13		
		4.3.3 Test Instruments	13		
		4.3.4 Test Procedure	12		
		4.3.6 EUT Operating Condition	13		
		4.3.7 Test Results	14		
	44	Conducted Out of Band Emission Measurement	15		
		4.4.1 Limits of Conducted Out of Band Emission Measurement	15		
		4.4.2 Test Setup	. 15		
		4.4.3 Test Instruments	. 15		
		4.4.4 Test Procedure	. 15		
		4.4.5 Deviation from Test Standard	15		
		4.4.6 EUT Operating Condition	15		
		4.4.7 Test Results	16		
Δr	open	dix – Information of the Testing Laboratories	. 17		
	-001				



Release Control Record

Issue No.	Description	Date Issued
RFCCOG-WTW-P22060454-2	Original Release	Oct. 28, 2022



1 Certificate of Conformity

Product:	EcoStruxure Panel Server Universal		
Brand:	Schneider Electric		
Test Model:	PAS600L		
Series Model:	PAS600T, PAS600		
Sample Status:	Identical Prototype		
Applicant: Schneider Electric Industries SAS			
Test Date: Sep. 15, 2022			
Standards:	47 CFR FCC Part 15, Subpart C (Section 15.247)		
	ANSI C63.10-2013		

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

ina wu

repared by :

Gina Liu / Specialist

in Jerem, 1

Date: Oct. 28, 2022

Oct. 28, 2022

Date:

Approved by :

Jeremy Lin / Project Engineer



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)						
FCC Clause	Test Item	Result	Remarks			
15.207	AC Power Conducted Emission	N/A	Refer to Note			
15.205 / 15.209 / 15.247(d) Radiated Emissions and Band Edge Measurement		N/A	Refer to Note			
15.247(d)	15.247(d) Antenna Port Emission		Meet the requirement of limit.			
15.247(a)(2) 6 dB Bandwidth		Pass	Meet the requirement of limit.			
15.247(b) Conducted power		Pass	Meet the requirement of limit.			
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.			
15.203	Antenna Requirement	Pass	Antenna connector is RP-SMA male not a standard connector.			

Note:

1. This report is a partial report, only antenna port conducted measurement tests were verified and recorded in this report. Other testing data please refer to report no.: RFBHBQ-WTW-P20090301C.

2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	EcoStruxure Panel Server Universal			
Brand	Schneider Electric			
Test Model PAS600L				
Series Model	PAS600T, PAS600			
Status of EUT	Identical Prototype			
	24Vdc for PAS600L			
Power Supply Rating	110-240Vac, 50-60Hz and 240Vdc for PAS600T			
	110-277Vac, 50-60Hz and 277Vdc for PAS600			
Modulation Type	O-QPSK			
Modulation Technology	DSSS			
Transfer Rate	250 kbps			
Operating Frequency	2405 ~ 2480 MHz			
Number of Channel	16			
Output Power	0.2328 mW			
Antenna Type	Refer to Note as below			
Antenna Connector	RP-SMA male for external antenna			
Accessory Device	External antenna (Brand: Schneider Electric; Model: PASA-ANT1)			
Data Cable Supplied	N/A			

Note:

 This report is prepared for FCC class II permissive change. The difference compared with the original report (BV CPS report no.: RFBHBQ-WTW-P20090301C) are reducing power setting and revise operating frequency and changing internal antenna gain. The output power is lowered via firmware/software settings only (and cannot be changed by end-user / any other third parties). Therefore, only antenna port conducted measurement tests were verified and recorded in this report.

2.	All models	are listed	as below.	Model:	PAS600L	is the	representative	for final	test.
----	------------	------------	-----------	--------	---------	--------	----------------	-----------	-------

Brand	Model	Difference			
	PAS600L	Power Supply Rating: 24Vdc			
Schneider Electric	PAS600T	(1) Power Supply Rating: 110-240Vac/dc with +/-10% tolerance(2) Without digital input			
	PAS600	(1) Power Supply Rating: 110 -277Vac/dc with +-/10% tolerance(2) Without digital input			

3. The EUT support 1TX diversity function in transmitter part.

4. The antenna information is listed as below.

No.	Туре	Ant. Type	Connector	Brand	Model	Gain (dBi)
1	Internal	PCB	-	Schneider Electric	U7_1	1.72
2	Internal	PCB	-	Schneider Electric	U8_1	1.48

5. Detail antenna specification please refer to antenna datasheet or an antenna gain measurement report.

6. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.



3.2 Description of Test Modes

16 channels are provided to this EUT:

Channel	Channel Frequency (MHz)		Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	17 2435		2475
18	2440	26	2480



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure	Applicable To	Description
Mode	APCM	Description
-	\checkmark	Antenna 2

Where APCM: Antenna Port Conducted Measurement

NOTE: "-"means no effect.

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type
-	11 to 26	11, 18, 26	OFDM	O-QPSK

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by	
APCM	25 deg. C, 65 % RH	24 Vdc	Wayne Lin	

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %





3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
1.	Load	N/A	N/A	N/A	N/A	
2.	DC Power Supply	Topward	33010D	807748	N/A	

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN Cable	1	1.5	N	0	
2.	LAN Cable	1	1.5	N	0	

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013 ANSI C63.10-2020

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.



4 Test Types and Results

4.1 6 dB Bandwidth Measurement

4.1.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

4.1.2 Test Setup



4.1.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Apr. 20, 2022	Apr. 19, 2023
Peak Power Analyzer KEYSIGHT	8990B	MY51000485	Jan. 18, 2022	Jan. 17, 2023
Wideband Power Sensor KEYSIGHT	N1923A	MY58020002	Jan. 17, 2022	Jan. 16, 2023

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 - 2. The test was performed in Oven room.

4.1.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW) \geq 3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.1.5 Deviation from Test Standard

No deviation.

4.1.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.1.7 Test Result

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
11	2405	1.67	0.5	Pass
18	2440	1.70	0.5	Pass
26	2480	1.68	0.5	Pass





4.2 Conducted Output Power Measurement

4.2.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

4.2.2 Test Setup



4.2.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.2.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.2.5 Deviation from Test Standard

No deviation.

4.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.2.7 Test Results

Channel	Freq. (MHz)	Peak Power		Average Power		Power Limit	
		(mW)	(mW)	(mW)	(dBm)	(dBm)	Pass / Fall
11	2405	0.1614	-7.92	0.04677	-13.30	30	Pass
18	2440	0.1774	-7.51	0.0798	-10.98	30	Pass
26	2480	0.2328	-6.33	0.1309	-8.83	30	Pass

4.3 Power Spectral Density Measurement

4.3.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.3.4 Test Procedure

- a. Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- 4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.





4.3.7 Test Results

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
11	2405	-26.78	8	Pass
18	2440	-24.43	8	Pass
26	2480	-22.27	8	Pass





4.4 Conducted Out of Band Emission Measurement

4.4.1 Limits of Conducted Out of Band Emission Measurement

Below -20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.3 to get information of above instrument.

4.4.4 Test Procedure

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW \geq 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.4.7 Test Results





Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26051924 Hsin Chu EMC/RF/Telecom Lab Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <u>service.adt@tw.bureauveritas.com</u> Web Site: <u>www.bureauveritas-adt.com</u>

The address and road map of all our labs can be found in our web site also.

--- END ----