





# **FCC Co-Location Test Report**

FCC ID : 2AU6R04011

Equipment : 802.11be (WiFi 7) Triple-Radio PoE Access

**Point** 

(Please refer to section 1.1.1 for more details)

Model No. : NWA130BE

(Please refer to section 1.1.1 for more details)

Brand Name : ZYXEL

Applicant : Zyxel Networks Corporation

Address : No.2 Industry East RD. IX, Hsinchu Science

Park, Hsinchu 30075, Taiwan, R.O.C

Standard : 47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

Received Date : Sep. 11, 2023

Tested Date : Dec. 13 ~ Dec. 18, 2023

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen/ Assistant Manager Gary Chang

Report No.: FR391101CO Page : 1 of 13



# **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	
1.2	The Equipment List	7
1.3	Test Standards	
1.4	Reference Guidance	8
1.5	Deviation from Test Standard and Measurement Procedure	8
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION	9
2.1	Testing Facility	9
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	10
3.1	Unwanted Emissions into Restricted Frequency Bands	10
4	TEST LABORATORY INFORMATION	13

Appendix A. Unwanted Emissions Into Restricted Frequency Bands



# **Release Record**

Report No.	Version	Description	Issued Date
FR391101CO	Rev. 01	Initial issue	Feb. 07, 2024

Report No.: FR391101CO Page : 3 of 13



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 40.67MHz 35.90 (Margin -4.10dB) - PK	Pass
15.209		Joseph Margan Model	

## **Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### **Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR391101CO Page: 4 of 13



# 1 General Description

# 1.1 Information

### 1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
ZYXEL	NWA130BE	802.11be (WiFi 7) Triple-Radio PoE Access Point	The difference
ZYXEL	WBE530	802.11be (WiFi 7) Triple-Radio unified Access Point	between the two models is marketing purpose.

Note: The above models, model **NWA130BE** was selected as a representative one for the final test and only its data was recorded in this report.

# 1.1.2 Specification of the Equipment under Test (EUT)

WLAN	
Operating Frequency	802.11b/g/n/ax/be: 2412 MHz ~ 2462 MHz 802.11a/n/ac/ax/be: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz, 5745 ~ 5825 MHz 5925 MHz ~ 6425 MHz; 6425 MHz ~ 6525 MHz; 6525 MHz ~ 6875 MHz; 6875 MHz ~ 7125 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac/ax/be: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM)

### 1.1.3 Antenna Details

#### For 2.4G

Ant.	Brand	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)
NO.			2400~2483.5		
1	A wintetle	DEA 40400 VO	PIFA	I I E I	1.77
2	Aristotle	RFA-12123-V2	PIFA	UFL	1.27

### For 5G

Ant.	I Brand   Model   Lyne   Connecto		Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)												
No.	Brana model Type		5150~5250	5250~5350	5470~5725	5725~5850	5850~5895									
1	Aristotle	RFA-12123-	DIEA	חובא	DIEA	PIFA	DIEA	DIEA	DIEA	DIEA	UFL	3.4	3.41	2.73	3.14	2.77
2	Ansiolie	V2	PIFA	UFL	5.14	5.14	4.77	4.77	4.4							

Report No.: FR391101CO Page: 5 of 13



### For 6G

Ant.	Brand	Model	Type	Connector	Operating	g Frequencies (	(MHz) / Antenna	Gain (dBi)	
No.	Brand	Model	Турс	Connector	5925~6425	6425~6525	6525~6875	6875~7125	
1	A riotatla	RFA-12123-V2	חוב	PIFA	DIEA	3.75	2.77	4.09	3.49
2	Aristotle	RFA-12123-V2	PIFA	UFL	1.11	2.45	2.75	2.75	

# 1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from AC adapter 56Vdc from POE
-------------------	---

Note: The above power supply are not bundled in market.

Report No.: FR391101CO Page : 6 of 13



# 1.2 The Equipment List

Test Item	Radiated Emission						
Test Site	966 chamber3 / (03CH03-WS)						
Tested Date	Dec. 13 ~ Dec. 18, 20	23					
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until		
Receiver	R&S	ESR3	101657	Mar. 03, 2023	Mar. 02, 2024		
Spectrum Analyzer	R&S	FSV40	101499	Mar. 16, 2023	Mar. 15, 2024		
Loop Antenna	R&S	HFH2-Z2	100330	Oct. 31, 2023	Oct. 30, 2024		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Jul. 04, 2023	Jul. 03, 2024		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Sep. 01, 2023	Aug. 31, 2024		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 30, 2023	Oct. 29, 2024		
Preamplifier	EMC	EMC02325	980187	Jul. 10, 2023	Jul. 09, 2024		
Preamplifier	EMC	EMC118A45SE	980897	Aug. 01, 2023	Jul. 31, 2024		
Preamplifier	EMC	EMC184045SE	980903	Jul. 17, 2023	Jul. 16, 2024		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 03, 2023	Oct. 02, 2024		
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Sep. 22, 2023	Sep. 21, 2024		
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Sep. 22, 2023	Sep. 21, 2024		
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Sep. 22, 2023	Sep. 21, 2024		
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Sep. 22, 2023	Sep. 21, 2024		
RF cable-8M	EMC	EMC104-SM-SM-80 00	181107	Sep. 22, 2023	Sep. 21, 2024		
HIGHPASS FILTER	WI	WHK3.1-18G-10SS	43	Sep. 27, 2023	Sep. 26, 2024		
Attenuator	Pasternack	PE7005-10	10-3	Sep. 27, 2023	Sep. 26, 2024		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		
Note: Calibration Inter	val of instruments liste	d above is one year.					

Report No.: FR391101CO Page : 7 of 13



# 1.3 Test Standards

47 CFR FCC Part 15.247 47 CFR FCC Part 15.407 ANSI C63.10-2013

### 1.4 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02
FCC KDB 662911 D01 Multiple Transmitter Output v02r01
FCC KDB 412172 D01 Determining ERP and EIRP v01r01
FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

# 1.5 Deviation from Test Standard and Measurement Procedure

None

# 1.6 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty			
Parameters	Uncertainty		
Unwanted Emission ≤ 1GHz	±3.96 dB		
Unwanted Emission > 1GHz	±4.51 dB		

Report No.: FR391101CO Page: 8 of 13



# 2 Test Configuration

# 2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)
Test Site	03CH03-WS
Address of Test Site	No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

FCC Designation No.: TW0009FCC site registration No.: 207696

➤ ISED#: 10807C

➤ CAB identifier: TW2732

# 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode		
Unwanted Emissions	2.4G 11b CH01 + 5G 11be EHT20 CH48 + 6G 11be EHT160 CH79		
NOTE: The selected channel is the maximum power channel of Wi-Fi mode.			

Report No.: FR391101CO Page: 9 of 13



# 3 Transmitter Test Results

# 3.1 Unwanted Emissions into Restricted Frequency Bands

# 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit					
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)		
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300		
0.490~1.705	24000/F(kHz)	33.8 - 23	30		
1.705~30.0	30	29	30		
30~88	100	40	3		
88~216	150	43.5	3		
216~960	200	46	3		
Above 960	500	54	3		

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Un-restricted band emissions above 1GHz Limit				
Operating Band	Limit			
5.15 - 5.25 GHz	e.i.r.p27 dBm [68.2 dBuV/m@3m]			
5.25 - 5.35 GHz	e.i.r.p27 dBm [68.2 dBuV/m@3m]			
5.47 - 5.725 GHz	e.i.r.p27 dBm [68.2 dBuV/m@3m]			
5.725 - 5.850 GHz	All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Report No.: FR391101CO Page: 10 of 13



Un-restricted band emissions above 1GHz Limit				
Operating Band	PK Limit	AV Limit		
5.925 – 7.125 GHz	e.i.r.p7 dBm [88.2 dBuV/m@3m]	e.i.r.p27 dBm [68.2 dBuV/m@3m]		

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

#### 3.1.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR391101CO Page: 11 of 13



# 3.1.3 Test Setup



### 3.1.4 Test Results

Refer to Appendix A.

Report No.: FR391101CO Page: 12 of 13



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No.30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan (R.O.C.)

#### Kwei Shan

Tel: 886-3-271-8666
No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

#### Kwei Shan Site II

Tel: 886-3-271-8640 No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0345

Email: ICC\_Service@icertifi.com.tw


==END==

Report No.: FR391101CO Page: 13 of 13



#### **POE** mode

# **Unwanted Emissions (Below 1GHz)**



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR391101CO Page No. : 1 of 6





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR391101CO Page No. : 2 of 6



### **Unwanted Emissions (Above 1GHz)**




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391101CO Page No. : 3 of 6





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391101CO Page No. : 4 of 6



### **Adapter mode**

### **Unwanted Emissions (Below 1GHz)**



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR391101CO Page No. : 5 of 6





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB/m)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR391101CO Page No. : 6 of 6