






F Test Report Report No.: R2006A0416-R3





























F Test Report Report No.: R2006A0416-R3





5.3 Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured.

The testing follows KDB 971168 D01 v03r01 Section 6.0

The EUT was connected to spectrum analyzer and system simulator via a power divider.

The band edges of low and high channels for the highest RF powers were measured.

RBW is set to 15 kHz, VBW is set to 51 kHz for LTE Band 4/66 (1.4MHz).

RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 4/66 (3MHz).

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 4/66/71 (5MHz).

RBW is set to 100 kHz, VBW is set to 300kHz for LTE Band 4/66/71 (10MHz).

RBW is set to 150 kHz, VBW is set to 510 kHz for LTE Band 4/66 (15MHz).

RBW is set to 200 kHz, VBW is set to 620 kHz for LTE Band 4/66 (20MHz)


RBW is set to 100 kHz, VBW is set to 300kHz for LTE Band 12(1.4MHz/3MHz/5MHz/10MHz). on spectrum analyzer.

Set spectrum analyzer with RMS detector.

The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

Checked that all the results comply with the emission limit line.

Test Setup



Limits

Rule Part 27.53(h) specifies that "for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be



attenuated below the transmitter power (P) in watts by at least 43 + 10 log₁₀ (P) dB"

Rule Part 27.53(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(m) (4)/ specifies that "for BRS and EBS stations. For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(4) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Example:

The limit line is derived from 43 + 10log (P) dB below the transmitter power P(Watts)

- = P(W)- [43 + 10log(P)] (dB)
- = [30 + 10log (P)] (dBm) [43 + 10log(P)] (dB) = -13dBm.


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U=0.684dB.



Test Result

All the test traces in the plots shows the test results clearly.



Report No.: R2006A0416-R3 LTE Band 4 QPSK 3MHz CH-Low, 100%RB LTE Band 4 QPSK 3MHz CH-High, 100%RB Clear Writ Clear Writ Span 10.00 MH: Sweep 13.7 ms (1001 pts LTE Band 4 QPSK 5MHz CH-Low, 1 RB LTE Band 4 QPSK 5MHz CH-High, 1 RB Ref 23.00 dBm Ref 23.00 dBm Max Hol Max Hol View/Blank Trace On View/Blank Trace On LTE Band 4 QPSK 5MHz CH-Low, 100%RB LTE Band 4 QPSK 5MHz CH-High, 100%RB RF SD & AC CORRECT RF | 50 Q AC | CORREC Center Freq 1.755000000 GHz Avg Type: RMS Avg|Hold>100/100 Avg Type: RMS Avg|Hold>100/10 Ref 23.00 dBm Ref 23.00 dBm Max Ho Max Ho Span 10.00 MH eep 4.73 ms (1001 pt

Report No.: R2006A0416-R3 LTE Band 4 QPSK 10MHz CH-Low, 1 RB LTE Band 4 QPSK 10MHz CH-High, 1 RB Clear Writ Clear Writ Span 10.00 MH Sweep 1.27 ms (1001 pt LTE Band 4 QPSK 10MHz CH-Low, 100%RB LTE Band 4 QPSK 10MHz CH-High, 100%RB Trig: Free Run Atten: 40 dB Select Trace Mkr1 1.755 00 G -28.716 dl Ref 23.00 dBm Ref 23.00 dBm Max Hol Max Hol View/Blank Trace On View/Blank Trace On LTE Band 4 QPSK 15MHz CH-Low, 1 RB LTE Band 4 QPSK 15MHz CH-High, 1 RB RF SD & AC CORRECT RF | 50 Q AC | CORREC Center Freq 1.755000000 GHz Avg Type: RMS Avg|Hold>100/100 Avg Type: RMS Avg|Hold>100/100 Ref 23.00 dBm Ref 23.00 dBm Max Ho Max Ho Span 10.00 MH reep 1.00 ms (1001 pt