

RF Exposure Report

Report No.: SA121015E01D

FCC ID: Q87-WAP300N

Test Model: WAP300N

Received Date: Apr. 28, 2016

Test Date: May 05, 2016

Issued Date: July 28, 2016

Applicant: LINKSYS LLC

Address: 121 Theory Drive, Irvine, CA 92617, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
3 Calculation Result of Maximum Conducted Power	6



A D T

Report Issue History Record

Issue No.	Reason for Change	Date Issued
SA121015E01	Original	Aug. 09, 2013
SA121015E01C	Upgrade the standard to section 15.407 under new rule for U-NII-1, U-NII-3 band.	May 09, 2016
SA121015E01D	Upgrade the standard to section 15.407 under new rule (16-24) for U-NII-3 band.	July 28, 2016

Release Control Record

Issue No.	Description	Date Issued
SA121015E01D	Original release.	July 28, 2016

1 Certificate of Conformity

Product: Selectable Dual-Band Wireless-N Access Point

Brand: Linksys

Test Model: WAP300N

Sample Status: MASS-PRODUCTION

Applicant: LINKSYS LLC

Test Date: May 05, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

July 28, 2016

Wendy Wu / Specialist

Approved by :



Date:

July 28, 2016

May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna Type	Gain (dBi) (Include cable loss)	Connector type	Frequency range (MHz to MHz)
Dipole	3.5	R-SMA	2400-2500 5150-5850

3 Calculation Result of Maximum Conducted Power

The data (Except UNII-3 band) was copied from the original test report (Report No.: SA121015E01C)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	420.632	6.51	20	0.37465	1
5180-5240	97.008	6.51	20	0.08640	1
5745-5825	72.789	6.51	20	0.06483	1

NOTE:

2.4GHz: Directional gain = 3.5dBi + 10log(2) = 6.51dBi

5GHz: Directional gain = 3.5dBi + 10log(2) = 6.51dBi

2.4GHz and 5GHz technology cannot transmit at same time.

--- END ---