



Test Report

FCC PART 15 SUBPART C 15.247

Test Report

On Behalf of

Shenzhen CTV Int Cloud Technology Co., Ltd

For

Baby Monitor

Model No.: ZY-BM1, ZY-BM2, ZY-BM3, Baby5, Baby6, Baby7, ZY-BM4,
ZY-BM5, ZY-BM6, Baby8, ZY-BM7, ZY-BM8, ZY-BM9, ZY-BB1, ZY-BB2,
ZY-BB3, ZY-BB4, ZY-BB5, ZY-BB6, ZY-BB7, ZY-BB8, ZY-BB9, ZY-BB10,
Baby1, Baby2, Baby3, Baby4, Baby9, Baby10

FCC ID: 2AZL7-ZY-BM1

Prepared For: Shenzhen CTV Int Cloud Technology Co., Ltd

501, Building A, Debaoli Industrial Park, Shangxue Technology City, Xinxue
Community, Bantian Street, Longgang District, Shenzhen, China

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone,
Baolong Street, Longgang District, Shenzhen, Guangdong, China

Date of Test: Apr. 08, 2024 ~ May 28, 2024

Date of Report: May 28, 2024

Report Number: DL-240606006ER



Test Result Certification

Applicant's Name: Shenzhen CTV Int Cloud Technology Co., Ltd

Address: 501, Building A, Debaoli Industrial Park, Shangxue Technology City,
Xinxue Community, Bantian Street, Longgang District, Shenzhen,
China

Manufacturer's Name.....: Shenzhen CTV Int Cloud Technology Co., Ltd

Address: 501, Building A, Debaoli Industrial Park, Shangxue Technology City,
Xinxue Community, Bantian Street, Longgang District, Shenzhen,
China

Product Description

Trade Mark.....: N/A

Product Name: Baby Monitor

Model and/or Type Reference ..: ZY-BM1, ZY-BM2, ZY-BM3, Baby5, Baby6, Baby7, ZY-BM4,
ZY-BM5, ZY-BM6, Baby8, ZY-BM7, ZY-BM8, ZY-BM9, ZY-BB1,
ZY-BB2, ZY-BB3, ZY-BB4, ZY-BB5, ZY-BB6, ZY-BB7, ZY-BB8,
ZY-BB9, ZY-BB10, Baby1, Baby2, Baby3, Baby4, Baby9, Baby10

Standards.....: **47 CFR FCC Part 15 Subpart C 15.247**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen DL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen DL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test:

Date (s) of Performance of Tests.....: **Apr. 08, 2024 ~ May 28, 2024**

Date of Issue: **May 28, 2024**

Test Result.....: **Pass**

Testing Engineer

Randy Xie

Randy Xie

Technical Manager

Jack Bu

Jack Bu

Authorized Signatory

Jade Yang

Jade Yang





Contents

Page

1	Test Summary	6
1.1	Test Description.....	6
1.2	Measurement Uncertainty	7
2	Information of the Test Laboratory	8
3	General Information.....	9
3.1	General Description of EUT	9
3.2	Carrier Frequency of Channels	10
3.3	Operation of EUT during Testing.....	10
3.4	Description of Test Conditions	11
3.5	Description of Test Setup	12
3.6	Description of Support Units.....	13
4	Equipments List for All Test Items.....	14
5	Test Result.....	15
5.1	Antenna Requirement.....	15
5.1.1	Standard Requirement.....	15
5.1.2	EUT Antenna	15
5.2	Conduction Emissions Measurement.....	16
5.2.1	Applied Procedures / Limit.....	16
5.2.2	Test Procedure	16
5.2.3	Test Setup.....	17
5.2.4	Test Results	18
5.3	Radiated Emissions Measurement.....	20
5.3.1	Applied Procedures / Limit.....	20
5.3.2	Test Setup.....	20
5.3.3	Test Result.....	22
5.4	Maximum Output Power Measurement.....	28
5.4.1	Limit.....	28
5.4.2	Test Procedure	28
5.4.3	Deviation from Standard	28
5.4.4	Test Setup.....	28
5.4.5	Test Results	28



5.5	Power Spectral Density	29
5.5.1	Limit.....	29
5.5.2	Test Procedure	29
5.5.3	Deviation from Standard	29
5.5.4	Test Setup.....	29
5.5.5	Test Results	30
5.6	6dB Bandwidth	32
5.6.1	Limit.....	32
5.6.2	Test Procedure	32
5.6.3	Deviation from Standard	32
5.6.4	Test Setup.....	32
5.6.5	Test Result.....	32
5.7	Occupied Bandwidth.....	34
5.7.1	Test Procedure	34
5.7.2	Deviation from Standard	34
5.7.3	Test Setup.....	34
5.7.4	Test Result.....	34
5.8	Band Edge.....	35
5.8.1	Limit.....	35
5.8.2	Test Procedure	35
5.8.3	Deviation from Standard	35
5.8.4	Test Setup.....	35
5.8.5	Test Results	36
5.9	Conducted Spurious Emissions	37
5.9.1	Applied Procedures / Limit.....	37
5.9.2	Test Procedure	37
5.9.3	Deviation from Standard	37
5.9.4	Test Setup.....	37
5.9.5	Test Results	38
6	Test Setup Photos	43
7	Photos of the EUT	45



**** Modified History ****

Revision	Description	Issued Data	Remark
Revision 1.0	Initial Test Report Release	May 28, 2024	



1 Test Summary

1.1 Test Description

Test Item	Test Requirement	Result
Antenna Requirement	§15.203/§15.247(b)(4)	PASS
Conducted Emission	FCC Part 15.207	PASS
Radiated Emissions	FCC Part 15.205/15.209	PASS
Maximum Peak Output Power	FCC Part 15.247(b)	PASS
Power Spectral Density	FCC Part 15.247 (e)	PASS
6dB Bandwidth & 99% Bandwidth	FCC Part 15.247(a)(2)	PASS
Spurious RF Conducted Emission	FCC Part 15.247(d)	PASS
Band Edge	FCC Part 15.247(d)	PASS



1.2 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	= 2.71dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.90dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 3.90dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.28dB, k=2



2 Information of the Test Laboratory

Shenzhen DL Testing Technology Co., Ltd.

Add.: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Testing Laboratory Authorization:

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118



3 General Information

3.1 General Description of EUT

EUT Name:	Baby Monitor
Model No:	ZY-BM1
Series Models:	ZY-BM2, ZY-BM3, Baby5, Baby6, Baby7, ZY-BM4, ZY-BM5, ZY-BM6, Baby8, ZY-BM7, ZY-BM8, ZY-BM9, ZY-BB1, ZY-BB2, ZY-BB3, ZY-BB4, ZY-BB5, ZY-BB6, ZY-BB7, ZY-BB8, ZY-BB9, ZY-BB10, Baby1, Baby2, Baby3, Baby4, Baby9, Baby10
Model Difference:	All model's the function, software and electric circuit are the same, only with product color and model named different. (ZY-BM1, ZY-BM2, ZY-BM3, Baby5, Baby6, Baby7, ZY-BM4, ZY-BM5, ZY-BM6, Baby8 are product color and model named different, other models are only product model named different.) Test sample model: ZY-BM1.
Trade Mark:	N/A
Operation Frequency:	905-925MHz
Modulation Technology:	OFDM
Hardware Version:	V1.0
Software Version:	V1.0
Antenna Type:	External antenna
Antenna Gain:	3.14dBi
Power Supply:	DC 5V from Type-C or DC3.7V from battery
Note: 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. Antenna gain Refer to the antenna specifications. 3. The cable loss data is obtained from the supplier. 4. The test results in the report only apply to the tested sample.	



3.2 Carrier Frequency of Channels

Description of Channel:					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905	6	915	11	925
2	907	7	917	12	
3	909	8	919	13	
4	911	9	921	14	
5	913	10	923	15	

3.3 Operation of EUT during Testing

Operating Mode

The mode is used: **Transmitting mode**

Low Channel: 905MHz

Middle Channel: 915MHz

High Channel: 925MHz



3.4 Description of Test Conditions

(1) E.U.T. test conditions:


For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

(2) Frequency range of radiated measurements:

The test range will be up to the tenth harmonic of the highest fundamental frequency.

(3) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.


(4) The duty cycle is 100%.





3.5 Description of Test Setup

Operation of EUT during Conducted and Radiation below 1GHz testing:



Operation of EUT during Above1GHz Radiation testing:



The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.



3.6 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model/Type No.	Specification	Note
1	Baby Monitor	N/A	ZY-BM1	N/A	EUT
2	USB Cable	N/A	N/A	Length: 1.5m	Accessory
3	Adapter	N/A	SA0051-0501000US	Input: AC100-240V, 50/60Hz, 0.2A Output: DC5V/1A, 5W	Accessory

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



4 Equipments List for All Test Items

Radiation test, Band-edge test and 20db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 04, 2023	Nov. 03, 2024
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 04, 2023	Nov. 03, 2024
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 04, 2023	Nov. 03, 2024
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 04, 2023	Nov. 03, 2024
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 04, 2023	Nov. 03, 2024
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 04, 2023	Nov. 03, 2024
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 04, 2023	Nov. 03, 2024
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 04, 2023	Nov. 03, 2024
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 04, 2023	Nov. 03, 2024
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 04, 2023	Nov. 03, 2024
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 04, 2023	Nov. 03, 2024
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 04, 2023	Nov. 03, 2024
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 04, 2023	Nov. 03, 2024
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 04, 2023	Nov. 03, 2024
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 04, 2023	Nov. 03, 2024
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 04, 2023	Nov. 03, 2024

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
2	EMI Receiver	R&S	ESR	101421	Nov. 04, 2023	Nov. 03, 2024
3	LISN	R&S	ENV216	102417	Nov. 04, 2023	Nov. 03, 2024
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 04, 2023	Nov. 03, 2024
5	10dB Attenuator	Schwarzbeck	VTSD9561F	00154	Nov. 04, 2023	Nov. 03, 2024

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



5 Test Result

5.1 Antenna Requirement

5.1.1 Standard Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is an External antenna, need professional installation, not easy to remove. It conforms to the standard requirements. The directional gains of antenna used for transmitting is 3.14dBi.

5.1.2 EUT Antenna





5.2 Conduction Emissions Measurement

5.2.1 Applied Procedures / Limit

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

5.2.2 Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.



5.2.3 Test Setup



Remark:

E.U.T: Equipment Under Test

LISN: Line Impedance Stabilization Network


Test table height=0.8m



5.2.4 Test Results

PASS

Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.4155	51.62	20.10	57.54	5.92	31.52	PK	L
2	0.5190	50.59	20.11	56.00	5.41	30.48	PK	L
3	1.3560	49.63	20.27	56.00	6.37	29.36	PK	L
4	2.6565	53.34	20.51	56.00	2.66	32.83	PK	L
5	4.2225	48.66	20.72	56.00	7.34	27.94	PK	L
6	11.8725	48.68	21.24	60.00	11.32	27.44	PK	L

Final Data List

NO.	Freq. [MHz]	Correction factor[dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	0.4171	20.10	50.59	57.51	6.92	30.49	34.09	47.51	13.42	13.99	L
2	0.5179	20.11	49.08	56.00	6.92	28.97	32.07	46.00	13.93	11.96	L
3	1.3527	20.26	46.39	56.00	9.61	26.13	30.66	46.00	15.34	10.40	L
4	2.6579	20.51	48.53	56.00	7.47	28.02	34.58	46.00	11.42	14.07	L
5	4.2447	20.72	42.59	56.00	13.41	21.87	30.50	46.00	15.50	9.78	L


Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.4200	47.15	20.19	57.45	10.30	26.96	PK	N
2	1.3605	44.73	20.34	56.00	11.27	24.39	PK	N
3	2.5845	48.78	20.56	56.00	7.22	28.22	PK	N
4	4.1280	43.21	20.76	56.00	12.79	22.45	PK	N
5	6.5400	43.35	20.95	60.00	16.65	22.40	PK	N
6	11.9580	44.57	21.22	60.00	15.43	23.35	PK	N

Final Data List

NO.	Freq. [MHz]	Correction factor[dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	2.5699	20.56	42.37	56.00	13.63	21.81	32.99	46.00	13.01	12.43	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



5.3 Radiated Emissions Measurement

5.3.1 Applied Procedures / Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Except when the requirements applicable to a given device state otherwise, emissions from license-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.


Radiated emission limits

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

5.3.2 Test Setup


Test Configuration:

- 1) 9 kHz to 30 MHz emissions:






2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 25 GHz emissions:

**Test Procedure**


1. The EUT was placed on turn table which is 0.8m above ground plane for below 1GHz test, and on a low permittivity and low loss tangent turn table which is 1.5m above ground plane for above 1GHz test.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.



5.3.3 Test Result

Below 1GHz Test Results:

Antenna polarity: H



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	103.79379	-14.69	32.68	17.99	43.50	25.51	100	352	Horizontal
2	208.65865	-15.01	45.33	30.32	43.50	13.18	100	296	Horizontal
3	261.09109	-13.28	40.01	26.73	46.00	19.27	100	356	Horizontal
4	286.33633	-12.36	42.62	30.26	46.00	15.74	100	359	Horizontal
5	443.63363	-8.65	39.96	31.31	46.00	14.69	100	301	Horizontal
6	845.61561	-1.48	52.56	51.08	46.00	-5.08	100	346	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	844.5371	-1.48	45.58	44.10	46.00	1.90	100	346	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;



Antenna polarity: V

**Suspected List**

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	77.577578	-18.02	45.70	27.68	40.00	12.32	100	326	Vertical
2	208.65865	-15.01	45.16	30.15	43.50	13.35	100	343	Vertical
3	717.44744	-4.22	37.35	33.13	46.00	12.87	100	349	Vertical
4	781.53153	-3.87	44.92	41.05	46.00	4.95	100	335	Vertical
5	844.64464	-1.53	42.25	40.72	46.00	5.28	100	324	Vertical
6	973.78378	-0.77	48.88	48.11	54.00	5.89	100	335	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level;

Harmonics and Spurious Emissions**Frequency Range (9 kHz-30MHz)**

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note:1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor.

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement.

**For 1GHz to 25GHz**

CH Low (905MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1810	55.13	-3.64	51.49	74	-22.51	peak
1810	41.29	-3.64	37.65	54	-16.35	AVG
2715	53.07	-0.95	52.12	74	-21.88	peak
2715	39.14	-0.95	38.19	54	-15.81	AVG

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1810	52.12	-3.64	48.48	74	-25.52	peak
1810	43.58	-3.64	39.94	54	-14.06	AVG
2715	50.06	-0.95	49.11	74	-24.89	peak
2715	40.29	-0.95	39.34	54	-14.66	AVG

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.



CH Middle (915MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1830	52.36	-3.51	48.85	74	-25.15	peak
1830	45.07	-3.51	41.56	54	-12.44	AVG
2745	51.29	-0.82	50.47	74	-23.53	peak
2745	42.58	-0.82	41.76	54	-12.24	AVG
Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.						

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1830	53.16	-3.51	49.65	74	-24.35	peak
1830	44.58	-3.51	41.07	54	-12.93	AVG
2745	51.63	-0.82	50.81	74	-23.19	peak
2745	41.29	-0.82	40.47	54	-13.53	AVG
Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.						



CH High (925MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1850	56.21	-3.43	52.78	74	-21.22	peak
1850	45.56	-3.43	42.13	54	-11.87	AVG
2775	53.64	-0.75	52.89	74	-21.11	peak
2775	46.38	-0.75	45.63	54	-8.37	AVG

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1850	55.75	-3.43	52.32	74	-21.68	peak
1850	42.31	-3.43	38.88	54	-15.12	AVG
2775	53.44	-0.75	52.69	74	-21.31	peak
2775	39.12	-0.75	38.37	54	-15.63	AVG

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Level-Limit.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) “F” denotes fundamental frequency; “H” denotes spurious frequency; “E” denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) The emissions are attenuated more than 20dB below the permissible limits are not record in the report.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
- (7) All modes of operation were investigated and the worst-case emissions are reported.



Band Edge Requirement:

Frequency (MHz)	Ant. Pol.	PK Reading (dBμV)	AV Reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin Peak(dB)
					Peak (dBμV/m)	AV (dBμV/m)			
902	H	55.16	---	-3.8	51.36	---	74	---	-22.64
902	H	55.08	---	-3.7	51.38	---	74	---	-22.62
928	V	54.52	---	-3.8	50.72	---	74	---	-23.28
928	V	53.44	---	-4.3	49.14	---	74	---	-24.86

Note:

1. Emission Level = Peak Reading + Correction Factor; Correction Factor = Antenna Factor + Cable loss – Pre-amplifier
2. Margin = Emission - Limit
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
5. Data of measurement shown “---“ in the above table mean that the reading of emissions is attenuated more than 20dB below the limits or the field strength is too small to be measured.



5.4 Maximum Output Power Measurement

5.4.1 Limit

The Maximum Peak Output Power Measurement is 30dBm.

5.4.2 Test Procedure


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The maximum Average conducted output power may be measured using a wideband RF power meter with a thermocouple detector or equivalent. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

5.4.3 Deviation from Standard

No deviation.

5.4.4 Test Setup



5.4.5 Test Results

Channel	Channel Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Low	905	27.62	30	Pass
Middle	915	28.14		Pass
High	925	29.21		Pass



5.5 Power Spectral Density

5.5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.5.2 Test Procedure

Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.

Set the RBW =3 kHz.

Set the VBW =10 KHz.

Set the span to 1.5 times the DTS channel bandwidth.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum power level.


If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

The resulting peak PSD level must be 8 dBm.

5.5.3 Deviation from Standard

No deviation.

5.5.4 Test Setup






5.5.5 Test Results


Channel	Channel Frequency (MHz)	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
Low	905	3.62	8.00	Pass
Middle	915	4.04		Pass
High	925	4.42		Pass

CH 01






CH 06



CH 11





5.6 6dB Bandwidth

5.6.1 Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.6.2 Test Procedure


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Deviation from Standard

No deviation.

5.6.4 Test Setup



5.6.5 Test Result

Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (KHz)	Result
905	1.752	≥ 500	Pass
915	1.800		Pass
925	1.752		Pass



5.7 Occupied Bandwidth

5.7.1 Test Procedure

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

RBW=1% to 5% of the OBW

VBW=approximately 3 X RBW

Detector=Peak

Trace Mode: Max Hold

Use the 99% power bandwidth function of the instrument to measure the Occupied Bandwidth and recorded.

5.7.2 Deviation from Standard

No deviation.

5.7.3 Test Setup



5.7.4 Test Result

N/A



5.8 Band Edge

5.8.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section (b)(3) of RSS 5.4(4), the attenuation required shall be 30 dB instead of 20 dB.


5.8.2 Test Procedure

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak, Trace = max hold

5.8.3 Deviation from Standard

No deviation.



5.8.4 Test Setup





5.8.5 Test Results

PASS





5.9 Conducted Spurious Emissions

5.9.1 Applied Procedures / Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section (b)(3) of RSS 5.4(4), the attenuation required shall be 30 dB instead of 20 dB.

For below 30MHz, For 9KHz-150kHz, 150K-10MHz, We use the RBW 1KHz, 10KHz, So the limit need to calculated by " $10\lg(BW1/BW2)$ ". for example For 9KHz-150kHz, RBW 1KHz, The Limit= the highest emission level-20- $10\lg(100/1)$ = the highest emission level-40.


5.9.2 Test Procedure

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak, Trace = max hold

5.9.3 Deviation from Standard

No deviation.

5.9.4 Test Setup







5.9.5 Test Results


PASS


CH 01







CH 06








CH 11










6 Test Setup Photos

Radiated Emission





Conducted Emission





7 Photos of the EUT

Reference to the reporter: ANNEX A of external photos and ANNEX B of internal photos

-----End of test report-----