

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an HEX RDC HxmdPrSrElStnrCrct EN GML2pkSLD operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

Modulation Type: GFSK.

The normal radiated output power (e.i.r.p) is: -1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -1.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 94.4dB μ V/m at 3m in the frequency 2466MHz

The EIRP = [(FS*D) ^2 / 30] mW = -0.83dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 92.0dB μ V/m at 3m in the frequency 2416MHz

The EIRP = [(FS*D) ^2 / 30] mW = -3.23dBm
which is within the production variation.

The maximum conducted output power specified is 2.0dBm= 1.585mW

The source- based time-averaging conducted output power
=1.585mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.466) mW

= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: PQN68126TX2G4