FCC TEST REPORT

(PART 22)

REPORT NO.:	RF140616C01
MODEL NO.:	0PCV220
FCC ID:	NM80PCV220
RECEIVED:	Jun. 16, 2014
TESTED:	Jun. 24, 2014 ~ Jul. 24, 2014
ISSUED:	Jul. 28, 2014

APPLICANT:	HTC Corporation
ADDRESS:	1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231

ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
LAB ADDRESS:	No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)
TEST LOCATION:	No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD 3
1 CERTIFICATION 4
2 SUMMARY OF TEST RESULTS 5
2.1 MEASUREMENT UNCERTAINTY 5
2.2 TEST SITE AND INSTRUMENTS 6
3 GENERAL INFORMATION 7
3.1 GENERAL DESCRIPTION OF EUT 7
3.2 CONFIGURATION OF SYSTEM UNDER TEST 8
3.3 DESCRIPTION OF SUPPORT UNITS 8
3.4 TEST ITEM AND TEST CONFIGURATION 9
3.5 EUT OPERATING CONDITIONS 12
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS 12
4 TEST TYPES AND RESULTS 13
4.1 OUTPUT POWER MEASUREMENT 13
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 13
4.1.2 TEST PROCEDURES 13
4.1.3 TEST SETUP 14
4.1.4 TEST RESULTS 15
4.2 FREQUENCY STABILITY MEASUREMENT 22
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT 22
4.2.2 TEST PROCEDURE 22
4.2.3 TEST SETUP 22
4.2.4 TEST RESULTS 23
4.3 OCCUPIED BANDWIDTH MEASUREMENT 24
4.3.1 TEST PROCEDURES 24
4.3.2 TEST SETUP 24
4.3.3 TEST RESULTS 25
4.4 BAND EDGE MEASUREMENT 28
4.4.1 LIMITS OF BAND EDGE MEASUREMENT 28
4.4.2 TEST SETUP 28
4.4.3 TEST PROCEDURES 28
4.4.4 TEST RESULTS 29
4.5 CONDUCTED SPURIOUS EMISSIONS 34
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 34
4.5.2 TEST PROCEDURE 34
4.5.3 TEST SETUP 34
4.5.4 TEST RESULTS 35
4.6 RADIATED EMISSION MEASUREMENT 37
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT 37
4.6.2 TEST PROCEDURES 37
4.6.3 DEVIATION FROM TEST STANDARD 37
4.6.4 TEST SETUP 38
4.6.5 TEST RESULTS 39
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 51
6 INFORMATION ON THE TESTING LABORATORIES 52
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 53

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140616C01	Original release	Jul. 28, 2014

1 CERTIFICATION

PRODUCT:	Smartphone
MODEL:	0PCV220
BRAND:	HTC
APPLICANT:	HTC Corporation
TESTED:	Jun. 24, 2014 ~ Jul. 24, 2014
TEST SAMPLE:	Production Unit
STANDARDS:	**FCC PART 22, Subpart H**

The above equipment (model: 0PCV220) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ **, DATE :** Jul. 28, 2014

Ivonne Wu / Supervisor

APPROVED BY : _____ **, DATE :** Jul. 28, 2014

Sam Chen / Senior Project Engineer

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	**TEST TYPE**	**RESULT**	**REMARK**
2.1046 22.913 (a)	Effective Radiated Power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -29.33dB at 36.75MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 15, 2014	Apr. 14, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2013	Dec. 20, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 27. 2014	Feb. 26, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 19, 2014	Feb. 18, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 18, 2013	Dec. 17, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
Communications Tester-Wireless	E5515C	MY52102544	Sep. 05, 2012	Sep. 04, 2014
Radio Communication Analyzer	MT8820C	6201300640	Aug. 01, 2013	Jul. 31, 2014

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC 7450F-10.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smartphone	
MODEL NO.	0PCV220	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (battery)	
MODULATION TYPE	**GSM/GPRS**	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	BPSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	**GSM/GPRS/EDGE**	824.2MHz ~ 848.8MHz
	WCDMA	826.4MHz ~ 846.6MHz
	LTE 5 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE 5 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE 5 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE 5 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
MAX. ERP POWER	**GSM**	601.17mW
	EDGE	548.28mW
	WCDMA	64.86mW
	LTE 5 (Channel Bandwidth: 1.4MHz)	41.30mW
	LTE 5 (Channel Bandwidth: 3MHz)	49.20mW
	LTE 5 (Channel Bandwidth: 5MHz)	55.98mW
	LTE 5 (Channel Bandwidth: 10MHz)	60.12mW
EMISSION DESIGNATOR	**GSM**	244KGXW
	EDGE	246KG7W
	WCDMA	4M17F9W
	LTE 5 (Channel Bandwidth: 1.4MHz)	1M08G7D
	LTE 5 (Channel Bandwidth: 3MHz)	2M68G7D
	LTE 5 (Channel Bandwidth: 5MHz)	4M49G7D
	LTE 5 (Channel Bandwidth: 10MHz)	8M93G7D
ANTENNA TYPE	Fixed Internal Antenna	
I/O PORTS	Refer to users' manual	
DATA CABLE	Refer to NOTE as below	
ACCESSORY DEVICES	Refer to NOTE as below	

NOTE:

1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for ERP, X-axis for GSM/WCDMA and Z-axis for LTE for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT with battery 1
B	EUT with battery 2

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	128 to 251	128, 189, 251	GSM, EDGE
B	ERP	128 to 251	128, 189, 251	GSM
A	FREQUENCY STABILITY	128 to 251	189	GSM, EDGE
A	OCCUPIED BANDWIDTH	128 to 251	128, 189, 251	GSM, EDGE
A	BAND EDGE	128 to 251	128, 251	GSM, EDGE
A	CONDCUDETED EMISSION	128 to 251	189	GSM, EDGE
A	RADIATED EMISSION	128 to 251	189	GSM, EDGE
B	RADIATED EMISSION	128 to 251	189	GSM

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
A	FREQUENCY STABILITY	4132 to 4233	4182	WCDMA
A	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
A	BAND EDGE	4132 to 4233	4132, 4233	WCDMA
A	CONDCUDETED EMISSION	4132 to 4233	4182	WCDMA
A	RADIATED EMISSION	4132 to 4233	4182	WCDMA

LTE BAND 5 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
B	ERP	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
A	FREQUENCY STABILITY	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 2 RB Offset
		20415 to 20635	20525	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset
A	OCCUPIED BANDWIDTH	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	BAND EDGE	20407 to 20643	20407	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20643	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		20415 to 20635	20415	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20635	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		20425 to 20626	20425	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20600	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20450 to 20600	20450	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20600	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
A	CONDCUDETED EMISSION	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 2 RB Offset
		20415 to 20635	20525	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset
A, B	RADIATED EMISSION	20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	26deg. C, 58%RH	3.8Vdc	Anson Lin
FREQUENCY STABILITY	26deg. C, 58%RH	3.8Vdc	Dylan Yang
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.8Vdc	Dylan Yang
BAND EDGE	26deg. C, 58%RH	3.8Vdc	Dylan Yang
CONDCUDETED EMISSION	26deg. C, 58%RH	3.8Vdc	Dylan Yang
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2
FCC 47 CFR Part 22
ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for WCDMA, and 10MHz for LTE mode.
b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA & CDMA & LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



CONDUCTED POWER MEASUREMENT:



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GSM (1 Uplink)	**32.98**	32.95	32.88
GPRS 8 (GMSK, 1 slot)	32.91	32.86	32.78
GPRS 10 (GMSK, 2 slot)	31.36	31.31	31.23
GPRS 11 (GMSK, 3 slot)	29.71	29.66	29.58
GPRS 12 (GMSK, 4 slot)	28.27	28.22	28.14
GPRS 30 (GMSK, 1 slot)	32.51	32.46	32.38
GPRS 31 (GMSK, 2 slot)	31.23	31.18	31.10
GPRS 32 (GMSK, 3 slot)	29.42	29.37	29.29
GPRS 33 (GMSK, 4 slot)	28.19	28.14	28.06
EDGE 8 (GMSK, 1 Uplink)	32.72	32.67	32.59
EDGE 10 (GMSK, 2 Uplink)	31.26	31.21	31.13
EDGE 11 (GMSK, 3 Uplink)	29.56	29.51	29.43
EDGE 12 (GMSK, 4 Uplink)	28.02	27.97	27.89
EDGE 30 (GMSK, 1 Uplink)	32.20	32.15	32.07
EDGE 31 (GMSK, 2 Uplink)	30.93	30.88	30.80
EDGE 32 (GMSK, 3 Uplink)	29.68	29.63	29.55
EDGE 33 (GMSK, 4 Uplink)	28.37	28.32	28.24
EDGE 8 (8PSK, 1 Uplink)	26.00	25.95	25.87
EDGE 10 (8PSK, 2 Uplink)	25.62	25.57	25.49
EDGE 11 (8PSK, 3 Uplink)	25.36	25.31	25.23
EDGE 12 (8PSK, 4 Uplink)	23.80	23.75	23.67
EDGE 30 (8PSK, 1 Uplink)	25.90	25.85	25.77
EDGE 31 (8PSK, 2 Uplink)	25.56	25.51	25.43
EDGE 32 (8PSK, 3 Uplink)	25.39	25.34	25.26
EDGE 33 (8PSK, 4 Uplink)	23.90	23.85	23.77

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	**23.97**	23.87	23.66
HSDPA Subtest-1	22.98	22.85	22.62
HSDPA Subtest-2	22.94	22.81	22.58
HSDPA Subtest-3	22.44	22.31	22.08
HSDPA Subtest-4	22.41	22.28	22.05
HSUPA Subtest-1	22.47	22.34	22.11
HSUPA Subtest-2	21.36	21.23	21.00
HSUPA Subtest-3	21.92	21.79	21.56
HSUPA Subtest-4	21.44	21.31	21.08
HSUPA Subtest-5	22.83	22.70	22.47

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	22.12	22.22	22.09	0	21.10	21.20	21.07	1
	1	2	22.07	22.31	22.05	0	21.05	21.29	21.03	1
	1	5	22.08	22.13	22.03	0	21.06	21.11	21.01	1
	3	0	21.15	21.16	21.08	0	20.13	20.14	20.06	1
	3	1	21.13	21.20	21.07	0	20.11	20.18	20.05	1
	3	3	21.11	21.19	21.06	0	20.09	20.17	20.04	1
	6	0	21.21	21.23	21.17	1	20.19	20.21	20.15	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.25	22.35	22.22	0	21.23	21.33	21.20	1
	1	7	22.20	22.44	22.18	0	21.18	21.42	21.16	1
	1	14	22.21	22.26	22.16	0	21.19	21.24	21.14	1
	8	0	21.28	21.29	21.21	1	20.26	20.27	20.19	2
	8	3	21.26	21.33	21.20	1	20.24	20.31	20.18	2
	8	7	21.24	21.32	21.19	1	20.22	20.30	20.17	2
	15	0	21.34	21.36	21.30	1	20.32	20.34	20.28	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	23.14	23.24	23.11	0	22.12	22.22	22.09	1
	1	12	23.09	23.33	23.07	0	22.07	22.31	22.05	1
	1	24	23.10	23.15	23.05	0	22.08	22.13	22.03	1
	12	0	22.17	22.18	22.10	1	21.15	21.16	21.08	2
	12	6	22.15	22.22	22.09	1	21.13	21.20	21.07	2
	12	13	22.13	22.21	22.08	1	21.11	21.19	21.06	2
	25	0	22.23	22.25	22.19	1	21.21	21.23	21.17	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	23.26	23.36	23.23	0	22.24	22.34	22.21	1
	1	24	23.34	**23.45**	23.33	0	22.19	22.43	22.17	1
	1	49	23.22	23.27	23.17	0	22.20	22.25	22.15	1
	25	0	22.29	22.30	22.22	1	21.27	21.28	21.20	2
	25	12	22.27	22.34	22.21	1	21.25	21.32	21.19	2
	25	25	22.25	22.33	22.20	1	21.23	21.31	21.18	2
	50	0	22.35	22.37	22.31	1	21.33	21.35	21.29	2

ERP POWER (dBm)

MODE A

GSM							
Plane	**Channel**	**Frequency (MHz)**	**LVL (dBm)**	**Correction Factor(dB)**	**ERP(dBm)**	**ERP(mW)**	**Polarization (H/V)**
Y	128	824.2	-2.96	32.62	27.51	563.64	H
	189	836.4	-2.58	32.52	27.79	601.17	H
	251	848.8	-3.36	32.65	27.14	517.61	H
	128	824.2	-10.35	32.76	20.26	106.17	V
	189	836.4	-9.50	32.39	20.74	118.58	V
	251	848.8	-9.97	32.54	20.42	110.15	V

EDGE							
Plane	**Channel**	**Frequency (MHz)**	**LVL (dBm)**	**Correction Factor(dB)**	**ERP(dBm)**	**ERP(mW)**	**Polarization (H/V)**
Y	128	824.2	-3.48	32.62	26.99	500.03	H
	189	836.4	-2.98	32.52	27.39	548.28	H
	251	848.8	-3.86	32.65	26.64	461.32	H
	128	824.2	-11.50	32.76	19.11	81.47	V
	189	836.4	-10.15	32.39	20.09	102.09	V
	251	848.8	-10.72	32.54	19.67	92.68	V

WCDMA							
Plane	**Channel**	**Frequency (MHz)**	**LVL (dBm)**	**Correction Factor(dB)**	**ERP(dBm)**	**ERP(mW)**	**Polarization (H/V)**
Y	4132	826.4	-12.58	32.62	17.89	61.52	H
	4182	836.4	-12.25	32.52	18.12	64.86	H
	4233	846.6	-13.15	32.65	17.35	54.33	H
	4132	826.4	-19.86	32.76	10.75	11.89	V
	4182	836.4	-18.55	32.39	11.69	14.76	V
	4233	846.6	-19.95	32.54	10.44	11.07	V

LTE Band 5							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-14.55	32.62	15.92	39.08	H
	20525	836.5	-14.21	32.52	16.16	41.30	H
	20643	848.3	-14.96	32.65	15.54	35.81	H
	20407	824.7	-21.75	32.76	8.86	7.69	V
	20525	836.5	-21.23	32.39	9.01	7.96	V
	20643	848.3	-21.72	32.54	8.67	7.36	V

LTE Band 5							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-15.75	32.62	14.72	29.65	H
	20525	836.5	-15.01	32.52	15.36	34.36	H
	20643	848.3	-15.55	32.65	14.95	31.26	H
	20407	824.7	-22.21	32.76	8.40	6.92	V
	20525	836.5	-21.76	32.39	8.48	7.05	V
	20643	848.3	-22.28	32.54	8.11	6.47	V

LTE Band 5							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-13.89	32.62	16.58	45.50	H
	20525	836.5	-13.45	32.52	16.92	49.20	H
	20635	847.5	-14.22	32.65	16.28	42.46	H
	20415	825.5	-21.10	32.76	9.51	8.93	V
	20525	836.5	-20.54	32.39	9.70	9.33	V
	20635	847.5	-21.22	32.54	9.17	8.26	V

LTE Band 5							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-15.55	32.62	14.92	31.05	H
	20525	836.5	-14.58	32.52	15.79	37.93	H
	20635	847.5	-15.98	32.65	14.52	28.31	H
	20415	825.5	-22.25	32.76	8.36	6.85	V
	20525	836.5	-21.49	32.39	8.75	7.50	V
	20635	847.5	-22.12	32.54	8.27	6.71	V

LTE Band 5							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-13.25	32.62	17.22	52.72	H
	20525	836.5	-12.89	32.52	17.48	55.98	H
	20625	846.5	-13.55	32.65	16.95	49.55	H
	20425	826.5	-20.55	32.76	10.06	10.14	V
	20525	836.5	-19.71	32.39	10.53	11.30	V
	20625	846.5	-20.25	32.54	10.14	10.33	V

LTE Band 5							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-14.85	32.62	15.62	36.48	H
	20525	836.5	-14.20	32.52	16.17	41.40	H
	20625	846.5	-14.95	32.65	15.55	35.89	H
	20425	826.5	-21.69	32.76	8.92	7.80	V
	20525	836.5	-21.15	32.39	9.09	8.11	V
	20625	846.5	-21.96	32.54	8.43	6.97	V

LTE Band 5							
Channel Bandwidth: 10MHz / QPSK							
Plane	**Channel**	**Frequency (MHz)**	**LVL (dBm)**	**Correction Factor(dB)**	**ERP(dBm)**	**ERP(mW)**	**Polarization (H/V)**
Y	20450	829	-13.35	32.62	17.12	51.52	H
	20525	836.5	-12.58	32.52	17.79	60.12	H
	20600	844	-13.52	32.65	16.98	49.89	H
	20450	829	-20.36	32.76	10.25	10.59	V
	20525	836.5	-19.85	32.39	10.39	10.94	V
	20600	844	-20.25	32.54	10.14	10.33	V

LTE Band 5							
Channel Bandwidth: 10MHz / 16QAM							
Plane	**Channel**	**Frequency (MHz)**	**LVL (dBm)**	**Correction Factor(dB)**	**ERP(dBm)**	**ERP(mW)**	**Polarization (H/V)**
Y	20450	829	-14.45	32.62	16.02	39.99	H
	20525	836.5	-13.98	32.52	16.39	43.55	H
	20600	844	-14.55	32.65	15.95	39.36	H
	20450	829	-21.42	32.76	9.19	8.30	V
	20525	836.5	-20.88	32.39	9.36	8.63	V
	20600	844	-21.36	32.54	9.03	8.00	V

MODE B

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	-3.14	32.62	27.33	540.75	H
	189	836.4	-2.83	32.52	27.54	567.54	H
	251	848.8	-3.09	32.65	27.41	550.81	H
	128	824.2	-10.22	32.76	20.39	109.40	V
	189	836.4	-9.65	32.39	20.59	114.55	V
	251	848.8	-10.10	32.54	20.29	106.91	V

LTE Band 5							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829	-13.18	32.62	17.29	53.58	H
	20525	836.5	-12.66	32.52	17.71	59.02	H
	20600	844	-13.57	32.65	16.93	49.32	H
	20450	829	-20.12	32.76	10.49	11.19	V
	20525	836.5	-19.82	32.39	10.42	11.02	V
	20600	844	-20.02	32.54	10.37	10.89	V

LTE Band 5							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829	-14.42	32.62	16.05	40.27	H
	20525	836.5	-14.03	32.52	16.34	43.05	H
	20600	844	-14.67	32.65	15.83	38.28	H
	20450	829	-20.96	32.76	9.65	9.23	V
	20525	836.5	-20.77	32.39	9.47	8.85	V
	20600	844	-21.14	32.54	9.25	8.41	V

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
3.8	0.007	0.014	-0.002	-0.001	-0.004	-0.002	-0.003	2.5
3.6	0.012	0.016	0.003	-0.002	-0.001	-0.003	-0.004	2.5
4.35	0.004	0.015	0.004	-0.003	-0.004	-0.004	-0.002	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.35Vdc.

FREQUENCY ERROR vs. TEMPERATURE

TEMP. (℃)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
-30	0.011	0.017	-0.002	-0.004	-0.004	-0.002	-0.002	2.5
-20	0.010	0.013	0.004	-0.003	-0.005	-0.001	-0.004	2.5
-10	0.008	0.019	0.005	-0.002	-0.003	-0.005	-0.003	2.5
0	0.010	0.023	-0.003	-0.004	-0.001	-0.003	-0.002	2.5
10	0.006	0.017	-0.005	0.002	-0.002	-0.005	-0.004	2.5
20	0.004	0.016	0.002	-0.006	-0.003	0.003	0.002	2.5
30	0.007	0.017	0.003	-0.004	0.004	-0.004	-0.002	2.5
40	0.003	0.015	0.003	-0.001	0.003	-0.002	-0.004	2.5
50	0.005	0.013	-0.002	-0.003	-0.006	-0.004	0.002	2.5
60	0.008	0.021	0.003	-0.002	0.002	-0.004	0.002	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP



4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
128	824.2	244.05	243.71	4132	826.4	4.1641
189	836.4	243.88	245.80	4182	836.4	4.1696
251	848.8	243.48	242.93	4233	846.6	4.1615
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)
		GSM	EDGE			WCDMA
128	824.2	317.00	308.80	4132	826.4	4.671
189	836.4	320.40	315.50	4182	836.4	4.686
251	848.8	316.10	311.00	4233	846.6	4.672

SPECTRUM PLOT OF WORST VALUE

GSM



EDGE



WCDMA



LTE BAND 5							
CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.0774	1.0760	20415	825.5	2.6789	2.6797
20525	836.5	1.0787	1.0760	20525	836.5	2.6813	2.6795
20643	848.3	1.0767	1.0759	20635	847.5	2.6809	2.6801
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.242	1.228	20415	825.5	2.873	2.861
20525	836.5	1.233	1.240	20525	836.5	2.875	2.879
20643	848.3	1.236	1.225	20635	847.5	2.872	2.878

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 5							
CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.4904	4.4835	20450	829.0	8.9284	8.9189
20525	836.5	4.4918	4.4845	20525	836.5	8.9302	8.9298
20625	846.5	4.4818	4.4823	20600	844.0	8.9057	8.9022
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.818	4.804	20450	829.0	9.387	9.428
20525	836.5	4.812	4.795	20525	836.5	9.370	9.372
20625	846.5	4.784	4.786	20600	844.0	9.310	9.387

SPECTRUM PLOT OF WORST VALUE	
5MHz / QPSK	5MHz / 16QAM
	
10MHz / QPSK	10MHz / 16QAM
	

4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP



4.4.3 TEST PROCEDURES

a. All measurements were done at low and high operational frequency range.
b. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3.9kHz and VB of the spectrum is 12kHz (GSM/EDGE).
c. The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
d. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 13kHz and VB of the spectrum is 51kHz (LTE Channel Bandwidth 1.4MHz).
e. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Channel Bandwidth 3MHz).
f. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Channel Bandwidth 5MHz/10MHz).
g. Record the max trace plot into the test report.

4.4.4 TEST RESULTS

GSM			
CHANNEL	128	CHANNEL	251
			
EDGE			
CHANNEL	128	CHANNEL	251
			
WCDMA			
CHANNEL	4132	CHANNEL	4233
			

LTE BAND 5					
CHANNEL BANDWIDTH: 1.4MHz					
CHANNEL	20407	1 RB	CHANNEL	20643	1 RB
					
CHANNEL	20407	6 RB	CHANNEL	20643	6 RB
					

LTE BAND 5					
CHANNEL BANDWIDTH: 3MHz					
CHANNEL	20415	1 RB	CHANNEL	20635	1 RB
					
CHANNEL	20415	15 RB	CHANNEL	20635	15 RB
					

LTE BAND 5					
CHANNEL BANDWIDTH: 5MHz					
CHANNEL	20425	1 RB	CHANNEL	20625	1 RB
					
CHANNEL	20425	25 RB	CHANNEL	20625	25 RB
					

LTE BAND 5					
CHANNEL BANDWIDTH: 10MHz					
CHANNEL	20450	1 RB	CHANNEL	20600	1 RB
					
CHANNEL	20450	50 RB	CHANNEL	20600	50 RB
					

4.5 CONDUCTED SPURIOUS EMISSIONS

4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit is equal to -13dBm.

4.5.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
b. Measuring frequency range is from 30 MHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP



4.5.4 TEST RESULTS

GSM	EDGE
CHANNEL 189	CHANNEL 189
	
WCDMA	
CHANNEL 4182	
	

LTE BAND 5	
CHANNEL 20525	
Channel Bandwidth: 1.4MHz	Channel Bandwidth: 3MHz
	
Channel Bandwidth: 5MHz	Channel Bandwidth: 10MHz
	

4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit is equal to -13dBm.

4.6.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.6.5 TEST RESULTS

MODE A

GSM:

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GSM850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	52.14	-51.65	-46.75	-13.00	-38.65	-4.90	Peak
2	108.03	-57.04	-46.47	-13.00	-44.04	-10.57	Peak
3	182.82	-50.55	-44.54	-13.00	-37.55	-6.01	Peak
4	328.00	-61.28	-55.11	-13.00	-48.28	-6.17	Peak
5	485.50	-67.35	-63.89	-13.00	-54.35	-3.46	Peak
6	652.10	-64.43	-65.01	-13.00	-51.43	0.58	Peak
7	1672.80	-49.73	-35.89	-13.00	-36.73	-13.84	Peak
8 pp	2509.20	-46.57	-36.58	-13.00	-33.57	-9.99	Peak

Data: 10



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GSM850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	36.75	-42.33	-40.18	-13.00	-29.33	-2.15	Peak
2	105.87	-60.69	-50.16	-13.00	-47.69	-10.53	Peak
3	169.05	-59.47	-52.79	-13.00	-46.47	-6.68	Peak
4	304.20	-67.65	-61.31	-13.00	-54.65	-6.34	Peak
5	508.60	-68.03	-65.15	-13.00	-55.03	-2.88	Peak
6	603.10	-64.41	-64.11	-13.00	-51.41	-0.30	Peak
7	1672.80	-48.56	-34.72	-13.00	-35.56	-13.84	Peak
8	2509.20	-49.85	-39.86	-13.00	-36.85	-9.99	Peak

EDGE:

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : EDGE 850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1672.00	-62.42	-48.58	-13.00	-49.42	-13.84	Peak

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : EDGE 850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1672.80	-63.42	-49.58	-13.00	-50.42	-13.84	Peak

WCDMA:

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : Band V Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1672.80	-51.23	-37.39	-13.00	-38.23	-13.84	Peak

Data: 6



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : Band V Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1672.80	-50.67	-36.83	-13.00	-37.67	-13.84	Peak

LTE BAND 5

CHANNEL BANDWIDTH: 10MHz / QPSK

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : LTE Band 5_10M_QPSK(1,24) Link
Tested by: Anson Lin
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	51.06	-53.04	-48.29	-13.00	-40.04	-4.75	Peak
2	176.88	-51.38	-44.96	-13.00	-38.38	-6.42	Peak
3	211.44	-52.17	-44.74	-13.00	-39.17	-7.43	Peak
4	306.30	-60.42	-54.09	-13.00	-47.42	-6.33	Peak
5	592.60	-64.97	-64.41	-13.00	-51.97	-0.56	Peak
6	696.20	-63.97	-65.35	-13.00	-50.97	1.38	Peak
7 pp	1673.00	-49.61	-35.77	-13.00	-36.61	-13.84	Peak

Data: 10



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : LTE Band 5_10M_QPSK(1,24) Link
Tested by: Anson Lin
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	57.00	-47.13	-41.48	-13.00	-34.13	-5.65	Peak
2	157.17	-59.10	-52.63	-13.00	-46.10	-6.47	Peak
3	209.82	-60.32	-52.81	-13.00	-47.32	-7.51	Peak
4	365.10	-68.97	-63.07	-13.00	-55.97	-5.90	Peak
5	654.20	-63.87	-64.50	-13.00	-50.87	0.63	Peak
6	732.60	-63.41	-65.08	-13.00	-50.41	1.67	Peak
7 pp	1673.00	-44.01	-30.17	-13.00	-31.01	-13.84	Peak

MODE B

GSM:

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : GSM850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	56.19	-53.66	-48.16	-13.00	-40.66	-5.50	Peak
2	104.52	-59.28	-48.78	-13.00	-46.28	-10.50	Peak
3 pp	176.61	-51.44	-45.02	-13.00	-38.44	-6.42	Peak
4	309.80	-61.28	-54.97	-13.00	-48.28	-6.31	Peak
5	356.00	-65.86	-59.90	-13.00	-52.86	-5.96	Peak
6	619.90	-64.62	-64.62	-13.00	-51.62	0.00	Peak
7	1672.80	-60.40	-46.56	-13.00	-47.40	-13.84	Peak
8	2509.20	-53.70	-43.71	-13.00	-40.70	-9.99	Peak

Data: 10



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : GSM850 Link
Tested by: Anson Lin
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	35.67	-43.03	-40.67	-13.00	-30.03	-2.36	Peak
2	154.74	-60.58	-54.14	-13.00	-47.58	-6.44	Peak
3	205.50	-60.54	-52.85	-13.00	-47.54	-7.69	Peak
4	347.60	-69.41	-63.38	-13.00	-56.41	-6.03	Peak
5	563.90	-66.50	-65.14	-13.00	-53.50	-1.36	Peak
6	700.40	-64.25	-65.70	-13.00	-51.25	1.45	Peak
7	1672.80	-61.59	-47.75	-13.00	-48.59	-13.84	Peak
8	2509.20	-54.90	-44.91	-13.00	-41.90	-9.99	Peak

LTE BAND 5

CHANNEL BANDWIDTH: 10MHz / QPSK

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 3m HORIZONTAL
Remark : LTE Band 5_10M_QPSK(1,24) Link
Tested by: Anson Lin
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	55.92	-53.91	-48.41	-13.00	-40.91	-5.50	Peak
2	106.41	-58.83	-48.28	-13.00	-45.83	-10.55	Peak
3	177.96	-52.33	-46.29	-13.00	-39.33	-6.04	Peak
4	337.80	-63.32	-57.22	-13.00	-50.32	-6.10	Peak
5	589.10	-67.09	-66.42	-13.00	-54.09	-0.67	Peak
6	683.60	-65.54	-66.69	-13.00	-52.54	1.15	Peak
7 pp	1673.00	-52.03	-38.19	-13.00	-39.03	-13.84	Peak

Data: 10



Site : 966 Chamber 5
Condition: PART22/24 3m VERTICAL
Remark : LTE Band 5_10M_QPSK(1,24) Link
Tested by: Anson Lin
Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	37.56	-43.61	-41.66	-13.00	-30.61	-1.95	Peak
2	55.38	-49.07	-43.72	-13.00	-36.07	-5.35	Peak
3	155.28	-60.35	-53.91	-13.00	-47.35	-6.44	Peak
4	503.70	-69.05	-66.04	-13.00	-56.05	-3.01	Peak
5	598.20	-66.56	-66.16	-13.00	-53.56	-0.40	Peak
6	730.50	-64.97	-66.62	-13.00	-51.97	1.65	Peak
7	1673.00	-48.58	-34.74	-13.00	-35.58	-13.84	Peak

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---