

FCC ID: Z63-K8B048

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: FPC Antenna

Antenna Gain: 3.6 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.130	2.588	5±1	6.0	3.981	<5	1.23400	3.00	YES
	2.441	5.300	3.388	5±1	6.0	3.981	<5	1.24398	3.00	YES
	2.480	4.840	3.048	5±1	6.0	3.981	<5	1.25388	3.00	YES
π/4-DQPSK	2.402	1.750	1.496	2.5±1	3.5	2.239	<5	0.69393	3.00	YES
	2.441	3.040	2.014	2.5±1	3.5	2.239	<5	0.69954	3.00	YES
	2.480	2.530	1.791	2.5±1	3.5	2.239	<5	0.70511	3.00	YES
8DPSK	2.402	2.140	1.637	2.5±1	3.5	2.239	<5	0.69393	3.00	YES
	2.441	3.390	2.183	2.5±1	3.5	2.239	<5	0.69954	3.00	YES
	2.480	2.880	1.941	2.5±1	3.5	2.239	<5	0.70511	3.00	YES

BLE:


Antenna Type: FPC Antenna

Antenna Gain: 3.6dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.08	2.559	4±1	5	3.162	<5	0.98020	3.00	YES
	2.44	4.76	2.992	4±1	5	3.162	<5	0.98793	3.00	YES
	2.480	4.73	2.972	4±1	5	3.162	<5	0.99599	3.00	YES

Conclusion:

For the max result : $1.25388 \leq 3.0$ for 1-g SAR, No SAR is required.


Signature:**Date:** 2018-11-27**NAME AND TITLE** (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China