



浙江省东阳市东磁诚基电子有限公司 RoHS H/F

Zhe Jiang DONGYANG DMEGC Chen ji Electronics CO., LTD

产 品 规 格 书

PRODUCT SPECIFICATION

产品信息 Product Information	品名/Description	双线圈模组		
	规格型号/Part No.	DM-TS9352B-15		
	文件编号/DN			
	设计/Designed	审核/Checked	批准/Approved	
	王欣欣	苗晓峰	周仕	

客户信息 Customer Information	客户名称/Customer	
	机型/Model	
	客户料号/Part NO.	
	客户承认/Customer Approved	

地址：中国浙江省东阳市横店工业区

Address: Hengdian industrial Area, DongYang City, Zhejiang Province China

邮编/P.C: 322118

电话/TEL: +0086-0579-86588315 (86588791)

传真/FAX: +0086-0579-86553611



产品规格书

PRODUCT SPECIFICATION

DM-TS9352B-15
NO.2/5

重要提示 Important Notes:

1. 如对发射/接收线圈模組的性能和（或）寿命有任何争议，仅基于此规格书作出判断。

If there is any argument on TX/Rx Coil Unit performance and/or life, judgment is to be made base on this specification only.

2. 客户方有责任确认该发射/接收线圈模組能满足您的使用要求。

Customer has the responsibility to ensure that TX/Rx Coil Unit can satisfy the requirement of your application.

3. 如果公司未提供技术规格，该文件将详细叙述与贵公司商定的技术规格。

In the event that an official specification is not present by customer, this document will specify the agreed technical specification.

4. 在满足规格的条件下，我司可以改变零件材料、尺寸及形状来改善品质（或）性能（或）生产效率。

Within the limitation to satisfy this specification, DMEGC has the convenience to change the materials, size and shapes of components of the motor for the purpose of improving quality, and/or performance, and/or production efficiency.

5. 收到此规格书后，贵司应于下订单之前将规格书副本签回以示贵司已确认。如贵司未能在规定时间内签回副本，我司将认为贵司已收到并承认该规格书。

After the receipt of this specification, customer should send a signed copy to DMEGC, before you issued purchase order for the confirmation on acknowledgement. DMEGC, regard it as the receipt of this specification acknowledged if customer fails to return the confirmation to us within the described period.




DM-TS9352B-15
NO.3/5

更改履历

Revised History

[illegible]

1. 尺寸 DIMENSION(mm)



2. 原理图 SCHEMATIC DIAGRAM



3. 绕线参数

序号 NO	线规格 Line size	圈数 Number of turns	是否交叉 Cross or not
1	silk-covered wire 0.08*105P	9Ts	是 YES

3. 电气特性 ELECTRICAL CHARACTERISTICS:

100KHz/1Vrms, 温度 TEMPERATURE: 25 ± 10°C, 湿度 RELATIVE HUMIDITY: 65 ± 20%

序号 NO		上线圈 Upper coil	下线圈 Lower coil
1	Ls	7.0 ± 0.3 uH	7.1 ± 0.3 uH
2	RDC	60 mΩ MAX	60 mΩ MAX



产品规格书

PRODUCT SPECIFICATION

DM-TS9352B-15
NO.5/5

4.材料清单

BOM 表			
序号 NO	物料名称 Material name	物料规格 Material specification	UL FILE NO
1	锡头 Tin head	高温锡条 High temperature tin bar	/
2	胶带 Adhesive tape	8mm and 5mm high temperature tape	E483388
3	线圈 coil	0.08*105P Silk-covered wire	/
4	磁片 Magnetic sheet	锰锌铁氧体 Manganese zinc ferrite	/
5	胶水 glue	Strong structural adhesive	/
6	背胶 Rubber backing	0.08mm double faced adhesive tape	/

5. 材料符合 RoHS 及无卤标准要求。

Materials comply with RoHS and halogen-free standards