

Test Report

FCC ID: 2ASJR-CM2-1112120

Date of issue: June 15, 2019

Report Number:	MTi190614E097
Sample Description:	GT-Sense SMA Connectors
Model(s):	CM2-1112120, CM2-1102120
Applicant:	Globetracker, ApS
Address:	Strandgade 91, 4th Floor, DK-1401 Copenhagen K, DK
Date of Test:	Feb. 25, 2019 to June 15, 2019

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

Table of Contents

1. GENERAL INFORMATION.....	5
1.1. DESCRIPTION OF EUT.....	5
1.2. OPERATION CHANNEL LIST.....	5
1.3. TEST CHANNEL LIST.....	6
1.4. ANCILLARY EQUIPMENT LIST.....	6
1.5. DESCRIPTION OF SUPPORT UNITS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. TEST FACILITIES AND ACCREDITATIONS.....	8
.....	8
.....	8
3.1. TEST LABORATORY.....	8
3.2. ENVIRONMENTAL CONDITIONS.....	8
3.3. MEASUREMENT UNCERTAINTY.....	8
3.4. TEST SOFTWARE.....	8
4. EQUIPMENT LIST.....	9
5. TEST RESULT.....	10
5.1. ANTENNA REQUIREMENT.....	10
.....	10
.....	10
.....	10
.....	10
.....	10
5.1.1 STANDARD REQUIREMENT.....	10
5.1.2 EUT ANTENNA.....	10
5.2. PEAK OUTPUT POWER TEST.....	11
.....	11
5.2.1 LIMIT.....	11
5.2.2 TEST SETUP.....	11
5.2.3 TEST PROCEDURE.....	11
5.2.4 EUT OPERATION CONDITION.....	11
5.2.5 TEST RESULTS.....	11
5.3. CONDUCTED EMISSION.....	14
.....	14
5.3.1 LIMITS.....	14
5.3.2 TEST SETUP.....	14
5.3.3 TEST PROCEDURE.....	15
5.3.4 TEST RESULTS.....	15
5.4 RADIATED SPURIOUS EMISSION.....	20
5.4.1 LIMITS.....	20
5.4.2 TEST SETUP.....	21
5.4.3 TEST PROCEDURE.....	22
5.4.4 TEST RESULTS.....	23
5.4.4.1 RADIATION EMISSION.....	23
5.4.4.2 BANDEDGE-RADIATED.....	27
5.4.4.3 SPURIOUS EMISSION IN RESTRICTED BAND 3260MHZ-18000MHZ.....	28
5.5 POWER SPECTRAL DENSITY TEST.....	29
5.5.1 LIMIT.....	29
5.5.2 TEST PROCEDURE.....	29
5.5.3 TEST SETUP.....	29
5.5.4 EUT OPERATION CONDITIONS.....	29

5.5.5 TEST RESULTS.....	30
5.6 6DB BANDWIDTH.....	32
5.6.1 LIMIT.....	32
5.6.2 TEST PROCEDURE.....	32
5.6.3 TEST SETUP.....	32
5.6.4 EUT OPERATION CONDITIONS.....	32
5.6.5 TEST RESULT.....	32
5.7 CONDUCTED BANDEDGE.....	35
5.7.1 LIMITS.....	35
5.7.2 TEST SETUP.....	35
5.7.3 TEST PROCEDURE.....	35
5.7.4 EUT OPERATION CONDITIONS.....	35
5.7.5 TEST RESULT.....	35
PHOTOGRAPHS OF THE TEST SETUP.....	37
PHOTOGRAPHS OF THE EUT.....	39

PRODUCT INFORMATION

Applicant's name: Globetracker, ApS

Address: Strandgade 91, 4th Floor, DK-1401 Copenhagen K, DK

Manufacture's Name: Danchell

Address: Lyngvej 8-DK-4450 4450 Jyderup Denmark

Product name: GT-Sense SMA Connectors

Trademark: GT-Sense

Model name: CM2-1112120, CM2-1102120

Standards: FCC Part 15.247

Test Procedure: ANSI C63.10:2013
KDB 558074 D01 DTS Meas Guidance v05r02

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:



Demi Mu

June 15, 2019

Reviewed by:



Blue Zheng

June 15, 2019

Approved by:



Smith Chen

June 15, 2019

1. General Information

1.1. Description of EUT

Product name:	GT-Sense SMA Connectors
Model name:	CM2-1112120
Serial model:	CM2-1102120
Difference in series models:	All the model are the same circuit and RF module, except the CM2-110210 has some temperature, humidity and pressure sensors removed.
Operation frequency:	2402-2480MHz
Modulation type:	GFSK
Bit Rate of transmitter:	1 Mbps
Antenna type:	Chip Antenna
Antenna gain:	0.5dBi
Max. output power:	-1.570dBm
Hardware version:	3
Software version:	60_3
Power supply:	DC 3.7V from battery or DC 36V from adapter
Adapter information:	N/A
Battery:	DC 3.7V 1800mAh

1.2. Operation channel list

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478

9	2420	19	2440	29	2460	39	2480
---	------	----	------	----	------	----	------

1.3. Test channel list

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	19	2440
High	39	2480

1.4. Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
Adapter	/	/	/	/

1.5. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
/	/	/	/	/	
/	/	/	/	/	

Note:

(1)The support equipment was authorized by Declaration of Confirmation.

(2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2. Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	15.205	Band Edge Emission	Pass	

3. Test Facilities and Accreditations

3.1. Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2. Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$ where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3.4. Test software

Software Name	Manufacturer	Model	Version
RF Test System	Farad	LZ-RF	Lz_Rf 3A3

4. Equipment list

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E001	Spectrum Analyzer	Agilent	E4407B	MY41441082	2018/09/18	2019/09/17
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI	1000314	2018/09/18	2019/09/17
MTI-E006	Broadband antenna	schwarzbeck	VULB9163	872	2018/09/18	2019/09/17
MTI-E007	Horn antenna	schwarzbeck	BBHA9120D	1201	2018/09/18	2019/09/17
MTI-E014	amplifier	America	8447D	3113A06150	2018/09/18	2019/09/17
MTI-E015	Conduction Immunity Signal Generator	Schloder	CDG6000	126A1343/2015	2018/09/18	2019/09/17
MTI-E016	Coupled decoupling network	Schloder	CND M2/M3	A2210332/2015	2018/09/18	2019/09/17
MTI-E034	amplifier	Agilent	8449B	3008A02400	2018/09/18	2019/09/17
MTI-E037	Artificial power network	Schwarzbeck	NSLK8127	#841	2018/09/18	2019/09/17
MTI-E040	Spectrum analyzer	Agilent	N9020A	MY49100060	2018/09/18	2019/09/17
MTI-E041	Signal generator	Agilent	N5182A	MY49060455	2018/09/18	2019/09/17
MTI-E042	Analog signal generator	Agilent	E4421B	GB40051240	2018/09/18	2019/09/17
MTI-E043	Power sensor	Dare Instruments	RPR3006W	16I00054SN016	2018/09/18	2019/09/17
MTI-E047	10dB attenuator	Mini-Circuits	UNAT-10+	15542	2018/09/18	2019/09/17
MTI-E049	spectrum analyzer	Rohde&schwarz	FSP-38	100019	2018/09/18	2019/09/17
MTI-E050	PSG Signal generator	Agilent	E8257D	MY46520873	2018/09/18	2019/09/17
MTI-E061	Active Loop Antenna 9kHz - 30MHz	Schwarzbeck	FMZB 1519 B	00044	2018/09/18	2019/09/17
MTI-E052	18-40GHz amplifier	Chengdu step Micro Technology	ZLNA-18-40G-21	1608001	2018/09/18	2019/09/17
MTI-E053	15-40G Antenna	Schwarzbeck	BBHA9170	BBHA9170582	2018/09/18	2019/09/17
MTI-E058	Artificial power network	Schwarzbeck	NSLK8127	#841	2018/09/18	2019/09/17
Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).						

5. Test Result

5.1. Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna

The EUT antenna is Chip antenna (0.5dBi). It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2. Peak output power test

5.2.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.2.2 Test setup



5.2.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.2.4 EUT operation condition

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.2.5 Test results

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V by battery


TX BLE mode

Test Channel	Frequency	Maximum Conducted Output Power(PK)	Limit
	(MHz)	(dBm)	dBm
CH00	2402	-1.622	30
CH19	2440	-1.570	30
CH39	2480	-2.267	30


2402MHz



2440MHz



2480MHz



5.3. Conducted emission

5.3.1 Limits


FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note

(1)The tighter limit applies at the band edges.

(2)The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.3.2 Test setup



Note: 1.Support units were connected to second LISN .

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.3.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.3.4 Test results


Test data

EUT :	GT-Sense SMA Connectors	Model Name. :	CM2-1112120
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 36V from adapter AC 120V/60Hz	Test Mode :	Charging+TX




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	38.44	10.51	48.95	66.00	-17.05	QP	
2		0.1500	18.49	10.51	29.00	56.00	-27.00	AVG	
3		0.2500	30.98	10.47	41.45	61.76	-20.31	QP	
4		0.2500	15.60	10.47	26.07	51.76	-25.69	AVG	
5		0.4500	30.66	10.43	41.09	56.88	-15.79	QP	
6	*	0.4500	23.54	10.43	33.97	46.88	-12.91	AVG	
7		1.1300	18.40	10.36	28.76	56.00	-27.24	QP	
8		1.1300	12.14	10.36	22.50	46.00	-23.50	AVG	
9		3.3300	17.92	10.21	28.13	56.00	-27.87	QP	
10		3.3300	9.82	10.21	20.03	46.00	-25.97	AVG	
11		6.7060	15.23	10.47	25.70	60.00	-34.30	QP	
12		6.7060	5.96	10.47	16.43	50.00	-33.57	AVG	

EUT :	GT-Sense SMA Connectors	Model Name. :	CM2-1112120
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 36V from adapter AC 120V/60Hz	Test Mode :	Charging+TX




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	36.65	10.51	47.16	65.79	-18.63	QP	
2		0.1539	19.78	10.51	30.29	55.79	-25.50	AVG	
3		0.2460	30.00	10.48	40.48	61.89	-21.41	QP	
4		0.2460	18.38	10.48	28.86	51.89	-23.03	AVG	
5		0.4460	32.01	10.42	42.43	56.95	-14.52	QP	
6	*	0.4460	22.98	10.42	33.40	46.95	-13.55	AVG	
7		1.2620	20.63	10.35	30.98	56.00	-25.02	QP	
8		1.2620	11.27	10.35	21.62	46.00	-24.38	AVG	
9		4.4060	21.33	10.26	31.59	56.00	-24.41	QP	
10		4.4060	13.28	10.26	23.54	46.00	-22.46	AVG	
11		25.6780	20.39	11.07	31.46	60.00	-28.54	QP	
12		25.6780	6.88	11.07	17.95	50.00	-32.05	AVG	

EUT :	GT-Sense SMA Connectors	Model Name. :	CM2-1112120
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 36V from adapter AC 240V/60Hz	Test Mode :	Charging+TX



EUT :	GT-Sense SMA Connectors	Model Name. :	CM2-1112120
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 36V from adapter AC 240V/60Hz	Test Mode :	Charging+TX



5.4 Radiated spurious emission

5.4.1 Limits


Frequency (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.4.2 Test setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.4.3 Test procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter shield area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

5.4.4 Test results

5.4.4.1 Radiation emission

Below 30MHz

EUT:	GT-Sense SMA Connectors	Model Name:	CM2-1112120
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage:	DC 36V from adapter
Test Mode:	Charging+TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

Between 30MHz – 1GHz:


Note: The high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is CH39.

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Relative Humidity:	52%	Phase:	H
Pressure:	1010 hPa	Test Voltage :	DC 36V from adapter
Test Mode :	Charging+TX		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		58.4074	26.48	-10.94	15.54	40.00	-24.46	QP
2		88.6524	33.12	-13.44	19.68	43.50	-23.82	QP
3		137.9028	30.83	-14.83	16.00	43.50	-27.50	QP
4		197.2001	29.24	-12.16	17.08	43.50	-26.42	QP
5	*	317.7011	39.68	-8.25	31.43	46.00	-14.57	QP
6		601.4265	27.84	-5.33	22.51	46.00	-23.49	QP

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Relative Humidity:	52%	Phase:	V
Pressure:	1010 hPa	Test Voltage :	DC 36V from adapter
Test Mode :	Charging+TX		



1G-25GHz

- Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(3) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G									
4804.34	62.63	5.21	35.59	44.30	59.13	74.00	-14.87	Pk	Vertical
4804.34	41.54	5.21	35.59	44.30	38.04	54.00	-15.96	AV	Vertical
7206.11	61.89	6.48	36.27	44.60	60.04	74.00	-13.96	Pk	Vertical
7206.11	42.17	6.48	36.27	44.60	40.32	54.00	-13.68	AV	Vertical
4804.17	63.72	5.21	35.55	44.30	60.18	74.00	-13.82	Pk	Horizontal
4804.17	42.57	5.21	35.55	44.30	39.03	54.00	-14.97	AV	Horizontal
7206.21	60.99	6.48	36.27	44.52	59.22	74.00	-14.78	Pk	Horizontal
7206.21	41.75	6.48	36.27	44.52	39.98	54.00	-14.02	AV	Horizontal
Mid Channel (2440 MHz)-Above 1G									
4880.47	63.61	5.21	35.66	44.20	60.28	74.00	-13.72	Pk	Vertical
4880.47	44.36	5.21	35.66	44.20	41.03	54.00	-12.97	AV	Vertical
7320.27	65.18	7.10	36.50	44.43	64.35	74.00	-9.65	Pk	Vertical
7320.27	40.84	7.10	36.50	44.43	40.01	54.00	-13.99	AV	Vertical
4880.37	63.19	5.21	35.66	44.20	59.86	74.00	-14.14	Pk	Horizontal
4880.37	41.48	5.21	35.66	44.20	38.15	54.00	-15.85	AV	Horizontal
7320.23	59.44	7.10	36.50	44.43	58.61	74.00	-15.39	Pk	Horizontal
7320.23	44.47	7.10	36.50	44.43	43.64	54.00	-10.36	AV	Horizontal
High Channel (2480 MHz)- Above 1G									
4960.48	64.52	5.21	35.52	44.21	61.04	74.00	-12.96	Pk	Vertical
4960.48	41.32	5.21	35.52	44.21	37.84	54.00	-16.16	AV	Vertical
7440.13	64.62	7.10	36.53	44.60	63.65	74.00	-10.35	Pk	Vertical
7440.13	48.68	7.10	36.53	44.60	47.71	54.00	-6.29	AV	Vertical
4960.33	64.13	5.21	35.52	44.21	60.65	74.00	-13.35	Pk	Horizontal
4960.33	45.64	5.21	35.52	44.21	42.16	54.00	-11.84	AV	Horizontal
7440.2	63.74	7.10	36.53	44.60	62.77	74.00	-11.23	Pk	Horizontal
7440.2	45.70	7.10	36.53	44.60	44.73	54.00	-9.27	AV	Horizontal

5.4.4.2 Bandedge-radiated

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(3) All other emissions more than 20dB below the limit.

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK									
2310.00	62.43	2.97	27.80	43.80	49.40	74	-24.60	Pk	Horizontal
2310.00	44.13	2.97	27.80	43.80	31.10	54	-22.90	AV	Horizontal
2310.00	61.75	2.97	27.80	43.80	48.72	74	-25.28	Pk	Vertical
2310.00	42.50	2.97	27.80	43.80	29.47	54	-24.53	AV	Vertical
2390.00	63.80	3.14	27.21	43.80	50.35	74	-23.65	Pk	Vertical
2390.00	42.48	3.14	27.21	43.80	29.03	54	-24.97	AV	Vertical
2390.00	63.73	3.14	27.21	43.80	50.28	74	-23.72	Pk	Horizontal
2390.00	43.21	3.14	27.21	43.80	29.76	54	-24.24	AV	Horizontal
2483.50	62.64	3.58	27.70	44.00	49.92	74	-24.08	Pk	Vertical
2483.50	42.80	3.58	27.70	44.00	30.08	54	-23.92	AV	Vertical
2483.50	65.25	3.58	27.70	44.00	52.53	74	-21.47	Pk	Horizontal
2483.50	44.55	3.58	27.70	44.00	31.83	54	-22.17	AV	Horizontal

5.4.4.3 Spurious Emission in Restricted Band 3260MHz-18000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
3260	63.53	4.04	29.57	44.70	52.44	74	-21.56	Pk	Vertical
3260	56.51	4.04	29.57	44.70	45.42	54	-8.58	AV	Vertical
3260	64.55	4.04	29.57	44.70	53.46	74	-20.54	Pk	Horizontal
3260	57.37	4.04	29.57	44.70	46.28	54	-7.72	AV	Horizontal
3332	64.17	4.26	29.87	44.40	53.90	74	-20.10	Pk	Vertical
3332	56.24	4.26	29.87	44.40	45.97	54	-8.03	AV	Vertical
3332	65.26	4.26	29.87	44.40	54.99	74	-19.01	Pk	Horizontal
3332	50.31	4.26	29.87	44.40	40.04	54	-13.96	AV	Horizontal
17797	43.73	10.99	43.95	43.50	55.17	74	-18.83	Pk	Vertical
17797	34.37	10.99	43.95	43.50	45.81	54	-8.19	AV	Vertical
17788	44.18	11.81	43.69	44.60	55.08	74	-18.92	Pk	Horizontal
17788	34.34	11.81	43.69	44.60	45.24	54	-8.76	AV	Horizontal

5.5 Power spectral density test

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5

5.5.2 Test procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test setup




5.5.4 EUT operation conditions

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing


5.5.5 Test results

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V by battery
Test Mode :	TX Mode /CH00, CH19, CH39		


Frequency	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2402 MHz	-14.100	8	PASS
2440 MHz	-14.193	8	PASS
2480 MHz	-15.190	8	PASS



TX CH19



TX CH39



5.6 6dB bandwidth

5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5

5.6.2 TEST PROCEDURE

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 TEST SETUP




5.6.4 EUT operation conditions

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing


5.6.5 Test Result

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V by battery
Test Mode :	TX Mode /CH00, CH19, CH39		


Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	692.1	500	Pass
Middle	2440	690.9	500	Pass
High	2480	685.5	500	Pass



TX CH 19



TX CH 39



5.7 Conducted bandedge

5.7.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.7.2 Test setup



5.7.3 Test procedure

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.


5.7.4 EUT operation conditions

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing


5.7.5 Test Result

EUT :	GT-Sense SMA Connectors	Model Name :	CM2-1112120
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V by battery
Test Mode :	TX Mode /CH00, CH39		

BLE: Band Edge, Left Side





BLE: Band Edge, Right Side



Photographs of the Test Setup

Radiated emission



Conducted emission



Photographs of the EUT

See the APPENDIX 1: EUT PHOTO in the report No.: MTi190614E097-1.

----END OF REPORT----