

Analysis Report

The Equipment Under Test (EUT) is a Bluetooth version 2.1 speaker operating from 2402-2480MHz with 1MHz channel spacing. The EUT is powered by 1 x 3.7VDC rechargeable battery. After switch on the EUT and paired with smart device, music can be played by EUT. Also, Music can be played by AUX in cable.

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength: 95.5dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 98.5dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 2.124\text{mw}$

Conducted power = Radiated Power (EIRP) – Antenna Gain
So;

Conducted Power = 2.124mW.

The SAR Exclusion Threshold Level:

$= 3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$
 $= 3.0 \cdot 5 / \sqrt{2.480} \text{ mW}$
 $= 9.53 \text{ mW}$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.