

FCC TEST REPORT

according to

FCC Rules and Regulations

Part 15 Subpart C

Applicant	SerComm Corporation
Address	3F No.81 YuYi Rd. Chu-Nan Miao-Li 350 Taiwan R.O.C.
Equipment	Wireless Network Camera
Model No.	NC802APT
Series No.	ICA-550W , ALL2250 , RV-E1 , NC802A , ICA-150W , ALL2211 , NC802AN
FCC ID	P270V910
Trade Name	SerComm / Planet / ALLNET

Laboratory Accreditation



1332

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Exclusive Certification Corp.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Contents

CERTIFICATE OF COMPLIANCE	4
1. Report of Measurements and Examinations.....	5
1.1 List of Measurements and Examinations	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment under Test.....	6
2.2 Test Mode and Test Software	7
2.3 Description of Test System.....	7
2.4 Connection Diagram of Test System.....	7
2.5 RF Specifications	8
2.6 The series name and model	8
2.7 History of this test report	8
2.8 General Information of Test.....	9
3. Antenna Requirements.....	10
3.1 Standard Applicable	10
3.2 Antenna Construction and Directional Gain.....	10
4. Test of Conducted Emission.....	11
4.1 Test Limit	11
4.2 Test Procedures	11
4.3 Typical Test Setup	12
4.4 Measurement equipment	12
4.5 Test Result and Data.....	13
4.6 Test Photographs	15
5. Test of Radiated Emission	16
5.1 Test Limit	16
5.2 Test Procedures	17
5.3 Typical Test Setup	18
5.4 Measurement equipment	18
5.5 Test Result and Data.....	19
5.6 Test Photographs	35
6. 6dB Bandwidth Measurement Data.....	36
6.1 Test Limit	36
6.2 Test Procedures	36
6.3 Test Setup Layout	36
6.4 Measurement equipment	36
6.5 Test Result and Data.....	36
7. Maximum Peak Output Power	40
7.1 Test Limit	40
7.2 Test Procedures	40
7.3 Test Setup Layout	40
7.4 Measurement equipment	40
7.5 Test Result and Data.....	40
8. Band Edges Measurement.....	44
8.1 Test Limit	44
8.2 Test Procedure :	44
8.3 Test Setup Layout	44
8.4 Measurement equipment	44

8.5	Test Result and Data.....	44
8.6	Restrict band emission Measurement Data.....	49
9.	Power Spectral Density	50
9.1	Test Limit	50
9.2	Test Procedures	50
9.3	Test Setup Layout :	50
9.4	List of Measuring Equipment Used	50
9.5	Test Result and Data.....	50
10.	Restricted Bands of Operation.....	54
10.1	Labeling Requirement.....	54
Appendix A. Photographs of EUT.....		A1 ~ A9

CERTIFICATE OF COMPLIANCE

according to

FCC Rules and Regulations

Part 15 Subpart C


Applicant	SerComm Corporation
Address	3F No.81 YuYi Rd. Chu-Nan Miao-Li 350 Taiwan R.O.C.
Equipment	Wireless Network Camera
Model No.	NC802APT
Series No.	ICA-550W , ALL2250 , RV-E1 , NC802A , ICA-150W , ALL2211 , NC802AN
FCC ID	P270V910

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2003)**.

The test was carried out on Aug. 04, 2006 at **Exclusive Certification Corp.**

Signature


Anson Chou / Manager

1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(c)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(d)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass

Test engineer: _____

Jerry

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Mode	NC802APT
Dimensions	107mm (W) * 136mm (H) * 66mm (D)
Operating temperature	0 to 40
Storage Temperature	-20 to 70
Network Protocols	TCP/IP, DHCP, SMTP, NTP, HTTP, UPnP (Discovery only)
Network Interface	1 Ethernet 10/ 100BaseT (RJ45) LAN connection
Wireless interface	IEEE 802.11b/802.11g compatible, Infrastructure/Ad-hoc mode, WEP/WPA-Personal security support, roaming support
LEDs	3
Power Adapter	5V/205A DC External
Stream Live Video to Multiple Users.	The MPEG4 encoder and HTTP server built into the camera generate a ready-to-view video stream. Just connect to the camera using your Web browser or the provided Windows utility to view live video.
Multi-Protocol Support	Supporting TCP/IP networking, SMTP (E-mail), HTTP and other Internet related protocols, the Network Camera can be easily integrated into your existing network.
Audio Support	You can listen as well as look! Audio is encoded with the video if desired. You can use either the built-in microphone or an external microphone.
PoE Support.	You can use PoE (Power over Ethernet) to provide power to the Network Camera, so only a single cable connection is required.

2.2 Test Mode and Test Software

The following test mode and test software was performed for conduction and radiation test:


- 802.11b (CH01: 2412MHz) • 802.11b (CH06: 2437MHz) • 802.11b (CH11: 2462MHz)
- 802.11g (CH01: 2412MHz) • 802.11g (CH06: 2437MHz) • 802.11g (CH11: 2462MHz)
- An executive programs, "telnet.exe" Application under WIN XP.

2.3 Description of Test System

Use Cable:

Cable	Description
RJ 45*1	Unshielding, 5 m

2.4 Connection Diagram of Test System



1. The I/O cable is connected from Remote workstation to the EUT

2.5 RF Specifications

- Standards Compliant. The Network Camera complies with the IEEE802.11g (DSSS) specifications for Wireless LANs.
- Supports both 802.11b and 802.11g Standards. The Network Camera supports both 802.11b and 802.11g standards.
- Speeds to 54Mbps. All speeds up to the 802.11g maximum of 54Mbps are supported.
- Wired and Wireless Network Support. The Network Camera supports either wired and wireless transmission.
- WEP Support. Full WEP support (64/128 Bit) on the Wireless interface is provided.
- WPA-Personal Support. The WPA-Personal (WPA1) standard is also supported, allowing advanced encryption of wireless data.

2.6 The series name and model

APT (Video with Motor)	A (Video w/o Motor)	AN (Video with Night View)	Trademark
NC802APT	NC802A	NC802AN	X
ICA-550W	ICA-150W	---	Planet
ALL2250	ALL2211	---	ALLNET
RV-E1	---	---	X

2.7 History of this test report

ORIGINAL.

2.8 General Information of Test

Test Site:	Exclusive Certification Corp. 4F-2, No. 28, Lane 78, Xing-Ai Rd. Nei-hu, Taipei City 114 Taiwan R.O.C.
Test Site Location (OATS1-SD):	No.68-1, Shihbachongsi, shihding Township, Taipei City 223, Taiwan, R.O.C.
Registration Number:	632249
Test Voltage:	AC 120V/ 60Hz
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna type: Reverse SMA Dipole Antenna

Antenna Gain: 2 dBi.

.

4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

4.3 Typical Test Setup




4.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date
Receiver	SCR3501	Schaffner	437	2006/11/03
LISN	NNB-2/16Z	MESS TEC	02/10191	2007/03/30
LISN	NNB-2/16Z	ROLF HEINE	03/10058	2007/04/26

4.5 Test Result and Data

EUT : NC802APT
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : MU18-2050250-A1

Pol/Phase : NEUTRAL
 Temperature : 25 °C
 Humidity : 54 %




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.15	45.63	0.28	45.91	65.81	-19.91	QP
2	0.15	32.36	0.28	32.64	55.81	-23.18	AVERAGE
3	0.18	43.26	0.24	43.50	64.69	-21.19	QP
4	0.18	27.65	0.24	27.89	54.69	-26.80	AVERAGE
5	0.44	37.26	0.49	37.75	57.09	-19.34	QP
6	0.44	23.20	0.49	23.69	47.09	-23.40	AVERAGE
7	1.51	39.33	0.46	39.79	56.00	-16.21	QP
8	1.51	25.00	0.46	25.46	46.00	-20.54	AVERAGE
9	3.01	38.13	0.56	38.69	56.00	-17.31	QP
10	3.01	26.39	0.56	26.95	46.00	-19.05	AVERAGE
11	5.03	36.23	0.60	36.83	60.00	-23.17	QP
12	5.03	26.22	0.60	26.82	50.00	-23.18	AVERAGE

- Remarks:
1. Level = Read Level + Factor
 2. Factor = LISN(ISN) Factor + Cable Loss
 3. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
 4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 5. The data is worse case.

EUT : NC802APT
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : MU18-2050250-A1

Pol/Phase : LINE
 Temperature : 25 °C
 Humidity : 54 %



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB	dBuV	dBuV	dBuV	
1	0.15	45.86	0.28	46.14	65.81	-19.68	QP
2	0.15	28.63	0.28	28.91	55.81	-26.91	AVERAGE
3	0.18	25.73	0.24	25.97	54.71	-28.74	AVERAGE
4	0.18	42.96	0.24	43.20	64.71	-21.51	QP
5	0.44	18.86	0.50	19.36	47.05	-27.69	AVERAGE
6	0.44	36.94	0.50	37.44	57.05	-19.61	QP
7	0.92	33.12	0.50	33.62	56.00	-22.38	QP
8	0.92	11.93	0.50	12.43	46.00	-33.57	AVERAGE
9	2.71	38.73	0.60	39.33	56.00	-16.67	QP
10	2.71	26.63	0.60	27.23	46.00	-18.77	AVERAGE
11	4.93	25.76	0.60	26.36	46.00	-19.64	AVERAGE
12	4.93	34.98	0.60	35.58	56.00	-20.42	QP

- Remarks:
1. Level = Read Level + Factor
 2. Factor = LISN(ISN) Factor + Cable Loss
 3. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
 4. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
 5. The data is worse case.

Test engineer:

Ben

5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions. For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V/ M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0


For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37

5.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.3 Typical Test Setup




5.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date
EMI Receiver	8546A	HP	3807A00454	2007/05/11
Spectrum Analyzer	FSP40	R&S	10047	2007/01/16
Horn Antenna	3115	EMCO	31589	2007/02/12
Horn Antenna	3116	EMCO	31970	2007/02/09
Bilog Antenna	CBL6112B	Schaffner	2840	2007/04/19
Amplifier	8449B	Agilent	3008A01954	2007/01/08
Amplifier	8447D	Agilent	2944A10531	2006/08/09

5.5 Test Result and Data

EUT	: NC802APT	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 68 %
Operation Channel	: 1	Atmospheric Pressure	: 1010 hPa
Modulation Type	: 802.11g		
Rate	: 54 Mbps		
Memo	: MU18-2050250-A1		



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	59.98	51.59	-22.64	28.95	40.00	-11.05	Peak	200	0
2	75.00	46.82	-19.09	27.73	40.00	-12.27	Peak	200	52
3	124.99	45.89	-14.11	31.78	43.50	-11.72	Peak	200	120
4	133.08	41.22	-13.83	27.39	43.50	-16.11	Peak	200	193
5	150.00	40.10	-13.05	27.05	43.50	-16.45	Peak	200	221
6	168.00	46.63	-15.02	31.61	43.50	-11.89	Peak	200	296
7	180.02	44.70	-15.90	28.80	43.50	-14.70	Peak	200	296
8	190.81	41.11	-15.01	26.10	43.50	-17.40	Peak	200	0
9	202.50	45.47	-15.13	30.34	43.50	-13.16	Peak	200	16
10	250.00	47.20	-11.59	35.61	46.00	-10.39	Peak	200	69
11	300.00	45.74	-8.72	37.02	46.00	-8.98	Peak	200	77

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : NC802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	348.00	48.56	-7.72	40.84	46.00	-5.16	QP	200	351
2	405.00	42.58	-6.75	35.83	46.00	-10.17	Peak	200	22
3	432.20	40.60	-6.41	34.19	46.00	-11.81	Peak	200	0
4	480.05	41.25	-6.03	35.22	46.00	-10.78	Peak	200	0
5	504.00	42.62	-5.80	36.82	46.00	-9.18	Peak	200	55
6	633.23	43.98	-2.49	41.49	46.00	-4.51	QP	200	93
7	808.90	44.63	-2.22	42.41	46.00	-3.59	QP	200	93

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : NC802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	54.00	56.89	-20.45	36.44	40.00	-3.56	QP	100	156
2	60.02	58.92	-22.26	36.66	40.00	-3.34	QP	100	156
3	66.00	59.32	-23.19	36.13	40.00	-3.87	QP	100	177
4	78.04	52.97	-21.58	31.39	40.00	-8.61	Peak	100	26
5	124.99	42.65	-17.01	25.64	43.50	-17.86	Peak	100	93
6	133.08	46.12	-17.16	28.96	43.50	-14.54	Peak	100	82
7	159.96	46.83	-17.83	29.00	43.50	-14.50	Peak	100	82
8	167.95	48.53	-17.23	31.30	43.50	-12.20	Peak	100	222
9	180.00	49.74	-14.50	35.24	43.50	-8.26	Peak	100	196
10	200.00	48.99	-15.42	33.57	43.50	-9.93	Peak	100	196
11	202.50	52.63	-15.49	37.14	43.50	-6.36	Peak	100	223
12	250.00	49.33	-8.87	40.46	46.00	-5.54	QP	100	223
13	300.02	51.39	-8.47	42.92	46.00	-3.08	QP	100	336

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : NC802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	323.81	46.53	-8.47	38.06	46.00	-7.94	Peak	100	47
2	348.30	46.25	-8.47	37.78	46.00	-8.22	Peak	100	89
3	375.00	46.59	-8.56	38.03	46.00	-7.97	Peak	100	193
4	400.12	41.42	-8.65	32.77	46.00	-13.23	Peak	100	221
5	480.04	45.51	-5.67	39.84	46.00	-6.16	Peak	100	293
6	500.11	45.33	-5.24	40.09	46.00	-5.91	QP	100	293
7	633.23	45.95	-4.25	41.70	46.00	-4.30	QP	100	360
8	660.78	42.50	-3.61	38.89	46.00	-7.11	Peak	100	360
9	717.91	43.62	-4.64	38.98	46.00	-7.02	Peak	100	63
10	810.00	39.14	-2.90	36.24	46.00	-9.76	Peak	100	50

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 1
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure : 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.06	35.64	5.71	41.35	54.00	-12.65	Average	100	188
2	4824.06	47.40	5.71	53.11	74.00	-20.89	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.12	36.85	5.71	42.56	54.00	-11.44	Average	100	82
2	4824.12	48.59	5.71	54.30	74.00	-19.70	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 6
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure : 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.91	35.41	5.85	41.26	54.00	-12.74	Average	100	188
2	4873.91	47.29	5.85	53.14	74.00	-20.86	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 6
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.96	36.93	5.85	42.78	54.00	-11.22	Average	100	82
2	4873.96	48.64	5.85	54.49	74.00	-19.51	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 11
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure : 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.02	35.88	5.99	41.87	54.00	-12.13	Average	100	188
2	4924.02	47.50	5.99	53.49	74.00	-20.51	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 11
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa




Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.93	36.47	5.99	42.46	54.00	-11.54	Average	100	82
2	4923.93	48.23	5.99	54.22	74.00	-19.78	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT	: IP802APT	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 68 %
Operation Channel	: 1	Atmospheric Pressure	: 1010 hPa
Modulation Type	: 802.11g		
Rate	: 54 Mbps		
Memo	: MU18-2050250-A1		



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4823.89	35.36	5.71	41.07	54.00	-12.93	Average	100	188
2	4823.89	47.11	5.71	52.82	74.00	-21.18	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.12	35.56	5.71	41.27	54.00	-12.73	Average	100	82
2	4824.12	47.33	5.71	53.04	74.00	-20.96	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 6
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4873.96	35.63	5.85	41.48	54.00	-12.52	Average	100	188
2	4873.96	47.35	5.85	53.20	74.00	-20.80	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 6
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure : 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.11	35.69	5.85	41.54	54.00	-12.46	Average	100	82
2	4874.11	47.38	5.85	53.23	74.00	-20.77	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 11
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)


Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.97	35.70	5.99	41.69	54.00	-12.31	Average	100	188
2	4923.97	47.53	5.99	53.52	74.00	-20.48	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : IP802APT
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 11
 Modulation Type : 802.11g
 Rate : 54 Mbps
 Memo : MU18-2050250-A1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 68 %
 Atmospheric Pressure: 1010 hPa



Trace: (Discrete)

Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4923.92	35.79	5.99	41.78	54.00	-12.22	Average	100	82
2	4923.92	47.55	5.99	53.54	74.00	-20.46	Peak	100	82

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

6.3 Test Setup Layout



6.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

6.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	12.0
06	2437	12.1
11	2462	11.6

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	16.6
06	2437	16.6
11	2462	16.6

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 26.JUL.2006 14:48:58

Channel:06




Date: 26.JUL.2006 15:49:57

Channel:11




Date: 26.JUL.2006 15:16:39

Modulation Standard:802.11g (54Mbps)
 Channel:01




Date: 26.JUL.2006 16:45:21

Channel:06



Date: 27.JUL.2006 09:47:15

Channel:11



Date: 27.JUL.2006 10:12:37

7. Maximum Peak Output Power


7.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

7.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

7.3 Test Setup Layout



7.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

7.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	18.25	66.8
06	2437	18.29	67.5
11	2462	18.28	67.3

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	14.06	25.5
06	2437	14.02	25.2
11	2462	14.01	25.2

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 26.JUL.2006 13:45:22

Channel:06




Date: 26.JUL.2006 14:22:42

Channel: 11




Date: 26.JUL.2006 14:02:10

Modulation Standard: 802.11g (54Mbps)
Channel: 01


Date: 26.JUL.2006 16:43:45

Channel: 06



Date: 27.JUL.2006 09:45:21

Channel:11



Date: 27.JUL.2006 10:10:56

8. Band Edges Measurement


8.1 Test Limit

Below –20dB of the highest emission level of operating band
(In 100 kHz Resolution Bandwidth)

8.2 Test Procedure :

- 1.The transmitter output was connected to the spectrum analyzer via a low lose cable.
- 2.Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- 3.The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

8.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa

Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2399.0	-46.78
11	2462	2590.0	-43.22


(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2399.6	-41.10
11	2462	2590.0	-55.08

Modulation Standard: 802.11b (11Mbps)

Channel: 01




Date: 26.JUL.2006 15:04:05




Date: 26.JUL.2006 15:05:00

Channel: 11




Date: 26.JUL.2006 15:38:09




Date: 26.JUL.2006 15:40:01

Modulation Standard: 802.11g (54Mbps)

Channel: 01




Date: 26.JUL.2006 16:57:02




Date: 26.JUL.2006 16:58:34

Channel: 11



Date: 27.JUL.2006 10:34:22



Date: 27.JUL.2006 10:35:55

8.6 Restrict band emission Measurement Data

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 04, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.968	H	52.33	-0.75	51.58	Peak	74	54	-22.42	188	1.1
2389.968	H	41.35	-0.75	40.60	Ave	74	54	-13.40	188	1.1
2389.764	V	55.91	-0.75	55.16	Peak	74	54	-18.84	82	1.0
2389.968	V	44.83	-0.75	44.08	Ave	74	54	-9.92	82	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2491.944	H	52.62	-0.43	52.19	Peak	74	54	-21.81	188	1.1
2483.508	H	41.25	-0.45	41.07	Ave	74	54	-12.93	188	1.1
2491.184	V	56.08	-0.43	55.65	Peak	74	54	-18.35	82	1.0
2483.508	V	45.15	-0.45	44.70	Ave	74	54	-9.30	82	1.0

Modulation Standard: 802.11g (54Mbps)

Test Date: Aug. 04, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2388.013	H	52.04	-0.75	51.29	Peak	74	54	-22.71	188	1.1
2389.764	H	41.12	-0.75	40.37	Ave	74	54	-13.63	188	1.1
2389.968	V	55.59	-0.75	54.84	Peak	74	54	-19.16	82	1.0
2389.968	V	44.53	-0.75	43.78	Ave	74	54	-10.22	82	1.0

c) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2486.588	H	52.22	-0.44	51.78	Peak	74	54	-22.22	188	1.1
2483.508	H	41.35	-0.45	40.90	Ave	74	54	-13.10	188	1.1
2488.904	V	55.59	-0.44	55.15	Peak	74	54	-18.85	82	1.0
2483.622	V	44.70	-0.45	44.25	Ave	74	54	-9.75	82	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

9. Power Spectral Density


9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

9.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- c. The power spectral density was measured and recorded.
- d. The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

9.3 Test Setup Layout :



9.4 List of Measuring Equipment Used

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

9.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-12.87
06	2437	-12.86
11	2462	-10.73

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Jul. 26, 2006 Temperature: 25 Humidity: 68% Atmospheric pressure: 1010 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-21.28
06	2437	-21.03
11	2462	-21.75

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 26.JUL.2006 15:02:40

Channel:06




Date: 26.JUL.2006 14:34:49

Channel: 11




Date: 26.JUL.2006 15:34:46

Modulation Standard: 802.11g (54Mbps)
 Channel: 01




Date: 26.JUL.2006 16:55:09

Channel: 06



Date: 27.JUL.2006 09:57:27

Channel:11



Date: 27.JUL.2006 10:24:03

10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.