

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	33.59	24.75	38.45	PASS
GSM850	190	5	33.81	24.97	38.45	PASS
GSM850	251	5	33.25	24.41	38.45	PASS
GSM1900	512	0	30.70	28.86	33.00	PASS
GSM1900	661	0	30.88	29.04	33.00	PASS
GSM1900	810	0	30.55	28.71	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	33.60	24.76	38.45	PASS
GPRS850	128	5	2	32.41	23.57	38.45	PASS
GPRS850	128	5	3	29.96	21.12	38.45	PASS
GPRS850	128	5	4	28.54	19.7	38.45	PASS
GPRS850	190	5	1	33.81	24.97	38.45	PASS
GPRS850	190	5	2	32.65	23.81	38.45	PASS
GPRS850	190	5	3	30.27	21.43	38.45	PASS
GPRS850	190	5	4	28.84	20	38.45	PASS
GPRS850	251	5	1	33.23	24.39	38.45	PASS
GPRS850	251	5	2	31.93	23.09	38.45	PASS
GPRS850	251	5	3	29.51	20.67	38.45	PASS
GPRS850	251	5	4	28.06	19.22	38.45	PASS
GPRS1900	512	0	1	30.74	28.9	33.00	PASS
GPRS1900	512	0	2	29.97	28.13	33.00	PASS
GPRS1900	512	0	3	27.79	25.95	33.00	PASS
GPRS1900	512	0	4	26.13	24.29	33.00	PASS
GPRS1900	661	0	1	30.89	29.05	33.00	PASS
GPRS1900	661	0	2	30.11	28.27	33.00	PASS
GPRS1900	661	0	3	28.03	26.19	33.00	PASS
GPRS1900	661	0	4	26.39	24.55	33.00	PASS
GPRS1900	810	0	1	30.53	28.69	33.00	PASS
GPRS1900	810	0	2	29.82	27.98	33.00	PASS
GPRS1900	810	0	3	27.87	26.03	33.00	PASS
GPRS1900	810	0	4	26.24	24.4	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	28.68	19.84	38.45	PASS
EGPRS850	128	8	2	27.51	18.67	38.45	PASS
EGPRS850	128	8	3	25.49	16.65	38.45	PASS
EGPRS850	128	8	4	24.27	15.43	38.45	PASS
EGPRS850	190	8	1	28.62	19.78	38.45	PASS
EGPRS850	190	8	2	27.48	18.64	38.45	PASS
EGPRS850	190	8	3	25.44	16.6	38.45	PASS
EGPRS850	190	8	4	24.26	15.42	38.45	PASS
EGPRS850	251	8	1	28.59	19.75	38.45	PASS
EGPRS850	251	8	2	27.42	18.58	38.45	PASS
EGPRS850	251	8	3	25.43	16.59	38.45	PASS
EGPRS850	251	8	4	24.26	15.42	38.45	PASS
EGPRS1900	512	2	1	27.34	25.5	33.00	PASS
EGPRS1900	512	2	2	26.17	24.33	33.00	PASS
EGPRS1900	512	2	3	24.01	22.17	33.00	PASS
EGPRS1900	512	2	4	22.78	20.94	33.00	PASS
EGPRS1900	661	2	1	27.65	25.81	33.00	PASS
EGPRS1900	661	2	2	26.48	24.64	33.00	PASS
EGPRS1900	661	2	3	24.40	22.56	33.00	PASS
EGPRS1900	661	2	4	23.10	21.26	33.00	PASS
EGPRS1900	810	2	1	27.58	25.74	33.00	PASS
EGPRS1900	810	2	2	26.44	24.6	33.00	PASS
EGPRS1900	810	2	3	24.36	22.52	33.00	PASS
EGPRS1900	810	2	4	22.98	21.14	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.71	13	PASS
EGPRS850	190	8	5.57	13	PASS
GSM1900	661	0	2.7	13	PASS
EGPRS1900	661	2	5.79	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24638	0.3085	---	PASS
GSM850	190	5	0.24451	0.3176	---	PASS
GSM850	251	5	0.24594	0.3163	---	PASS
EGPRS850	128	8	0.24942	0.3143	---	PASS
EGPRS850	190	8	0.24630	0.3150	---	PASS
EGPRS850	251	8	0.24575	0.3105	---	PASS
GSM1900	512	0	0.24546	0.3133	---	PASS
GSM1900	661	0	0.24777	0.3138	---	PASS
GSM1900	810	0	0.24412	0.3104	---	PASS
EGPRS1900	512	2	0.24859	0.3030	---	PASS
EGPRS1900	661	2	0.24881	0.3139	---	PASS
EGPRS1900	810	2	0.24741	0.3025	---	PASS

Test Graphs






Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	824.00	-22.94	-13	PASS
GSM850	251	5	849.01	-23.94	-13	PASS
EGPRS850	128	8	823.98	-32.62	-13	PASS
EGPRS850	251	8	849.02	-32.01	-13	PASS
GSM1900	512	0	1850.00	-27.80	-13	PASS
GSM1900	810	0	1910.02	-26.15	-13	PASS
EGPRS1900	512	2	1849.99	-18.43	-13	PASS
EGPRS1900	810	2	1910.04	-15.08	-13	PASS

Test Graphs




JianYan Testing Group Shenzhen Co., Ltd.

No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2406068




Appendix E: Conducted Spurious Emission


Test Result


Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-54.23	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-41.15	-13	PASS
GSM850	128	5	30~1000MHz	426.34	-44.07	-13	PASS
GSM850	128	5	1000~10000MHz	1648.3	-28.05	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-54.13	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-42.78	-13	PASS
GSM850	190	5	30~1000MHz	966.47	-43.63	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-28.43	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-56.08	-33	PASS
GSM850	251	5	0.15~30MHz	0.15	-43.16	-13	PASS
GSM850	251	5	30~1000MHz	961.46	-44.08	-13	PASS
GSM850	251	5	1000~10000MHz	2546.5	-30.45	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-56.24	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-43.43	-23	PASS
GSM1900	512	0	30~1000MHz	831.93	-40.44	-13	PASS
GSM1900	512	0	1000~18000MHz	16949.4	-21.15	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-55.98	-43	PASS
GSM1900	661	0	0.15~30MHz	0.15	-41.39	-23	PASS
GSM1900	661	0	30~1000MHz	834.07	-44.52	-13	PASS
GSM1900	661	0	1000~18000MHz	17000.4	-21.77	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-57.91	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-42.73	-23	PASS
GSM1900	810	0	30~1000MHz	886.32	-45.73	-13	PASS
GSM1900	810	0	1000~18000MHz	16220.67	-22.35	-13	PASS


Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs









Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	4.65	0.005558	±2.5	Pass
	-20	4.10	0.004901		
	-10	5.20	0.006216		
	0	1.52	0.001817		
	10	3.42	0.004088		
	20	0.94	0.001124		
	30	0.32	0.000383		
	40	-0.55	-0.000657		
	50	0.45	0.000538		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	6.65	0.007949	±2.5	Pass
	3.87	5.10	0.006096		
	4.45	3.58	0.004279		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-1.10	-0.001315	±2.5	Pass
	-20	-2.94	-0.003514		
	-10	-6.97	-0.008331		
	0	-2.78	-0.003323		
	10	-3.52	-0.004208		
	20	-7.33	-0.008762		
	30	-5.49	-0.006562		
	40	-4.33	-0.005176		
	50	-3.52	-0.004208		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-7.91	-0.009455	±2.5	Pass
	3.87	-4.58	-0.005475		
	4.45	-3.26	-0.003897		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	9.33	0.004963	Within authorized band for PCS 1900	Pass
	-20	7.88	0.004191		
	-10	4.10	0.002181		
	0	5.20	0.002766		
	10	-1.81	-0.000963		
	20	-1.87	-0.000995		
	30	2.42	0.001287		
	40	-0.42	-0.000223		
	50	-4.84	-0.002574		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	14.08	0.007489	Within authorized band for PCS 1900	Pass
	3.87	4.91	0.002612		
	4.45	13.53	0.007197		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-7.26	-0.003862	Within authorized band for PCS 1900	Pass
	-20	-7.49	-0.003984		
	-10	-9.56	-0.005085		
	0	-6.39	-0.003399		
	10	-10.65	-0.005665		
	20	-5.88	-0.003128		
	30	-8.46	-0.004500		
	40	4.49	0.002388		
	50	-3.45	-0.001835		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-4.33	-0.002303	Within authorized band for PCS 1900	Pass
	3.87	-8.52	-0.004532		
	4.45	-11.27	-0.005995		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

