



FCC PART 15.231 TEST REPORT

On Behalf of

Dongguan Beijia Electronic Technology Co., Ltd

Room 403, 4th Floor, 102 Yanwu Road, Dalingshan Town, Dongguan City, Guangdong
Province

FCC ID: 2AZUG-WA144

Model: WA144, BJ610, WA144B, WA144C

November 24, 2023

This Report Concerns:

☒ Original Report

Equipment Type:

Wireless Transmitter

Test Engineer:

Fan Yang / 

Report Number:

QCT23KR-2201E-01

Test Date:

November 6~15, 2023

Reviewed By:

Gordon Tan / 

Approved By:

Kendy Wang / 



Prepared By:

Shenzhen QC Testing Laboratory Co., Ltd.

East of 1/F., Building E, Xinghong Science Park, No.111,
Shuiku Road, Fenghuanggang, Xixiang Street, Bao'an
District, Shenzhen, Guangdong, China

Tel: 0755-23008269

Fax: 0755-23726780



Table of Contents

1. GENERAL INFORMATION.....	4
1.1 Product Description for Equipment under Test (EUT)	4
1.2 System Test Configuration	4
1.3 Test Facility.....	5
1.4 Measurement Uncertainty.....	5
2. SUMMARY OF TEST RESULTS	6
3. LIST OF TEST AND MEASUREMENT INSTRUMENTS	7
3.1 Radiated Emission Test.....	7
3.2 RF Conducted test.....	7
4. ANTENNA REQUIREMENT	8
5. RADIATED EMISSION METHOD	9
5.1 Applicable Standard.....	9
5.2 Limit	9
5.3 Receiver setup.....	9
5.4 Test setup.....	10
5.5 Test Procedure	10
5.6 Test Data	11
6. 20DB OCCUPY BANDWIDTH	14
6.1 Applicable Standard.....	14
6.2 Limit	14
6.3 Test setup.....	14
6.4 Test Data	14
7. DWELL TIME	16
7.1 Applicable Standard.....	16
7.2 Limit	16
7.3 Test setup.....	16
7.4 Test Data	16
8. DUTY CYCLE.....	17
8.1 Applicable Standard.....	17
8.2 Limit	17
8.3 Test setup.....	17
8.4 Test Procedure	17
8.5 Test Data	17



Report Number

Description

Issued Date

QCT23KR-2201E-01

Initial Issue

2023-11-24



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Description	Wireless Transmitter
Model No.	WA144, BJ610, WA144B, WA144C
Tested Model	WA144
Sample(s) Status	Engineer sample
Operation Frequency:	433.92MHz
Channel numbers:	1
Modulation type:	ASK
Antenna Type:	Spring Antenna
Antenna gain*1:	0dBi
Power supply:	DC 3V (Powered by 2*1.5V AAA battery)
Trade Mark:	N/A
Applicant	Dongguan Beijia Electronic Technology Co., Ltd
Address	Room 403, 4th Floor, 102 Yanwu Road, Dalingshan Town, Dongguan City, Guangdong Province
Manufacturer	Dongguan Beijia Electronic Technology Co., Ltd
Address	Room 403, 4th Floor, 102 Yanwu Road, Dalingshan Town, Dongguan City, Guangdong Province
Sample No.	Y23K2201E01YN

Note: *1This information provided by Manufacturer, SZ QC Lab is not responsible for the accuracy of this information.

1.2 System Test Configuration

1.2.1 Support Equipment

N/A

1.2.2 Test mode and voltage

Transmitting mode: Keep the EUT in continuously transmitting.

Test voltage: DC 3V



1.3 Test Facility

Test Firm : Shenzhen QC Testing Laboratory Co., Ltd.

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS – Registration No.: L8464

The EMC Laboratory has been accredited by CNAS, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

A2LA Certificate Number: 6759.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 561109

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 29628

CAB identifier: CN0141

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

1.4 Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 1.42 \times 10^{-4}\%$
RF output power, conducted	$\pm 1.06\text{dB}$
Power Spectral Density, conducted	$\pm 1.06\text{dB}$
Unwanted Emissions, conducted	$\pm 1.80\text{dB}$
Radiated Spurious Emission test (9kHz-30MHz)	$\pm 2.66\text{dB}$
Radiated Spurious Emission test (30MHz-1000MHz)	$\pm 4.04\text{dB}$
Radiated Spurious Emission test (1000MHz-18000MHz)	$\pm 4.70\text{ dB}$
Radiated Spurious Emission test (18GHz-40GHz)	$\pm 4.80\text{dB}$
Temperature	$\pm 0.8^{\circ}\text{C}$
Humidity	$\pm 3.2\%$
DC and low frequency voltages	$\pm 0.1\%$
Time	$\pm 5\%$
Duty cycle	$\pm 5\%$

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



2. Summary of Test Results

Test Item	Section	Result
Antenna Requirement	15.203	Pass
Conduction Emission	15.207	N/A
Field strength of the Fundamental Signal	15.231 (b)	Pass
Spurious Emissions	15.231 (b)/15.209	Pass
20dB Bandwidth	15.231 (c)	Pass
Dwell Time	15.231 (a)(1)	Pass

Note:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013
- 3.. All indications of Pass/Fail in this report are opinions expressed by Shenzhen QC Testing Laboratory Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



3. List of Test and Measurement Instruments

3.1 Radiated Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1.	Spectrum Analyzer	ROHDE&SCHWARZ	FSV 40	101458	2023.04.12	2024.04.11
2.	Logarithmic compound broadband Antenna	SCKWARZBECK	VULB9168	VULB9168-1-588	2023.04.01	2025.03.31
3.	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB 7	2277573376	2023.04.12	2024.04.11
4.	EMI Test Receiver	R&S	ESPI	101131	2023.03.21	2024.03.20
5.	Horn Antenna	SCHWARZBECK	BBHA9120D	02069	2023.04.01	2025.03.31
6.	Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2023.01.12	2025.01.09
7.	Amplifier	R&S	BBV9721	9721-031	2023.03.21	2024.03.20
8.	Amplifier	HPX	BP-01G-18G	210902	2023.03.21	2024.03.20
9.	Pre-amplifier	COM-MW	DLAN-18000-40000-02	10229104	2023.01.11	2024.01.10
10.	966 Chamber	ZhongYu Electron	9*6*6	/	2022.07.25	2025.07.24
Radiated Emission Measurement Software: EZ EMC						

3.2 RF Conducted test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1.	Wideband Radio Communication Tester	Rohde & Schwarz	CW500	151583	2023.03.21	2024.03.20
2.	Spectrum Analyzer	ROHDE&SCHWARZ	FSV 40	101458	2023.04.12	2024.04.11
3.	Signal Generator	Agilent	N5182A	MY50141563	2023.03.21	2024.03.20
4.	RF Automatic Test System	MW	MW100-RFCB/MW100-PSB	MW2007004	2023.03.21	2024.03.20
RF Conducted Measurement Software: MTS 8310						



4. Antenna requirement

Standard requirement: FCC Part15 C Section 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna: The antenna is Spring Antenna, reference to the Internal Photos for details.

5. Radiated Emission Method

5.1 Applicable Standard

FCC Part15 C Section 15.231 (b)& Section 15.209

5.2 Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
30-88	3	40	100
88-216	3	43.5	150
216-960	3	46	200
Above 960	3	54	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

In addition to the provisions of 15.231(b) and RSS 210-A1.1.2, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Funda-mental fre-quency (MHz)	Field strength of funda-mental (microvolts/ meter)	Field strength of spurious emissions (microvolts/meter)
40.66—40.70.	2,250	225
70—130	1,250	125
130—174	¹ 1,250 to 3,750	¹ 125 to 375
174—260	3,750	375
260—470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

¹ Linear interpolations.


[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 260-470 MHz, µV/m at 3 meters =41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

5.3 Receiver setup


Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

5.4 Test setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



5.5 Test Procedure

1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.



5.6 Test Data

Temperature	23.5 °C	Humidity	48%
ATM Pressure	101.1kPa	Antenna Gain	0dBi
Test by	Fan Yang	Test result	PASS


Measurement data:

9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Below 1GHz:

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	45.3754	6.41	14.71	21.12	40.00	18.88	QP
2	146.8876	5.41	14.51	19.92	43.50	23.58	QP
3	356.6758	12.14	16.40	28.54	46.00	17.46	QP
4	419.1081	22.02	18.23	40.25	46.00	5.75	QP
5	433.92	66.29	18.57	84.86	100.82	15.96	peak
6	867.84	18.17	25.89	44.06	80.82	36.76	peak



Vertical

80.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.7313	19.74	12.78	32.52	40.00	7.48	QP
2	59.0251	16.92	13.68	30.60	40.00	9.40	QP
3	63.7588	16.89	12.94	29.83	40.00	10.17	QP
4	370.7023	10.39	16.62	27.01	46.00	18.99	QP
5	413.2706	19.44	17.86	37.30	46.00	8.70	QP
6	433.92	54.03	18.27	72.30	100.82	28.52	peak
7	867.84	7.58	25.71	33.29	80.82	47.54	peak

**Above 1G:****Peak value:**

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	polarization
1301.76	59.38	-15.15	44.23	80.82	36.59	Horizontal
2169.6	61.92	-11.57	50.35	80.82	30.47	
2603.52	59.77	-10.17	49.6	80.82	31.22	
3037.44	60.86	-8.58	52.28	80.82	28.54	
3471.36	61.07	-7.81	53.26	80.82	27.56	
3905.28	69.37	-6.98	62.39	80.82	18.43	
4339.2	65.03	-5.86	59.17	80.82	21.65	Vertical
2169.6	60.42	-11.54	48.88	80.82	31.94	
3037.44	60.01	-8.3	51.71	80.82	29.11	
3471.36	60.47	-7.79	52.68	80.82	28.14	
3905.28	64.39	-6.81	57.58	80.82	23.24	
4339.2	59.31	-5.93	53.38	80.82	27.44	

Field Strength of The Fundamental Signal**Peak value:**

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	polarization
433.92	66.29	18.57	84.86	100.82	15.96	Horizontal
433.92	54.03	18.27	72.30	100.82	28.52	Vertical

Remarks:

1. Level = Reading + Factor

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

6. 20dB Occupy Bandwidth


6.1 Applicable Standard

FCC Part15 C Section 15.231 (c)

6.2 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

6.3 Test setup



6.4 Test Data

Temperature	23.5 °C	Humidity	48%
ATM Pressure	101.1kPa	Antenna Gain	0dBi
Test by	Fan Yang	Test result	PASS


Please refer to following table and plots.



Test Frequency (MHz)	20dB bandwidth (MHz)	Limit (MHz)	Result
433.92	0.01331	1.085	Pass

Note: Limit= Fundamental frequency \times 0.25%
433.92 \times 0.25%=1.085MHz

Test plot as follows:



Date: 22.NOV.2023 09:59:27

7. Dwell Time


7.1 Applicable Standard

FCC Part15 C Section 15.231 (a)(1)

7.2 Limit

Not more than 5 seconds.

7.3 Test setup




7.4 Test Data

Temperature	23.5 °C	Humidity	48%
ATM Pressure	101.1kPa	Antenna Gain	0dBi
Test by	Fan Yang	Test result	PASS

Please refer to following table and plots.

Frequency (MHz)	Duration of each TX (second)	Limit (second)	Result
433.92	0.268	<5.0	Pass



Date: 22.NOV.2023 10:02:08

8. Duty Cycle


8.1 Applicable Standard

FCC Part15 C Section 15.231

8.2 Limit

No dedicated limit specified in the Rules.

8.3 Test setup



8.4 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set centre frequency of spectrum analyzer=operating frequency.
4. Set the spectrum analyzer as RBW=100kHz, VBW=100KHz, Span=0Hz, Adjust Sweep=100ms to obtain the "worst-case" pulse on time
5. Repeat above procedures until all frequency measured was complete.

8.5 Test Data

N/A

Remarks: Since the peak value is less than the average limit, the average value does not need to be tested.

----- THE END OF TEST REPORT -----