

FCC & IC REPORT

Applicant: Horizon Hobby, LLC

Address of Applicant: 2904 Research Rd., Champaign, IL 61822

Equipment Under Test (EUT)

Product Name: DX6e Transmitter

Model No.: DX6e, DX8e

Trade mark: Spektrum

FCC ID: BRWP68CEVAUR

Canada IC: 6157A-P68CEVAUR

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-Gen Issue 5, April 2018
RSS-247 Issue 2, February 2017

Date of sample receipt: 04 Jan., 2019

Date of Test: 04 Jan., to 07 Mar., 2019

Date of report issued: 08 Mar., 2019

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	23 Jan., 2019	Original
01	08 Mar., 2019	Update sections 6.3 and 6.10

Tested by:

Mike.ou

Date:

08 Mar., 2019

Test Engineer

Reviewed by:

Wimer Zhang

Date:

08 Mar., 2019

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY.....	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST ENVIRONMENT AND TEST MODE	6
5.4	DESCRIPTION OF SUPPORT UNITS	6
5.5	MEASUREMENT UNCERTAINTY.....	6
5.6	LABORATORY FACILITY	6
5.7	LABORATORY LOCATION	6
5.8	TEST INSTRUMENTS LIST	7
6	TEST RESULTS AND MEASUREMENT DATA.....	8
6.1	ANTENNA REQUIREMENT.....	8
6.2	CONDUCTED EMISSIONS	9
6.3	CONDUCTED OUTPUT POWER	10
6.4	OCCUPY BANDWIDTH.....	12
6.5	CARRIER FREQUENCIES SEPARATION.....	14
6.6	HOPPING CHANNEL NUMBER.....	17
6.7	DWELL TIME	19
6.8	BAND EDGE.....	20
6.8.1	Conducted Emission Method	20
6.8.2	Radiated Emission Method	22
6.9	SPURIOUS EMISSION.....	27
6.9.1	Conducted Emission Method	27
6.9.2	Radiated Emission Method	29
6.10	FREQUENCY STABILITY	34
7	TEST SETUP PHOTO	36
8	EUT CONSTRUCTIONAL DETAILS.....	37

4 Test Summary

Test Items	Section		Result
	FCC	IC	
Antenna Requirement	15.203	RSS-GEN Section 6.8	Pass
AC Power Line Conducted Emission	15.207	RSS-GEN Section 8.8	N/A
Conducted Peak Output Power	15.247 (b)(1)	RSS-247 Section 5.4 (b)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	RSS-247 Section 5.1 (a)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	RSS-247 Section 5.1 (b)	Pass
Hopping Channel Number	15.247 (a)(iii)	RSS-247 Section 5.1 (d)	Pass
Dwell Time	15.247 (a)(iii)	RSS-247 Section 5.1 (d)	Pass
Spurious Emission	15.205/15.209	RSS-GEN Section 8.9 8.10 RSS-247 Section 5.5	Pass
Band Edge	15.247(d)	RSS-247 Section 5.5	Pass
Frequency stability	/	RSS-GEN Section 6.11	Pass
Pass: The EUT complies with the essential requirements in the standard. N/A: Not Applicable.			

5 General Information

5.1 Client Information

Applicant:	Horizon Hobby, LLC
Address:	2904 Research Rd., Champaign, IL 61822
Manufacturer:	Horizon Hobby, LLC
Address:	2904 Research Rd., Champaign, IL 61822

5.2 General Description of E.U.T.

Product Name:	DX6e Transmitter
Model No.:	DX6e, DX8e
Operation Frequency:	2404MHz ~ 2476MHz
Transfer rate:	1Mbits/s
Number of channel:	23
Channel separation:	3MHz and 4MHz
Modulation type:	GFSK
Modulation technology:	FHSS
Antenna Type:	Internal Antenna
Antenna gain:	2.0dBi
Power supply:	DC 6V ('AA' * 4 battery)
Remark:	Model No.: DX6e, DX8e were identical inside, the electrical circuit design, layout, components used and internal wiring. The difference between them is as follows: 1. Model name. 2. The DX8e has 2 additional servo control channels.

Test channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2404MHz	06	2424MHz	12	2443MHz	18	2463MHz
01	2407MHz	07	2427MHz	13	2446MHz	19	2466MHz
02	2411MHz	08	2430MHz	14	2450MHz	20	2469MHz
03	2414MHz	09	2433MHz	15	2453MHz	21	2473MHz
04	2417MHz	10	2437MHz	16	2456MHz	22	2476MHz
05	2420MHz	11	2440MHz	17	2459MHz		
Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test. Channel No. 00, 11 & 22 were selected as Lowest, Middle and Highest channel.							

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test Modes:	
Non-hopping mode:	Keep the EUT in continuous transmitting mode with worst case data rate.
Hopping mode:	Keep the EUT in hopping mode.
The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working with a fresh battery, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±2.22 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com


5.8 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-16-2018	03-15-2019
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		


Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-07-2018	03-06-2019
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-07-2018	03-06-2019
LISN	CHASE	MN2050D	1447	03-19-2018	03-18-2019
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2019
Cable	HP	10503A	N/A	03-07-2018	03-06-2019
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and measurement data


6.1 Antenna Requirement

Standard requirement:	FCC Part 15 C Section 15.203 & 247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Low-power transceiver antenna is an internal antenna which permanently attached, and the best case gain of the antenna is 2 dBi.	
	

6.2 Conducted Emissions

Test Requirement:	FCC Part 15 C Section 15.207, RSS-GEN Section 8.8		
Test Method:	ANSI C63.10:2013		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.		
Test Instruments:	Refer to section 5.8 for details		
Test mode:	Hopping mode		
Test results:	N/A		


6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(1), RSS-247 Section 5.4(b)
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW $\leq$ 1 MHz) RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz and < 3MHz)
Limit:	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:


Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	4.08	21.00	Pass
Middle	4.08	21.00	Pass
Highest	4.72	21.00	Pass

Test plot as follows:




Date: 7.MAR.2019 18:01:02

Lowest channel



Date: 7.MAR.2019 18:01:33


Middle channel



Date: 7.MAR.2019 18:06:57

Highest channel


6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1), RSS-247 Section 5.1(a)
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	NA
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:


Test channel	20dB Occupy Bandwidth (kHz)	99% Occupy Bandwidth (kHz)
Lowest	1260	1168
Middle	1200	1128
Highest	1124	1064

Test plot as follows:




Date: 15.JAN.2019 16:38:56

Lowest channel




Date: 15.JAN.2019 17:15:40

Lowest channel




Date: 15.JAN.2019 16:55:38

Middle channel




Date: 15.JAN.2019 17:17:07

Middle channel



Date: 15.JAN.2019 16:57:10


Highest channel



Date: 15.JAN.2019 17:14:14

Highest channel

6.5 Carrier Frequencies Separation

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1), RSS-247 Section 5.1(b)
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=100 kHz, VBW=300 kHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a 'Non-Conducted Table', which is a rectangular platform supported by two vertical legs. Below this table is a 'Ground Reference Plane', represented by a thick grey horizontal bar.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass


Measurement Data:

Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	4004	840.00	Pass
Middle	3052	800.00	Pass
Highest	4060	749.33	Pass


Note: According to section 6.4

Test channel	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
Lowest	1260	840.00
Middle	1200	800.00
Highest	1124	749.33


Test plot as follows:



Date: 15.JAN.2019 16:16:39




Date: 15.JAN.2019 16:22:33



Date: 15.JAN.2019 16:25:04


6.6 Hopping Channel Number

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1), RSS-247 Section 5.1(d)
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. The setup is placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass


Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK	23	15	Pass

Test plot as follows:



6.7 Dwell Time


Test Requirement:	FCC Part 15 C Section 15.247 (a)(1), RSS-247 Section 5.1(d)
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=1 MHz, VBW=1 MHz, Span=0 Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data (Worse case):

Test channel	Dwell time (second)	Limit (second)	Result
Middle channel	0.05328	0.4	Pass


Remark:
 $T \text{ period} = 0.4(\text{s}) * \text{channel number} = 0.4(\text{s}) * 23 = 9.2(\text{s})$
 $\text{Dwell time} = \text{per on time slot} * \text{Number of pulses in period} = (0.00148) (\text{s}) * 36 = 0.05328(\text{s})$

Test plot as follows:




6.8 Band Edge


6.8.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d), RSS-GEN Section 8.10 RSS-247 Section 5.5
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode and hopping mode
Test results:	Pass


Test plot as follows:



6.8.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205, RSS-GEN Section 8.9 8.10 RSS-247 Section 5.5				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	2.3GHz to 2.5GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 5.8 for details				
Test mode:	Non-hopping mode				
Test results:	Passed				

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




REMARK :								
	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	20.06	27.37	4.69	0.00	52.12	74.00	-21.88 Peak
2	2390.000	7.24	27.37	4.69	0.00	39.30	54.00	-14.70 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




REMARK :

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	19.83	27.37	4.69	0.00	51.89	74.00	-22.11 Peak
2	2390.000	7.30	27.37	4.69	0.00	39.36	54.00	-14.64 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




REMARK :									
	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.57	27.57	4.81	0.00	52.95	74.00	-21.05	Peak
2	2483.500	8.10	27.57	4.81	0.00	40.48	54.00	-13.52	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



REMARK :


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.85	27.57	4.81	0.00	53.23	74.00	-20.77	Peak
2	2483.500	8.15	27.57	4.81	0.00	40.53	54.00	-13.47	Average

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.9 Spurious Emission



6.9.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d), RSS-247 Section 5.5
Test Method:	ANSI C63.10:2013 and KDB 558074 D01 15.247 Meas Guidance v05r01
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emissions. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a thick grey horizontal bar labeled 'Ground Reference Plane'.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Test plot as follows:



6.9.2 Radiated Emission Method


Test Requirement:	FCC Part 15 C Section 15.209, RSS-GEN Section 8.9 8.10 RSS-247 Section 5.5				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9 kHz to 25 GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
74.0			Peak Value		
Test setup:	Below 1GHz				
					
	Above 1GHz				
					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)				

	/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):

Below 1GHz:

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




REMARK :

	Freq	ReadAntenna	Cable Preamp	Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	30.424	38.88	10.70	0.78	29.98	20.38	40.00	-19.62 QP
2	109.796	31.22	12.29	2.05	29.46	16.10	43.50	-27.40 QP
3	147.921	40.55	8.50	2.50	29.23	22.32	43.50	-21.18 QP
4	189.074	35.48	11.07	2.79	28.91	20.43	43.50	-23.07 QP
5	344.386	32.60	14.50	3.08	28.55	21.63	46.00	-24.37 QP
6	590.974	31.67	18.99	3.93	28.97	25.62	46.00	-20.38 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	DX6e Transmitter	Product Model:	DX6e
Test By:	Mike	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



REMARK :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
	Level Factor	Loss Factor	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	167.237	37.62	9.32	2.64	29.07	20.51	43.50
2	196.510	35.50	11.40	2.84	28.85	20.89	43.50
3	295.147	44.29	13.57	2.93	28.46	32.33	46.00
4	393.472	39.49	15.39	3.08	28.75	29.21	46.00
5	590.974	30.22	18.99	3.93	28.97	24.17	46.00
6	845.088	29.31	21.27	4.21	28.02	26.77	46.00


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4808.00	46.32	35.99	6.80	41.81	47.30	74.00	-26.70	Vertical
4808.00	45.21	35.99	6.80	41.81	46.19	74.00	-27.81	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4808.00	35.21	35.99	6.80	41.81	36.19	54.00	-17.81	Vertical
4808.00	34.25	35.99	6.80	41.81	35.23	54.00	-18.77	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4880.00	45.21	36.38	6.86	41.84	46.61	74.00	-27.39	Vertical
4880.00	44.98	36.38	6.86	41.84	46.38	74.00	-27.62	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4880.00	34.25	36.38	6.86	41.84	35.65	54.00	-18.35	Vertical
4880.00	33.69	36.38	6.86	41.84	35.09	54.00	-18.91	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4952.00	45.36	36.71	6.91	41.87	47.11	74.00	-26.89	Vertical
4952.00	46.25	36.71	6.91	41.87	48.00	74.00	-26.00	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4952.00	35.10	36.71	6.91	41.87	36.85	54.00	-17.15	Vertical
4952.00	36.98	36.71	6.91	41.87	38.73	54.00	-15.27	Horizontal
Remark:								
1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.								
2. The emission levels of other frequencies are very lower than the limit and not show in test report.								

6.10 Frequency Stability

Test Requirement:	RSS-GEN Section 6.11
Test Method:	RSS-GEN Section 6.11
Limit:	kept within at least the central 80% of its permitted operating frequency band.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The EUT is installed in an environment test chamber with external power source. 2. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT. 3. A sufficient stabilization period at each temperature is used prior to each frequency measurement. 4. When temperature is stabled, measure the frequency stability. 5. The test shall be performed under -20 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.
Test Instruments:	Refer to section 5.7 for details
Test mode:	Unmodulated carrier is not available, test at modulated carrier mode.
Test results:	Passed

Measurement Data:

Voltage vs. Frequency Stability

Test conditions		Measurement Frequency (MHz)	Limit (MHz)
Temp(°C)	Voltage(ac)		
20	6.6V	2403.997	2400 ~ 2483.5
	6.0V	2403.996	
	5.4V	2403.992	

Note: EUT stops working when the supply voltage is lower than DC 5.4V.

Temperature vs. Frequency Stability

Test conditions		Frequency(MHz)	Limit (MHz)
Voltage(dc)	Temp(°C)		
6 V	-20	2403.992	2400 ~ 2483.5
	-10	2403.995	
	0	2403.997	
	10	2403.996	
	20	2403.996	
	30	2403.995	
	40	2403.994	
	50	2403.992	

Test plot as follows (worst case):

