



Shenzhen Shuodian Electronic Technology Co.,Ltd

Specification

for

PPA102S.C1 2.4G Antenna

文件编号 Document No.	
日期 Release Date	2021/6/8
编制 Author	Zengxiaofeng
复核 Review	Liming

Shenzhen Shuodian Electronic Technology Co.,Ltd

No. 508 West, Building 64, Majialong Jinlong Industrial City, Nanshan District, Shenzhen

邮箱: **sz_shuodian@163.com**

电话: 0755-86006322

传真: 0755-86006323

1. Specifications

NO .	ITEMS	DETAILS
1	model	/
2	Frequency band	2400-2500MHz
3	VSWR	≤1.3
4	GAIN	3.86 dBi
5	Impedance	50 Ω
6	Antenna type	unipolar
7	Antenna implementation form	1.13 coaxial cable
8	picture	

3.Product electrical performance test data


3.1 Testing environment and instrument equipment



testing environment:	Test equipment:
temperature: 10℃——+30℃	Network analyzer
humidity: ≤80% (+40℃)	Agilent E8358A
atmospheric pressure: 750mmkg±30mmkg	ETS anechoic chamber

3.2 Product electrical performance test data:

S11 picture:

Marker	2450MHz	2400MHz	2500MHz
Returnloss	-20.6	-16.4	-14.7
VSWR	1.1	1.3	1.3





3.3 Gain efficiency and directional pattern of antenna:

频率 (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	2.70	2.73	2.71	2.93	3.22	3.40	3.57	3.86	3.79	3.85	4.18
Efficiency (%)	43.5	44.3	44.8	45.1	46.0	46.3	47.1	50.2	49.6	49.7	50.3

2450MHz Direction diagram:

