

TEST REPORT

On behalf of

Savant Technologies LLC, dba GE Lighting, a Savant company

Product Name: Cync Tile

Model No.: CFIXTIHC DEN

FCC ID: PUU-TILE-CDEN

Prepared For: Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road, Cleveland, OH 44112

Prepared By: Audix Technology (Shanghai) Co., Ltd.
3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500



File No. : C1D2211024
Report No. : ACI-F23011
Date of Test : 2022.11.24-2023.01.16
Date of Report : 2023.01.31

The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

| | Page |
|---|-----------|
| 1 SUMMARY OF STANDARDS AND RESULTS | 5 |
| 1.1 Description of Standards and Results | 5 |
| 2 GENERAL INFORMATION | 6 |
| 2.1 Description of Equipment Under Test | 6 |
| 2.2 EUT Specifications Assessed in Current Report | 7 |
| 2.3 Test Information | 7 |
| 2.4 Sample Description | 7 |
| 2.5 Supported equipment | 8 |
| 2.6 Description of Test Facility | 8 |
| 3 CONDUCTED EMISSION TEST | 9 |
| 3.1 Test Equipment | 9 |
| 3.2 Block Diagram of Test Setup | 9 |
| 3.3 Conducted Emission Limits (§15.207) | 10 |
| 3.4 Test Configuration | 10 |
| 3.5 Operating Condition of EUT | 10 |
| 3.6 Test Procedures | 10 |
| 3.7 Test Results | 11 |
| 4 RADIATED EMISSION TEST | 13 |
| 4.1 Test Equipment | 13 |
| 4.2 Block Diagram of Test Setup | 13 |
| 4.3 Radiated Emission Limit (§15.209) | 14 |
| 4.4 Test Configuration | 14 |
| 4.5 Operating Condition of EUT | 15 |
| 4.6 Test Procedures | 15 |
| 4.7 Test Results | 16 |
| 5 6 DB BANDWIDTH MEASUREMENT | 22 |
| 5.1 Test Equipment | 22 |
| 5.2 Block Diagram of Test Setup | 22 |
| 5.3 Specification Limits (§15.247(a)(2)) | 22 |
| 5.4 Operating Condition of EUT | 22 |
| 5.5 Test Procedure | 22 |
| 5.6 Test Results | 23 |
| 6 MAXIMUM PEAK OUTPUT POWER MEASUREMENT | 26 |
| 6.1 Test Equipment | 26 |
| 6.2 Block Diagram of Test Setup | 26 |
| 6.3 Specification Limits (§15.247(b)(3)) | 26 |
| 6.4 Operating Condition of EUT | 26 |
| 6.5 Test Procedure | 26 |
| 6.6 Test Results | 27 |
| 7 EMISSION LIMITATIONS MEASUREMENT | 30 |
| 7.1 Test Equipment | 30 |
| 7.2 Block Diagram of Test Setup | 30 |
| 7.3 Specification Limits (§15.247(d)) | 30 |

| | | |
|-----------|---|-----------|
| 7.4 | Operating Condition of EUT | 30 |
| 7.5 | Test Procedure | 30 |
| 7.6 | Test Results | 32 |
| 8 | POWER SPECTRAL DENSITY MEASUREMENT | 39 |
| 8.1 | Test Equipment..... | 39 |
| 8.2 | Block Diagram of Test Setup | 39 |
| 8.3 | Specification Limits (§15.247(e)) | 39 |
| 8.4 | Operating Condition of EUT | 39 |
| 8.5 | Test Procedure..... | 39 |
| 8.6 | Test Results | 40 |
| 9 | ANTENNA REQUIREMENT..... | 43 |
| 9.1 | Specification Limits (§15.203)..... | 43 |
| 9.2 | Result..... | 43 |
| 10 | DEVIATION TO TEST SPECIFICATIONS | 44 |
| 11 | MEASUREMENT UNCERTAINTY LIST | 45 |

TEST REPORT

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
EUT Description : Cync Tile
(A) Model No. : Refer to Sec.2.1
(B) Power Supply : 120V AC 60Hz
(C) Test Voltage : 120V/60Hz

Test Procedure Used:

FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10-2013

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested is technically compliance with the FCC limits.

This report applies to above tested Sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

The test results for EUT's WIFI function are contained in No.ACI-F23012 report.

Date of Test : 2022.11.24-2023.01.16 Date of Report : 2023.01.31

Producer :

Mindy Wang

MINDY WANG / Assistant

Review :

Byron Wu

BYRON WU / Deputy Assistant Manager



For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory :

Kamp Chen

Authorized Signature(s) KAMPCHEN / Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

| Description / Test Item | Test Standard | Results | Meets Limit |
|--|--|---------|---------------------------|
| EMISSION | | | |
| Conducted Emission | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.207 |
| Radiated Emission | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.209(a) 15.205(a)(c) |
| 6 dB Bandwidth Measurement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.247(a)(2) |
| Maximum Peak Output Power Measurement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.247(b)(3) |
| Emission Limitations Measurement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.247(d) |
| Band Edge Measurement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.247(d) |
| Power Spectral Density Measurement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.247(e) |
| Antenna Requirement | FCC RULES AND REGULATIONS PART 15 SUBPART C AND ANSI C63.10:2013 | Pass | 15.203 |
| N/A is an abbreviation for Not Applicable. | | | |

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : Cync Tile

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model Number : CFIXTIHCDEN

Radio Tech : BLE 4.2;
IEEE 802.11 b/g/n.

Note: : 802.11n-HT40 not support.

Channel Freq. : BLE: 2402MHz-2480MHz;
802.11b/g/n: 2412MHz-2462MHz.

Modulation : BLE: GFSK;
802.11b: DSSS (CCK, DQPSK, DBPSK);
802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK).

Antenna Info. : Antenna Type: PCB Antenna
Antenna Gain: 2.31 dBi

Applicant : Savant Technologies LLC, dba GE Lighting, a Savant company
1975 Noble Road, Cleveland, OH 44112

Manufacturer : same as Applicant

Factory #1 : LEEDARSON LIGHTING CO LTD.
XINGDA RD, XINGTAI INDUSTRIAL ZONE,
CHANGTAI COUNTY, ZHANGZHOU, FUJIAN
363900 CHINA.

Factory #2 : LEEDARSON IOT TECHNOLOGY (THAILAND)
CO., LTD.
71 Moo.5 T. Bang Samak(Building A) , Wellgrow
Industrial Estate, A.Bang Pakong District,
Chachoengsao province, 24130 Thailand

2.2 EUT Specifications Assessed in Current Report

| Mode | Modulation | Data Rate(Mbps) |
|------|------------|-----------------|
| BLE | GFSK | 1 |

| Channel List | | | |
|--------------|-----------------|-------------|-----------------|
| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
| 00 | 2402 | 20 | 2442 |
| 01 | 2404 | 21 | 2444 |
| 02 | 2406 | 22 | 2446 |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| 17 | 2436 | 37 | 2476 |
| 18 | 2438 | 38 | 2478 |
| 19 | 2440 | 39 | 2480 |

2.3 Test Information

The test software “RTLBTAPP.exe” was used to control EUT work in TX mode, Power Setting and select test channel.

| Modulation | data rate (Mbps) | Power Setting | Test Channel | | Frequency (MHz) |
|------------|------------------|---------------|--------------|----|-----------------|
| BLE | 1 | Default | Low: | 00 | 2402 |
| | | Default | Middle: | 19 | 2440 |
| | | Default | High: | 39 | 2480 |

2.4 Sample Description

| Test Item | Model Number | Sample Number | Date of receipted |
|--------------------|--------------|-----------------|-------------------|
| Conducted Emission | CFIXTIHCDEN | E2211822-01/03 | 2022.11.08 |
| Radiated Emission | CFIXTIHCDEN | E2211822a-02/03 | 2022.11.08 |
| Conducted RF Test | CFIXTIHCDEN | E2211822a-01/03 | 2022.11.08 |

2.5 Supported equipment

Brand : Acer
Product Name: : Notebook PC
Model Name : TravelMate P238 series
Model Number : N15W8

Product Name : Test Fixture
Product Function : USB to TTL

2.6 Description of Test Facility

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China.

Accredited by NVLAP, Lab Code : 200371-0

FCC Designation Number : CN5027

Test Firm Registration Number : 954668

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|--------------------------------|--------------|-----------|-------------|------------|---------------|
| 1. | Test Receiver | R&S | ESCI | 101302 | 2022.06.07 | 1 Year |
| 2. | Artificial Mains Network (AMN) | R&S | ENV216 | 101514 | 2022.09.23 | 1 Year |
| 3. | Software | Audix | e3 | 6.2009-1-15 | -- | -- |

3.2 Block Diagram of Test Setup

3.2.1 Conducted Disturbance Test Setup



3.3 Conducted Emission Limits (§15.207)

| Frequency Range (MHz) | Limits dB(μV) | |
|---|---------------|---------|
| | Quasi-peak | Average |
| 0.15 ~ 0.5 | 66~56 | 56~46 |
| 0.5 ~ 5 | 56 | 46 |
| 5 ~ 30 | 60 | 50 |
| NOTE 1 – The lower limit shall apply at the transition frequencies. NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz | | |

3.4 Test Configuration

The EUT (listed in Sec.2.1) was installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner which tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipment.

3.5.3 Turn the EUT on the test mode, and then test.

3.6 Test Procedures

The EUT was placed upon a non-metallic table, which is 0.8 m above the horizontal conducting ground plane and 0.4 m from a vertical reference plane. The EUT was connected to the power mains through an Artificial Mains Network (AMN) to provide a 50 Ω coupling impedance for the measuring equipment. Both sides of AC line (Line & Neutral) were checked to find out the maximum conducted emission according to FCC Part 15 Subpart C and ANSI C63.10: 2013 requirements during conducted disturbance test.

The I.F. bandwidth of Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

Test with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. (According to KDB 174176 D01 Line Conducted FAQ)

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Worst case emission:

| No. | Operation | Modulation | Channel | Frequency (MHz) | Data Page |
|-----|--------------|------------|---------|--------------------|-----------|
| 1. | Transmitting | BLE | 00 | 2402 | P12 |

NOTE 1 – Level = Read Level + AMN Factor + Cable Loss

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – The emission levels which not reported are too low against the official limit.

Worst case emissionEUT : Cync Tile Temperature : 22°CModel No. : CFIXTIHCDEN Humidity : 51%RHTest Mode : Transmitting Date of Test : 2023.01.16

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | AMN Factor (dB) | Cable Loss (dB) | Emission Level dB (μV) | Limits dB (μV) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------|-----------------|------------------------|----------------|-------------|---------|
| Line | 0.1942 | 42.1 | 9.7 | 0.03 | 51.83 | 63.85 | 12.02 | QP |
| | 0.1942 | 28.4 | 9.7 | 0.03 | 38.13 | 53.85 | 15.72 | Average |
| | 0.2017 | 41 | 9.7 | 0.03 | 50.73 | 63.54 | 12.81 | QP |
| | 0.2017 | 28.8 | 9.7 | 0.03 | 38.53 | 53.54 | 15.01 | Average |
| | 0.2558 | 40.9 | 9.7 | 0.03 | 50.63 | 61.57 | 10.94 | QP |
| | 0.2558 | 25.6 | 9.7 | 0.03 | 35.33 | 51.57 | 16.24 | Average |
| | 0.2712 | 38.7 | 9.7 | 0.03 | 48.43 | 61.08 | 12.65 | QP |
| | 0.2712 | 24.2 | 9.7 | 0.03 | 33.93 | 51.08 | 17.15 | Average |
| | 0.324 | 33.5 | 9.75 | 0.03 | 43.28 | 59.6 | 16.32 | QP |
| | 0.324 | 18 | 9.75 | 0.03 | 27.78 | 49.6 | 21.82 | Average |
| | 0.3859 | 33.8 | 9.73 | 0.04 | 43.57 | 58.15 | 14.58 | QP |
| | 0.3859 | 19.4 | 9.73 | 0.04 | 29.17 | 48.15 | 18.98 | Average |
| Neutral | 0.1928 | 39.2 | 9.7 | 0.03 | 48.93 | 63.92 | 14.99 | QP |
| | 0.1928 | 26 | 9.7 | 0.03 | 35.73 | 53.92 | 18.19 | Average |
| | 0.2066 | 37.4 | 9.7 | 0.03 | 47.13 | 63.34 | 16.21 | QP |
| | 0.2066 | 21.8 | 9.7 | 0.03 | 31.53 | 53.34 | 21.81 | Average |
| | 0.2566 | 37.5 | 9.7 | 0.03 | 47.23 | 61.54 | 14.31 | QP |
| | 0.2566 | 25.5 | 9.7 | 0.03 | 35.23 | 51.54 | 16.31 | Average |
| | 0.2684 | 37.1 | 9.7 | 0.03 | 46.83 | 61.17 | 14.34 | QP |
| | 0.2684 | 25.8 | 9.7 | 0.03 | 35.53 | 51.17 | 15.64 | Average |
| | 0.3937 | 29.7 | 9.71 | 0.04 | 39.45 | 57.99 | 18.54 | QP |
| | 0.3937 | 18.9 | 9.71 | 0.04 | 28.65 | 47.99 | 19.34 | Average |
| | 0.413 | 29.3 | 9.7 | 0.04 | 39.04 | 57.59 | 18.55 | QP |
| | 0.413 | 14.8 | 9.7 | 0.04 | 24.54 | 47.59 | 23.05 | Average |

TEST ENGINEER: Jarey

4 RADIATED EMISSION TEST

4.1 Test Equipment

The following test equipment are used during the radiated emission test in a semi-anechoic chamber:


| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|------------------------------|--------------|-----------------------|---------------------|------------|---------------|
| 1. | Preamplifier | Agilent | 8447D | 2944A10548 | 2022.06.06 | 1 Year |
| 2. | Preamplifier | HP | 8449B | 3008A00864 | 2022.06.06 | 1 Year |
| 3. | Spectrum Analyzer | Agilent | N9010A | MY52221182 | 2022.09.15 | 1 Year |
| 4. | Test Receiver | R&S | ESCI | 101303 | 2022.06.06 | 1 Year |
| 5. | Bilog Antenna+6dB Attenuator | Schwarz beck | VULB 9168+EMCI-N-6-06 | 707+AT-N0637 | 2022.07.25 | 1 Year |
| 6. | Horn Antenna | ETS | 3115 | 9607-4878 | 2022.07.27 | 1 Year |
| 7. | Horn Antenna | EMCO | 3116 | 00062643 | 2021.12.13 | 2 Year |
| 8. | Cavity Band Rejection Filter | Microwave | WT-A3882-R 10 | WT200312-1-1 | 2022.06.06 | 1 Year |
| 9. | Software | Audix | e3 | SET00200 9912M295-2 | -- | -- |

4.2 Block Diagram of Test Setup


4.2.1 EUT & Peripherals



4.2.2 Below 1GHz



4.2.3 Above 1GHz



4.3 Radiated Emission Limit (§15.209)

| Frequency (MHz) | Distance (m) | Field strength limits (μV/m) | |
|-----------------|--------------|------------------------------|----------|
| | | (μV/m) | dB(μV/m) |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216 ~ 960 | 3 | 200 | 46.0 |
| Above 960 | 3 | 500 | 54.0 |

NOTE 1 - Emission Level dB (μV/m) = 20 log Emission Level (μV/m)

NOTE 2 - The tighter limit applies at the band edges.

NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Average value detector above 1GHz.

NOTE 5 - Above 1 GHz, the limit on peak emission is 20 dB above the maximum permitted average emission limit applicable to the EUT

4.4 Test Configuration

The EUT (listed in Sec.2.1) and the simulators (listed in Sec.2.2) were installed as shown on Sec.4.2 to meet FCC requirements and operating in a manner that tends to maximize its emission level in a normal application.

4.5 Operating Condition of EUT

4.5.1 Setup the EUT as shown in Sec. 4.2.

4.5.2 Turn on the power of all equipment.

4.5.3 Connect the HCI of EUT and Notebook PC through Test fixture, use the software as section 2.3 to change test mode, then remove the test fixture and notebook PC. Then test.

4.5.4 Repeat the step 4.5.3, until all test mode finished.

4.6 Test Procedures

Radiated emission test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209. A pre-amp is necessary for this measurement. For measurement above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

The EUT was placed on a turntable. Below 1 GHz, the table height is 80 cm above the reference ground plane. Above 1 GHz, the table height is 1.5 m. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (Calibrated Bilog Antenna) or Horn antenna was used as receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.10: 2013 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESCI was set at 120 kHz from 30MHz to 1000MHz.

The bandwidth of Agilent N9010A was set at 1MHz for above 1GHz.

The frequency range from 30 MHz to 25 GHz (Up to 10th harmonics from fundamental frequency) was checked.

All the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Frequency range: below 1GHz (Worst case emission)

| No. | Operation | Modulation | Channel | Frequency | Data Page |
|-----|--------------|------------|---------|-----------|-----------|
| 1. | Transmitting | BLE | 00 | 2402 MHz | P17 |

Frequency range: above 1GHz

| No. | Operation | Modulation | Channel | Frequency | Data Page |
|-----|--------------|------------|---------|-----------|-----------|
| 1. | Transmitting | BLE | 00 | 2402 MHz | P18 |
| 2. | | | 19 | 2440 MHz | P18 |
| 3. | | | 39 | 2480 MHz | P19 |

Band-Edge:

| No. | Operation | Modulation | Channel | Frequency | Data Page |
|-----|--------------|------------|---------|-----------|-----------|
| 1. | Transmitting | BLE | 00 | 2402 MHz | P20 |
| 2. | | | 39 | 2480 MHz | P20 |

Restricted bands:

| No. | Operation | Modulation | Channel | Frequency | Data Page |
|-----|--------------|------------|---------|-----------|-----------|
| 1. | Transmitting | BLE | 00 | 2402 MHz | P21 |
| 2. | | | 39 | 2480 MHz | P21 |

NOTE 1 – Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

NOTE 2 – “QP” means “Quasi-Peak” values

NOTE 3 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 4 – The emission levels which not reported are too low against the official limit.

NOTE 5 – The emission levels recorded below is data of EUT configured in Lying direction, for this direction was the maximum emission direction during the test. The data of Side & Standing direction are too low against the official limit to be reported.

NOTE 6 – All reading are Quasi-Peak values below or equal to 1GHz, Peak and Average values above 1GHz.

For above 1GHz test, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

NOTE 7 – The frequency range 2310-2390MHz & 2483.5-2500MHz were tested for Restricted bands.

Worst case emission < 1GHz

EUT : Cync Tile Temperature : 22°C

Model No. : CFIXTIHCDEN Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2022.11.29

BLE CH2402MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|--------|
| Horizontal | 64.887 | 24.6 | 19 | 0.87 | 28.14 | 16.33 | 40 | 23.67 | QP |
| | 117.77 | 33.26 | 16.83 | 1.18 | 27.91 | 23.36 | 43.5 | 20.14 | QP |
| | 143.83 | 33.44 | 19.1 | 1.29 | 27.82 | 26.01 | 43.5 | 17.49 | QP |
| | 301.42 | 36.83 | 19.32 | 1.92 | 27.02 | 31.05 | 46 | 14.95 | QP |
| | 331.36 | 38.98 | 20.2 | 1.98 | 27.21 | 33.95 | 46 | 12.05 | QP |
| | 539.48 | 30.89 | 24 | 2.52 | 27.9 | 29.51 | 46 | 16.49 | QP |
| Vertical | 34.396 | 34.86 | 18.76 | 0.61 | 28.27 | 25.96 | 40 | 14.04 | QP |
| | 118.19 | 37.13 | 16.8 | 1.18 | 27.91 | 27.2 | 43.5 | 16.3 | QP |
| | 144.84 | 36.44 | 19.1 | 1.29 | 27.82 | 29.01 | 43.5 | 14.49 | QP |
| | 197.2 | 39.51 | 16.3 | 1.55 | 27.42 | 29.94 | 43.5 | 13.56 | QP |
| | 302.48 | 38.56 | 19.35 | 1.92 | 27.02 | 32.81 | 46 | 13.19 | QP |
| | 331.36 | 38.3 | 20.2 | 1.98 | 27.21 | 33.27 | 46 | 12.73 | QP |

TEST ENGINEER: Jarey

Radiated Emission > 1GHz

EUT : Cync Tile Temperature : 22°C

Model No. : CFIXTIHCDEN Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2022.11.29

BLE CH2402MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------|--------------------------|------------------|-------------|--------|
| Horizontal | 3568 | 42.7 | 31.48 | 6.4 | 35.12 | 45.46 | 74 | 28.54 | Peak |
| | 5488 | 39.97 | 34.1 | 8.04 | 34.7 | 47.41 | 74 | 26.59 | Peak |
| | 7048 | 37.32 | 35.75 | 9.26 | 34.8 | 47.53 | 74 | 26.47 | Peak |
| | 8452 | 38.27 | 38.51 | 10.46 | 34.75 | 52.49 | 74 | 21.51 | Peak |
| | 9556 | 37.81 | 38.31 | 11.06 | 34.64 | 52.54 | 74 | 21.46 | Peak |
| | 11104 | 37.04 | 38.8 | 11.76 | 34.38 | 53.22 | 74 | 20.78 | Peak |
| Vertical | 3496 | 43.59 | 31.3 | 6.36 | 35.14 | 46.11 | 74 | 27.89 | Peak |
| | 5260 | 39.28 | 34.05 | 7.89 | 34.7 | 46.52 | 74 | 27.48 | Peak |
| | 6892 | 37.1 | 35.36 | 9.18 | 34.79 | 46.85 | 74 | 27.15 | Peak |
| | 8380 | 36.92 | 38.39 | 10.4 | 34.76 | 50.95 | 74 | 23.05 | Peak |
| | 9784 | 36.84 | 38.36 | 11.24 | 34.62 | 51.82 | 74 | 22.18 | Peak |
| | 11056 | 36.65 | 38.8 | 11.64 | 34.39 | 52.7 | 74 | 21.3 | Peak |

BLE CH2440MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------|--------------------------|------------------|-------------|--------|
| Horizontal | 3628 | 41.5 | 31.63 | 6.49 | 35.1 | 44.52 | 74 | 29.48 | Peak |
| | 5296 | 38.38 | 34.06 | 7.94 | 34.7 | 45.68 | 74 | 28.32 | Peak |
| | 6604 | 38.13 | 34.64 | 8.93 | 34.76 | 46.94 | 74 | 27.06 | Peak |
| | 7648 | 37.57 | 37.09 | 9.9 | 34.8 | 49.76 | 74 | 24.24 | Peak |
| | 9100 | 37.27 | 38.22 | 10.79 | 34.69 | 51.59 | 74 | 22.41 | Peak |
| | 11236 | 36.58 | 38.8 | 11.87 | 34.35 | 52.9 | 74 | 21.1 | Peak |
| Vertical | 3472 | 42.09 | 31.25 | 6.36 | 35.15 | 44.55 | 74 | 29.45 | Peak |
| | 4924 | 39.86 | 33.72 | 7.67 | 34.72 | 46.53 | 74 | 27.47 | Peak |
| | 6736 | 37.71 | 34.98 | 9.01 | 34.77 | 46.93 | 74 | 27.07 | Peak |
| | 8068 | 37.49 | 37.83 | 10.28 | 34.79 | 50.81 | 74 | 23.19 | Peak |
| | 9448 | 38.31 | 38.29 | 11.06 | 34.65 | 53.01 | 74 | 20.99 | Peak |
| | 10984 | 37.04 | 38.77 | 11.64 | 34.41 | 53.04 | 74 | 20.96 | Peak |

BLE CH2480MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|--------|
| Horizontal | 3292 | 41.65 | 30.82 | 6.18 | 35.2 | 43.45 | 74 | 30.55 | Peak |
| | 4948 | 39.51 | 33.77 | 7.67 | 34.71 | 46.24 | 74 | 27.76 | Peak |
| | 6412 | 38.25 | 34.38 | 8.76 | 34.74 | 46.65 | 74 | 27.35 | Peak |
| | 8188 | 37.65 | 38.04 | 10.34 | 34.78 | 51.25 | 74 | 22.75 | Peak |
| | 9568 | 37.38 | 38.31 | 11.06 | 34.64 | 52.11 | 74 | 21.89 | Peak |
| | 10684 | 36.95 | 38.49 | 11.55 | 34.46 | 52.53 | 74 | 21.47 | Peak |
| Vertical | 3580 | 41.32 | 31.5 | 6.44 | 35.12 | 44.14 | 74 | 29.86 | Peak |
| | 4924 | 40.21 | 33.72 | 7.67 | 34.72 | 46.88 | 74 | 27.12 | Peak |
| | 6376 | 38.59 | 34.38 | 8.68 | 34.74 | 46.91 | 74 | 27.09 | Peak |
| | 7888 | 37.67 | 37.54 | 10.11 | 34.8 | 50.52 | 74 | 23.48 | Peak |
| | 9040 | 37.66 | 38.21 | 10.79 | 34.69 | 51.97 | 74 | 22.03 | Peak |
| | 11188 | 36.54 | 38.8 | 11.76 | 34.36 | 52.74 | 74 | 21.26 | Peak |

TEST ENGINEER: Jarey

Band-Edge:

EUT : Cync Tile Temperature : 22°C

Model No. : CFIXTIHCDEN Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2022.11.29

BLE CH2402MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|---------|
| Horizontal | 2390 | 49.07 | 28.21 | 5.36 | 35.86 | 46.78 | 74 | 27.22 | Peak |
| | 2390 | 38.21 | 28.21 | 5.36 | 35.86 | 35.92 | 54 | 18.08 | Average |
| Vertical | 2390 | 42.96 | 28.21 | 5.36 | 35.86 | 40.67 | 74 | 33.33 | Peak |
| | 2390 | 31.79 | 28.21 | 5.36 | 35.86 | 29.5 | 54 | 24.5 | Average |

BLE CH2480MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|---------|
| Horizontal | 2483.5 | 51.49 | 28.46 | 5.43 | 35.76 | 49.62 | 74 | 24.38 | Peak |
| | 2483.5 | 40.85 | 28.46 | 5.43 | 35.76 | 38.98 | 54 | 15.02 | Average |
| Vertical | 2483.5 | 43.63 | 28.46 | 5.43 | 35.76 | 41.76 | 74 | 32.24 | Peak |
| | 2483.5 | 33.66 | 28.46 | 5.43 | 35.76 | 31.79 | 54 | 22.21 | Average |

TEST ENGINEER: Jarey

Emissions in restricted frequency bands:

EUT : Cync Tile Temperature : 22°C

Model No. : CFIXTIHCDEN Humidity : 51%RH

Test Mode : Transmitting Date of Test : 2022.11.29

BLE CH2402MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|---------|
| Horizontal | 2320.5 | 49.83 | 28.03 | 5.29 | 35.93 | 47.22 | 74 | 26.78 | Peak |
| | 2320.5 | 38.48 | 28.03 | 5.29 | 35.93 | 35.87 | 54 | 18.13 | Average |
| | 2347.8 | 49.49 | 28.1 | 5.32 | 35.91 | 47 | 74 | 27 | Peak |
| | 2347.8 | 37.25 | 28.1 | 5.32 | 35.91 | 34.76 | 54 | 19.24 | Average |
| | 2372.2 | 49.1 | 28.17 | 5.32 | 35.88 | 46.71 | 74 | 27.29 | Peak |
| | 2372.2 | 38.05 | 28.17 | 5.32 | 35.88 | 35.66 | 54 | 18.34 | Average |
| Vertical | 2327.8 | 45.06 | 28.05 | 5.29 | 35.93 | 42.47 | 74 | 31.53 | Peak |
| | 2327.8 | 32.31 | 28.05 | 5.29 | 35.93 | 29.72 | 54 | 24.28 | Average |
| | 2355.5 | 44.7 | 28.12 | 5.32 | 35.9 | 42.24 | 74 | 31.76 | Peak |
| | 2355.5 | 32.37 | 28.12 | 5.32 | 35.9 | 29.91 | 54 | 24.09 | Average |
| | 2387.3 | 44.83 | 28.21 | 5.36 | 35.86 | 42.54 | 74 | 31.46 | Peak |
| | 2387.3 | 32.28 | 28.21 | 5.36 | 35.86 | 29.99 | 54 | 24.01 | Average |

BLE CH2480MHz

| Polarization | Frequency (MHz) | Meter Reading dB (μV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Emission Level dB (μV/m) | Limits dB (μV/m) | Margin (dB) | Remark |
|--------------|-----------------|-----------------------|-----------------------|-----------------|--------------------------|--------------------------|------------------|-------------|---------|
| Horizontal | 2484.6 | 52.06 | 28.46 | 5.47 | 35.76 | 50.23 | 74 | 23.77 | Peak |
| | 2484.6 | 40.3 | 28.46 | 5.47 | 35.76 | 38.47 | 54 | 15.53 | Average |
| | 2490 | 50.88 | 28.48 | 5.47 | 35.76 | 49.07 | 74 | 24.93 | Peak |
| | 2490 | 38.38 | 28.48 | 5.47 | 35.76 | 36.57 | 54 | 17.43 | Average |
| | 2496.4 | 49.94 | 28.5 | 5.47 | 35.76 | 48.15 | 74 | 25.85 | Peak |
| | 2496.4 | 38.29 | 28.5 | 5.47 | 35.76 | 36.5 | 54 | 17.5 | Average |
| Vertical | 2483.4 | 46.34 | 28.46 | 5.43 | 35.76 | 44.47 | 74 | 29.53 | Peak |
| | 2483.4 | 34.23 | 28.46 | 5.43 | 35.76 | 32.36 | 54 | 21.64 | Average |
| | 2491.7 | 44.11 | 28.48 | 5.47 | 35.76 | 42.3 | 74 | 31.7 | Peak |
| | 2491.7 | 32.21 | 28.48 | 5.47 | 35.76 | 30.4 | 54 | 23.6 | Average |
| | 2497.6 | 44.32 | 28.5 | 5.47 | 35.76 | 42.53 | 74 | 31.47 | Peak |
| | 2497.6 | 32.56 | 28.5 | 5.47 | 35.76 | 30.77 | 54 | 23.23 | Average |

TEST ENGINEER: Jarey


5 6 dB BANDWIDTH MEASUREMENT

5.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|-------------------|---------------|--------------------|--------------------|------------|---------------|
| 1. | Spectrum Analyzer | Agilent | N9010A | MY52221182 | 2022.09.15 | 1 Year |
| 2. | Coaxial Cable | WOKEN | SFL402-105F LEX | F02-150819-0 45 | 2022.03.07 | 1 Year |
| 3. | 10 dB Attenuator | Mini-Circuits | VAT-10W2+ | 001 | 2022.08.06 | 1 Year |

5.2 Block Diagram of Test Setup



5.3 Specification Limits (§15.247(a)(2))

The minimum 6 dB bandwidth shall be at least 500 kHz.

5.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

5.5 Test Procedure

The transmitter output was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measure by spectrum analyzer with settings: RBW = 100kHz, VBW $\geq 3 \times$ RBW.

The 6 dB bandwidth is defined as the total spectrum the power of which is lower than peak power minus 6 dB .

The test procedure is defined in ANSI C63.10-2013 (the 11.8.2 Measurement Procedure “Option 2” was used).

5.6 Test Results


PASSED.

All the test results are attached in next pages.


(Test Date: 2022.11.24-25 Temperature: 23°C Humidity: 51 %)

| Modulation | Channel | Frequency (MHz) | 6dB Bandwidth (kHz) | Limit |
|------------|---------|--------------------|------------------------|---------|
| BLE | 00 | 2402 | 657.4 | 500 kHz |
| | 19 | 2440 | 664.9 | 500 kHz |
| | 39 | 2480 | 656.6 | 500 kHz |


BLE CH2402MHz



BLE CH2440MHz



BLE CH2480MHz



6 MAXIMUM PEAK OUTPUT POWER MEASUREMENT

6.1 Test Equipment

The following test equipment was used during the maximum peak output power measurement:

| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|-------------------|---------------|--------------------|--------------------|------------|---------------|
| 1. | Spectrum Analyzer | Agilent | N9010A | MY52221182 | 2022.09.15 | 1 Year |
| 2. | Coaxial Cable | WOKEN | SFL402-105F LEX | F02-150819-0 45 | 2022.03.07 | 1 Year |
| 3. | 10 dB Attenuator | Mini-Circuits | VAT-10W2+ | 001 | 2022.08.06 | 1 Year |

6.2 Block Diagram of Test Setup

The Same as Section. 5.2.

6.3 Specification Limits ((§15.247(b)(3))

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5 MHz is: 1 Watt. (30 dBm)

6.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

6.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) $RBW \geq DTS \text{ Bandwidth}$.
- b) $VBW \geq [3 \times RBW]$.
- c) $Span \geq [3 \times RBW]$.
- d) Sweep time = auto.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

The test procedure is defined in ANSI C63.10-2013 (11.9.1.1 Measurement Procedure “ $RBW \geq DTS \text{ bandwidth}$ ” was used).

6.6 Test Results

PASSED.

All the test results are listed below.


(Test Date: 2022.11.24-25 Temperature: 23°C Humidity: 51 %)

| Modulation | Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit |
|------------|---------|--------------------|----------------------------|--------|
| BLE | 00 | 2402 | 8.057 | 30 dBm |
| | 19 | 2440 | 8.894 | 30 dBm |
| | 39 | 2480 | 8.679 | 30 dBm |


BLE CH2402MHz



BLE CH2440MHz



BLE CH2480MHz



7 EMISSION LIMITATIONS MEASUREMENT

7.1 Test Equipment

The following test equipment was used during the emission limitations test:

| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|-------------------|---------------|-----------------|----------------|------------|---------------|
| 1. | Spectrum Analyzer | Agilent | N9010A | MY52221182 | 2022.09.15 | 1 Year |
| 2. | Coaxial Cable | WOKEN | SFL402-105F LEX | F02-150819-045 | 2022.03.07 | 1 Year |
| 3. | 10 dB Attenuator | Mini-Circuits | VAT-10W2+ | 001 | 2022.08.06 | 1 Year |

7.2 Block Diagram of Test Setup

The Same as Section. 5.2.

7.3 Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). (※This test result attaching to Section. 3.7)

7.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

7.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Scan up through 10th harmonic.

The test procedure is defined in ANSI C63.10-2013 (11.11.2 Reference level measurement and 11.11.3 Emission level measurement was used).

7.6 Test Results

PASSED.


The test data was attached in the next pages.

(Test Date: 2022.11.24-25 Temperature: 23°C Humidity: 51 %)


| Modulation | Channel | Frequency (MHz) | Data Page |
|------------|---------|--------------------|-----------|
| BLE | 00 | 2402 | P33-34 |
| | 19 | 2440 | P35-36 |
| | 39 | 2480 | P37-38 |



BLE CH2402MHz

Reference level




Emission level







BLE CH2440MHz

Reference level



Emission level








BLE CH2480MHz

Reference level



Emission level





8 POWER SPECTRAL DENSITY MEASUREMENT

8.1 Test Equipment

The following test equipment was used during the power spectral density measurement:

| Item | Type | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|-------------------|---------------|--------------------|--------------------|------------|---------------|
| 1. | Spectrum Analyzer | Agilent | N9010A | MY52221182 | 2022.09.15 | 1 Year |
| 2. | Coaxial Cable | WOKEN | SFL402-105F LEX | F02-150819-0 45 | 2022.03.07 | 1 Year |
| 3. | 10 dB Attenuator | Mini-Circuits | VAT-10W2+ | 001 | 2022.08.06 | 1 Year |

8.2 Block Diagram of Test Setup

The Same as section 5.2.

8.3 Specification Limits (§15.247(e))

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band.

8.4 Operating Condition of EUT

The software as section 2.3 was used to enable the EUT to change the test mode one by one.

8.5 Test Procedure

The transmitter output was connected to the spectrum analyzer.

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

The test procedure is defined in ANSI C63.10-2013 (11.10.2 Measurement Procedure “Method PKPSD (peak PSD)” was used).

8.6 Test Results


PASSED.

All the test results are attached in next pages.


(Test Date: 2022.11.24-25 Temperature: 23°C Humidity: 51 %)

| Modulation | Channel | Frequency (MHz) | Power Spectral Density (dBm) | Limit |
|------------|---------|--------------------|---------------------------------|-------|
| BLE | 00 | 2402 | -7.282 | 8 dBm |
| | 19 | 2440 | -7.238 | 8 dBm |
| | 39 | 2480 | -5.153 | 8 dBm |


BLE CH2402 MHz



BLE CH2440 MHz



BLE CH2480 MHz



9 ANTENNA REQUIREMENT

9.1 Specification Limits (§15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 Result

According to KDB 353028 D1, the following describes the three ways that can be used to demonstrate compliance to Section 15.203:

- a) Antenna permanently attached.
- b) Unique (non-standard) antenna connector.
- c) Professional installation.

For this product, the antenna is:

- ☒ Antenna permanently attached
- ☐ Unique (non-standard) antenna connector
- ☐ Professional installation
- ☐ not meet any of ways list above

that

- ☒ compliant
- ☐ not compliant

with the requirement of Section 15.203.

10 DEVIATION TO TEST SPECIFICATIONS

None.

11 MEASUREMENT UNCERTAINTY LIST

The measurement uncertainty was estimated for test on the EUT according to CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage of K=2.

The uncertainties value is not used in determining the PASS/FAIL results.

| Test Items/Facilities | Frequency/Equipment/Unit | Uncertainty |
|--|----------------------------|----------------------|
| Conducted Emission No.1 Shielded Room | 9kHz~150kHz | ±3.1 dB |
| | 150kHz~30MHz | ±2.6 dB |
| Conducted Emission No.3 Shielded Room | 9kHz~150kHz | ±3.1 dB |
| | 150kHz~30MHz | ±2.6 dB |
| Radiated Emission | 30MHz~200MHz, Horizontal | ±3.8 dB |
| | 30MHz~200MHz, Vertical | ±4.1 dB |
| | 200MHz~1000MHz, Horizontal | ±3.6 dB |
| | 200MHz~1000MHz, Vertical | ±5.1 dB |
| | 1GHz~6GHz | ±5.3 dB |
| | 6GHz~18GHz | ±5.3 dB |
| | 18GHz~40GHz | ±3.5 dB |
| Output Power Test | 50MHz~18GHz | 0.77 dB |
| Power Density Test | 9kHz~6GHz | 1.08 dB |
| RF Frequency Test | 9kHz~40GHz | 6×10^{-4} |
| Bandwidth Test | 9kHz~6GHz | 1.5×10^{-3} |
| RF Radiated Power Test | 30MHz~1000MHz | 3.06 dB |
| Conducted Output Power Test | 50MHz~18GHz | 0.83 dB |
| AC Voltage(<10kHz) Test | 120V~230V | 0.04 % |
| DC Power Test | 0V~30V | 0.4 % |
| Temperature | -40°C~+100°C | 0.52 °C |
| Humidity | 30%~95% | 2.6 % |