

Pistol grip user manual

1. Power on

Press and hold the power button for 3s in the off state.
The buzzer sounds three times when the power is on.

2. Turn off

Method 1. Long press the power button for 3s under the power on state.
Method 2. Bluetooth is not connected for more than 3 minutes, device auto shutdown.
The buzzer sounds three times when the power is turned off.

3. Charging

Charging in progress:
USB charging or cradle charging in power on/off state.
Red light is always on.
Buzzer sounds once when USB or cradle is inserted.
Fully charged:
Green light is always on.
Buzzer sounds once when battery is full.

4. With Scanner

Put the scanner on the pistol grip and pull the trigger to trigger the scanner to scan.

5. FCC Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.
This equipment should be installed and operated with a minimum distance of 0mm between the radiator and your body.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable

protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.