

12

1

2

3

4

5

6

A

B

C

D

1

2

3

4

5

6

A

B

C

D

1

2

3

4

5

6

GENERAL INSTRUCTIONS:

SUPPLIER TO INSURE CORRECT REVISION LEVEL DWG FOR PRODUCTION. CONTACT B&D PURCHASING DEPT. FOR LATEST REVISION LEVEL DWG.

CONTACT B&D GRAPHICS DESIGN FOR ORIGINAL ARTWORK, COLOR STANDARDS AND CORPORATE GUIDELINES.

PROOFS OF ALL REVISIONS THAT AFFECT ARTWORK AND ALL NEW COLOR FORMULATIONS MUST BE SUBMITTED TO B&D GRAPHICS DESIGN FOR APPROVAL PRIOR TO MAKING PRODUCTION PARTS. SEE EP-1006.

SUPPLIER TO PROVIDE B&D GRAPHICS DESIGN WITH 6 SAMPLES OF ALL PRODUCTION PARTS. MARK B&D PART NO. AND REVISION LEVEL.

LABEL & MARKING LAYOUT COLOR VARIATIONS:

BACKGROUND: BLACK, ES006

COPY/SYMBOL: DEEP YELLOW, ES477

! WARNING: BLACK ON ANSI ORANGE

TOTAL NUMBER OF COLORS: 3

SYNTHETIC LABEL CONSTRUCTION:

SUPPLIER NAME:	LABEL MATERIAL:
TOPFLIGHT	P-660A OR 5 MIL POLYCARBONATE: 3 MIL CLEAR POLYESTER, SUB-SURFACED PRINTED, 2 MIL AS 113W ADHESIVE MATTE FINISH TEXTURED VARNISH OR EQUIVELANT

SPECIAL NOTES:

- SERIAL NO'S TO BE SUB-SURFACE PRINTED. 4 DIGITS MIN. (START WITH 1001). RANDOM ORDER ACCEPTABLE. NO TWO NAMEPLATES TO HAVE IDENTICAL NO'S. SEQUENCE TO BE ASSIGNED BY B&D PURCHASING DEPT. (APPLICABLE TO DeWALT PRODUCT ONLY.)
- ADHESIVE USED TO APPLY LABEL MUST BE A UL RECOGNIZED LABELING SYSTEM.
- ARTWORK PICTURED ON THIS DRAWING FOR REFERENCE PURPOSES ONLY. WHERE VARIATIONS BETWEEN DRAWING AND ORIGINAL ARTWORK EXIST, THE ARTWORK IS THE CONTROLLING DOCUMENT FOR GRAPHICAL REPRESENTATION ONLY. THIS DRAWING CONTROLS DIMENSIONS AND SPECS.

103.8

23.4

15.5

59.9

9.1

53.8

69.4

24.0

R5.0

R19.0

R36.0

MANUFACTURER'S B&D IDENTIFICATION CODE 1 MM MAX.

DeWALT DS100

JOBSITE SECURITY PORTABLE ALARM SYSTEM

WARNING TO REDUCE THE RISK OF INJURY, USER MUST READ AND UNDERSTAND INSTRUCTION MANUAL. USE ONLY WITH DeWALT AUTHORIZED POWER SOURCES DESIGNATED FOR THIS PRODUCT. NOT FOR PERSONAL PROTECTION. CONTAINS LEAD-ACID BATTERY. MUST BE RECYCLED OR DISPOSED OF PROPERLY. SEE INSTRUCTION MANUAL. SEE MANUAL FOR PATENTS.

ADVERTENCIA PARA DISMINUIR EL RIESGO DE LESIONES, EL USUARIO DEBERÁ LEER Y COMPRENDER EL MANUAL DE INSTRUCCIONES. UTILICE SOLAMENTE CON LAS FUENTES DE ENERGÍA AUTORIZADAS DeWALT SEÑALADAS PARA ESTE PRODUCTO. NO PARA PROTECCIÓN PERSONAL.

AVERTISSEMENT AFIN DE MINIMISER LES RISQUES DE BLESSURES, L'UTILISATEUR DOIT LIRE ET COMPRENDRE LE GUIDE D'UTILISATION. EMPLOYEZ SEULEMENT AVEC DES SOURCES D'ÉNERGIE AUTORISÉES PAR DeWALT INDIQUÉES POUR CE PRODUIT. LE PRODUIT N'ASSURE PAS UNE PROTECTION PERSONNELLE.

INPUT: 16.5V ~ 60Hz 1200mA SER.

THIS PRODUCT MEETS THE REQUIREMENTS OF 47 CFR PART 68.

US: HCOAL00B6263-BDK

FCC ID: HCO3B6ECNCA

IC: 2309A-ECNCA

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

SITELOCK LLC
626 HANOVER PIKE
HAMPSTEAD, MARYLAND 21074
MADE IN MEXICO

DeWALT DS100

JOBSITE SECURITY PORTABLE ALARM SYSTEM

WARNING TO REDUCE THE RISK OF INJURY, USER MUST READ AND UNDERSTAND INSTRUCTION MANUAL. USE ONLY WITH DeWALT AUTHORIZED POWER SOURCES DESIGNATED FOR THIS PRODUCT. NOT FOR PERSONAL PROTECTION. CONTAINS LEAD-ACID BATTERY. MUST BE RECYCLED OR DISPOSED OF PROPERLY. SEE INSTRUCTION MANUAL. SEE MANUAL FOR PATENTS.

ADVERTENCIA PARA DISMINUIR EL RIESGO DE LESIONES, EL USUARIO DEBERÁ LEER Y COMPRENDER EL MANUAL DE INSTRUCCIONES. UTILICE SOLAMENTE CON LAS FUENTES DE ENERGÍA AUTORIZADAS DeWALT SEÑALADAS PARA ESTE PRODUCTO. NO PARA PROTECCIÓN PERSONAL.

AVERTISSEMENT AFIN DE MINIMISER LES RISQUES DE BLESSURES, L'UTILISATEUR DOIT LIRE ET COMPRENDRE LE GUIDE D'UTILISATION. EMPLOYEZ SEULEMENT AVEC DES SOURCES D'ÉNERGIE AUTORISÉES PAR DeWALT INDIQUÉES POUR CE PRODUIT. LE PRODUIT N'ASSURE PAS UNE PROTECTION PERSONNELLE.

INPUT: 16.5V ~ 60Hz 1200mA SER.

THIS PRODUCT MEETS THE REQUIREMENTS OF 47 CFR PART 68.

US: HCOAL00B6263-BDK

FCC ID: HCO3B6ECNCA

IC: 2309A-ECNCA

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

SITELOCK LLC
626 HANOVER PIKE
HAMPSTEAD, MARYLAND 21074
MADE IN MEXICO

THIS DOCUMENT IS THE PROPERTY OF BLACK & DECKER INC.

THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO BLACK & DECKER INC.

NEITHER THIS DOCUMENT NOR ITS' CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIZED PERSON, COPIED OR PUBLISHED WITHOUT PRIOR WRITTEN CONSENT OF BLACK & DECKER INC.

COPYRIGHT © 2004 BLACK & DECKER INC.

TOL UNLESS SPECIFIED

0 & 1 PLC DEC: ± 0.4

ANGLES: ± 1°

ALL DIMENSIONS mm

SIZE:

SHEET:

1 of 1

FOR ITEM DATA SEE PRINTED REPORT

DOC NO: 626821-PDF1

REV: 0

TITLE: LABEL, N/P DS100

EC: EC0223527

VERSION: 1

REL