

# YAZAKI (CHINA) INVESTMENT CORPORATION

## SAR COMPLIANCE REPORT

**REPORT TYPE:**

FCC SAR assessment report

**MODEL:**

73A1-0139-30(40A), 73A1-0140-30(80A)

**REPORT NUMBER:**

250100054SHA-002

**ISSUE DATE:**

March 24, 2025

**DOCUMENT CONTROL NUMBER:**

TTRFFCCSAR-01\_V1 © 2018 Intertek



## TEST REPORT

**Applicant:** YAZAKI (CHINA) INVESTMENT CORPORATION  
No.25 building, No.1188, Huyi Highway, Nanxiang Town, Jiading District, Shanghai, China

**Manufacturer:** YAZAKI (CHINA) INVESTMENT CORPORATION  
No.25 building, No.1188, Huyi Highway, Nanxiang Town, Jiading District, Shanghai, China

**Factory:** Zhangzhou Yazaki Auto Parts Co., Ltd.  
No. 6 Wuqiao North Road, Longwen District, Zhangzhou City, Fujian Province

**Type/Model:** 73A1-0139-30(40A), 73A1-0140-30(80A)

**FCC ID:** 2BNJL-73A1014030

## SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part1.1307(b)

PREPARED BY:

REVIEWED BY:

Scout Gong  
Project Engineer

  
Eric Li  
Reviewer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
250100054SHA-002	Rev. 01	Initial issue of report	March 24, 2025

## 1 General Information

### 1.1 Description of Equipment Under Test (EUT)

Product name:	NACS Charging Cable Assembly
Type/Model:	73A1-0139-30(40A), 73A1-0140-30(80A)
Description of EUT:	The product covered by this report is a NACS charging cable assembly. It works at 315MHz frequency. There are 2 models, the difference is the maximum allowed rated charging current. There is a 12V DC power supply to the internal RF circuit. Model 73A1-0140-30(80A) was tested as a representative. The worst results were listed in this report.
Rating:	DC 12V
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample Identification No.:	A250210-23-001
Sample received date:	February 10, 2025
Date of test:	February 10, 2025, to February 13, 2025

### 1.2 Technical Specification

Operation Frequency:	315MHz
Type of Modulation:	ASK
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Channel Number:	1
Antenna Designation:	Integral PCB antenna

### 1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 SAR Assessment

Test result: Pass

### 2.1 SAR Test Exclusion Limit

This method shall only be used at separation distances up to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula below:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

$f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20cm}$  is per Formula above.

The example values shown in below are for illustration only.

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

### 2.2 Assessment Results

As we can see from the test report 250100054SHA-001:

The highest EIRP adjusted with tune-up tolerance is:  $83.53 - 95.30 = -11.77 \text{ dBm} = 0.067 \text{ mW}$ .  
 $0.067 \text{ mW} < 39 \text{ mW}$  (Test Exclusion Thresholds of 300MHz at 5mm).

Therefore, the SAR requirement is deemed to be satisfied without test.

\*\*\*\*\*END\*\*\*\*\*