

## FCC/ISED Test Report

**Prepared for:** Garmin International, Inc.

**Address:** 1200 E. 151<sup>st</sup> Street  
Olathe, Kansas, 66062, USA

**Product:** A04448

**Test Report No:** R20230808-00-E7A

**Approved by:**

  
Fox Lane,  
EMC Test Engineer

**DATE:** September 29, 2023

**Total Pages:** 47

*The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.*



Report Number:

R20230808-00-E7A

Rev


A

Prepared for:

Garmin International, Inc.


## REVISION PAGE

Rev. No.	Date	Description
0	28 September 2023	Issued by FLane Reviewed by KVepuri Prepared by ESchmidt/FLane
A	29 September 2023	Corrected Customer information Page 5 - FL

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## CONTENTS

Revision Page .....	2
<b>1.0 Summary of test results.....</b>	<b>4</b>
<b>2.0 EUT Description .....</b>	<b>5</b>
2.1 Equipment under test .....	5
2.2 Description of test modes .....	5
2.3 Description of support units.....	5
<b>3.0 Laboratory and General Test Description .....</b>	<b>6</b>
3.1 Laboratory description.....	6
3.2 Test personnel.....	6
3.3 Test equipment.....	7
3.4 General Test Procedure and Setup for Radio Measuremnts.....	8
<b>4.0 Results .....</b>	<b>9</b>
4.1 Output Power .....	10
4.2 Bandwidth.....	11
4.3 Duty Cycle .....	12
4.4 Radiated emissions.....	13
4.5 Conducted Spurious Emissions .....	18
4.6 Band edges .....	21
4.7 Conducted AC Mains Emissions .....	23
<b>Appendix A: Sample Calculation .....</b>	<b>26</b>
<b>Appendix B – Measurement Uncertainty .....</b>	<b>28</b>
<b>Appendix C – Graphs and Tables .....</b>	<b>29</b>
<b>REPORT END.....</b>	<b>47</b>

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## 1.0 SUMMARY OF TEST RESULTS

The worst-case measurements were reported in this report. Summary of test results presented in this report correspond to the following section:

### FCC Part 15.247

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISSED RSS-Gen, Issue 5
- (3) ISSED RSS-247, Issue 3

APPLIED STANDARDS AND REGULATIONS		
Standard Section	Test Type	Result
FCC Part 15.35 RSS Gen, Issue 5, Section 6.10	Duty Cycle	Pass
FCC Part 15.247(b)(1) RSS-247 Issue 3 Section 5.1(b)	Peak output power	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 3 Section 5.1 (b)	Bandwidth	Pass
FCC Part 15.247(a)(1)(iii) RSS-247 Issue 3 Section 5.1(d)	Frequency Hopping System	Pass
FCC Part 15.209 RSS-Gen Issue 5, Section 7.3	Receiver Radiated Emissions	Pass
FCC Part 15.209 (restricted bands), 15.247 (unrestricted) RSS-247 Issue 3 Section 5.5, RSS-Gen Issue 5, Section 8.9	Transmitter Radiated Emissions	Pass
FCC Part 15.209, 15.247(d) RSS-247 Issue 3 Section 5.5	Band Edge Measurement	Pass
FCC Part 15.207 RSS-Gen Issue 5, Section 8.8	Conducted Emissions	Pass



Report Number: R20230808-00-E7A

Rev

A

Prepared for: Garmin International, Inc.

## 2.0 EUT DESCRIPTION

### 2.1 EQUIPMENT UNDER TEST

#### Summary and Operating Condition:

<b>EUT</b>	A04448
<b>FCC ID</b>	IPH-04448
<b>IC</b>	1792A-04448
<b>EUT Received</b>	24 August 2023
<b>EUT Tested</b>	28 August 2023 - 14 September 2023
<b>Serial No.</b>	3451928865 (Radiated Measurements) 3451928680 (Radiated Measurements) 3451928690 (Conducted Measurements)
<b>Operating Band</b>	2400 – 2483.5 MHz
<b>Device Type</b>	<input type="checkbox"/> GMSK <input type="checkbox"/> GFSK <input checked="" type="checkbox"/> BT BR <input type="checkbox"/> BT EDR 2MB <input type="checkbox"/> BT EDR 3MB <input type="checkbox"/> 802.11x
<b>Power Supply / Voltage</b>	Internal Battery / 5VDC Charger: Garmin (Phi Hong) Model: AQ27A-59CFA GPN: 362-00118-00 (Representative Power Supply)

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 2.2 DESCRIPTION OF TEST MODES

The operating range of the EUT is dependent on the device type found in section 2.1:


For BTBR Transmissions:

Channel	Frequency
Low	2402 MHz
Mid	2440 MHz
High	2480 MHz

These are the only representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequencies and designations.

### 2.3 DESCRIPTION OF SUPPORT UNITS

None

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

### 3.0 LABORATORY AND GENERAL TEST DESCRIPTION

#### 3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)  
 4740 Discovery Drive  
 Lincoln, NE 68521  
 A2LA Certificate Number: 1953.01  
 FCC Accredited Test Site Designation No: US1060  
 Industry Canada Test Site Registration No: 4294A-1  
 NCC CAB Identification No: US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of  $35 \pm 4\%$   
 Temperature of  $22 \pm 3^\circ$  Celsius




#### 3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Fox Lane	Test Engineer	Review/Testing and Report
2	Blake Winter	Test Engineer	Testing
3	Ethan Schmidt	Test Technician	Testing and Report
4	Karthik Vepuri	Test Engineer	Review/Testing

**Notes:**

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		


### 3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Keysight MXE Signal Analyzer (44GHz)	N9038A	MY59050109	July 17, 2023	July 17, 2025
Keysight MXE Signal Analyzer (26.5GHz)	N9038A	MY56400083	July 17, 2023	July 17, 2025
Keysight EXA Signal Analyzer	N9010A	MY56070862	July 18, 2023	July 17, 2025
SunAR RF Motion	JB1	A091418	July 27, 2023	July 26, 2024
ETS-Lindgren Red Horn Antenna	3115	218576	July 31, 2023	July 30, 2024
EMCO Horn Antenna	3116	2576	July 31, 2023	July 30, 2024
Com-Power LISN, Single Phase	LI-220C	20070017	July 17, 2023	July 17, 2025
Agilent Preamp*	87405A	3950M00669	June 5, 2023	June 5, 2025
Rohde & Schwarz Preamplifier*	TS-PR18	3545700803	June 5, 2023	June 5, 2025
Trilithic High Pass Filter*	6HC330	23042	June 5, 2023	June 5, 2025
RF Cable (antenna to 10m chamber bulkhead)	FSCM 64639	01E3872	June 5, 2023	June 5, 2025
RF Cable (10m chamber bulkhead to control room bulkhead)	FSCM 64639	01E3874	June 5, 2023	June 5, 2025
RF Cable (control room bulkhead to test receiver)	FSCM 64639	01F1206	June 5, 2023	June 5, 2025
N connector bulkhead (10m chamber)	PE9128	NCEEBH1	June 5, 2023	June 5, 2025
N connector bulkhead (control room)	PE9128	NCEEBH2	June 5, 2023	June 5, 2025
TDK Emissions Lab Software	V11.25	700307	NA	NA
ETS – Lindgren- VSWR on 10m Chamber	10m Semi-anechoic chamber-VSWR	4740 Discovery Drive	July 30, 2020	July 30, 2024
NCEE Labs-NSA on 10m Chamber	10m Semi-anechoic chamber-NSA	NCEE-001	May 25, 2022	May 25, 2025

\*Internal Characterization

**Notes:**

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

### 3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS

Measurement type presented in this report (Please see the checked box below):

#### Conducted ☒

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 1 - Bandwidth Measurements Test Setup

#### Radiated ☒

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 2 - Radiated Emissions Test Setup





Report Number: R20230808-00-E7A

Rev

A

Prepared for: Garmin International, Inc.

**4.0 RESULTS**

DSS Radio Measurements								
CHANNEL	Transmitter	Occupied Bandwidth (kHz)	20 dB Bandwidth (kHz)	AVERAGE OUTPUT POWER (dBm)	AVERAGE OUTPUT POWER (mW)	RESULT	No. of Hopping Channels	ON Time (µs)
							79	372.00
Low	Continuous	966.23	1120.00	11.640	14.588	PASS	Channel Separation (MHz)	Time of Occupancy (ms)
Mid	Continuous	930.97	1123.00	9.990	9.977	PASS		
High	Continuous	929.93	1122.00	9.730	9.397	PASS		
Peak Output Power Limit = 125mW; Occupied Bandwidth = N/A; Channel Separation Limit: > 2/3 * 20 dB; Bandwidth.			Time of Occupancy Limit < 0.4s; Time of Occupancy = ON Time * # of transmissions over, period of time of occupancy= 0.000372*32*10 (See Figure 11 in appendix C) =0.11904s Period of Time of Occupancy = 0.4 * # of Channels = 0.4 * 79 = 31.6s					
Unrestricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level (dBuV)	Relative Fundamental (dBuV)	Delta (dB)	Min Delta (dB)	Result	
Low	Continuous	2400.00	71.56	118.06	46.50	30.0	PASS	
Low	Hopping	2400.00	68.64	117.83	49.19	30.0	PASS	
High	Continuous	2483.50	56.78	116.26	59.47	30.0	PASS	
High	Hopping	2483.50	51.44	117.27	65.84	30.0	PASS	
Peak Restricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)	Measurement Type	Limit* (dBuV/m @ 3m)	Margin	Result	
Low	Continuous	2390.00	50.74	Peak	73.98	23.24	PASS	
High	Continuous	2483.50	51.54	Peak	73.98	22.45	PASS	
*Limit shown is the peak limit taken from FCC Part 15.209								
Average Restricted Band-Edge								
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)**	Measurement Type	Limit (dBuV/m @ 3m)*	Margin	Result	
Low	Continuous	2390.00	39.65	Average	53.98	14.33	PASS	
High	Continuous	2483.50	40.76	Average	53.98	13.22	PASS	
*Limit shown is the average limit taken from FCC Part 15.209 See Sec 4.3 for more information on DCCF								



Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		

#### 4.1 OUTPUT POWER

**Test Method:**

All the radio measurements were performed using section 11.9.2.2.4 from ANSI C63.10.

**Limits of power measurements:****For FCC Part 15.247 Device:**

The maximum allowed peak output power is 125mW.

**Test procedures:**

Details can be found in section 3.4 of this report. See section 4.3 for Duty cycle used.

**Deviations from test standard:**

No deviation.

**Test setup:**


Details can be found in section 3.4 of this report.

**EUT operating conditions:**

Details can be found in section 2.1 of this report.

**Test results:****Pass****Comments:**

1. All the output power plots can be found in Appendix C.
2. All the measurements were found to be compliant.
3. The measurements are listed in the tables below.
4. Compiled values can be found in the Results section, 4.0.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## 4.2 BANDWIDTH

### Test Method:

All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

### Limits of bandwidth measurements:

#### For FCC Part 15.247 Device:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### Test procedures:

Details can be found in section 3.4 of this report.

### Deviations from test standard:

No deviation.

### Test setup:

Test setup details can be found in section 3.4 of this report.

### EUT operating conditions:

Details can be found in section 2.1 of this report.

### Test results:

## Pass

#### Comments:

1. All the bandwidth plots can be found in Appendix C.
2. All the measurements were found to be compliant.



Report Number:

R20230808-00-E7A

Rev

A

Prepared for:

Garmin International, Inc.

### 4.3 DUTY CYCLE

**Test Method:**

Manufacture declares worst case duty cycle for the transmitters in this report will be 80%

DCCF (For Emissions) =  $20 \cdot \log(.8) = -1.94\text{dB}$

#### 4.4 RADIATED EMISSIONS

**Test Method:**

ANSI C63.10-2013, Section 6.5, 6.6

**Limits for radiated emissions measurements:**

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH ( $\mu\text{V/m}$ )	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) =  $20 * \log * \text{Emission level } (\mu\text{V/m})$ .
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.
4. The EUT was tested for spurious emissions while running off of battery power and external USB power. The worse-case emissions were produced while running off of USB power, so results from this mode are presented.

**Test procedures:**

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements from 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.

**Test setup:**



**Figure 3 - Radiated Emissions Test Setup**

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

**Deviations from test standard:**


No deviation.

**EUT operating conditions**


Details can be found in section 2.1 of this report.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

### Test results:



**Figure 4 - Radiated Emissions Plot, Receive**



**Figure 5 - Radiated Emissions Plot, BTBR, Low Channel**

### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level.
5. Emissions were found to be at least 10dB below limit line and were not reported.





Report Number: R20230808-00-E7A

Rev

A

Prepared for: Garmin International, Inc.

**Quasi-Peak Measurements, BTBR**

Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
283.217520	27.69	46.02	18.33	104.14	278.50	H		Rx
46.266000	28.49	40.00	11.51	104.38	67.50	V		Rx

The EUT was maximized in all 3 orthogonal axes. The worst-case is shown in the plot and table above.

All other measurements were found to be at least 6 dB Below the limit.

**Peak Measurements, BTBR**


Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
7206.522000	60.38	N/A	N/A	559.91	100.00	H	Low	BTBR
7320.180000	60.48	73.98	13.50	214.00	207.25	V	Mid	BTBR
7439.370000	59.92	73.98	14.06	120.32	103.75	H	High	BTBR

All other emissions found to be at least 6dB below limit line

**Average Measurements, BTBR**

Frequency	Level	DCCF	Corrected Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dB	dBμV/m	dBμV/m	dB	cm.	deg.			
7206.522000	54.25	-1.94	52.31	N/A	N/A	559.91	100.00	H	Low	BTBR
<b>7320.180000</b>	<b>55.07</b>	<b>-1.94</b>	<b>53.13</b>	<b>53.98</b>	<b>0.85</b>	<b>214.00</b>	<b>207.25</b>	<b>V</b>	<b>Mid</b>	<b>BTBR</b>
7439.370000	54.63	-1.94	52.69	53.98	1.29	120.32	103.75	H	High	BTBR

Corrected Level = Level + DCCF

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## 4.5 CONDUCTED SPURIOUS EMISSIONS

### Test Method:

ANSI C63.10-2013, Section 6.7

### Limits of spurious emissions:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### Test procedures:

The highest emissions level was measured and recorded. All spurious measurements were evaluated to 20dB below the fundamental. More details can be found in section 3.4 of this report.

### Deviations from test standard:

None

### Test setup:

Test setup details can be found in section 3.4 of this report.

### EUT operating conditions:

Details can be found in section 2.1 of this report.

### Test results:




Figure 6 - Radiated Emissions Plot, BTBR, 30M – 1G




Figure 7 - Radiated Emissions Plot, BTBR, 1G – 3.6G





Figure 8 - Radiated Emissions Plot, BTBR, 3.6G – 25G

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## 4.6 BAND EDGES

### Test Method:

All the radio measurements were performed using the sections from ANSI C63.10. Restricted band edges are using Sec 6.10.5.

### Limits of band-edge measurements:

#### For FCC Part 15.247 Device:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

### Test procedures:

The highest emissions level beyond the band-edge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209. More details can be found in section 3.4 of this report.

### Deviations from test standard:

No deviation.

### Test setup:

Test setup details can be found in section 3.4 of this report.

### EUT operating conditions:

Details can be found in section 2.1 of this report.



Report Number:

R20230808-00-E7A

Rev

A

Prepared for:


Garmin International, Inc.

**Test results:**

**Pass**

Comments:

1. All the band edge plots can be found in Appendix C.
2. If the device falls under FCC Part 15.247 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 20 dB between peak and the band edge.
3. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## 4.7 CONDUCTED AC MAINS EMISSIONS

### Test Method:

ANSI C63.10-2013, Section(s) 6.2

### Limits for conducted emissions measurements:

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

### Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### Test Procedures:

- a. The EUT was placed 0.8m above a ground reference plane and 0.4 meters from the conducting wall of a shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). The LISN provides 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference as well as the ground.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits are not reported.
- d. Results were compared to the 15.207 limits.

### Deviation from the test standard:

No deviation

### EUT operating conditions:

Details can be found in section 2.1 of this report.

## Test Results:




Figure 9 - Conducted Emissions Plot, Line, TX




Figure 10 - Conducted Emissions Plot, Neutral, TX






Figure 11 - Conducted Emissions Plot, Line, IDLE





Figure 12 - Conducted Emissions Plot, Neutral, IDLE

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## APPENDIX A: SAMPLE CALCULATION

### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

AV = Averaging Factor (if applicable)


Assume a receiver reading of 55 dB $\mu$ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB $\mu$ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB $\mu$ V/m value can be mathematically converted to its corresponding level in  $\mu$ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \text{ } \mu\text{V/m}$$

AV is calculated by taking the  $20 \cdot \log(T_{on}/100)$  where  $T_{on}$  is the maximum transmission time in any 100ms window.

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

### EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation.

$$EIRP (Watts) = [Field Strength (V/m) \times antenna distance (m)]^2 / 30$$

$$Power (watts) = 10^{[Power (dBm)/10]} / 1000$$

$$Voltage (dB\mu V) = Power (dBm) + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$Field Strength (V/m) = 10^{[Field Strength (dB\mu V/m) / 20]} / 10^6$$


$$Gain = 1 \text{ (numeric gain for isotropic radiator)}$$

Conversion from 3m field strength to EIRP (d=3):

$$EIRP = [FS(V/m) \times d^2]/30 = FS [0.3] \quad \text{for } d = 3$$

$$EIRP(dBm) = FS(dB\mu V/m) - 10(\log 10^9) + 10\log[0.3] = FS(dB\mu V/m) - 95.23$$

$10\log(10^9)$  is the conversion from micro to milli


	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## APPENDIX B – MEASUREMENT UNCERTAINTY


Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	±4.31
Radiated Emissions, 3m	1GHz - 18GHz	±5.08
Emissions limits, conducted	150kHz – 30MHz	±3.03


Expanded uncertainty values are calculated to a confidence level of 95%.


	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		

## APPENDIX C – GRAPHS AND TABLES





01 Average Power, Low Channel, BTBR

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		



02 Average Power, Mid Channel, BTBR

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		



**03 Average Power, High Channel, BTBR**




Report Number: R20230808-00-E7A

Rev

A

Prepared for: Garmin International, Inc.



04 OBW-20dB, Low Channel, BTBR






Report Number: R20230808-00-E7A


Rev


A

Prepared for: Garmin International, Inc.



05 OBW-20dB, Mid Channel, BTBR


	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		



06 OBW-20dB, High Channel, BTBR




Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		



07 Lower Bandedge, Unrestricted, BTBR



Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		



08 Higher Bandedge, Unrestricted, BTBR



Report Number:


R20230808-00-E7A

Rev

A

Prepared for:


Garmin International, Inc.




09 Lower Bandedge, Restricted, BTBR




Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		





10 Higher Bandedge, Restricted, BTBR

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		




11 Dwell Time, 3.16S (reported for better resolution)


	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		




12 Dwell Time, 31.6S




	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		




13 Channel Count, 2400-2441.5M

	Report Number:	R20230808-00-E7A	Rev	A
	Prepared for:	Garmin International, Inc.		



14 Channel Count, 2441.5-2482M



15 Frequency Separation




Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		



16 Higher Bandedge, Unrestricted, Hopping




Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		



17 Lower Bandedge, Unrestricted, Hopping



Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		



18 ON Time BTBR Hopping



Report Number:	R20230808-00-E7A	Rev	A
Prepared for:	Garmin International, Inc.		

REPORT END