



Maximum Permissible Exposure Report

1. Product Information

FCC ID	: 2AVBM-AM02
EUT	: Mini PC
Test Model	: AM02
Additional Model No.	: AM03, AMR5, AM06, AM07, AM08, AD01, AD02, AD03, AD05
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	: Input: 12V $\overline{=}$ 6A For AC Adapter Input: 100-240V~, 50/60Hz, 0.4A Max Adapter Output: 12.0V $\overline{=}$ 6.0A, 72.0W
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz-2480MHz
Channel Number	: 79 channels for Bluetooth V4.2(DSS) 40 channels for Bluetooth V4.2 (DTS)
Channel Spacing	: 1MHz for Bluetooth V4.2 (DSS) 2MHz for Bluetooth V4.2 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.2(DSS) GFSK for Bluetooth V4.2 (DTS)
Bluetooth Version	: V4.2
Antenna Description	: PIFA Antenna, 2.0dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz-2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 2.0dBi(Max.)
5.2G WLAN	:
Frequency Range	: 5180MHz-5240MHz
Channel Number	: 4 channels for 20MHz bandwidth(5180MHz-5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PIFA Antenna, 2.0dBi(Max.)



2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



5. Antenna Information

KE2EM-Plus can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna	PIFA antenna	2400-6000 MHz	2.0dBi	BT/WIFI Antenna

6. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Max Conducted Output Power (dBm)
GFSK	00	2402	0.89
	39	2441	2.03
	79	2480	0.54
$\pi/4$ -DQPSK	00	2402	0.06
	39	2441	0.97
	79	2480	-0.35
8-DPSK	00	2402	0.13
	39	2441	1.31
	79	2480	-0.13

[BT LE]

Mode	Channel	Frequency (MHz)	Max Conducted Output Power (dBm)
GFSK	00	2402	0.63
	19	2440	1.77
	39	2480	0.33

[2.4G WLAN]

Mode	Channel	Frequency (MHz)	ANT0 Max Conducted Output Power (dBm)	ANT1 Max Conducted Output Power (dBm)
IEEE 802.11b	1	2412	15.57	15.02
	6	2437	15.00	15.45
	11	2462	15.27	14.86
IEEE 802.11g	1	2412	12.60	12.70
	6	2437	13.66	13.03
	11	2462	12.59	12.59
IEEE 802.11n HT20 SISO	1	2412	11.86	12.94
	6	2437	12.26	12.98
	11	2462	12.52	12.77
IEEE 802.11n HT40 SISO	3	2422	11.88	13.00
	6	2437	12.06	13.03
	9	2462	12.55	13.04

[2.4GWIFI Max Conducted Power] ANT 0+ANT 1

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20MIMO	1	2412	15.44
	6	2437	15.65
	11	2462	15.66
11N40MIMO	3	2422	15.49
	6	2437	15.58
	9	2452	15.81



[5.2G WLAN]

Mode	Channel	Frequency (MHz)	ANT0 Max Conducted Output Power (dBm)	ANT1 Max Conducted Output Power (dBm)
IEEE 802.11a	36	5180	5.80	6.64
	40	5200	5.65	7.33
	48	5240	5.64	8.18
IEEE 802.11n HT20 SISO	36	5180	5.68	7.03
	40	5200	6.08	7.47
	48	5240	5.58	7.99
IEEE 802.11n HT40 SISO	38	5190	6.25	7.48
	46	5230	5.77	8.11
IEEE 802.11ac VHT20 SISO	36	5180	5.49	7.01
	40	5200	5.49	7.44
	48	5240	5.49	7.91
IEEE 802.11ac VHT40 SISO	38	5190	5.70	7.53
	46	5230	5.80	8.10
IEEE 802.11ac VHT80 SISO	42	5210	6.25	8.16

[5.2GWIFI Max Conducted Power] ANT 0+ANT 1

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	36	5180	9.42
	40	5200	9.84
	48	5240	9.96
11N40 MIMO	38	5190	9.92
	46	5230	10.11
11AC20 MIMO	36	5180	9.33
	40	5200	9.58
	48	5240	9.88
11AC40 MIMO	38	5190	9.72
	46	5230	10.11
11AC80 MIMO	42	5210	10.32



7. Manufacturing Tolerance

GFSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	2.0	0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8-DPSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	0	1.5	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BT LE			
Channel	Channel 00	Channel 19	Channel 39
Target (dBm)	0.5	1.5	0.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11b			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.0	15.5	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11g			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.0	13.0	12.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n20 MIMO			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.5	15.5	15.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n40 MIMO			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	15.5	15.5	15.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WLAN]			
IEEE 802.11a			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.5	7.5	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 MIMO			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.5	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 MIMO			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	



IEEE 802.11ac VHT20 MIMO			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.5	9.5	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 MIMO			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance ± (dB)	1.0	1.0	
IEEE 802.11ac VHT80 MIMO			
Channel	Channel 42		
Target (dBm)	10.5		
Tolerance ± (dB)	1.0		



8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	3.0	1.9953	2.0	1.5849	0.0006	1.0000
$\pi/4$ -DQPSK	2.0	1.5849	2.0	1.5849	0.0005	1.0000
8-DPSK	2.5	1.7783	2.0	1.5849	0.0006	1.0000

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT LE	2.5	1.7783	2.0	1.5849	0.0006	1.0000

[2.4G WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	16.5	44.6684	2.0	1.5849	0.0141	1.0000
IEEE 802.11g	14.0	25.1189	2.0	1.5849	0.0079	1.0000
IEEE 802.11n HT20 MIMO	16.5	44.6684	2.0	1.5849	0.0141	1.0000
IEEE 802.11n HT40 MIMO	16.5	44.6684	2.0	1.5849	0.0141	1.0000

[5.2G WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	8.5	7.0795	2.0	1.5849	0.0022	1.0000
IEEE 802.11n HT20 MIMO	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11n HT40 MIMO	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT20 MIMO	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT40 MIMO	11.0	12.5893	2.0	1.5849	0.0040	1.0000
IEEE 802.11ac VHT80 MIMO	11.5	14.1254	2.0	1.5849	0.0045	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one 2.4G WLAN&5.2G WLAN, another one 2.4G WLAN&5.2G WLAN and another one BT transmit antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0



2.4G WLAN +BT			
Mode	Σ MPE ratios	Limit	Results
IEEE 802.11b + GFSK	0.0147	1.000	Pass
IEEE 802.11g + GFSK	0.0085	1.000	Pass
IEEE 802.11n20 + GFSK	0.0147	1.000	Pass
IEEE 802.11n40 + GFSK	0.0147	1.000	Pass
IEEE 802.11b + $\pi/4$ -DQPSK	0.0146	1.000	Pass
IEEE 802.11g + $\pi/4$ -DQPSK	0.0084	1.000	Pass
IEEE 802.11n20 + $\pi/4$ -DQPSK	0.0146	1.000	Pass
IEEE 802.11n40 + $\pi/4$ -DQPSK	0.0146	1.000	Pass
IEEE 802.11b + 8-DPSK	0.0147	1.000	Pass
IEEE 802.11g + 8-DPSK	0.0085	1.000	Pass
IEEE 802.11n20 + 8-DPSK	0.0147	1.000	Pass
IEEE 802.11n40 + 8-DPSK	0.0147	1.000	Pass

2.4G WLAN +BT LE			
Mode	Σ MPE ratios	Limit	Results
IEEE 802.11b + GFSK	0.0147	1.000	Pass
IEEE 802.11g + GFSK	0.0085	1.000	Pass
IEEE 802.11n20 + GFSK	0.0147	1.000	Pass
IEEE 802.11n40 + GFSK	0.0147	1.000	Pass

2.4G WLAN + 5.2G WLAN			
Mode	Σ MPE ratios	Limit	Results
IEEE 802.11b + 11A	0.0163	1.000	Pass
IEEE 802.11b + 11N20	0.0181	1.000	Pass
IEEE 802.11b + 11N40	0.0181	1.000	Pass
IEEE 802.11b + 11AC20	0.0181	1.000	Pass
IEEE 802.11b + 11AC40	0.0181	1.000	Pass
IEEE 802.11b + 11AC80	0.0186	1.000	Pass
IEEE 802.11g + 11A	0.0101	1.000	Pass
IEEE 802.11g + 11N20	0.0119	1.000	Pass
IEEE 802.11g + 11N40	0.0119	1.000	Pass
IEEE 802.11g + 11AC20	0.0119	1.000	Pass
IEEE 802.11g + 11AC40	0.0119	1.000	Pass
IEEE 802.11g + 11AC80	0.0124	1.000	Pass
IEEE 802.11n20 + 11A	0.0163	1.000	Pass
IEEE 802.11n20 + 11N20	0.0181	1.000	Pass
IEEE 802.11n20 + 11N40	0.0181	1.000	Pass
IEEE 802.11n20 + 11AC20	0.0181	1.000	Pass
IEEE 802.11n20 + 11AC40	0.0181	1.000	Pass
IEEE 802.11n20 + 11AC80	0.0186	1.000	Pass
IEEE 802.11n40 + 11A	0.0163	1.000	Pass
IEEE 802.11n40 + 11N20	0.0181	1.000	Pass
IEEE 802.11n40 + 11N40	0.0181	1.000	Pass
IEEE 802.11n40 + 11AC20	0.0181	1.000	Pass
IEEE 802.11n40 + 11AC40	0.0181	1.000	Pass
IEEE 802.11n40 + 11AC80	0.0186	1.000	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----