

FCC ID: SWN-LC10UT

According to KDB 447498 D01 General RF Exposure Guidance v06.

For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C).

- 1) For test separation distance > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f_{\text{MHz}})]$
- 2) For test separation distance ≤ 50 mm, the power threshold determined by the equation in C) 1) for 50mm and 100 MHz is multiplied by $1/2$

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f_{\text{MHz}}}] \leq 3.0$$

1. SAR test exclusion threshold: 3.0

Step a): at 100 MHz and 50 mm, power threshold = $(3.0 * 50) / \sqrt{0.1} = 474.342$ mW

Step b1): $474.342 + (50 - 50) \times (27.145/150) = 474.342$ mW

Step c1): $474.342 \times [1 + \log(100/27.145)] = 742.967$ mW

Step c2): $742.967/2 = 371.483$ mW

Frequency	Maximum Average Target Power	Maximum Tune up	Maximum Average Output Power		Limit
	(dBm)	(dB)	(dBm)	(mW)	
27.145 MHz	17	2	19	79.433	371.483 mW

2. Conclusion: No SAR is required.

Note: Measured maximum output power: 17.40 dBm / Tune-up tolerance : 17 dBm \pm 2 dB