



FCC Part 1 Subpart I  
FCC Part 2 Subpart J  
INDUSTRY CANADA RSS 102 ISSUE 5

RF EXPOSURE REPORT

FOR

GDO with 900MHz FHSS Transceiver and 2.4GHz WiFi Module

MODEL NUMBER: 001D8850

FCC ID: HBW1D8088  
IC: 2666A-1D8088

REPORT NUMBER: 11752100B

ISSUE DATE: 2017-06-15

*Prepared for*  
**CHAMBERLAIN GROUP INC.**  
300 Windsor Dr.  
Oak Brook, IL 60523

*Prepared by*  
**UL LLC**  
333 Pfingsten Rd.  
Northbrook, IL 60062  
TEL: (847) 272-8800



NVLAB LAB CODE: 100414-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--		Initial Issue	

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION.....	5
5. MAXIMUM PERMISSIBLE RF EXPOSURE .....	6
5.1. FCC RULES .....	6
5.2. IC RULES .....	7
5.3. EQUATIONS .....	8
5.4. IC EXEMPTION.....	9
6. RF EXPOSURE RESULTS .....	10

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** CHAMBERLAIN GROUP INC.  
300 Windsor Dr.  
Oak Brook, IL 60523

**EUT DESCRIPTION:** GDO with 900MHz FHSS Transceiver and 2.4GHz WiFi Module

**MODEL:** 001D8850

**SERIAL NUMBER:** non-serialized

**DATE TESTED:** May 1, 2017 to May 12, 2017

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass
INDUSTRY CANADA RSS 102 ISSUE 5	Pass

UL LLC. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Approved & Released For  
UL LLC By: Jeffrey Moser



EMC PROGRAM MANAGER  
UL LLC

Calculated By: Bart Mucha



EMC STAFF ENGINEER  
UL LLC

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 2.1091, 2.1093 and DDB 447498 D01 V06 and IC Safety Code 6, RSS 102 Issue 5.

## 3. REFERENCES

Document FCC Grant for HBW1D8088, operation in the 902-928MHz band, and FCC Grant for COFWMNBM11, operation in the 2.4GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the above reference documents.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 333 Pfingsten Road, Northbrook, IL 60062 USA.

UL NBK is accredited by NVLAP, Laboratory Code 100414-0. The full scope of accreditation can be viewed at <https://www-s.nist.gov/>

## 5. MAXIMUM PERMISSIBLE RF EXPOSURE

### 5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

#### **Notes:**

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

## 5.2. IC RULES

IC Safety Code 6 (2015), Section 2.2.2: To ensure compliance with the basic restrictions outlined in Section 2.1, at frequencies between 10 MHz and 300 GHz, the reference levels for electric- and magnetic-field strength and power density must be complied with.

**TABLE 5:** Reference Levels for Electric Field Strength, Magnetic Field Strength and Power Density in Uncontrolled Environments

Frequency (MHz)	Electric Field Strength ( $E_{RL}$ ), (V/m, RMS)	Magnetic Field Strength ( $H_{RL}$ ), (A/m, RMS)	Power Density ( $S_{RL}$ ), (W/m <sup>2</sup> )	Reference Period (minutes)
10–20	27.46	0.0728	2	6
20–48	$58.07 / f^{0.25}$	$0.1540 / f^{0.25}$	$8.944 / f^{0.5}$	6
48–300	22.06	0.05852	1.291	6
300–6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000–15000	61.4	0.163	10	6
15000–150000	61.4	0.163	10	$616000 / f^{1.2}$
150000–300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000 / f^{1.2}$

Frequency,  $f$ , is in MHz.

**TABLE 6:** Reference Levels for Electric Field Strength, Magnetic Field Strength and Power Density in Controlled Environments

Frequency (MHz)	Electric Field Strength ( $E_{RL}$ ), (V/m, RMS)	Magnetic Field Strength ( $H_{RL}$ ), (A/m, RMS)	Power Density, ( $S_{RL}$ ), (W/m <sup>2</sup> )	Reference Period (minutes)
10–20	61.4	0.163	10	6
20–48	$129.8 / f^{0.25}$	$0.3444 / f^{0.25}$	$44.72 / f^{0.5}$	6
48–100	49.33	0.1309	6.455	6
100–6000	$15.60 f^{0.25}$	$0.04138 f^{0.25}$	$0.6455 f^{0.5}$	6
6000–15000	137	0.364	50	6
15000–150000	137	0.364	50	$616000 / f^{1.2}$
150000–300000	$0.354 f^{0.5}$	$9.40 \times 10^{-4} f^{0.5}$	$3.33 \times 10^{-4} f$	$616000 / f^{1.2}$

Frequency,  $f$ , is in MHz.

### NOTES FOR TABLES 5 AND 6:

- For exposures shorter than the reference period, field strengths may exceed the reference levels, provided that the time average of the squared value of the electric or magnetic field strength over any time period equal to the reference period shall not exceed  $E_{RL}^2$  or  $H_{RL}^2$ , respectively. For exposures longer than the reference period, including indefinite exposures, the time average of the squared value of the electric or magnetic field strength over any time period equal to the reference period shall not exceed  $E_{RL}^2$  or  $H_{RL}^2$ , respectively.

### **5.3. EQUATIONS**

#### **POWER DENSITY**

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

#### **DISTANCE**

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>



## **MIMO AND COLOCATED TRANSMITTERS**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as  
(Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

## **5.4. IC EXEMPTION**

### **INDUSTRY CANADA EXEMPTION**

RSS-102 Clause 2.5.2 RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;

## 6. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

### Notes:

- 1) For MPE the new KDB 447498 requires the calculations to use the maximum rated power; that power should be declared by the manufacturer, and should not be lower than the measured power. If the power has a tolerance then we also need to check that the measured power is within the tolerance.

Multiple chain or colocated transmitters

<b>Band</b>	<b>(GHz)</b>	0.9	2.4
<b>Mode</b>		FHSS	WLAN
<b>Transmitter</b>		Gateway	Chain 0
<b>Separation Distance</b>	<b>(cm)</b>	20	20
<b>Output Power</b>	<b>(dBm)</b>	12.1	23.7
<b>Antenna Gain</b>	<b>(dBi)</b>	-2.0	2.0
<b>Duty Cycle</b>	<b>(%)</b>	100	100
<b>Source Based EIRP</b>	<b>(mW)</b>	10.3	375.0
<b>FCC Power Density</b>	<b>(mW/cm<sup>2</sup>)</b>	0.0020	0.0746
<b>FCC Power Density Limit</b>	<b>(mW/cm<sup>2</sup>)</b>	0.6	1
<b>IC Power Density</b>	<b>(W/m<sup>2</sup>)</b>	0.020	0.746
<b>IC Power Density Limit</b>	<b>(W/m<sup>2</sup>)</b>	6	10
<b>Fraction of Limit</b>	<b>(%)</b>	0.3	7.5
<b>Sum of Fractions (%)</b>	<b>7.8</b>		

For the 900MHz FHSS transceiver the actual maximum power is 12.118dBm. For the 2.4GHz WiFi radio the maximum power measured based on the report for the module is set to 23.7dBm.

## END OF REPORT