

## FCC PART 15.231



## TEST REPORT

For

**ZHEJIANG JIECANG LINEAR MOTION TECHNOLOGY CO., LTD**

No.19 XinTao Road, Provincial High Tech Park, XinChang county, ZheJiang, Province, 312500 China

**FCC ID: 2ANKDJCP-Y4Y6-H-0**

|   |   |
|---|---|
| <b>Report Type:</b><br>Original Report  | <b>Product Name:</b><br>Wi-Fi Bridge  |
| <b>Report Number:</b> RSHA240522002-00B   |   |
| <b>Report Date:</b> 2025-01-23  |   |
| <b>Reviewed By:</b>   | Bard Liu  |
| <b>Approved By:</b>   | Kyle Xu   |
| <b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Kunshan)<br>No.248 Chenghu Road, Kunshan, Jiangsu province, China<br>Tel: +86-512-86175000<br>Fax: +86-512-88934268<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |   |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S.Government.

## **TABLE OF CONTENTS**

|  |           |
|--|-----------|
| <b>REPORT REVISION HISTORY.....</b>  | <b>4</b>  |
| <b>GENERAL INFORMATION.....</b>  | <b>5</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                   | 5         |
| OBJECTIVE .....  | 5         |
| TEST METHODOLOGY .....   | 5         |
| MEASUREMENT UNCERTAINTY.....   | 6         |
| TEST FACILITY .....  | 6         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                      | <b>7</b>  |
| JUSTIFICATION .....  | 7         |
| EUT EXERCISE SOFTWARE .....  | 7         |
| EQUIPMENT MODIFICATIONS .....  | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                   | 7         |
| EXTERNAL I/O CABLE.....  | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....  | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                       | <b>10</b> |
| <b>TEST EQUIPMENT LIST .....</b>   | <b>11</b> |
| <b>FCC §1.1310 &amp; §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b> | <b>12</b> |
| <b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>                               | <b>14</b> |
| APPLICABLE STANDARD .....  | 14        |
| ANTENNA CONNECTED CONSTRUCTION .....                                       | 14        |
| <b>FCC §15.207 (A) – AC POWER LINE CONDUCTED EMISSIONS .....</b>           | <b>15</b> |
| APPLICABLE STANDARD .....  | 15        |
| TEST SYSTEM SETUP.....   | 15        |
| EMI TEST RECEIVER SETUP.....   | 15        |
| TEST PROCEDURE .....   | 16        |
| TEST RESULTS SUMMARY .....   | 16        |
| <b>FCC §15.205, §15.209, §15.231 (B) - RADIATED EMISSIONS .....</b>        | <b>17</b> |
| APPLICABLE STANDARD .....  | 17        |
| TEST SYSTEM SETUP .....  | 18        |
| EMI TEST RECEIVER SETUP.....   | 20        |
| TEST PROCEDURE .....   | 20        |
| TEST RESULTS SUMMARY .....   | 20        |
| TEST DATA: SEE APPENDIX .....  | 20        |
| <b>FCC §15.231(A) (2) - DEACTIVATION TESTING.....</b>                      | <b>21</b> |
| APPLICABLE STANDARD .....  | 21        |
| TEST SYSTEM SETUP .....  | 21        |
| TEST PROCEDURE .....   | 21        |
| TEST DATA: SEE APPENDIX .....  | 21        |
| <b>FCC §15.231(C) - 20DB EMISSION BANDWIDTH TESTING.....</b>               | <b>22</b> |
| APPLICABLE STANDARD .....  | 22        |
| TEST SYSTEM SETUP .....  | 22        |
| TEST PROCEDURE .....   | 22        |
| TEST DATA: SEE APPENDIX .....  | 22        |
| <b>APPENDIX - TEST DATA.....</b>   | <b>23</b> |

|  |           |
|--|-----------|
| ENVIRONMENTAL CONDITIONS & TEST INFORMATION..... | 23        |
| AC POWER LINE CONDUCTED EMISSIONS.....           | 24        |
| RADIATED EMISSIONS.....                          | 26        |
| DEACTIVATION TESTING.....                        | 31        |
| 20 dB EMISSION BANDWIDTH TESTING.....            | 32        |
| <b>EUT PHOTOGRAPHS .....</b>                     | <b>33</b> |
| <b>TEST SETUP PHOTOGRAPHS .....</b>              | <b>34</b> |

REPORT REVISION HISTORY

| Number of Revisions | Report No.        | Version | Issue Date | Description     |
|---------------------|-------------------|---------|------------|-----------------|
| 0                   | RSHA240522002-00B | R1V1    | 2025-01-23 | Initial Release |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                               |  |
|-------------------------------|--|
| Applicant:                    | ZHEJIANG JIECANG LINEAR MOTION TECHNOLOGY CO., LTD |
| Product Name:                 | Wi-Fi Bridge                                       |
| Tested Model:                 | JCP-Y4Y6-H-0                                       |
| Power Supply:                 | DC 5V from adapter                                 |
| RF Function:                  | SRD  |
| Operating Band/Frequency:     | 433.92 MHz   |
| Field Strength of Fundamental | 79.57 dBμV/m@3m                                    |
| Channel Number:               | 1  |
| Modulation Type:              | ASK; FSK   |
| Antenna Type:                 | Spring Antenna                                     |

#### Adapter Information:

Model: MLF-A260502000UU

Input: AC 100-240V, 50/60Hz, 0.4A max

Output: DC 5.0V, 2.0A

*All measurement and test data in this report was gathered from production sample serial number: RSHA240522002-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-05-22.)*

### Objective

This test report is prepared for *ZHEJIANG JIECANG LINEAR MOTION TECHNOLOGY CO., LTD*. All the test measurements were performed according to the measurement procedure described in ANSI C63.10 - 2013.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209, 15.35(c) and 15.231 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10 - 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

**Measurement Uncertainty**

| Item                               |                | Uncertainty |
|------------------------------------|----------------|-------------|
| AC Power Lines Conducted Emissions |                | 3.19 dB     |
| RF conducted test with spectrum    |                | 0.9 dB      |
| Radiated emission                  | 9 kHz~150 kHz  | 3.8 dB      |
|                                    | 150 kHz~30 MHz | 3.4 dB      |
|                                    | 30 MHz~1 GHz   | 6.11 dB     |
|                                    | 1 GHz~6 GHz    | 4.45 dB     |
|                                    | 6 GHz~18 GHz   | 5.23 dB     |
| Occupied Bandwidth                 |                | 0.5 kHz     |
| Temperature                        |                | 1.0 °C      |
| Humidity                           |                | 6%          |

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

## SYSTEM TEST CONFIGURATION

### Justification

Channel List:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 1       | 433.92          |

### EUT Exercise Software

Engineering Mode was provided by manufacturer★. The maximum power was configured default setting.

### Equipment Modifications

No modification was made to the EUT.

### Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| Lenovo       | Notebook    | Y700P | PF2B7PL5      |
| /            | Telephone   | /     | TX-KS-A044    |

### External I/O Cable

| Cable Description | Length (m) | From Port      | To Port   |
|-------------------|------------|----------------|-----------|
| Power Cable       | 1.0        | AC Source/LISN | Adapter   |
| USB Cable         | 3.0        | EUT            | Adapter   |
| RJ45 Cable        | 1.5        | EUT            | Notebook  |
| RJ11 Cable        | 3.0        | EUT            | Telephone |


## Block Diagram of Test Setup

For Conducted Emissions:




For Radiated Emissions(Below 1GHz & Abve 1GHz):

For adapter (Below 1GHz)



For adapter (Abve 1GHz)



**SUMMARY OF TEST RESULTS**

| FCC Rules                    | Description of Test                | Result    |
|------------------------------|------------------------------------|-----------|
| §1.1310 & §2.1091            | MAXIMUM PERMISSIBLE EXPOSURE (MPE) | Compliant |
| §15.203                      | Antenna Requirement                | Compliant |
| §15.207(a)                   | Conducted Emissions                | Compliant |
| §15.205, §15.209, §15.231(b) | Radiated Emissions                 | Compliant |
| §15.231 (c)                  | 20dB Emission Bandwidth            | Compliant |
| §15.231 (a) (1)              | Deactivation                       | Compliant |

## TEST EQUIPMENT LIST

| Manufacturer                               | Description         | Model     | Serial Number | Calibration Date | Calibration Due Date |
|--|---------------------|-----------|---------------|------------------|----------------------|
| <b>Radiated Emission Test (Chamber 1#)</b> |                     |           |               |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver   | ESCI      | 100195        | 2024-04-23       | 2025-04-22           |
| Sunol Sciences                             | Hybrid Antenna      | JB3       | A090314-1     | 2024-11-08       | 2027-11-07           |
| Narda                                      | 6dB Attenuator      | 773-6     | 10690812-2-1  | 2024-11-08       | 2027-11-07           |
| Sonoma Instrument                          | Amplifier           | 310N      | 171205        | 2024-04-23       | 2025-04-22           |
| BACL                                       | Active Loop Antenna | 1313-1A   | 4041511       | 2024-11-22       | 2027-11-21           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-8   | 008           | 2024-04-23       | 2025-04-22           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-9   | 009           | 2024-04-23       | 2025-04-22           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-10  | 010           | 2024-04-23       | 2025-04-22           |
| Rohde & Schwarz                            | Test Software       | EMC32     | 100361        | N/A              | N/A                  |
| Rohde & Schwarz                            | Spectrum Analyzer   | FSU26     | 200103        | 2024-04-24       | 2025-04-23           |
| <b>Radiated Emission Test (Chamber 2#)</b> |                     |           |               |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver   | ESU40     | 100207/040    | 2024-04-25       | 2025-04-23           |
| ETS-LINDGREN                               | Horn Antenna        | 3115      | 9207-3900     | 2024-11-03       | 2027-11-02           |
| A.H.Systems,inc                            | Amplifier           | PAM-0118P | 512           | 2024-04-25       | 2025-04-24           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-11  | 011           | 2024-04-25       | 2025-04-24           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-12  | 012           | 2024-04-25       | 2025-04-24           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-13  | 013           | 2024-04-25       | 2025-04-24           |
| Rohde & Schwarz                            | Test Software       | EMC32     | 100361        | N/A              | N/A                  |
| <b>Conducted Emission Test</b>             |                     |           |               |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver   | ESR       | 101746        | 2024-04-23       | 2025-04-22           |
| Rohde & Schwarz                            | LISN                | ENV216    | 101115        | 2024-04-23       | 2025-04-22           |
| Audix                                      | Test Software       | e3        | V9            | N/A              | N/A                  |
| Rohde & Schwarz                            | Pulse Limiter       | ESH3-Z2   | 0357.8810.54  | 2024-04-23       | 2025-04-22           |
| MICRO-COAX                                 | Coaxial Cable       | Cable-15  | 015           | 2024-04-23       | 2025-04-22           |

**Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

### **Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                                      |                                      |  |                                 |
|--|--------------------------------------|--------------------------------------|--|---------------------------------|
| <b>Frequency Range (MHz)</b>                                   | <b>Electric Field Strength (V/m)</b> | <b>Magnetic Field Strength (A/m)</b> | <b>Power Density (mW/cm<sup>2</sup>)</b> | <b>Averaging Time (minutes)</b> |
| 0.3-1.34   | 614                                  | 1.63                                 | *(100)                                   | 30                              |
| 1.34-30  | 824/f                                | 2.19/f                               | *(180/f <sup>2</sup> )                   | 30                              |
| 30-300   | 27.5                                 | 0.073                                | 0.2                                      | 30                              |
| 300-1500   | /                                    | /                                    | f/1500                                   | 30                              |
| 1500-100,000   | /                                    | /                                    | 1.0                                      | 30                              |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### **Calculated Formulary**

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

**Calculated Data:**

| Mode         | Frequency Range (MHz) | Antenna Gain |           | Maximum peak output power* |        | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|--------------|-----------------------|--------------|-----------|----------------------------|--------|--------------------------|-------------------------------------|---------------------------------|
|              |                       | (dBi)        | (numeric) | (dBm)                      | (mW)   |                          |                                     |                                 |
| 802.11b      | 2412-2462             | 1.88         | 1.54      | 19.53                      | 89.74  | 20                       | 0.0275                              | 1.0                             |
| 802.11g      |                       | 1.88         | 1.54      | 23.39                      | 218.27 | 20                       | 0.0669                              | 1.0                             |
| 802.11n-HT20 |                       | 1.88         | 1.54      | 22.20                      | 165.96 | 20                       | 0.0508                              | 1.0                             |
| BLE-1M       | 2402-2480             | 1.88         | 1.54      | 8.5                        | 7.08   | 20                       | 0.0022                              | 1.0                             |

| Mode | Frequency Range (MHz) | Tune-up EIRP* |      | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|------|-----------------------|---------------|------|--------------------------|-------------------------------------|---------------------------------|
|      |                       | (dBm)         | (mW) |                          |                                     |                                 |
| SRD  | 433.92                | -15.5         | 0.03 | 20                       | <0.0001                             | 0.3                             |

**Note:**

1. For the above tune up power were declared by the manufacturer.
2. The EUT contains a certified module, FCC ID: 2ANDL-CR3L (Grant on: 12/28/2020) without any modifications.
3. The SRD EIRP = 79.57 dBμV/m -95.2 = -15.63 dBm.
4. WiFi, BLE and SRD cannot be transmitted simultaneously.

**Conclusion:** The device meets MPE at distance 20cm.

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has a spring antenna which were permanently attached, fulfill the requirement of this section. Please refer to EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)

### Test System Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | RBW   | VBW    |
|------------------|-------|--------|
| 150 kHz - 30 MHz | 9 kHz | 30 kHz |

## Test Procedure

During the conducted emission test, the EUT was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

## Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Factor (dB)} &= \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)} \\ \text{Level (dB}\mu\text{V)} &= \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)}\end{aligned}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

**Test Data: See Appendix**

**FCC §15.205, §15.209, §15.231 (b) - RADIATED EMISSIONS****Applicable Standard**

FCC §15.205, §15.209, §15.231 (b)

According to FCC §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

| Fundamental frequency (MHz) | Field strength of fundamental (microvolts/meter) | Field strength of spurious emission (microvolts/meter) |
|-----------------------------|--|--|
| 40.66-40.70                 | 2250   | 225  |
| 70-130                      | 1250   | 125  |
| 130-174                     | <sup>1</sup> 1250 to 3750                        | <sup>1</sup> 125 to 375                                |
| 174-260                     | 3750   | 375  |
| 260-470                     | <sup>1</sup> 3750 to 12500                       | <sup>1</sup> 375 to 1250                               |
| Above 470                   | 12500  | 1250   |

<sup>1</sup> Linear interpolations.


(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.


## Test System Setup

### 9 kHz-30 MHz:



### 30 MHz-1 GHz:



**Above 1 GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10 - 2013. The specification used was the FCC 15 § 15.209, 15.205 and 15.231.

### EMI Test Receiver Setup

During the radiated emission test, the EMI test Receiver was set with the following configurations:

| Frequency Range   | RBW     | VBW     | IF B/W  | Measurement |
|-------------------|---------|---------|---------|-------------|
| 9 kHz – 150 kHz   | 200 Hz  | 1 kHz   | 200 Hz  | QP/Average  |
| 150 kHz – 30 MHz  | 9 kHz   | 30 kHz  | 9 kHz   | QP/ Average |
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | /       | Peak        |
|                   | /       | /       | 120 kHz | QP          |
| ABOVE 1GHz        | 1MHz    | 3 MHz   | /       | Peak        |

For 9 kHz-30 MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

### Test Procedure

Maximizing procedure was performed on at least six (6) highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB $\mu$ V/m) = Meter Reading (dB $\mu$ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB $\mu$ V/m) – Corrected Amplitude (dB $\mu$ V/m)

### Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.205, §15.209, §15.231 (b).


**Test Data: See Appendix**

## FCC §15.231(a) (2) - DEACTIVATION TESTING

### Applicable Standard

Per FCC §15.231(a), (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

### Test System Setup



### Test Procedure

1. With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer.
2. Set center frequency of spectrum analyzer=operating frequency.
3. Set the spectrum analyzer as RBW=100k VBW=300k Span=0Hz.
4. Repeat above procedures until all frequency measured was complete.


**Test Data: See Appendix**

## FCC §15.231(c) - 20dB EMISSION BANDWIDTH TESTING

### Applicable Standard

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

### Test System Setup



### Test Procedure

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

**Test Data:** See Appendix


APPENDIX - TEST DATA

Environmental Conditions & Test Information

| Test Item:         | AC POWER LINE<br>CONDUCTED EMISSIONS | RADIATED EMISSIONS |              |             |
|--------------------|--------------------------------------|--------------------|--------------|-------------|
|                    |                                      | 9 kHz-30 MHz       | 30 MHz-1 GHz | Above 1 GHz |
| Test Date:         | 2025-01-08                           | 2025-01-06         | 2025-01-10   | 2025-01-10  |
| Temperature:       | 16.3 °C                              | 17.1 °C            | 15.9 °C      | 15.9 °C     |
| Relative Humidity: | 36 %                                 | 52 %               | 32 %         | 32 %        |
| ATM Pressure:      | 102.5 kPa                            | 102.4 kPa          | 103.2 kPa    | 103.2 kPa   |
| Test Result:       | Pass                                 | Pass               | Pass         | Pass        |
| Test Engineer:     | Myles Miao                           | Jerry Yan          | Jerry Yan    | Destine Wu  |


| Test Item:         | DEACTIVATION TESTING | 20dB EMISSION BANDWIDTH TESTING |
|--------------------|----------------------|---------------------------------|
| Test Date:         | 2025-01-07           | 2025-01-07                      |
| Temperature:       | 16.5 °C              | 16.5 °C                         |
| Relative Humidity: | 51 %                 | 51 %                            |
| ATM Pressure:      | 102.6 kPa            | 102.6 kPa                       |
| Test Result:       | Pass                 | Pass                            |
| Test Engineer:     | Neil Zhou            | Neil Zhou                       |

## AC POWER LINE CONDUCTED EMISSIONS



Site : CE  
Condition : limit\FCC PART 15.207  
: DET:Peak  
Project No. : RSHA240522002  
Model : JCP-Y4Y6-H-0  
Phase : L  
Voltage : 120V/60Hz  
Mode : Transmitting in maximum output power ASK mode  
Test Equipment : ENV216,ESR  
Receiver Setting : RBW: 9 kHz, VBW: 30 kHz, Sweep Time: Auto  
Temperature : 16.3℃  
Humidity : 36%  
Atmospheric pressure: 102.5kPa  
Test Engineer : Myles Miao

|      | Read  |        | Limit | Over  |                   |
|------|-------|--------|-------|-------|-------------------|
| Freq | Level | Factor | Level | Line  | Limit Remark      |
| MHz  | dBuV  | dB     | dBuV  | dBuV  | dB                |
| 1    | 0.479 | 14.65  | 20.17 | 34.82 | 56.35 -21.53 Peak |
| 2    | 0.603 | 19.34  | 20.09 | 39.43 | 56.00 -16.57 Peak |
| 3    | 0.656 | 23.48  | 20.08 | 43.56 | 56.00 -12.44 Peak |
| 4    | 1.017 | 15.04  | 19.73 | 34.77 | 56.00 -21.23 Peak |
| 5    | 1.311 | 14.36  | 19.89 | 34.25 | 56.00 -21.75 Peak |
| 6    | 1.850 | 13.35  | 20.11 | 33.46 | 56.00 -22.54 Peak |





Site : CE  
Condition : limit\FCC PART 15.207  
: DET:Peak  
Project No. : RSHA240522002  
Model : JCP-Y4Y6-H-0  
Phase : N  
Voltage : 120V/60Hz  
Mode : Transmitting in maximum output power ASK mode  
Test Equipment : ENV216,ESR  
Receiver Setting : RBW: 9 kHz, VBW: 30 kHz, Sweep Time: Auto  
Temperature : 16.3℃  
Humidity : 36%  
Atmospheric pressure: 102.5kPa  
Test Engineer : Myles Miao

|   | Freq  | Read<br>Level | Factor | Level | Limit<br>Line | Over<br>Limit | Remark |
|---|-------|---------------|--------|-------|---------------|---------------|--------|
|   | MHz   | dBuV          | dB     | dBuV  | dBuV          | dB            |        |
| 1 | 0.226 | 20.18         | 20.12  | 40.30 | 62.61         | -22.31        | Peak   |
| 2 | 0.458 | 11.10         | 20.22  | 31.32 | 56.73         | -25.41        | Peak   |
| 3 | 0.588 | 16.46         | 20.10  | 36.56 | 56.00         | -19.44        | Peak   |
| 4 | 0.653 | 21.93         | 20.08  | 42.01 | 56.00         | -13.99        | Peak   |
| 5 | 1.032 | 11.93         | 19.74  | 31.67 | 56.00         | -24.33        | Peak   |
| 6 | 1.324 | 11.12         | 19.89  | 31.01 | 56.00         | -24.99        | Peak   |

**RADIATED EMISSIONS**

Test mode: Transmitting

After pre-scan in the X, Y and Z axes of orientation, the worst case X axes is below:

**ASK****9 kHz-30 MHz:****Parallel(Transmitting in maximum output power ASK mode)****9kHz-150kHz****150kHz-30MHz**Project No.RSHA240522002  
Date: 6.JAN.2025 17:47:44

Tester:Jerry Yan

Project No.RSHA240522002  
Date: 6.JAN.2025 17:50:38

Tester:Jerry Yan

**9kHz-150kHz**


| Frequency (MHz) | Corrected Amplitude (dBμV/m) @3m | Detector PK/QP/Ave. | Corrected Factor (dB/m) | Limit (dBμV/m) @3m | Margin (dB) |
|-----------------|----------------------------------|---------------------|-------------------------|--------------------|-------------|
| 0.01323         | 42.25                            | PK                  | 54.31                   | 125.17             | 82.92       |
| 0.019152        | 40.79                            | PK                  | 50.54                   | 121.96             | 81.17       |
| 0.026202        | 40.46                            | PK                  | 48.26                   | 119.24             | 78.78       |
| 0.031278        | 41.4                             | PK                  | 46.87                   | 117.70             | 76.30       |

**150kHz-30MHz**

| Frequency (MHz) | Corrected Amplitude (dBμV/m) @3m | Detector PK/QP/Ave. | Corrected Factor (dB/m) | Limit (dBμV/m) @3m | Margin (dB) |
|-----------------|----------------------------------|---------------------|-------------------------|--------------------|-------------|
| 0.15000         | 41.94                            | PK                  | 50.90                   | 104.08             | 62.14       |
| 0.74700         | 28.23                            | PK                  | 20.11                   | 70.14              | 41.91       |
| 2.12010         | 24.1                             | PK                  | 13.90                   | 69.54              | 45.44       |
| 5.28420         | 23.1                             | PK                  | 7.99                    | 69.54              | 46.44       |

**ASK****30 MHz-1 GHz:****Common Information**

|                      |   |
|----------------------|---|
| Project No:          | RSHA240522002                                       |
| EUT Model:           | JCP-Y4Y6-H-0  |
| Test Mode:           | Transmitting  |
| Standard:            | FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.231 |
| Test Equipment:      | ESCI, JB3, 310N                                     |
| Receiver Setting:    | RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto        |
| Temperature:         | 15.9°C  |
| Humidity:            | 32%   |
| Barometric Pressure: | 103.2 kPa   |
| Test Engineer:       | Jerry Yan   |
| Test Date:           | 2025/1/10   |

**Critical Freqs**


| Frequency (MHz) | MaxPeak (dBµ V/m) | Limit (dBµ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|-------------------|-----------------|-------------|-----|--------------|
| 36.668750       | 29.79             | 40.00           | 10.21       | V   | -9.1         |
| 43.701250       | 29.26             | 40.00           | 10.74       | V   | -13.4        |
| 90.625000       | 31.70             | 43.50           | 11.80       | H   | -16.7        |
| 152.462500      | 32.70             | 43.50           | 10.80       | V   | -11.8        |
| 249.947500      | 28.43             | 46.00           | 17.57       | H   | -12.1        |
| 433.883750      | 79.57             | 80.82           | 1.25        | H   | -7.1         |
| 867.958750      | 39.80             | 46.00           | 6.20        | V   | -0.2         |

Note: If the spurious emissions maximized peak measured value complies with the QP/Average limit, it is unnecessary to perform QP/Average measurement.

**ASK****1 GHz-5 GHz:****Common Information**

|                |   |
|----------------|---|
| Project No.:   | RSHA240522002                                     |
| Test Mode:     | Transmitting                                      |
| Standard:      | FCC Part 15.231& FCC Part 15.205& FCC Part 15.209 |
| Test Engineer: | Destine Hu  |

Full Spectrum


**Critical Freqs**

| Frequency (MHz) | MaxPeak (dB μ V/m) | Average (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|--------------------|--------------------|------------------|-------------|-----|--------------|
| 1735.200000     | 30.76              | ---                | 74.00            | 43.24       | H   | -13.3        |
| 2169.600000     | 37.49              | ---                | 74.00            | 36.51       | H   | -11.2        |
| 3037.600000     | 53.20              | ---                | 74.00            | 20.80       | H   | -8.3         |
| 3905.600000     | 42.41              | ---                | 74.00            | 31.59       | V   | -6.0         |
| 4340.000000     | 43.54              | ---                | 74.00            | 30.46       | H   | -4.8         |
| 4774.400000     | 44.38              | ---                | 74.00            | 29.62       | H   | -3.3         |

Note: If the spurious emissions maximized peak measured value more than 20dB below peak limit which can complies with average limit, it is unnecessary to perform Average measurement.

**FSK**  
**30 MHz-1 GHz:****Common Information**

|                      |   |
|----------------------|---|
| Project No:          | RSHA240522002                                       |
| EUT Model:           | JCP-Y4Y6-H-0  |
| Test Mode:           | Transmitting  |
| Standard:            | FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.231 |
| Test Equipment:      | ESCI, JB3, 310N                                     |
| Receiver Setting:    | RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto        |
| Temperature:         | 15.9°C  |
| Humidity:            | 32%   |
| Barometric Pressure: | 103.2 kPa   |
| Test Engineer:       | Jerry Yan   |
| Test Date:           | 2025/1/10   |

**Critical Freqs**

| Frequency (MHz) | MaxPeak (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|-------------------|-----------------|-------------|-----|--------------|
| 36.668750       | 28.92             | 40.00           | 11.08       | V   | -9.1         |
| 92.443750       | 30.91             | 43.50           | 12.59       | V   | -16.2        |
| 149.188750      | 33.72             | 43.50           | 9.78        | V   | -11.6        |
| 249.947500      | 27.44             | 46.00           | 18.56       | H   | -12.1        |
| 372.652500      | 31.46             | 46.00           | 14.54       | H   | -8.6         |
| 433.883750      | 78.34             | 80.82           | 2.48        | H   | -7.1         |
| 867.837500      | 36.75             | 46.00           | 9.25        | H   | -0.2         |


Note: If the spurious emissions maximized peak measured value complies with the QP/Average limit, it is unnecessary to perform QP/Average measurement.

**FSK**  
**1 GHz-5 GHz:**

### Common Information

|                |   |
|----------------|---|
| Project No.:   | RSHA240522002                                     |
| Test Mode:     | Transmitting                                      |
| Standard:      | FCC Part 15.231& FCC Part 15.205& FCC Part 15.209 |
| Test Engineer: | Destine Hu  |

Full Spectrum



### Critical Freqs

| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Average (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|------------------------|------------------------|----------------------|-------------|-----|--------------|
| 1735.200000     | 34.21                  | ---                    | 74.00                | 39.79       | V   | -13.3        |
| 2169.600000     | 43.27                  | ---                    | 74.00                | 30.73       | V   | -11.2        |
| 3037.600000     | 51.56                  | ---                    | 74.00                | 22.44       | V   | -8.3         |
| 3905.600000     | 51.43                  | ---                    | 74.00                | 22.57       | H   | -6.0         |
| 4339.200000     | 52.35                  | ---                    | 74.00                | 21.65       | V   | -4.8         |
| 4773.600000     | 52.54                  | ---                    | 74.00                | 21.46       | H   | -3.3         |


Note: If the spurious emissions maximized peak measured value more than 20dB below peak limit which can complies with average limit, it is unnecessary to perform Average measurement.

## DEACTIVATION TESTING

Test mode: Transmitting


| Channel Frequency (MHz) | Modulation | T <sub>on</sub> (S) | Limit (s) | Result |
|-------------------------|------------|---------------------|-----------|--------|
| 433.92                  | ASK        | 0.918               | <5        | Pass   |
| 433.92                  | FSK        | 2.917               | <5        | Pass   |

### ASK



ProjectNo.:RSHA240522002 Tester:Neil Zhou  
Date: 7-JAN-2025 16:27:29

### FSK



ProjectNo.:RSHA240522002 Tester:Neil Zhou  
Date: 7-JAN-2025 15:45:11


**20 dB EMISSION BANDWIDTH TESTING***Test Mode: Transmitting***ASK**

| Channel Frequency (MHz) | 20dB Bandwidth (kHz) | Limit (kHz) | Result |
|-------------------------|----------------------|-------------|--------|
| 433.92                  | 9.62                 | 1084.8      | Pass   |


**FSK**

| Channel Frequency (MHz) | 20dB Bandwidth (kHz) | Limit (kHz) | Result |
|-------------------------|----------------------|-------------|--------|
| 433.92                  | 82.05                | 1084.8      | Pass   |

**Note:** Limit = 0.25% \* Center Frequency = 0.25% \* 433.92 MHz = 1084.8 kHz

**ASK**

ProjectNo.: RSHA240522002 Tester: Neil Zhou  
Date: 7-JAN-2025 16:50:31

**FSK**

ProjectNo.: RSHA240522002 Tester: Neil Zhou  
Date: 7-JAN-2025 15:27:00

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

### **Declarations**

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $k=2$  with the 95.45% confidence interval.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***