



RF Exposure Evaluation Report

APPLICANT : Sinocastel Co., Ltd.
EQUIPMENT : OBD GPS Tracker
BRAND NAME : OBD-Smart
MODEL NAME : IDD-213N
FCC ID : S8U213N
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Deputy Manager

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA431904	Rev. 01	Initial issue of report	Jan. 08, 2015

**1. Administration Data****1.1. Testing Laboratory**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595

Applicant	
Company Name	Sinocastel Co., Ltd.
Address	5F, 5th Building, Software Park, No. 2 Gaoxin C. 3rd Road, Nanshan District, Shezhen, China

Manufacturer	
Company Name	Sinocastel Co., Ltd.
Address	5F, 5th Building, Software Park, No. 2 Gaoxin C. 3rd Road, Nanshan District, Shezhen, China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	OBD GPS Tracker
Brand Name	OBD-Smart
Model Name	IDD-213N
FCC ID	S8U213N
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Mode	• GPRS/EGPRS • RMC 12.2Kbps • HSDPA • HSUPA
Antenna Type	WWAN: PIFA Antenna
HW Version	C
SW Version	V2.2.5
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF average output power among production units

Mode	GSM 850	GSM 1900
	Average power(dBm)	
GPRS (GMSK, 1 Tx slot)	31.0	29.5
GPRS (GMSK, 2 Tx slots)	31.5	29.5
EDGE (8PSK, 1 Tx slot)	26.0	25.5
EDGE (8PSK, 2 Tx slots)	26.0	25.5

Mode	WCDMA Band V	WCDMA Band II
	average power(dBm)	
RMC 12.2Kbps	23.5	21.5
HSDPA Subtest-1	23.5	21.5
HSDPA Subtest-2	22.5	21.5
HSDPA Subtest-3	22.5	21.0
HSDPA Subtest-4	22.0	21.0
HSUPA Subtest-1	22.5	21.0
HSUPA Subtest-2	20.5	19.0
HSUPA Subtest-3	21.5	20.5
HSUPA Subtest-4	20.5	19.5
HSUPA Subtest-5	22.5	21.5

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
GPRS 850 (1 Tx slot)	824.2	0.86	31.0	31.86	1.53	193.20	0.04	0.55
GPRS 850 (2 Tx slots)	824.2	0.86	31.5	32.36	1.72	432.51	0.09	0.55
EGPRS 850 (1 Tx slot)	824.2	0.86	26.0	26.86	0.49	61.09	0.01	0.55
EGPRS 850 (2 Tx slots)	824.2	0.86	26.0	26.86	0.49	121.90	0.02	0.55
GPRS 1900 (1 Tx slot)	1850.2	1.32	29.5	30.82	1.21	152.05	0.03	1.00
GPRS 1900 (2 Tx slots)	1850.2	1.32	29.5	30.82	1.21	303.39	0.06	1.00
EGPRS 1900 (1 Tx slot)	1850.2	1.32	25.5	26.82	0.48	60.53	0.01	1.00
EGPRS 1900 (2 Tx slots)	1850.2	1.32	25.5	26.82	0.48	120.78	0.02	1.00
WCDMA Band V	826.4	0.86	23.5	24.36	0.27	272.90	0.05	0.55
WCDMA Band II	1852.4	1.32	21.5	22.82	0.19	191.43	0.04	1.00

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.