



FCC Part 15E Test Report

FCC ID: 2BBO6-Q3MAX

Applicant: XiXi Technology (Shenzhen) CO, Ltd

Address: 5 / F, Building 2, Watsi Science Park, Datang Road, Guanlan, Longhua District, Shenzhen

Manufacturer: XiXi Technology (Shenzhen) CO, Ltd

Address: 5 / F, Building 2, Watsi Science Park, Datang Road, Guanlan, Longhua District, Shenzhen

EUT: repeater

Trade Mark: N/A

Model Number: q3max

Date of Receipt: Aug. 02, 2024

Test Date: Aug. 02, 2024 - Aug. 29, 2024

Date of Report: Aug. 29, 2024

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 E 15.407
ANSI C63.10:2013
KDB 662911 D01 Multiple Transmitter Output v02r01

Test Result: Pass

Report Number: DL-240802027ER

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3 . EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	10
3.1.2 TEST PROCEDURE	10
3.1.3 DEVIATION FROM TEST STANDARD	10
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	15
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8 TEST RESULTS (1GHZ~40GHZ)	21
3.3 RADIATED BAND EMISSION MEASUREMENT	26
3.3.1 TEST REQUIREMENT:	26
3.3.2 TEST PROCEDURE	26
3.3.3 DEVIATION FROM TEST STANDARD	26
3.3.4 TEST SETUP	26
3.3.5 EUT OPERATING CONDITIONS	26
4 . PEAK OUTPUT POWER	29
4.1 APPLIED PROCEDURES / LIMIT	29
4.1.1 TEST PROCEDURE	29
4.1.2 DEVIATION FROM STANDARD	29



Table of Contents	Page
4.1.3 TEST SETUP	29
4.1.4 EUT OPERATION CONDITIONS	29
4.1.5 TEST RESULTS	30
5 . POWER SPECTRAL DENSITY TEST	38
5.1 APPLIED PROCEDURES / LIMIT	38
5.1.1 TEST PROCEDURE	38
5.1.2 DEVIATION FROM STANDARD	38
5.1.3 TEST SETUP	38
5.1.4 EUT OPERATION CONDITIONS	38
5.1.5 TEST RESULTS	39
6 . 6DB BANDWIDTH TEST	47
6.1 APPLIED PROCEDURES / LIMIT	47
6.1.1 TEST PROCEDURE	47
6.1.2 DEVIATION FROM STANDARD	47
6.1.3 TEST SETUP	47
6.1.4 EUT OPERATION CONDITIONS	47
6.1.5 TEST RESULTS	48
7 . DUTY CYCLE TEST SIGNAL	55
7.1 APPLIED PROCEDURES / LIMIT	55
7.1.1 TEST PROCEDURE	55
7.1.2 DEVIATION FROM STANDARD	55
7.1.3 TEST SETUP	55
7.1.4 EUT OPERATION CONDITIONS	55
7.1.5 TEST RESULTS	56
8 . FREQUENCY STABILITY	59
8.1 APPLIED PROCEDURES / LIMIT	59
8.1.1 TEST PROCEDURE	59
8.1.2 DEVIATION FROM STANDARD	59
8.1.3 TEST SETUP	59
8.1.4 EUT OPERATION CONDITIONS	59
8.1.5 TEST RESULTS	60
9 . TRANSMISSION IN THE ABSENCE OF DATA	62
9.1 STANDARD REQUIREMENT	62
9.2 TEST RESULT	62
10 . ANTENNA REQUIREMENT	62
10.1 STANDARD REQUIREMENT	62
10.2 EUT ANTENNA	62



Table of Contents	Page
11 . TEST SEUUP PHOTO	61
12 . EUT PHOTO	61



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Peak Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(e)	6dB bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) Test Facility: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	6dB Bandwidth	$\pm 0.2\text{MHz}$
9	PSD	$\pm 0.69\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	repeater
Trademark	N/A
Model No.:	q3max
Model Difference	N/A
Operation Frequency:	5745-5825MHz(802.11a/n/ac(HT20)) 5755-5795MHz(802.11n/ac(HT40)) 5775MHz (802.11ac(HT80))
Channel numbers:	See channel list
Channel separation:	20MHz/40MHz/80MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: Up to 500Mbps
Antenna Type:	External antenna
Antenna gain:	2.72dBi Both antennas have the same gain
Power Supply:	100-240V~ 50/60Hz
Note:	The MIMO mode only support external External antenna3 and External antenna4 the 802.11n/ac mode, the Directional Gain=2.72dBi+10log(2)=5.73dBi.

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	/	/

2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted Emission		
Pretest Mode	Channel	Band 4
Mode 1	802.11a/n/acHT20	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH151, CH159
Mode 3	802.11acHT80	CH155
Mode 4	Link Mode	
Mode 5	MIMO Mode	


For Radiated Emission		
Pretest Mode	Channel	Band 4
Mode 1	802.11a/n/acHT20	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH151, CH159
Mode 3	802.11acHT80	CH155
Mode 4	Link Mode	
Mode 5	MIMO Mode	

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power Line Conducted Emission Test



2.3 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	repeater	q3max	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: WLAN Meter 2.8.8.81			
Mode	802.11a	802.11n HT20	802.11n HT40	802.11ac HT20/HT40/HT80
Data Rate	6Mbps	MSC0	MSC0	MSC0
Power Setting of Softwave	60	60	66	66

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 04, 2023	Nov. 03, 2024
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 04, 2023	Nov. 03, 2024
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 04, 2023	Nov. 03, 2024
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 04, 2023	Nov. 03, 2024
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 04, 2023	Nov. 03, 2024
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 04, 2023	Nov. 03, 2024
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 04, 2023	Nov. 03, 2024
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 04, 2023	Nov. 03, 2024
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 04, 2023	Nov. 03, 2024
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 04, 2023	Nov. 03, 2024
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 04, 2023	Nov. 03, 2024
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 04, 2023	Nov. 03, 2024
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 04, 2023	Nov. 03, 2024
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 04, 2023	Nov. 03, 2024
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 04, 2023	Nov. 03, 2024
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 04, 2023	Nov. 03, 2024

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 06, 2023	Nov. 05, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 04, 2023	Nov. 03, 2024
3	LISN	R&S	ENV216	102417	Nov. 04, 2023	Nov. 03, 2024
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 04, 2023	Nov. 03, 2024

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2354	30.04	10.13	40.17	62.26	-22.09	QP	P	
2	0.2354	7.75	10.13	17.88	52.26	-34.38	AVG	P	
3 *	0.5820	26.76	10.14	36.90	56.00	-19.10	QP	P	
4	0.5820	9.58	10.14	19.72	46.00	-26.28	AVG	P	
5	1.1130	19.72	10.04	29.76	56.00	-26.24	QP	P	
6	1.1130	-1.70	10.04	8.34	46.00	-37.66	AVG	P	
7	2.0445	16.73	10.06	26.79	56.00	-29.21	QP	P	
8	2.0445	-3.92	10.06	6.14	46.00	-39.86	AVG	P	
9	6.0810	12.22	10.60	22.82	60.00	-37.18	QP	P	
10	6.0810	-5.42	10.60	5.18	50.00	-44.82	AVG	P	
11	12.0030	10.73	11.42	22.15	60.00	-37.85	QP	P	
12	12.0030	-3.11	11.42	8.31	50.00	-41.69	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	34.26	10.14	44.40	65.28	-20.88	QP	P	
2	0.1635	9.61	10.14	19.75	55.28	-35.53	AVG	P	
3 *	0.5595	27.93	10.16	38.09	56.00	-17.91	QP	P	
4	0.5595	12.81	10.16	22.97	46.00	-23.03	AVG	P	
5	0.9870	20.52	10.11	30.63	56.00	-25.37	QP	P	
6	0.9870	0.21	10.11	10.32	46.00	-35.68	AVG	P	
7	1.5180	18.95	10.08	29.03	56.00	-26.97	QP	P	
8	1.5180	-0.02	10.08	10.06	46.00	-35.94	AVG	P	
9	4.5870	16.68	10.24	26.92	56.00	-29.08	QP	P	
10	4.5870	-1.12	10.24	9.12	46.00	-36.88	AVG	P	
11	21.4935	10.85	12.11	22.96	60.00	-37.04	QP	P	
12	21.4935	-6.87	12.11	5.24	50.00	-44.76	AVG	P	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

15.407(b) Undesirable emission limits. Except as shown in paragraph (b) (10) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850GHz band:
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		57.7962	26.48	-13.53	12.95	40.00	-27.05	QP
2		237.4760	29.92	-13.52	16.40	46.00	-29.60	QP
3		357.9287	49.29	-10.43	38.86	46.00	-7.14	QP
4		473.8347	42.25	-7.94	34.31	46.00	-11.69	QP
5		721.7259	39.65	-3.83	35.82	46.00	-10.18	QP
6	*	774.1584	44.27	-2.57	41.70	46.00	-4.30	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		193.0944	42.20	-15.39	26.81	43.50	-16.69	QP
2		332.5187	39.87	-11.16	28.71	46.00	-17.29	QP
3		455.9058	43.07	-8.08	34.99	46.00	-11.01	QP
4	*	580.7026	44.16	-5.71	38.45	46.00	-7.55	QP
5		677.5798	35.80	-4.51	31.29	46.00	-14.71	QP
6		774.1584	33.54	-2.57	30.97	46.00	-15.03	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



3.2.8 TEST RESULTS (1ghz~40ghZ)

802.11a band 4

We test all antenna's data, the data only show the antenna3 mode 1 worst mode.

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	54.25	49.05	15.3	37.39	57.89	74	-16.11	PK
V	11490	41.14	49.05	15.3	37.39	44.78	54	-9.22	AV
V	17235	55.99	49.16	15.27	40.45	62.55	68.2	-5.65	PK
V	17235	40.92	49.16	15.27	40.45	47.48	54	-6.52	AV
H	11490	52.11	49.05	15.3	37.39	55.75	74	-18.25	PK
H	11490	42.89	49.05	15.3	37.39	46.53	54	-7.47	AV
H	17235	51.35	49.16	15.27	40.45	57.91	68.2	-10.29	PK
H	17235	40.13	49.16	15.27	40.45	46.69	54	-7.31	AV
operation frequency:5785									
V	11570	51.91	49.09	15.34	37.42	55.58	74	-18.42	PK
V	11570	41.89	49.09	15.34	37.42	45.56	54	-8.44	AV
V	17355	50.15	49.18	15.29	40.47	56.73	68.2	-11.47	PK
V	17355	40.25	49.18	15.29	40.47	46.83	54	-7.17	AV
H	11570	50.73	49.09	15.34	37.42	54.4	74	-19.60	PK
H	11570	42.04	49.09	15.34	37.42	45.71	54	-8.29	AV
H	17355	48.39	49.18	15.29	40.47	54.97	68.2	-13.23	PK
H	17355	40.95	49.18	15.29	40.47	47.53	54	-6.47	AV
operation frequency:5825									
V	11650	52.31	49.11	15.37	37.46	56.03	74	-17.97	PK
V	11650	41.88	49.11	15.37	37.46	45.6	54	-8.40	AV
V	17475	49.56	49.21	15.34	40.51	56.2	68.2	-12.00	PK
V	17475	40.14	49.21	15.34	40.51	46.78	54	-7.22	AV
H	11650	57.63	49.11	15.37	31.31	55.2	74	-18.80	PK
H	11650	48.85	49.11	15.37	31.31	46.42	54	-7.58	AV
H	17475	49.24	49.21	15.34	40.51	55.88	68.2	-12.32	PK
H	17475	40.33	49.21	15.34	40.51	46.97	54	-7.03	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

We test all antenna's data, the data only show the mode 5 worst mode.

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	49.44	49.05	15.3	37.39	53.08	74	-20.92	PK
V	11490	42.95	49.05	15.3	37.39	46.59	54	-7.41	AV
V	17235	48.31	49.16	15.27	40.45	54.87	68.2	-13.33	PK
V	17235	40.45	49.16	15.27	40.45	47.01	54	-6.99	AV
H	11490	49.36	49.05	15.3	37.39	53	74	-21.00	PK
H	11490	41.25	49.05	15.3	37.39	44.89	54	-9.11	AV
H	17235	48.14	49.16	15.27	40.45	54.7	68.2	-13.50	PK
H	17235	40.43	49.16	15.27	40.45	46.99	54	-7.01	AV
operation frequency:5785									
V	11570	52.48	49.09	15.34	37.42	56.15	74	-17.85	PK
V	11570	42.64	49.09	15.34	37.42	46.31	54	-7.69	AV
V	17355	49.36	49.18	15.29	40.47	55.94	68.2	-12.26	PK
V	17355	40.35	49.18	15.29	40.47	46.93	54	-7.07	AV
H	11570	49.99	49.09	15.34	37.42	53.66	74	-20.34	PK
H	11570	43.94	49.09	15.34	37.42	47.61	54	-6.39	AV
H	17355	49.14	49.18	15.29	40.47	55.72	68.2	-12.48	PK
H	17355	40.36	49.18	15.29	40.47	46.94	54	-7.06	AV
operation frequency:5825									
V	11650	51.14	49.11	15.37	37.46	54.86	74	-19.14	PK
V	11650	41.39	49.11	15.37	37.46	45.11	54	-8.89	AV
V	17475	48.25	49.21	15.34	40.51	54.89	68.2	-13.31	PK
V	17475	40.16	49.21	15.34	40.51	46.8	54	-7.20	AV
H	11650	57.87	49.11	15.37	31.31	55.44	74	-18.56	PK
H	11650	44.66	49.11	15.37	31.31	42.23	54	-11.77	AV
H	17475	49.34	49.21	15.34	40.51	55.98	68.2	-12.22	PK
H	17475	40.28	49.21	15.34	40.51	46.92	54	-7.08	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

We test all antenna's data, the data only show the mode 5 worst mode.

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	49.36	49.07	15.33	37.41	53.03	74	-20.97	PK
V	11510	41.27	49.07	15.33	37.41	44.94	54	-9.06	AV
V	17265	49.64	49.17	15.28	40.46	56.21	68.2	-11.99	PK
V	17265	40.79	49.17	15.28	40.46	47.36	54	-6.64	AV
H	11510	48.64	49.07	15.33	37.41	52.31	74	-21.69	PK
H	11510	41.13	49.07	15.33	37.41	44.8	54	-9.20	AV
H	17265	49.64	49.17	15.28	40.46	56.21	68.2	-11.99	PK
H	17265	40.43	49.17	15.28	40.46	47	54	-7.00	AV
operation frequency:5795									
V	11590	49.24	49.11	15.37	37.46	52.96	74	-21.04	PK
V	11590	41.28	49.11	15.37	37.46	45	54	-9.00	AV
V	17385	48.29	49.21	15.34	40.51	54.93	68.2	-13.27	PK
V	17385	40.45	49.21	15.34	40.51	47.09	54	-6.91	AV
H	11590	57.53	49.11	15.37	31.31	55.1	74	-18.90	PK
H	11590	44.14	49.11	15.37	31.31	41.71	54	-12.29	AV
H	17385	48.63	49.21	15.34	40.51	55.27	68.2	-12.93	PK
H	17385	40.87	49.21	15.34	40.51	47.51	54	-6.49	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT20

We test all antenna's data, the data only show the mode 5 worst mode.

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	49.63	49.05	15.3	37.39	53.27	74	-20.73	PK
V	11490	42.24	49.05	15.3	37.39	45.88	54	-8.12	AV
V	17235	48.14	49.16	15.27	40.45	54.7	68.2	-13.50	PK
V	17235	40.33	49.16	15.27	40.45	46.89	54	-7.11	AV
H	11490	48.96	49.05	15.3	37.39	52.6	74	-21.40	PK
H	11490	41.14	49.05	15.3	37.39	44.78	54	-9.22	AV
H	17235	48.63	49.16	15.27	40.45	55.19	68.2	-13.01	PK
H	17235	40.25	49.16	15.27	40.45	46.81	54	-7.19	AV
operation frequency:5785									
V	11570	48.63	49.09	15.34	37.42	52.3	74	-21.70	PK
V	11570	41.89	49.09	15.34	37.42	45.56	54	-8.44	AV
V	17355	49.41	49.18	15.29	40.47	55.99	68.2	-12.21	PK
V	17355	40.53	49.18	15.29	40.47	47.11	54	-6.89	AV
H	11570	49.55	49.09	15.34	37.42	53.22	74	-20.78	PK
H	11570	43.14	49.09	15.34	37.42	46.81	54	-7.19	AV
H	17355	49.13	49.18	15.29	40.47	55.71	68.2	-12.49	PK
H	17355	40.85	49.18	15.29	40.47	47.43	54	-6.57	AV
operation frequency:5825									
V	11650	49.36	49.11	15.37	37.46	53.08	74	-20.92	PK
V	11650	41.44	49.11	15.37	37.46	45.16	54	-8.84	AV
V	17475	48.96	49.21	15.34	40.51	55.6	68.2	-12.60	PK
V	17475	40.11	49.21	15.34	40.51	46.75	54	-7.25	AV
H	11650	57.96	49.11	15.37	31.31	55.53	74	-18.47	PK
H	11650	44.52	49.11	15.37	31.31	42.09	54	-11.91	AV
H	17475	48.53	49.21	15.34	40.51	55.17	68.2	-13.03	PK
H	17475	40.58	49.21	15.34	40.51	47.22	54	-6.78	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT40

We test all antenna's data, the data only show the mode 5 worst mode.

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	49.13	49.07	15.33	37.41	52.8	74	-21.20	PK
V	11510	42.59	49.07	15.33	37.41	46.26	54	-7.74	AV
V	17265	48.34	49.17	15.28	40.46	54.91	68.2	-13.29	PK
V	17265	41.63	49.17	15.28	40.46	48.2	54	-5.80	AV
H	11510	48.77	49.07	15.33	37.41	52.44	74	-21.56	PK
H	11510	42.84	49.07	15.33	37.41	46.51	54	-7.49	AV
H	17265	48.36	49.17	15.28	40.46	54.93	68.2	-13.27	PK
H	17265	40.87	49.17	15.28	40.46	47.44	54	-6.56	AV
operation frequency:5795									
V	11590	49.46	49.11	15.37	37.46	53.18	74	-20.82	PK
V	11590	41.38	49.11	15.37	37.46	45.1	54	-8.90	AV
V	17385	48.36	49.21	15.34	40.51	55	68.2	-13.20	PK
V	17385	40.14	49.21	15.34	40.51	46.78	54	-7.22	AV
H	11590	57.36	49.11	15.37	31.31	54.93	74	-19.07	PK
H	11590	44.63	49.11	15.37	31.31	42.2	54	-11.80	AV
H	17385	48.92	49.21	15.34	40.51	55.56	68.2	-12.64	PK
H	17385	40.24	49.21	15.34	40.51	46.88	54	-7.12	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

We test all antenna's data, the data only show the mode 5 worst mode.

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5775									
V	11550	48.36	49.07	15.33	37.41	52.03	74	-21.97	PK
V	11550	42.78	49.07	15.33	37.41	46.45	54	-7.55	AV
V	17325	49.54	49.17	15.28	40.46	56.11	68.2	-12.09	PK
V	17325	40.96	49.17	15.28	40.46	47.53	54	-6.47	AV
H	11550	48.54	49.07	15.33	37.41	52.21	74	-21.79	PK
H	11550	41.88	49.07	15.33	37.41	45.55	54	-8.45	AV
H	17325	48.93	49.17	15.28	40.46	55.5	68.2	-12.70	PK
H	17325	40.96	49.17	15.28	40.46	47.53	54	-6.47	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 CONDUCTED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average	


3.3.2 TEST PROCEDURE

Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



3.3.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT



Each antenna has been tested and has a margin of more than 3 dB, the data only show the antenna3 worst mode, so the MIMO mode is definitely Pass.

802.11a




5745MHz



5825MHz

802.11n HT20



5745MHz



5825MHz

802.11n HT40




5755MHz



5795MHz



802.11ac HT20



5745MHz



5825MHz

802.11ac HT40



5755MHz



5795MHz

802.11ac HT80



5775MHz



4. AVERAGING OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.


4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW = 1MHz
Span $\geq$ 99%OBW(30MHz/60MHz/120MHz etc.)
VBW $\geq$ 3*RBW
Sweep = auto
Detector function = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
Trace = max hold

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**4.1.5 TEST RESULTS**

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz

Antenna3

Mode	Test Channel	Peak Output Power (dBm)	Duty factor (dB)	Total Output Power(dBm)	LIMIT (dBm)
802.11a	Low	8.635	1.08	9.715	30
	Middle	8.145	1.08	9.225	30
	High	8.895	1.08	9.975	30
802.11n HT20	Low	9.236	0.13	9.366	30
	Middle	8.844	0.13	8.974	30
	High	9.633	0.13	9.763	30
802.11n HT40	Low	8.979	0.26	9.239	30
	High	8.586	0.26	8.846	30
802.11ac HT20	Low	9.279	0.13	9.409	30
	Middle	8.964	0.13	9.094	30
	High	9.861	0.13	9.991	30
802.11ac HT40	Low	9.148	0.26	9.408	30
	High	8.657	0.26	8.917	30
802.11ac HT80	/	8.835	0.5	9.335	30

Antenna4

Mode	Test Channel	Peak Output Power (dBm)	Duty factor (dB)	Total Output Power(dBm)	LIMIT (dBm)
802.11a	Low	8.615	0.87	9.485	30
	Middle	8.151	0.87	9.021	30
	High	8.894	0.87	9.764	30
802.11n HT20	Low	9.233	0.13	9.363	30
	Middle	8.923	0.13	9.053	30
	High	9.591	0.13	9.721	30
802.11n HT40	Low	8.958	0.26	9.218	30
	High	8.638	0.26	8.898	30
802.11ac HT20	Low	9.243	0.13	9.373	30
	Middle	8.954	0.13	9.084	30
	High	9.78	0.13	9.91	30
802.11ac HT40	Low	9.135	0.26	9.395	30
	High	8.637	0.26	8.897	30
802.11ac HT80	/	8.844	0.5	9.344	30




For MIMO

Mode	Test Channel	Antenna	Total Output Power(dBm)	Limit (dBm)	Result
802.11n20	Low	Antenna3+ Antenna4	12.37	30.00	PASS
	Middle		12.02	30.00	PASS
	High		12.75	30.00	PASS
802.11n40	Low		12.24	30.00	PASS
	High		11.88	30.00	PASS
802.11ac HT20	Low		12.40	30.00	PASS
	Middle		12.10	30.00	PASS
	High		12.96	30.00	PASS
802.11ac HT40	Low		12.41	30.00	PASS
	High		11.92	30.00	PASS
802.11ac HT80	/		12.35	30.00	PASS




Antenna3


802.11a




802.11n HT20



5745MHz




5745MHz



5785MHz



5785MHz



5825MHz

5825MHz




802.11n HT40




802.11ac HT20



5755MHz



5745MHz



5795MHz




5785MHz



5825MHz




802.11ac HT40



802.11ac HT80



5755MHz




5775MHz

5795MHz




Antenna4

802.11a




802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz




802.11n HT40




802.11ac HT20



5755MHz



5745MHz



5795MHz




5785MHz



5825MHz




802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 1MHz for band 1 RBW $\geq$ 510KHz for band 4
VB	VBW $\geq$ 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).
we test all antennas, the antenna 1 was worst mode and the data recording in the report.
7. Duty factor Reference is made to the test results in Section 7.1.5.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

Antenna3

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
Band4	802.11a	Low	-3.954	1.08	-2.874	30.00	PASS
		Middle	-3.865	1.08	-2.785	30.00	PASS
		High	-3.033	1.08	-1.953	30.00	PASS
	802.11n20	Low	-3.36	0.13	-3.23	30.00	PASS
		Middle	-3.689	0.13	-3.559	30.00	PASS
		High	-2.92	0.13	-2.79	30.00	PASS
	802.11n40	Low	-6.989	0.26	-6.729	30.00	PASS
		High	-7.953	0.26	-7.693	30.00	PASS
	802.11ac20	Low	-3.363	0.13	-3.233	30.00	PASS
		Middle	-3.87	0.13	-3.74	30.00	PASS
		High	-2.707	0.13	-2.577	30.00	PASS
	802.11ac40	Low	-6.892	0.26	-6.632	30.00	PASS
		High	-7.617	0.26	-7.357	30.00	PASS
	802.11ac80	/	-9.181	0.5	-8.681	30.00	PASS

Antenna4

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
Band4	802.11a	Low	-3.501	0.87	-2.631	30.00	PASS
		Middle	-4.39	0.87	-3.52	30.00	PASS
		High	-3.034	0.87	-2.164	30.00	PASS
	802.11n20	Low	-3.512	0.13	-3.382	30.00	PASS
		Middle	-3.588	0.13	-3.458	30.00	PASS
		High	-2.832	0.13	-2.702	30.00	PASS
	802.11n40	Low	-7.3	0.26	-7.04	30.00	PASS
		High	-7.463	0.26	-7.203	30.00	PASS
	802.11ac20	Low	-3.68	0.13	-3.55	30.00	PASS
		Middle	-3.651	0.13	-3.521	30.00	PASS
		High	-2.849	0.13	-2.719	30.00	PASS
	802.11ac40	Low	-7.355	0.26	-7.095	30.00	PASS
		High	-7.513	0.26	-7.253	30.00	PASS
	802.11ac80	/	-9.093	0.5	-8.593	30.00	PASS




For MIMO

Mode	Test Channel	Antenna	PSD (dBm/ 500kHz)	Limit (dBm/ 500kHz)	Result
802.11n20	Low	Antenna3+ Antenna4	-0.30	30.00	PASS
	Middle		-0.50	30.00	PASS
	High		0.26	30.00	PASS
802.11n40	Low		-3.87	30.00	PASS
	High		-4.43	30.00	PASS
802.11ac20	Low		-0.38	30.00	PASS
	Middle		-0.62	30.00	PASS
	High		0.36	30.00	PASS
802.11ac40	Low		-3.85	30.00	PASS
	High		-4.29	30.00	PASS
802.11ac80	/		-5.63	30.00	PASS




Antenna3





802.11n HT40 	802.11ac HT20 
5755MHz 	5745MHz 
5795MHz 	5785MHz 
	5825MHz





Antenna4

802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz




5785MHz




5825MHz

5825MHz



802.11n HT40 	802.11ac HT20 
5755MHz 	5745MHz 
5795MHz 	5785MHz 
	5825MHz





6. 6DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

There is no limit bandwidth for U-NII-1, U-NII-2-A and U-NII-2-C.

The minimum of 6dB Bandwidth measurement is 0.5 MHz for U-NII-3

6.1.1 TEST PROCEDURE

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**6.1.5 TEST RESULTS**

		Test Channel	6dB Bandwidth (MHz)		6dB Bandwidth Limit (MHz)	Result
			Antenna3	Antenna4		
Band 4	802.11a	Low	15.738	16.291	>0.5	Pass
		Middle	15.711	15.759	>0.5	Pass
		High	15.37	16.307	>0.5	Pass
	802.11n HT20	Low	16.023	15.658	>0.5	Pass
		Middle	16.644	16.327	>0.5	Pass
		High	15.657	15.432	>0.5	Pass
	802.11n HT40	Low	35.446	35.386	>0.5	Pass
		High	35.782	35.444	>0.5	Pass
	802.11ac HT20	Low	16.28	16.519	>0.5	Pass
		Middle	16.331	16.161	>0.5	Pass
		High	15.424	14.946	>0.5	Pass
	802.11ac HT40	Low	35.464	35.426	>0.5	Pass
		High	35.501	35.895	>0.5	Pass
	802.11ac HT80	/	75.115	75.076	>0.5	Pass



Antenna3

802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz


5825MHz



802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz





5785MHz



5825MHz



802.11ac HT40  Center Freq 5.755000000 GHz Center Freq: 5.755000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 100/100 Radio Device: BTS Ref Offset 8.39 dB Ref 28.39 dBm Mkr3 5.772696 GHz -11.592 dBm Center 5.755 GHz #Res BW 100 kHz #VBW 300 kHz Span 60 MHz Sweep 6 ms Occupied Bandwidth 35.987 MHz Total Power 15.4 dBm Transmit Freq Error -35.548 kHz % of OBW Power 99.00 % x dB Bandwidth 35.46 MHz x dB -6.00 dB	802.11ac HT80  Center Freq 5.775000000 GHz Center Freq: 5.775000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 100/100 Radio Device: BTS Ref Offset 8.41 dB Ref 28.41 dBm Mkr3 5.812465 GHz -10.866 dBm Center 5.775 GHz #Res BW 100 kHz #VBW 300 kHz Span 120 MHz Sweep 12 ms Occupied Bandwidth 75.433 MHz Total Power 15.4 dBm Transmit Freq Error -92.689 kHz % of OBW Power 99.00 % x dB Bandwidth 75.12 MHz x dB -6.00 dB
5755MHz  Center Freq 5.795000000 GHz Center Freq: 5.795000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 100/100 Radio Device: BTS Ref Offset 8.48 dB Ref 28.48 dBm Mkr3 5.812708 GHz -12.388 dBm Center 5.795 GHz #Res BW 100 kHz #VBW 300 kHz Span 60 MHz Sweep 6 ms Occupied Bandwidth 36.030 MHz Total Power 14.9 dBm Transmit Freq Error -42.758 kHz % of OBW Power 99.00 % x dB Bandwidth 35.50 MHz x dB -6.00 dB	5775MHz  Center Freq 5.795000000 GHz Center Freq: 5.795000000 GHz Radio Std: None Trig: Free Run Avg/Hold: 100/100 Radio Device: BTS Ref Offset 8.48 dB Ref 28.48 dBm Mkr3 5.812708 GHz -12.388 dBm Center 5.795 GHz #Res BW 100 kHz #VBW 300 kHz Span 60 MHz Sweep 6 ms Occupied Bandwidth 36.030 MHz Total Power 14.9 dBm Transmit Freq Error -42.758 kHz % of OBW Power 99.00 % x dB Bandwidth 35.50 MHz x dB -6.00 dB
5795MHz	



Antenna4

802.11a



802.11n HT20




5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz




802.11n HT40



802.11ac HT20



5755MHz



5745MHz





5795MHz



5785MHz

5825MHz



802.11ac HT40  Center Freq 5.755000000 GHz Center Freq: 5.755000000 GHz Radio Std: None Ref Offset 8.39 dB Ref 28.39 dBm Mkr3 5.772674 GHz -12.183 dBm Center 5.755 GHz #Res BW 100 kHz #VBW 300 kHz Span 60 MHz Sweep 6 ms Occupied Bandwidth 36.033 MHz Total Power 15.4 dBm Transmit Freq Error -38.536 kHz % of OBW Power 99.00 % x dB Bandwidth 35.43 MHz x dB -6.00 dB	802.11ac HT80  Center Freq 5.775000000 GHz Center Freq: 5.775000000 GHz Radio Std: None Ref Offset 8.41 dB Ref 28.41 dBm Mkr3 5.812435 GHz -11.253 dBm Center 5.775 GHz #Res BW 100 kHz #VBW 300 kHz Span 120 MHz Sweep 12 ms Occupied Bandwidth 75.408 MHz Total Power 15.5 dBm Transmit Freq Error -102.68 kHz % of OBW Power 99.00 % x dB Bandwidth 75.08 MHz x dB -6.00 dB
5755MHz  Center Freq 5.795000000 GHz Center Freq: 5.795000000 GHz Radio Std: None Ref Offset 8.48 dB Ref 28.48 dBm Mkr3 5.812924 GHz -13.792 dBm Center 5.795 GHz #Res BW 100 kHz #VBW 300 kHz Span 60 MHz Sweep 6 ms Occupied Bandwidth 36.060 MHz Total Power 14.8 dBm Transmit Freq Error -23.424 kHz % of OBW Power 99.00 % x dB Bandwidth 35.90 MHz x dB -6.00 dB	5775MHz 
5795MHz	



7. DUTY CYCLE TEST SIGNAL

7.1 APPLIED PROCEDURES / LIMIT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

7.1.1 TEST PROCEDURE

1. Set RBW = 1 MHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Sweep = auto couple.
5. Allow the trace to stabilize.
6. Span=0

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.1.5 TEST RESULTS

Antenna3

Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 4	802.11a	78.26	1.06
	802.11n(HT20)	97.01	0.13
	802.11n(HT40)	94.2	0.26
	802.11ac(HT20)	97.06	0.13
	802.11ac(HT40)	94.2	0.26
	802.11ac(HT80)	89.19	0.5


Antenna4

Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 4	802.11a	81.82	0.87
	802.11n(HT20)	97.04	0.13
	802.11n(HT40)	94.2	0.26
	802.11ac(HT20)	97.04	0.13
	802.11ac(HT40)	94.29	0.26
	802.11ac(HT80)	89.19	0.5




Antenna3


802.11a




802.11n HT20




802.11n HT40




802.11ac HT20



802.11ac HT40




802.11ac HT80






Antenna4


802.11a




802.11n HT20




802.11n HT40




802.11ac HT20



802.11ac HT40



802.11ac HT80





8. FREQUENCY STABILITY

8.1 APPLIED PROCEDURES / LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


8.1.1 TEST PROCEDURE

1. The EUT was placed inside temperature chamber and powered and powered by nominal DC voltage.
2. Set EUT as normal operation.
3. Turn the EUT on and couple its output to spectrum.
4. Turn the EUT off and set the chamber to the highest temperature specified.
5. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT and measure the operating frequency.
6. Repeat step with the temperature chamber set to the lowest temperature.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.5 TEST RESULTS

We test all antenna's data, the data only show the antenna3 worst mode.

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)			Δ Frequency (MHz)		
			802.11a	802.11n HT20	802.11ac HT20	802.11a	802.11n HT20	802.11ac HT20
132V	-20℃	5745	5745.0335	5745.0356	5745.0366	-0.0335	-0.0356	-0.0366
		5785	5785.0354	5785.0328	5785.0338	-0.0354	-0.0328	-0.0338
		5825	5825.0328	5825.0364	5825.0323	-0.0328	-0.0364	-0.0323
108V		5745	5745.0233	5745.0276	5745.0257	-0.0233	-0.0276	-0.0257
		5785	5785.0374	5785.0363	5785.0334	-0.0374	-0.0363	-0.0334
		5825	5825.0445	5825.0448	5825.0422	-0.0445	-0.0448	-0.0422
120V	25℃	5745	5745.0332	5745.0324	5745.0327	-0.0332	-0.0324	-0.0327
		5785	5785.0427	5785.0415	5785.0454	-0.0427	-0.0415	-0.0454
		5825	5825.0266	5825.0236	5825.0236	-0.0266	-0.0236	-0.0236
132V	50℃	5745	5745.0674	5745.0677	5745.0653	-0.0674	-0.0677	-0.0653
		5785	5785.0431	5785.0454	5785.0485	-0.0431	-0.0454	-0.0485
		5825	5825.0646	5825.0665	5825.0634	-0.0646	-0.0665	-0.0634
108V	50℃	5745	5745.0464	5745.0426	5745.0452	-0.0464	-0.0426	-0.0452
		5785	5785.0213	5785.0268	5785.0267	-0.0213	-0.0268	-0.0267
		5825	5825.0754	5825.0754	5825.0774	-0.0754	-0.0754	-0.0774

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)		Δ Frequency (MHz)	
			802.11n HT40	802.11ac HT40	802.11n HT40	802.11ac HT40
132V	-20℃	5755	5755.0544	5755.0554	-0.0544	-0.0554
		5795	5795.0666	5795.0637	-0.0666	-0.0637
108V		5755	5755.0238	5755.0546	-0.0238	-0.0546
		5795	5795.0472	5795.0445	-0.0472	-0.0445
120V	25℃	5755	5755.0283	5755.0234	-0.0283	-0.0234
		5795	5795.0536	5795.0553	-0.0536	-0.0553
132V	50℃	5755	5755.0445	5755.0468	-0.0445	-0.0468
		5795	5795.0364	5795.0374	-0.0364	-0.0374
108V	50℃	5755	5755.0325	5755.0366	-0.0325	-0.0366
		5795	5795.0436	5795.0476	-0.0436	-0.0476



Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)	Δ Frequency (MHz)
			802.11ac HT80	802.11ac HT80
132V	-20°C	5775	5775.0158	-0.0158
108V		5775	5775.0376	-0.0376
120V	25°C	5775	5775.0434	-0.0434
132V	50°C	5775	5775.0243	-0.0243
108V	50°C	5775	5775.0567	-0.0567



9. TRANSMISSION IN THE ABSENCE OF DATA

9.1 STANDARD REQUIREMENT

According to §15.407(c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

9.2 TEST RESULT

No non-compliance noted:
Refer to the theory of operation.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is External antenna, It comply with the standard requirement.

11. TEST SEUUP PHOTO

Reference to the appendix I for details.

12. EUT PHOTO

Reference to the appendix II for details.

***** END OF REPORT *****