

MPE ESTIMATION

FCC ID: OYR-CFAC1200

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)		
300MHz1.5GHz	F/1500	30		
1.5GHz100GHz	1.0	30		

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm²)
2.4G WIFI	15.41	15±1(16)	39.811	3	2	0.01584
5.2G WIFI	16.09	16±1(17)	50.119	3	2	0.01994
5.8G WIFI	15.55	15±1(16)	39.811	3	2	0.01584

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2002280202-1E/2E/3E**, antenna gain=3dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01994mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

-----The End-----