

# FCC Radio Test Report

## FCC ID: RWO-RC30021203

This report concerns (check one): ☒ Original Grant ☐ Class II Change

**Project No.** : 1612C189  
**Equipment** : Gaming Mouse  
**Test Model** : RC30-021203  
**Applicant** : Razer Inc.  
**Address** : 201 3rd Street, Suite 900, San Francisco, CA 94103

**Date of Receipt** : Dec. 16, 2016  
**Date of Test** : Dec. 16, 2016 ~ Dec. 27, 2016  
**Issued Date** : Dec. 28, 2016  
**Tested by** : BTL Inc.

**Testing Engineer**

:

*Shawn Xiao*

(Shawn Xiao)

**Technical Manager**

:

*David Mao*

(David Mao)

**Authorized Signatory**

:

*Steven Lu*

(Steven Lu)

# B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
<b>1 . CERTIFICATION</b>	<b>6</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>7</b>
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
<b>3 . GENERAL INFORMATION</b>	<b>9</b>
3.1 DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.5 DESCRIPTION OF SUPPORT UNITS	12
<b>4 . EMC EMISSION TEST</b>	<b>13</b>
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.1.6 EUT TEST CONDITIONS	14
4.1.7 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	15
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	19
4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)	19
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	20
<b>5 . BANDWIDTH TEST</b>	<b>21</b>
5.1 TEST PROCEDURE	21
5.2 DEVIATION FROM STANDARD	21
5.3 TEST SETUP	21
5.4 EUT OPERATION CONDITIONS	21
5.5 EUT TEST CONDITIONS	21
5.6 TEST RESULTS	21
<b>6 . MEASUREMENT INSTRUMENTS LIST</b>	<b>22</b>
<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>23</b>

## Table of Contents

## Page

<b>ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)</b>	<b>26</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>31</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>38</b>
<b>ATTACHMENT E - BANDWIDTH</b>	<b>51</b>

## REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-2-1612C189	Original Issue.	Dec. 28, 2016

## 1. CERTIFICATION

Equipment : Gaming Mouse  
Brand Name : RAZER  
Model Name : RC30-021203  
Applicant : Razer Inc.  
Manufacturer : Razer (Asia-Pacific) Pte.,Ltd.  
Address : 514 Chai Chee Lane #07-01 ~ 06 Singapore 469029  
Factory : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD  
Address : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park Keji  
South Road, Hi-Tech Industrial Park, Shenzhen 518057, China  
Date of Test : Dec. 16, 2016 ~ Dec. 27, 2016  
Test Sample : Engineering Sample  
Standard(s) : FCC Part15, Subpart C (15.249) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1612C189) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.249)			
Standard(s) Section	Test Item	Judgment	Remark
15.207(a)	Conducted Emission	PASS	
15.205	Restricted Band of Operation	PASS	
15.209 15.249(a)	Radiated Emissions	PASS	
15.215(c)	20dB Bandwidth Test	PASS	

NOTE:

(1)" N/A" denotes test is not applicable to this device.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

### A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	1.94

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.



### 3. GENERAL INFORMATION

#### 3.1 DESCRIPTION OF EUT

Equipment	Gaming Mouse	
Brand Name	RAZER	
Model Name	RC30-021203	
Model Difference	The system's model name is RZ01-0212, and the system is contain a Gaming Mouse (Model name: RC30-021203) and USB Dongle (Model name: DGRFG5).	
Product Description	Operation Frequency	2403-2479 MHz
	Modulation Technology	GFSK
	Bit Rate of Transmitter	2 Mbps
	Field Strength	97.16 dBuV/m (Peak Max) 91.00 dBuV/m (AVG Max)
Power Source	#1 Supplied from Lithium Polymer Battery. Model: PL343850 #2 Supplied from USB port for charging.	
EUT Power Rating	#1 DC 3.8V, 800mAh #2 DC 5V, 500mA	

**Note:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

## 2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453		
25	2427	52	2454		
26	2428	53	2455		
27	2429	54	2456		

## 3. Table for Filed Antenna

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	YAGEO	ANT5320LL24R 2400A	Chip	N/A	1.99

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:


For Conducted Test	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX Mode <b>NOTE (1)</b>

Note:

(1) The measurements are performed at the high, middle, low available channels.

### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	-

Note:

- (1) The support equipment was authorized by Declaration of Conformity (DOC).

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 23°C

Relative Humidity: 60%

Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “\*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) “N/A” denotes test is not applicable to this device.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (FCC 15.209 )

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

### LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.209 )

FREQUENCY (MHz)	(dBuV/m) (at 3m)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### LIMITS OF RADIATED EMISSION MEASUREMENT (FCC Part 15.249)

FCC Part15 (15.249) , Subpart C	
Limit	Frequency Range(MHz)
Field strength of fundamental 50000 $\mu$ V/m (94 dB $\mu$ V/m) @ 3 m	2400-2483.5
Field strength of harmonics 500 $\mu$ V/m (54 dB $\mu$ V/m) @ 3 m	Above 2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector



#### **4.2.2 TEST PROCEDURE**


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### **4.2.3 DEVIATION FROM TEST STANDARD**


No deviation

#### 4.2.4 TEST SETUP


##### (A) Radiated Emission Test Set-Up Frequency Below 1 GHz



##### (B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 60%

Test Voltage: DC 3.8V

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Attachment C.

Remark:

- (1) Measuring frequency range from 30MHz to 1000MHz.
- (2) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

#### 4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (2) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (3) EUT Orthogonal Axis:  
"X" - denotes Laid on Table, "Y" - denotes Vertical Stand, "Z" - denotes Side Stand
- (4) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (5) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. BANDWIDTH TEST


### 5.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

### 5.2 DEVIATION FROM STANDARD

No deviation.

### 5.3 TEST SETUP



### 5.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

### 5.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 60%  
Test Voltage: DC 3.8V

### 5.6 TEST RESULTS

Please refer to the Attachment E.

## 6. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 27, 2017
2	LISN	EMCO	3816/2	52765	Mar. 27, 2017
3	50Ω Terminator	SHX	TF2-3G-A	8122901	Mar. 27, 2017
4	TWO-LINE V-NETWORK	R&S	ENV216	101447	Mar. 27, 2017
5	Cable	emci	RG223(9KHz-30 MHz)(5m)	N/A	Mar. 10, 2017
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 27, 2017
2	Amplifier	HP	8447D	2944A09673	Oct. 20, 2017
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 04, 2017
4	Test Cable	emci	LMR-400(30MHz-1GHz)	C-01	Jun. 26, 2017
5	Controller	CT	SC100	N/A	N/A
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
7	Antenna	ETS	3115	00075789	Mar. 27, 2017
8	Amplifier	Agilent	8449B	3008A02274	Nov. 01, 2017
9	Test Cable	emci	EMC104-SM-S M-10000(1GHz-26.5GHz)	C-68	Jun. 26, 2017
10	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Mar. 27, 2017
11	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 27, 2017
12	EMI Test Receiver	R&S	ESCI	100895	Mar. 27, 2017
13	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Sep. 07, 2017

Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 04, 2017

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

## ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX MODE

# Line



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.154	42.99	9.52	52.51	65.78	-13.27	peak	
2	0.406	29.93	9.55	39.48	57.73	-18.25	peak	
3	0.550	35.58	9.64	45.22	56.00	-10.78	peak	
4 *	0.550	27.90	9.64	37.54	46.00	-8.46	AVG	
5	0.962	23.45	9.76	33.21	56.00	-22.79	peak	
6	2.598	24.52	10.09	34.61	56.00	-21.39	peak	
7	13.214	18.77	10.30	29.07	60.00	-30.93	peak	



Test Mode: TX MODE

# Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.150	43.40	9.52	52.92	66.00	-13.08	peak	
2		0.182	37.04	9.47	46.51	64.39	-17.88	peak	
3		0.322	28.75	9.53	38.28	59.66	-21.38	peak	
4		0.558	35.61	9.44	45.05	56.00	-10.95	peak	
5	*	0.558	26.00	9.44	35.44	46.00	-10.56	AVG	
6		2.866	25.76	9.79	35.55	56.00	-20.45	peak	
7		13.726	22.41	10.35	32.76	60.00	-27.24	peak	

## ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0151	32.10	0.02	32.12	124.03	-91.91	AVG	
2	*	0.0234	32.30	0.02	32.32	120.22	-87.90	AVG	
3		0.0376	24.10	0.02	24.12	116.10	-91.98	AVG	

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.1965	24.10	0.04	24.14	101.74	-77.60	AVG	
2		0.5980	24.60	0.07	24.67	72.07	-47.40	QP	
3	*	2.3090	33.40	0.11	33.51	69.54	-36.03	QP	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0141	32.80	0.02	32.82	124.62	-91.80	AVG	
2		0.0230	29.10	0.02	29.12	120.37	-91.25	AVG	
3	*	0.0390	25.70	0.02	25.72	115.78	-90.06	AVG	

Test Mode: TX Mode

Ant 90°




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.2061	24.60	0.04	24.64	101.32	-76.68	AVG	
2		1.6020	22.60	0.10	22.70	63.51	-40.81	QP	
3	*	2.3836	28.80	0.11	28.91	69.54	-40.63	QP	

## ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2403MHz

# Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		55.220	30.30	-13.38	16.92	40.00	-23.08	peak	
2		101.780	36.48	-15.32	21.16	43.50	-22.34	peak	
3		202.660	33.32	-14.48	18.84	43.50	-24.66	peak	
4		231.760	32.70	-13.45	19.25	46.00	-26.75	peak	
5		537.310	28.45	-5.86	22.59	46.00	-23.41	peak	
6	*	709.970	27.41	-2.08	25.33	46.00	-20.67	peak	



Test Mode: TX 2403MHz


### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		101.780	32.94	-15.32	17.62	43.50	-25.88	peak	
2		210.420	28.53	-14.63	13.90	43.50	-29.60	peak	
3		313.240	26.25	-10.44	15.81	46.00	-30.19	peak	
4		397.630	26.86	-7.94	18.92	46.00	-27.08	peak	
5		556.710	27.75	-4.88	22.87	46.00	-23.13	peak	
6	*	671.170	27.01	-3.31	23.70	46.00	-22.30	peak	

Test Mode: TX 2440MHz


# Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	70.740	43.91	-16.53	27.38	40.00	-12.62	peak	
2		101.780	35.85	-15.32	20.53	43.50	-22.97	peak	
3		135.730	31.73	-13.16	18.57	43.50	-24.93	peak	
4		192.960	35.59	-14.09	21.50	43.50	-22.00	peak	
5		292.870	29.28	-10.93	18.35	46.00	-27.65	peak	
6		533.430	34.54	-6.26	28.28	46.00	-17.72	peak	

Test Mode:	TX 2440MHz
------------	------------


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		46.490	26.44	-12.60	13.84	40.00	-26.16	peak	
2		101.780	32.62	-15.32	17.30	43.50	-26.20	peak	
3		408.300	27.71	-7.81	19.90	46.00	-26.10	peak	
4		553.800	27.65	-4.73	22.92	46.00	-23.08	peak	
5		708.030	27.94	-2.08	25.86	46.00	-20.14	peak	
6	*	898.150	27.11	2.50	29.61	46.00	-16.39	peak	

Test Mode: TX 2479MHz


# Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	54.250	31.20	-13.53	17.67	40.00	-22.33	peak	
2		101.780	35.73	-15.32	20.41	43.50	-23.09	peak	
3		163.860	29.80	-12.18	17.62	43.50	-25.88	peak	
4		214.300	34.86	-14.47	20.39	43.50	-23.11	peak	
5		400.540	28.07	-7.78	20.29	46.00	-25.71	peak	
6		559.620	27.97	-5.03	22.94	46.00	-23.06	peak	

Test Mode: TX 2479MHz

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		46.490	27.48	-12.60	14.88	40.00	-25.12	peak	
2		101.780	32.67	-15.32	17.35	43.50	-26.15	peak	
3		191.990	29.82	-14.03	15.79	43.50	-27.71	peak	
4		300.630	26.50	-10.17	16.33	46.00	-29.67	peak	
5		391.810	27.93	-8.34	19.59	46.00	-26.41	peak	
6 *		552.830	27.79	-4.68	23.11	46.00	-22.89	peak	

## ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)


Test Mode	TX Mode_2403 MHz
-----------	------------------

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2400.000	22.95	33.05	56.00	74.00	-18.00	peak	
2		2400.000	13.49	33.05	46.54	54.00	-7.46	AVG	
3		2402.700	57.78	33.06	90.84	114.00	-23.16	peak	
4	*	2403.050	54.74	33.06	87.80	94.00	-6.20	AVG	


Test Mode	TX Mode_2403 MHz
-----------	------------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4805.960	47.40	4.77	52.17	74.00	-21.83	peak	
2	*	4806.020	46.22	4.77	50.99	54.00	-3.01	AVG	




Test Mode TX Mode\_2403 MHz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2400.000	22.94	33.05	55.99	74.00	-18.01	peak	
2		2400.000	13.67	33.05	46.72	54.00	-7.28	AVG	
3	*	2403.050	57.54	33.06	90.60	94.00	-3.40	AVG	
4		2403.350	60.61	33.07	93.68	114.00	-20.32	peak	


Test Mode	TX Mode_2403 MHz
-----------	------------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4805.985	45.18	4.77	49.95	74.00	-24.05	peak	
2	*	4806.100	43.23	4.77	48.00	54.00	-6.00	AVG	

Test Mode	TX Mode_2440 MHz
-----------	------------------


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	2440.050	57.78	33.22	91.00	94.00	-3.00	AVG	
2		2440.350	63.94	33.22	97.16	114.00	-16.84	peak	

Test Mode	TX Mode_2440 MHz
-----------	------------------


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4880.000	47.69	5.09	52.78	74.00	-21.22	peak	
2	*	4880.020	45.81	5.09	50.90	54.00	-3.10	AVG	

Test Mode	TX Mode_2440 MHz
-----------	------------------


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	2440.050	56.84	33.22	90.06	94.00	-3.94	AVG	
2		2440.350	63.94	33.22	97.16	114.00	-16.84	peak	

Test Mode	TX Mode_2440 MHz
-----------	------------------


# Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4879.910	48.54	5.09	53.63	74.00	-20.37	peak	
2	*	4880.710	45.76	5.09	50.85	54.00	-3.15	AVG	


Test Mode TX Mode\_2479 MHz

# Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2479.050	56.64	33.38	90.02	94.00	-3.98	AVG	
2		2479.350	59.80	33.38	93.18	114.00	-20.82	peak	
3		2483.500	24.94	33.40	58.34	74.00	-15.66	peak	
4		2483.500	13.34	33.40	46.74	54.00	-7.26	AVG	


Test Mode	TX Mode_2479 MHz
-----------	------------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	4958.020	44.46	5.43	49.89	54.00	-4.11	AVG	
2		4958.040	45.78	5.43	51.21	74.00	-22.79	peak	




Test Mode	TX Mode_2479 MHz
-----------	------------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2479.050	63.21	33.38	96.59	114.00	-17.41	peak	
2	*	2479.050	57.61	33.38	90.99	94.00	-3.01	AVG	
3		2483.500	22.94	33.40	56.34	74.00	-17.66	peak	
4		2483.500	13.44	33.40	46.84	54.00	-7.16	AVG	

Test Mode	TX Mode_2479 MHz
-----------	------------------

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4957.970	45.01	5.43	50.44	74.00	-23.56	peak	
2	*	4958.010	43.04	5.43	48.47	54.00	-5.53	AVG	

## ATTACHMENT E - BANDWIDTH

Test Mode:	TX Mode_2403 MHz/2440 MHz/2479 MHz
------------	------------------------------------


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)
2403	2.010	1.830
2440	1.870	1.780
2479	1.904	1.790

### TX Mode\_2403 MHz




Date: 22.DEC.2016 09:45:11

### TX Mode\_2440 MHz



Date: 28.DEC.2016 15:42:59

### TX Mode\_2479 MHz



Date: 22.DEC.2016 09:57:03