

RF Exposure Evaluation Report

Report No.:	2405X67746EE
Applicant:	Dragino Technology Co., Limited.
Address:	Room 202,BaoChengTai industrial park,No.8 CaiYun LongCheng Street,LongGang District,Shenzhen China
Product Name:	LoRaWAN CO2 Sensor
Product Model:	AQS01-L
Multiple Models:	N/A
Trade Mark:	DRAGINO
FCC ID:	ZHZAQS01-L
Standards:	47 CFR §1.1307 KDB 447498 D04 Interim General RF Exposure Guidance v01
Test Date:	2024-09-26
Test Result:	Complied
Report Date:	2024-09-29

Reviewed by:

Abel chen

Approved by:

Jacob Gong

Abel Chen Project Engineer Jacob Kong Manager

Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk " \star "



Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd

2. The results in this report apply only to the sample tested.

3. This sample tested is in compliance with the limits of the above regulation.

4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

5. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description		
00	2024-09-29	Original		



Contents

1	General Information			
	1.1	Client Information	4	
	1.2	Product Description of EUT	4	
	1.3	Laboratory Location	4	
2 RF Exposure Evaluation			5	
	2.1	Standard	5	
	2.2	Result	7	

1 General Information

1.1 Client Information

Applicant: Dragino Technology Co., Limited.				
Address:	Room 202,BaoChengTai industrial park,No.8 CaiYun LongCheng Street, LongGang District, Shenzhen China			
Manufacturer:	Dragino Technology Co., Limited.			
Address:	Room 202,BaoChengTai industrial park,No.8 CaiYun LongCheng Street, LongGang District, Shenzhen China			

1.2 Product Description of EUT

The EUT is LoRaWAN CO2 Sensor that contains BLE and LoRa radios.

Sample Serial Number	2R1C-3 for RE test, 2R1C-4 for RF conducted test (assigned by WATC)				
Sample Received Date	2024-09-05				
Sample Status	Good Condition				
Frequency Range	BLE1M: 2402MHz - 2480MHz				
	Lora-DSS: 902.3MHz-914.9MHz				
	Lora-DTS: 903MHz-914.2MHz				
Maximum Conducted	BLE1M: 0.72dBm				
Output Power	Lora- DSS: 10.76dBm				
	Lora-DTS: 10.85dBm				
Modulation Technology	Lora, GFSK				
Antenna Gain [#]	Lora: 0.61dBi				
	BLE1M: 0.37dBi				
Spatial Streams	SISO (1TX, 1RX)				
Power Supply	DC 3.6V from battery				
Adapter Information	N/A				
Modification	Sample No Modification by the test lab				

1.3 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: <u>qa@watc.com.cn</u>

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.



2 **RF Exposure Evaluation**

2.1 Standard

According to \$1.1307(b)(3)(i), For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by:

$$P_{th} (mW) = \begin{cases} ERP_{20 \ cm} (d/20 \ cm)^{x} & d \le 20 \ cm \\ \\ ERP_{20 \ cm} & 20 \ cm < d \le 40 \ cm \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20} cm\sqrt{f}}\right)$$
 and f is in GHz;

and

$$ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).



RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

Table 1 to § 1.1307(b)(3)(i)(C)—Single RF Sources Subject to Routine Environmental Evaluation

According to §1.1307(b)(3)(ii), For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$



2.2 Result

Single RF source:

Option C:

Radio	Frequency (MHz)	Distance (mm)	Exemption ERP (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP		Result
						dBm	mW	0,000,000
BLE	2402-2480	200	768	1.0	0.37	-0.78	0.84	exempt
Lora	902.3-914.9/ 903-914.2	200	462	11.0	0.61	9.46	8.83	exempt

Note: The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Multiple RF sources transmission simultaneously consider:

According to applicant, the BLE and Lora can transmission simultaneously.

The ratio=0.84/768+8.83/462=0.02<1.0

Result: Complied

---End of Report---