

MPE ESTIMATION

FCC ID: 2A359-CT220D

1,Limit for General Population/ Uncontrolled Exposures

| Frequency | Power density (mW/ cm ²) | Averaging time(minutes) | | |
|--------------|--------------------------------------|-------------------------|--|--|
| 300MHz1.5GHz | F/1500 | 30 | | |
| 1.5GHz100GHz | 1.0 | 30 | | |

Note: F= Frequency in MHz

2, Estimation Result

| Mod | le | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (numerical) | MPE (mW/cm²) |
|-----|----|-----------------------------|-----------------------|--------------------------|----------------------|--------------------------------|-----------------|
| BLI | = | -6.69 | -7±1(-6) | 0.25 | 0 | 1 | 0.00005 |

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2201050051-E**, antenna gain=0dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00005 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

-----The End-----