

TEST REPORT

Applicant:	Sercomm Corporation
EUT Description:	G5SEM
Model:	G5SEM
Brand:	N/A
FCC ID:	P27-TMOG5SEM
Standards:	FCC CFR Title 47 Part 2
	FCC CFR Title 47 Part 24
	FCC CFR Title 47 Part 27
	FCC CFR Title 47 Part 96
Date of Receipt:	2025/02/06
Date of Test:	2025/02/06 to 2025/04/18
Date of Issue:	2025/04/18

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.

Huang Kun Approved By:

PG 2 22

Chen Chengfu Reviewed By:



Revision History

Rev.	Issue Date	Description	Revised by
01	2025/04/18	Original	Chen Chengfu



Summary of Test Results

FCC Part	Test Band	Test Item	Test Result
§2.1046, §27.50(c)(10)	NR Band n71	Effective Radiated Power	Pass
§2.1046, §27.50(h)(2) §24.232(c) §27.50(d)(4) §27.50(k)(3) §27.50(j)(3)	NR Band n41 NR Band n25 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz)	Effective Isotropic Radiated Power	Pass
§96.41	NR Band n48	Maximum EIRP and Maximum PSD	Pass
§24.232(d) §27.50(d)(5) §96.41	NR Band n25 Others NR Band NR Band n48	Peak-Average Ratio	Pass
§2.1049	All NR Band	Occupied Bandwidth	Pass
\$2.1051 \$27.53(m4) \$24.238(a) \$27.53(g) \$27.53(h) \$27.50(n)(2) \$27.53(l)(2) \$96.41	NR Band n41 NR Band n25 NR Band n71 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz) NR Band n48	Band Edge	Pass
§2.1051 §27.53(m) §24.238(a) §27.53(g) §27.53(h) §27.50(n)(2) §27.53(l)(2) §96.41	NR Band n41 NR Band n25 NR Band n71 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz) NR Band n48	Spurious Emission at Antenna Terminals	Pass
§2.1051 §27.53(m) §24.238(a) §27.53(g) §27.53(h) §27.50(n)(2) §27.53(l)(2) §96.41	NR Band n41 NR Band n25 NR Band n71 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz) NR Band n48	Field Strength of Spurious Radiation	Pass
§2.1055 §24.235 §27.54 §96.41	NR Band n25 Others NR Band NR Band n48	Frequency Stability	Pass
§96.41	NR Band n48	Adjacent Channel Leakage Ratio	Pass
Remark: Pass: Mee	et the requirement.		



Table of Contents

1	Gene	eral De	scription	5
	1.1	Lal	o Information	5
		1.1.1	Testing Location	5
		1.1.2	Test Facility / Accreditations	5
	1.2	Cli	ent Information	5
		1.2.1	Applicant	5
		1.2.2	Manufacturer	5
	1.3	Pro	duct Information	6
2	Test	Config	uration	8
	2.1	Tes	st Channel	8
	2.2	Wa	rst-case configuration and Mode1	4
	2.3	Su	oport Unit used in test1	4
	2.4	Tes	st Environment1	4
	2.5	Tes	at RF Cable1	4
	2.6	Мо	difications1	4
	2.7	Tes	st Setup Diagram1	5
		2.7.1	Conducted Configuration1	5
		2.7.2	Radiated Configuration1	6
3	Equi	pment	and Measurement Uncertainty1	7
	3.1	Tes	st Equipment List1	7
	3.2	Ме	asurement Uncertainty1	8
4	Test	Result	s1	9
	4.1	Ou	tput Power(ERP / EIRP)1	9
	4.2	Ма	ximum EIRP and Maximum PSD2	1
	4.3	Pea	ak-Average Ratio2	3
	4.4	Ос	cupied Bandwidth2	4
	4.5	Ba	nd Edge and Emission Mask2	5
	4.6	Sp	urious Emission at Antenna Terminals2	7
	4.7	Fie	Id Strength of Spurious Radiation2	9
	4.8	Fre	quency Stability V.S. Temperature, Voltage3	1
5	Test	Setup	Photos3	2
	Арр	endix		3



1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 Tel.: +86-755-27212361

Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory. CAB identifier: CN0152 Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	Sercomm Corporation
Address:	8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.

1.2.2 Manufacturer

Manufacturer:	Sercomm Corporation
Address:	8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.



EUT Description: G5SEM Model: G5SEM N/A Brand: Hardware Version: V1.1 Software Version: 0.00.02 **RF** Conducted 355660790004917 IMEI: RSE 355660790005120 Technical specification: Band **TX Frequency RX** Frequency NR Band n25 1850 to 1915MHz 1930 to 1995 MHz NR Band n41 2496 to 2690 MHz 2496 to 2690 MHz NR Band n48 3550 to 3700 MHz 3550 to 3700 MHz NR Band n66 1710 to 1780 MHz 2110 to 2200 MHz NR Band n71 663 to 698 MHz 617 to 652 MHz 3450 to 3550 MHz 3450 to 3550 MHz Operation NR Band n77 3700 to 3980 MHz 3700 to 3980 MHz Frequency Range: NSA: DC_66A_n25A; DC_2A_n41A; DC_66A_n41A; DC_2A_n66A; DC_2A_n71A; DC_66A_n71A; NR CA: n25A-n41A; n25A-n48A; n25A-n66A; n41A-n66A; n48A-n66A; n25A-n71A; n41A-n71A; n48A-n71A; n66A-n71A; n25A-n77A; n66A-n77A; n71A-n77A; Class 2: n41/77 for NSA: n25/66/71 for SA UL MIMO/TXD Power Class: Class 1.5: n41 and n77 for SA UL MIMO/TXD Class 3: All UL 2*2 MIMO: Feature: NR Band n25; NR Band n41; NR Band n48; NR Band n66; NR Band n71; NR Band n77: Pi/2-BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM DFT-s-OFDM: Type of Modulation: CP-OFDM: QPSK, 16-QAM, 64-QAM, 256-QAM Bandwidth (MHz) SCS NR Band (kHz) 5 10 25 35 40 45 50 70 15 20 30 60 80 90 100 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ n25 15 $\sqrt{}$ 1 1 1 1 1 1 1 $\sqrt{}$ $\sqrt{}$ 30 $\sqrt{}$ n41 / Operation Bandwidth: n48 30 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ / 1 1 1 1 $\sqrt{}$ 1 1 1 1 1 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ / / / 1 n66 15 1 / $\sqrt{}$ n71 15 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ 1 / 1 1 1 / 1 1 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ n77 30 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ 1 🛛 External, 🗌 Integrated Antenna Type: Band Ant1(dBi) Ant2(dBi) Ant7(dBi) Ant8(dBi) NR Band n25 4.5 Antenna Gain: 4.5 1 NR Band n41 2.5 2.5

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd.

Email: info@towewireless.com

Tel.: +86-755-27212361 TOWE-QP-15-F05 Rev.1.1 All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.



Page 7 / 33 Report No.: TCWA25010004602

	NR Band n48	0	/	0	/	
	NR Band n66	1.5	/	1.5	/	
	NR Band n71	/	4.4	/	4.4	
	NR Band n77 (3450 to 3550 MHz)	0	/	0	1	
	NR Band n77 (3700 to 3980 MHz)	0	/	0	/	
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user						
manual for more detailed description.						



2.1 Test Channel

5G NR Band n25 and SCS 15 kHz						
		TX Frequence	;y	RX Frequency		
Bandwidth	Range	Carrier centre (ARFCN)	Carrier centre (MHz)	Range	Carrier centre (ARFCN)	Carrier centre (MHz)
	Low	370500	1852.5	Low	386500	1932.5
5MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	382500	1912.5	High	398500	1992.5
	Low	371000	1855	Low	387000	1935
10MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	382000	1910	High	398000	1990
	Low	371500	1857.5	Low	387500	1937.5
15MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	381500	1907.5	High	397500	1987.5
	Low	372000	1860	Low	388000	1940
20MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	381000	1905	High	397000	1985
	Low	372500	1862.5	Low	388500	1942.5
25MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	380500	1902.5	High	396500	1982.5
	Low	373000	1865	Low	389000	1945
30MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	380000	1900	High	396000	1980
	Low	373500	1867.5	Low	389500	1947.5
35MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	379500	1897.5	High	395500	1977.5
	Low	374000	1870	Low	390000	1950
40MHz	Middle	376500	1882.5	Middle	392500	1962.5
	High	379000	1895	High	395000	1975



Page 9 / 33 Report No.: TCWA25010004602

5G NR Band n41, SCS 30 kHz and ΔF_{Raster} 30 kHz					
		TX & RX Frequency			
Bandwidth	Range	Carrier centre (ARFCN)	Carrier centre (MHz)		
	Low	500202	2501.01		
10MHz	Middle	518598	2592.99		
	High	537000	2685		
	Low	500700	2503.5		
15MHz	Middle	518598	2592.99		
	High	536496	2682.48		
	Low	501204	2506.02		
20MHz	Middle	518598	2592.99		
	High	535998	2679.99		
	Low	501702	2508.51		
25MHz	Middle	518598	2592.99		
	High	535500	2677.5		
	Low	502200	2511		
30MHz	Middle	518598	2592.99		
	High	534996	2674.98		
	Low	502704	2513.52		
35MHz	Middle	518598	2592.99		
	High	534498	2672.49		
	Low	503202	2516.01		
40MHz	Middle	518598	2592.99		
	High	534000	2670		
	Low	503700	2518.50		
45MHz	Middle	518598	2592.99		
	High	533496	2667.48		
	Low	504204	2521.02		
50MHz	Middle	518598	2592.99		
	High	532998	2664.99		
	Low	505200	2526		
60MHz	Middle	518598	2592.99		
	High	531996	2659.98		
	Low	506200	2531		
70MHz	Middle	518598	2592.29		
	High	531000	2655		
	Low	507204	2536.02		
80MHz	Middle	518598	2592.99		
	High	529998	2649.99		
	Low	508200	2541		
90MHz	Middle	518598	2592.99		
	High	528996	2644.98		
	Low	509202	2546.01		
100MHz	Middle	518598	2592.99		
	High	528000	2640		



Page 10 / 33 Report No.: TCWA25010004602

5G NR Band n48, SCS 30 kHz and ΔF _{Raster} 30 kHz					
	TX & RX Frequency				
Bandwidth	Range	Carrier centre	Carrier centre		
	Range	(ARFCN)	(MHz)		
	Low	637000	3555		
10MHz	Middle	641666	3624.99		
	High	646332	3694.98		
	Low	637168	3557.52		
15MHz	Middle	641666	3624.99		
	High	646166	3692.49		
	Low	637334	3560.01		
20MHz	Middle	641666	3624.99		
	High	646000	3690		
	Low	637668	3565.02		
30MHz	Middle	641666	3624.99		
	High	645666	3684.99		
	Low	638000	3570		
40MHz	Middle	641666	3624.99		
	High	645332	3679.98		

	5G NR Band n66, SCS 15 kHz						
	<u> </u>	TX Frequence	cy		RX Frequency		
Bandwidth	Range	Carrier centre (ARFCN)	Carrier centre (MHz)	Range	Carrier centre (ARFCN)	Carrier centre (MHz)	
	Low	435500	1712.5	Low	422500	2112.5	
5MHz	Middle	342500	1745	Middle	431000	2155	
	High	349000	1777.5	High	439500	2197.5	
	Low	343000	1715	Low	423000	2115	
10MHz	Middle	349000	1745	Middle	431000	2155	
	High	355000	1775	High	439000	2195	
ļ	Low	343500	1717.5	Low	423500	2117.5	
15MHz	Middle	349000	1745	Middle	431000	2155	
	High	354500	1772.5	High	438500	2192.5	
,	Low	344000	1720	Low	424000	2120	
20MHz	Middle	349000	1745	Middle	431000	2155	
l I	High	354000	1770	High	438000	2190	
,	Low	344500	1722.5	Low	424500	2122.5	
25MHz	Middle	349000	1745	Middle	431000	2155	
<u>'</u>	High	353500	1767.5	High	437500	2187.5	
,	Low	345000	1725	Low	425000	2125	
30MHz	Middle	349000	1745	Middle	431000	2155	
[High	353000	1765	High	437000	2185	
,	Low	345500	1727.5	Low	425500	2127.5	
35MHz	Middle	349000	1745	Middle	431000	2155	
l'	High	352500	1762.5	High	436500	2182.5	
,	Low	346000	1730	Low	426000	2130	
40MHz	Middle	349000	1745	Middle	431000	2155	
1	High	352000	1760	High	436000	2180	
,	Low	346500	1732.5	Low	426500	2132.5	
45MHz	Middle	349000	1745	Middle	431000	2155	
	High	351500	1757.5	High	435500	2177.5	



Page 11 / 33 Report No.: TCWA25010004602

5G NR Band n71, SCS 15 kHz						
		TX Frequence	;y	RX Frequency		
Bandwidth	Pango	Carrier centre	Carrier centre	Pango	Carrier centre	Carrier centre
	Kange	(ARFCN)	(MHz)	Kange	(ARFCN)	(MHz)
	Low	133100	665.5	Low	123900	619.5
5MHz	Middle	136100	680.5	Middle	126900	634.5
	High	139100	695.5	High	129900	649.5
	Low	133600	668	Low	124400	622
10MHz	Middle	136100	680.5	Middle	126900	634.5
	High	138600	693	High	129400	647
	Low	134100	670.5	Low	124900	624.5
15MHz	Middle	136100	680.5	Middle	126900	634.5
	High	138100	690.5	High	128900	644.5
	Low	134600	673	Low	125400	627
20MHz	Middle	136100	680.5	Middle	126900	634.5
	High	137600	688	High	128400	642
	Low	135100	675.5	Low	125900	629.5
25MHz	Middle	136100	680.5	Middle	126900	634.5
	High	137100	685.5	High	127900	639.5
	Low	135600	678	Low	126400	632
30MHz	Middle	136100	680.5	Middle	126900	634.5
	High	136600	683	High	127400	637
	Low			Low		
35MHz	Middle	136100	680.5	Middle	126900	634.5
	High			High		



5G NR Band n77(3450~3550MHz), SCS 30 kHz and Δ F _{Raster} 30 kHz				
		TX & RX Frequency		
Bandwidth	Range	Carrier centre	Carrier centre	
		(ARFCN)	(MHZ)	
	Low	630334	3455.01	
10MHz	Middle	633334	3500.01	
	High	636334	3545.01	
	Low	630500	3457.5	
15MHz	Middle	633334	3500.01	
	High	636166	3542.49	
	Low	630668	3460.02	
20MHz	Middle	633334	3500.01	
	High	636000	3540	
	Low	630835	3462.52	
25MHz	Middle	633334	3500.01	
	High	635833	3537.50	
	Low	631000	3465	
30MHz	Middle	633334	3500.01	
	High	635666	3534.99	
	Low	631334	3470.01	
40MHz	Middle	633334	3500.01	
	High	635334	3530.01	
	Low	631668	3475.02	
50MHz	Middle	633334	3500.01	
F	High	635000	3525	
	Low	632000	3480	
60MHz	Middle	633334	3500.01	
F	High	634666	3519.99	
	Low	632334	3485.01	
70MHz	Middle	633334	3500.01	
	High	634334	3515.01	
	Low	632668	3490.02	
80MHz	Middle	633334	3500.01	
	High	634000	3510	
	Low	633000	3495	
90MHz	Middle	633334	3500.01	
	High	633666	3504 99	
	low			
100MHz	Middle	633334	3500 01	
	Hiah			



5G NF	<u>R Band n77(3700~3980MHz</u>	ΔF_{Raster}), SCS 30 kHz and ΔF_{Raster}	30 kHz
		TX & RX Frequency	
Bandwidth	Pango	Carrier centre	Carrier centre
	Kange	(ARFCN)	(MHz)
	Low	647000	3705
10MHz	Middle	656000	3840
	High	665000	3975
	Low	647168	3707.52
15MHz	Middle	656000	3840
	High	664832	3972.48
	Low	647334	3710.01
20MHz	Middle	656000	3840
	High	664666	3969.99
	Low	647501	3712.515
25MHz	Middle	656000	3840
	High	664499	3967.485
	Low	647666	3714.99
30MHz	Middle	656000	3840
	High	664334	3965.01
	Low	648000	3720
40MHz	Middle	656000	3840
	High	664000	3960
	Low	648334	3725.01
50MHz	Middle	656000	3840
	High	663666	3954.99
	Low	648668	3730.02
60MHz	Middle	656000	3840
	High	663332	3949.98
	Low	649000	3735
70MHz	Middle	656000	3840
	High	663000	3945
	Low	649334	3740.01
80MHz	Middle	656000	3840
	High	662666	3939.99
	Low	649668	3745.02
90MHz	Middle	656000	3840
	High	662332	3934.98
	Low	650000	3750
100MHz	Middle	656000	3840
	High	662000	3930

2.2 Worst-case configuration and Mode

Test Mode	Description
TM 1	EUT communication with simulated station in DFT-s-OFDM BPSK mode
TM 2	EUT communication with simulated station in DFT-s-OFDM QPSK mode
TM 3	EUT communication with simulated station in DFT-s-OFDM 16QAM mode
TM 4	EUT communication with simulated station in DFT-s-OFDM 64QAM mode
TM 5	EUT communication with simulated station in DFT-s-OFDM 256QAM mode
TM 6	EUT communication with simulated station in CP QPSK mode
TM 7	EUT communication with simulated station in CP 16QAM mode
TM 8	EUT communication with simulated station in CP 64QAM mode
TM 9	EUT communication with simulated station in CP 256QAM mode

Note:

1. The maximum Conducted Power is calculated from max output power and max antenna gain, only the maximum Conducted Power is shown in the report.

- 2. ERP/EIRP of all antennas are tested, and only the worst data is presented.
- NR n25/n41/n48/n66/n71/n77 support UL MIMO mode is correlated, the n25/n41/n48/n66/n71/n77 MIMO antenna gain = 10log[(10^{G1/20}+10^{G2/20})²/2]. The conducted BE/Spurious are tested at single antenna port and add 10*log(N_{ANT}) according to KDB 662911 D01.
- 4. NR n41/n48/n66/n71/n77 support SA and NSA mode. The whole testing has assessed SA mode by referring to the higher conducted power.
- 5. The device supports HPUE mode for NR n41/n77 and PC1.5 for NR n41/n77 UL MIMO.

2.3 Support Unit used in test

Description	Manufacturer	Model	Serial Number	
Development Board *	N/A	DBG-G5SEM	/	
Remark: * the information of table is provided by client.				

2.4 Test Environment

Temperature:	Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C	
Relative Humidity	45 ~ 56 % RH Ambient	
Voltage:	Nominal: 3.8 Vdc, Extreme: Low 3.3 Vdc, High 4.4 Vdc	

2.5 Test RF Cable

For all conducted test items: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

2.6 Modifications

No modifications were made during testing.



2.7 Test Setup Diagram

2.7.1 Conducted Configuration









3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable recognized national standards.

3.1 Test Equipment List

RF07					
Description	Manufacturer	Model	SN	Last Due	Cal Due
Radio Communication Test Station	Anritsu	MT8000A	6262208297	2024/11/04	2025/11/03
Signal Apolyzor	Kovoight	NOODOA	MV52280106	2024/03/25	2025/03/24
Signal Analyzei	Keysight	N9020A	IVI 1 53260 106	2025/03/11	2026/03/10
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2024/05/30	2025/05/29
EC ND Respectation	StortDoint		SD20676	2024/03/25	2025/03/24
SG INR Dasestation	StanPoint SP9500-CI		SP20070	2025/03/11	2026/03/10
Measurement Software	Tonscend	TS1120 V3.1.46	10636	N/A	N/A

Radiated Emission					
Description	Manufacturer	Model	SN	Last Due	Cal Due
Biconic Logarithmic Periodic Antennas	Schwarzbeck	VULB9163	1643	2023/06/25	2025/06/24
Double-Ridged Horn Antennas	Schwarzbeck	BBHA 9120D	2809	2023/06/25	2025/06/24
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	1290	2023/06/25	2025/06/24
Loop Antenna	Schwarzbeck	FMZB 1519C	1519C-028	2023/06/29	2025/06/28
Signal Analyzar	Kovojaht	NOODOA	MV/40400252	2024/03/25	2025/03/24
Signal Analyzer	Reysign	N9020A	MT49100252	2025/03/11	2026/03/10
EXA Signal Analyzer, Multi- touch	Keysight	N9010B	MY63440541	2024/05/30	2025/05/29
Wideband Radio	P&S		150645	2024/03/25	2025/03/24
Communication Tester	R&3	CIVIV500	150045	2025/03/11	2026/03/10
Low Noiso Amplifiar	Topscond		A D 22 A 8060272	2023/04/08	2025/04/07
	Tonscend	TAF 9N3040	AF23A0000273	2025/03/11	2027/03/10
Low Noise Amplifier	Topoond		A D 2 2 C 9 0 6 2 5 9	2023/04/08	2025/04/07
	Tonscend	TAPU1010050	AF22G600256	2025/03/11	2027/03/10
Low Noise Amplifier	Tanaaand	TA D40040040	400000047	2023/04/08	2025/04/07
Low Noise Ampliner	Tonscena	TAP 18040048	AP22G806247	2025/03/11	2027/03/10
Hygrometer	BINGYU	HTC-1	N/A	2023/06/01	2025/05/31
Test Software	Tonscend	TS+ V5.0.0	N/A	N/A	N/A



3.2 Measurement Uncertainty

Parameter	U _{lab}
Frequency error	50.30Hz
Output power	0.74dB
Conducted spurious emissions	2.22dB
Radiated Emissions(9kHz~30MHz)	2.40dB
Radiated Emissions(30MHz~1000MHz)	4.66dB
Radiated Emissions(1GHz~18GHz)	5.42dB
Radiated Emissions(18GHz~40GHz)	5.46dB

Uncertainty figures are valid to a confidence level of 95%



4 Test Results

4.1 Output Power(ERP / EIRP)

Limits

FCC Part	Test Band	Limit
§24.232(c)	NR Band n25	Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.
§27.50(h)(2)	NR Band n41	Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power
§27.50(d)(4)	NR Band n66	Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780MHz bands are limited to 1watt EIRP. Fixed stations operating in the 1710-1755MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.
§27.50(c)(10)	NR Band n71	Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3watts ERP.
§27.50(k)(3)	5G NR n77 (3450-3550MHz)	Mobile devices are limited to 1Watt (30 dBm) EIRP
§27.50(j)(3)	5G NR n77 (3700-3980MHz)	Mobile and portable stations are limited to 1 Watt EIRP

Test Procedure

FCC KDB 971168 D01 V03r01 Section 5.2.1, for Conducted Output Power;

FCC KDB 971168 D01 V03r01 Section 5.2, for 4.2 for Effective (Isotropic) Radiated Power

Test Settings

Conducted Output Power:

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to the simulated base station. The simulated station was set to force the EUT to its maximum power setting, Transmitter output power was read off in dBm, Read values have added cable loss and attenuation.

Effective (Isotropic) Radiated Power:

The formula for calculating ERP/EIRP based on conduction power is as follows: EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi) ERP=EIRP - 2.15dB



Test Setup

Refer to section 2.7.1 Setup 1

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



FCC Part	Test Band	Limit		
§96.41		Device	Maximum EIRP (dBm/10 megahertz)	Maximum PSD (dBm/MHz)
	NR Band n48	End User Device	23	n/a
		Category A CBSD	30	20
		Category B CBSD ¹	47	37

Test Procedure

KDB 971168 D01 V03r01 Section 5.4

Test Settings

- 1. Set span to $2 \times to 3 \times the OBW$.
- 2. Set RBW = 1% to 5% of the OBW.
- 3. Set VBW \geq 3 × RBW.
- 4. Set number of measurement points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
- 5. Sweep time:
 - a) Set = auto-couple, or
 - Set \geq [10 × (number of points in sweep) × (transmission symbol period)] for single sweep b) (automation-compatible) measurement.
- 6. Detector = power averaging (rms).
- 7. Set sweep trigger to "free run."
- 8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.
- 9. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function with band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- 10. Add 10 log (1/duty cycle) to the measured power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 dB$ if the duty cycle is a constant 25%.

Test notes

- 1. When average PSD limits are specified, the same fundamental measurement condition applies as previously discussed (i.e., averaging is to be performed only over durations of active transmissions at maximum output power level). Thus, when performing this measurement, the EUT must either be configured to transmit continuously at full power while the compliance measurement is performed, or else the measurement instrumentation must be configured to acquire data only over durations when the EUT is actively transmitting at full power. In circumstances where neither of these conditions can be realized, then alternative procedures are provided for both constant duty cycle and non-constant duty cycle transmissions.
- The PSD is measured following the same procedures described in 5.2.4.4 for measuring the total average 2. power, but with the RBW set to the reference bandwidth specified by the applicable regulatory requirement, and by using the marker function to identify the maximum PSD instead of summing the power across the OBW. If the fundamental measurement condition cannot be realized, then one of the alternative procedures in 5.2.4.4.2 or 5.2.4.4.3 should be selected.



Page 22 / 33 Report No.: TCWA25010004602

Test Setup

Refer to section 2.7.1 Setup 2

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



§24.232(d): The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

§27.50(d)(5): The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

§96.41: The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test Procedure

FCC KDB 971168 D01 V03r01 Section 5.7.1

Test Settings

The following guidelines are offered for performing a CCDF measurement.

- 11. Set resolution/measurement bandwidth \geq OBW or specified reference bandwidth.
- 12. Set the number of counts to a value that stabilizes the measured CCDF curve.
- 13. Set the measurement interval as follows:
 - a) For continuous transmissions, set to the greater of [10 × (number of points in sweep) × (transmission symbol period)] or 1 ms.
 - b) For burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize. Set the measurement interval to a time that is less than or equal to the burst duration.
 - c) If there are several carriers in a single antenna port, the peak power shall be determined for each individual carrier (by disabling the other carriers while measuring the required carrier) and the total peak power calculated from the sum of the individual carrier peak powers.
- 14. Record the maximum PAPR level associated with a probability of 0.1%.
- 15. The peak power level is calculated form the sum of the PAPR value from step d) to the measured average power.

Test Setup

Refer to section 2.7.1 Setup 2

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



For Reporting Purposes only

Test Procedure

FCC KDB 971168 D01 V03r01 Section 4.2 & 4.3

Test Settings

- 1. The transmitter output was connected to a calibrated coaxial cable and coupler, The other end is connected to the spectrum analyzer and simulated station.
- 2. The signal analyzer automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by ant intermediate power nulls in the fundamental emission.
- 3. The simulated base station was set to force the EUT to its maximum power setting.
- 4. RBW = 1 5% of the expected OBW
- 5. VBW = 3 times the RBW
- 6. Sweep = Auto
- 7. Detector = Peak
- 8. Trace = Max hold
- 9. The trace was allowed to stabilize

Test Setup

Refer to section 2.7.1 Setup 2

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



Band	Limit
NR Band n25 NR Band n71 NR Band n66	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.
NR Band n41	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 MHz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 MHz and X MHz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.
NR Band n77 (3450-3550MHz)	In the 1 MHz bands immediately outside and adjacent to the licensee's frequency block: ≤-13 dB/(1% EBW, but no exceed 200kHz). In the bands between 1 and 5 MHz removed from the
	licensee's frequency block: ≤-13 dB/(500 kHz, or grater)
NR Band n77 (3550-3980MHz)	In the 1 MHz bands immediately outside and adjacent to the licensee's frequency block: ≤-13 dB/(1% EBW, or 350 kHz). In the bands between 1 and 5 MHz removed from the
	licensee's frequency block: ≤-13 dB/(500 kHz, or grater)
NR Band n48	for channel and frequency assignments made by the SAS to CBSDs, the conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed –13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge.

Test Procedure

FCC KDB 971168 D01 V03r01 Section 6.0

Test Settings

- 1. The transmitter output was connected to a calibrated coaxial cable and coupler, The other end is connected to the spectrum analyzer and simulated station.
- 2. The simulated base station was set to force the EUT to its maximum power setting.
- 3. Start and stop frequency were set such that the band edge would be placed in the center of the plot.
- 4. RBW \ge 1% of the emission bandwidth
- 5. VBW \geq 3 times the RBW
- 6. Detector = RMS
- 7. Number of sweep point \geq 2 times Span/RBW
- 8. Sweep = Auto
- 9. Trace = Max hold
- 10. The trace was allowed to stabilize



Page 26 / 33 Report No.: TCWA25010004602

Test Setup

Refer to section 2.7.1. Setup 2

Test Notes

Transmit signals are correlated				
Band	ANT Gain1/2 (dBi)	ANT Gain7/8 (dBi)	Directional gain (dBi)	
NR Band n25:	4.5	4.5	7.51	
NR Band n41:	2.5	2.5	5.51	
NR Band n48:	0	0	3.01	
NR Band n66:	1.5	1.5	4.51	
NR Band n71:	4.4	4.4	7.41	
NR Band n77: (3450 to 3550 MHz)	0	0	3.01	
NR Band n77: (3700 to 3980 MHz)	0	0	3.01	

The test results, combined with directional gain, still meet the limit requirements.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



4.6 Spurious Emission at Antenna Terminals

<u>Limits</u>

Band	Limit
NR Band n25 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz) NR Band n71	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.
NR Band n41	All frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.
NR Band n48	for channel and frequency assignments made by the SAS to CBSDs, the conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any emission shall not exceed -25 dBm/MHz.

Test Procedure

FCC KDB 971168 D01 V03r01 Section 6.0

Test Settings

- 1. The transmitter output was connected to a calibrated coaxial cable and coupler, The other end is connected to the spectrum analyzer and simulated station.
- 2. The simulated base station was set to force the EUT to its maximum transmitting power.
- 3. Start frequency was set to 9kHz and stop frequency was set to 10th harmonic.
- 4. RBW and VBW (see test notes)
- 5. Detector = RMS
- 6. Sweep = Auto
- 7. Sweep point = below 30MHz(1001pts); 30MHz 1GHz(2001pts); above 1GHz(40001pts)
- 8. Trace = trace average for continuous emissions, max hold for pulse emissions
- 9. Allow trace to fully stabilize

Test Notes

- 1. Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100kHz or greater for measurements below 1GHz. However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission is attenuated at least 26dB below the transmitter power
- 2. 9kHz 150kHz: RBW=1kHz, VBW≥3 times the RBW
- 3. 150kHz 30MHz: RBW=10kHz, VBW≥3 times the RBW



Transmit signals are correlated			
Band	ANT Gain1/2 (dBi)	ANT Gain7/8 (dBi)	Directional gain (dBi)
NR Band n25:	4.5	4.5	7.51
NR Band n41:	2.5	2.5	5.51
NR Band n48:	0	0	3.01
NR Band n66:	1.5	1.5	4.51
NR Band n71:	4.4	4.4	7.41
NR Band n77: (3450 to 3550 MHz)	0	0	3.01
NR Band n77: (3700 to 3980 MHz)	0	0	3.01

The test results, combined with directional gain, still meet the limit requirements.

Test Setup

Refer to section 2.7.1. Setup 2

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



Band	Limit
NR Band n25 NR Band n71 NR Band n66 NR Band n77 (3450-3550MHz) NR Band n77 (3550-3980MHz)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.
NR Band n41	All frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz.
NR Band n48	for channel and frequency assignments made by the SAS to CBSDs, the conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed –13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any emission shall not exceed –25 dBm/MHz.

Test Procedure

FCC KDB 971168 D01 V03r01 Section 7

Test Settings

- 1. For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
- 2. For radiated emissions measurements performed at frequencies above 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the ground plane.
- 3. Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.
- 4. For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
- 5. The simulated base station was set to force the EUT to its maximum transmitting power.
- 6. spectrum analyzer setting:

Measurements 9kHz ~150kHz: RBW = 300Hz; VBW ≥ 3 kHz; Detector = RMS Measurements 150kHz ~30MHz: RBW = 10kHz; VBW ≥ 30 kHz; Detector = RMS Measurements 30MHz~1000MHz: RBW = 100kHz or 1MHz; VBW ≥ 1MHz or 3MHz; Detector = RMS Measurements Above 1000MHz: RBW = 1 MHz; VBW ≥ 3 MHz; Detector = RMS

7. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:

 $E(dB\mu V/m) = Measured amplitude level (dB\mu V) + Cable Loss (dB) + Antenna Factor (dB/m).$

E(dBµV/m) = Measured amplitude level (dBm) + 107 + Cable Loss (dB) + Antenna Factor (dB/m).

E(dBuV/m) = EIRP(dBm) - 20log(D) + 104.8; where D is the measurement distance(in the far field region) in m. EIRP(dBm) = E(dBµV/m) + 20log(D) - 104.8; where D is the measurement distance(in the far field region) in m.

So, from d: The measuring distance is usually at 3m, then 20*Log(3)=9.5424

```
Then, EIRP (dBm)= E (dBµV/m) +9.5424-104.8=E (dBµV/m)-95.2576
```



- 8. Repeat above procedures until all frequencies measured was complete.
- 9. Measure and record the results in the test report.

Test notes

- 1. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
- 3. Radiated spurious emissions were investigated from 9kHz to 30MHz, 30MHz-1GHz and above 1GHz. the disturbance between 9kHz to 30MHz, 30MHz-1GHz and 18GHz to 40GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be recorded, so only the harmonics had been displayed.
- 4. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Test Setup

Refer to section 2.7.2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result



4.8 Frequency Stability V.S. Temperature, Voltage

<u>Limits</u>

§24.235 / §27.54 / §96.41:

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure

FCC KDB 971168 D01 V03r01 Section 9

Test Settings

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Notes

a.) Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber. b.) Primary Supply Voltage:

The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Test Setup

Refer to section 2.7.1 Setup 3

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

<u>Test Result</u>



5 Test Setup Photos

The detailed test data see: Appendix-D WWAN Setup Photos



Appendix

Appendix List:

Appendix-B NR Band n25

Appendix-B NR Band n41

Appendix-B NR Band n48

Appendix-B NR Band n66

Appendix-B NR Band n71

Appendix-B NR Band n77(3450-3550)

Appendix-B NR Band n77(3700-3980)

Appendix-C Field Strength of Spurious Radiation-NR

~The End~