

# FCC Part 15D - Compliance Information

# **EUT AND PRODUCT INFORMATION**

Type of Equipment	UPCS (DECT 6.0)
Applicant Name	Panasonic Corporation
Address	1-62, 4-chome, Minoshima, Hakata-ku, Fukuoka, 812-8531 Japan
Contact	Michihito Miyazaki
Telephone	+81-70-1349-4205
Email	miyazaki.michihito@jp.panasonic.com
Brand Name	Panasonic

	Base Station	Handset / Portable	WRS	
EUT Type/System				
FCC ID		ACJ96NKX-TPA70		
ISED ID (Canada)		216A-KXTPA70		
Model name		KX-TPA70		
HW Version		PNLB2824ZAxx		
SW Version		Ver 00.01		
Maximum Antenna Gain		1.0 dBi		
Can the EUT be Initiating Device	☐ YES	⊠ YES □ YES		
Does the EUT transmit signaling channels	☐ YES	☐ YES ☐ YES		
Max. # of slots in use simultaneously		1slot		
Frequency Band	1921.536 – 1928.448 MHz			
Number of RF Channels	5			
Frame Period	10 ms			
Max. Burst length	723us			
Min. Burst Length	390us			
Min. # of System Channels	60 (12 duplex channels per RF carrier)			
Supported DECT Slot Types	⊠ Full Slot	□ Double Slot		
Operating Mode	☐ Simplex	⊠ Duplex		



# FCC Part 15D – Compliance Information

ANTENNAS						
Base Station	Antenna	Туре	Internal	External		
	1					
	2					
	3					
	4					
	Does RX and TX	use the same antenna(s)?	] Yes	□ No		
Handset	Antenna	Туре	Internal	External		
	1	$\lambda/4$ PIFAntenna				
	2					
	Does RX and TX	use the same antenna(s)?	☑ Yes	□ No		

ANTENNA DIVERSITY				
	Antenna	Diversity Supported		
		TX	RX	
Base Station	1			
	2			
	3			
	4			
Handset	1			
	2			

VOLTAGE AND TEMPERATURE RANGES				
VOLTAGES	Base Station	Base Station Handset or Portable WR		WRS
Nominal Voltage		DC 2.6V		
Cut-Off Voltage (if applicable)				
POWER SOURCE	Туре		Manufacturer	
Base Station or WRS				
Handset (Charger)	Ni-MH Battery cell X 2 Panasonic (PQLV219 (AC Adaptor))		Panasonic	
Connections on Base	<ul><li>□ PSTN</li><li>□ USB</li><li>□ Ethernet</li><li>⋈ Others (please spec</li></ul>	fy)RF		



# FCC Part 15D – Compliance Information

ANCILLARY EQUIPMENT				
Description AC Adapter and Charger				
Туре	PQLV219 (AC Adaptor)			
Manufacturer Panasonic				
HOST DEVICE				
Description				
Туре				
Manufacturer				

ADDITIONAL INFORMATION		



# FCC Part 15D – Compliance Information

MANUFACTURERS DECLARATIONS				
FCC part 15.323 (c)(5)				
The applicant declares that the system in this application has more than 20 duplex system access channels defined, and that the system is operating in Least Interfered Channel (LIC) mode in accordance with this section.				
Applicant Agrees	⊠ Yes		□ No	
FCC part 15.323 (c)(5)				
	ggregate bandwidth, o		ther shall during any frame period e than one third of the time and	
Applicant Agrees	⊠ Yes		□ No	
FCC part 15.323 (c)(10)	•			
The applicant hereby declares section.	s that the system in this	s application <b>does</b> (	use the criteria of (c)(10) of this	
Applicant Agrees	⊠ Yes		□ No	
FCC part 15.323 (c)(11)				
The applicant hereby declares section.	s that system in this ap	plication does not	use the criteria of (c)(11) of this	
Applicant Agrees	⊠ Yes		□ No	
FCC part 15.323 (c)(12)				
The provisions of (c)(10) or (c)(11) of this section <b>shall not</b> be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.				
Applicant Agrees	⊠ Yes		□ No	
ADDITIONAL REMARKS:				
>				
DECLARED BY:				
27 September 2019	Michihito Miyazaki	ito Miyazaki		
Date	Name (print)	Signature		



## FCC Part 15D - Compliance Information

## **About this document**

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15D. The form must be completed by the applicant and submitted to Nemko before testing is started.

### **Preparation of Equipment for Testing**

### Note (a): Number of samples for testing

The following samples are needed for FCC 15D testing:

#### RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is needed for these tests even if the equipment has more than one antenna.

#### Monitoring Tests:

One sample with 50 ohm antenna connectors fitted to all antennas (preferably SMA female). Additionally we need a companion device that will work together with the EUT, the companion device must also have antenna connectors on all antennas.

#### Radiated Tests:

One sample with integral antennas. This sample will be used to measure Antenna Gain, Part 15B and Power-Line Conducted tests.

#### Note (b): Burst Mode

All RF tests are performed with the EUT in force transmit, aka burst mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

### Note (c): Monitoring Tests

Monitoring tests are performed in normal operating mode by establishing a connection from the handset (or the initiating device) to the base station (or the responding device). Most tests are performed by establishing connections from the initiating device to the responding device and observing which channel and/or timeslot is used.

For monitoring tests we need a EUT and a Companion device that both have antenna connectors on all antennas (preferably SMA female, again). Additionally, we need access to the CLK100 signal on the Base Station, this is necessary because some of the tests require that the interferers are synced to the DECT frame.

### Note (d): Connection to an external power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with batteries.

#### Note (e): Test-Mode (Loopback Mode)

Loopback Mode is usually not used for FCC testing.