

Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10640.000	51.54	54.00	-2.46	45.68	5.86	AV
2	15960.000	41.00	54.00	-13.00	29.70	11.30	AV

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	58.21	74.00	-15.79	52.44	5.77	РК
2	16500.000	50.98	68.22	-17.24	37.78	13.20	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	44.27	54.00	-9.73	38.50	5.77	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	65.19	74.00	-8.81	59.42	5.77	РК
2	16500.000	52.11	68.22	-16.11	38.91	13.20	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test Date : 2021/06/03



Vertical

* 1 Note:

11000.000

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

-3.22

45.01

5.77

AV

2. Emission Level = Reading Level + Correct Factor.

(dBuV/m)

50.78

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

54.00

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	61.09	74.00	-12.91	55.12	5.97	РК
2	16740.000	52.34	68.22	-15.88	38.88	13.46	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	46.32	54.00	-7.68	40.35	5.97	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	65.77	74.00	-8.23	59.80	5.97	РК
2	16740.000	54.01	68.22	-14.21	40.55	13.46	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	51.31	54.00	-2.69	45.34	5.97	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	61.72	74.00	-12.28	55.26	6.46	РК
2	17100.000	51.22	68.22	-17.00	37.93	13.29	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5700MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	46.21	54.00	-7.79	39.75	6.46	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5700MHz)
Test Date	:	2021/06/03

Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	64.21	74.00	-9.79	57.75	6.46	РК
2	17100.000	53.08	68.22	-15.14	39.79	13.29	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5700MHz)
Test Date	:	2021/06/03

Vertical



Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5745MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	61.98	74.00	-12.02	55.39	6.59	РК
2	17235.000	52.04	68.22	-16.18	39.21	12.83	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5745MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	47.28	54.00	-6.72	40.69	6.59	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5745MHz)
Test Date	:	2021/06/03

Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	65.74	74.00	-8.26	59.15	6.59	РК
2	17235.000	53.44	68.22	-14.78	40.61	12.83	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5745MHz)
Test Date	:	2021/06/03

Vertical



Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5785MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11570.000	62.79	74.00	-11.21	56.04	6.75	РК
2	17355.000	52.64	68.22	-15.58	39.67	12.97	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5785MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11570.000	47.64	54.00	-6.36	40.89	6.75	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5785MHz)
Test Date	:	2021/06/03

Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11570.000	65.78	74.00	-8.22	59.03	6.75	РК
2	17355.000	54.16	68.22	-14.06	41.19	12.97	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5785MHz)
Test Date	:	2021/06/03

Vertical



Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 1: Transmit (802.11a-6Mbps) (5825MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11650.000	62.08	74.00	-11.92	55.14	6.94	РК
2	17475.000	52.98	68.22	-15.24	39.91	13.07	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11650.000	47.33	54.00	-6.67	40.39	6.94	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11650.000	64.58	74.00	-9.42	57.64	6.94	РК
2	17475.000	54.82	68.22	-13.40	41.75	13.07	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11650.000	51.16	54.00	-2.84	44.22	6.94	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10360.000	59.45	68.22	-8.77	53.85	5.60	РК
2	15540.000	49.88	74.00	-24.12	39.76	10.12	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10360.000	63.24	68.22	-4.98	57.64	5.60	РК
2	15540.000	61.22	74.00	-12.78	51.10	10.12	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	15540.000	42.31	54.00	-11.69	32.19	10.12	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10440.000	61.38	68.22	-6.84	55.68	5.70	РК
2	15660.000	53.69	74.00	-20.31	43.18	10.51	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10440.000	62.84	68.22	-5.38	57.14	5.70	РК
2	15660.000	60.24	74.00	-13.76	49.73	10.51	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	15660.000	41.35	54.00	-12.65	30.84	10.51	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10480.000	58.66	68.22	-9.56	52.94	5.72	РК
2	15720.000	51.33	74.00	-22.67	40.46	10.87	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10480.000	63.34	68.22	-4.88	57.62	5.72	РК
2	15720.000	59.34	74.00	-14.66	48.47	10.87	PK

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	15720.000	41.21	54.00	-12.79	30.34	10.87	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10520.000	60.77	68.22	-7.45	55.02	5.75	РК
2	15780.000	52.13	74.00	-21.87	41.15	10.98	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10520.000	63.98	68.22	-4.24	58.23	5.75	РК
2	15780.000	58.99	74.00	-15.01	48.01	10.98	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	15780.000	41.88	54.00	-12.12	30.90	10.98	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10600.000	60.87	74.00	-13.13	55.01	5.86	РК
2	15900.000	50.11	74.00	-23.89	38.99	11.12	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10600.000	46.37	54.00	-7.63	40.51	5.86	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10600.000	65.48	74.00	-8.52	59.62	5.86	РК
2	15900.000	57.24	74.00	-16.76	46.12	11.12	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10600.000	50.89	54.00	-3.11	45.03	5.86	AV
2	15900.000	40.74	54.00	-13.26	29.62	11.12	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10640.000	60.12	74.00	-13.88	54.26	5.86	РК
2	15960.000	50.84	74.00	-23.16	39.54	11.30	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10640.000	46.33	54.00	-7.67	40.47	5.86	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10640.000	65.97	74.00	-8.03	60.11	5.86	РК
2	15960.000	54.98	74.00	-19.02	43.68	11.30	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	10640.000	50.21	54.00	-3.79	44.35	5.86	AV
2	15960.000	39.24	54.00	-14.76	27.94	11.30	AV

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	61.48	74.00	-12.52	55.71	5.77	РК
2	16500.000	51.84	68.22	-16.38	38.64	13.20	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	45.99	54.00	-8.01	40.22	5.77	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	64.85	74.00	-9.15	59.08	5.77	РК
2	16500.000	52.45	68.22	-15.77	39.25	13.20	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11000.000	50.38	54.00	-3.62	44.61	5.77	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	59.87	74.00	-14.13	53.90	5.97	РК
2	16740.000	51.79	68.22	-16.43	38.33	13.46	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	45.21	54.00	-8.79	39.24	5.97	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	64.51	74.00	-9.49	58.54	5.97	РК
2	16740.000	51.87	68.22	-16.35	38.41	13.46	РК

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11160.000	50.01	54.00	-3.99	44.04	5.97	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	59.54	74.00	-14.46	53.08	6.46	РК
2	17100.000	52.64	68.22	-15.58	39.35	13.29	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 2: Transmit (802.11ac-20BW 7.2Mbps) (5700MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	45.65	54.00	-8.35	39.19	6.46	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11400.000	63.84	74.00	-10.16	57.38	6.46	РК
2	17100.000	53.27	68.22	-14.95	39.98	13.29	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 2: Transmit (802.11ac-20BW 7.2Mbps) (5700MHz)
Test Date	:	2021/06/03

Vertical



Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 2: Transmit (802.11ac-20BW 7.2Mbps) (5720MHz)
Test Date	:	2020/06/23

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11440.000	59.63	74.00	-14.37	53.10	6.53	РК
2	17160.000	51.32	68.22	-16.90	38.24	13.08	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11440.000	45.98	54.00	-8.02	39.45	6.53	AV

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11440.000	65.12	74.00	-8.88	58.59	6.53	РК
2	17160.000	52.64	68.22	-15.58	39.56	13.08	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11440.000	50.67	54.00	-3.33	44.14	6.53	AV

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	61.85	74.00	-12.15	55.26	6.59	РК
2	17235.000	51.24	68.22	-16.98	38.41	12.83	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 2: Transmit (802.11ac-20BW 7.2Mbps) (5745MHz)
Test Date	:	2021/06/03

Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	46.99	54.00	-7.01	40.40	6.59	AV

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Vertical



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11490.000	66.97	74.00	-7.03	60.38	6.59	РК
2	17235.000	53.22	68.22	-15.00	40.39	12.83	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product	:	WCDMA/LTE/5G Mobile Phone
Test Item	:	Harmonic Radiated Emission Data
Test Mode	:	Mode 2: Transmit (802.11ac-20BW 7.2Mbps) (5745MHz)
Test Date	:	2021/06/03

Vertical



Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.

2. Emission Level = Reading Level + Correct Factor.

3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.

4. The average measurement was not performed when the peak measured data under the limit of average detection.

5. The emission levels of other frequencies are very lower than the limit and not show in test report.



Horizontal



No	Frequency	Emission	Limit	Margin	Reading Level	Correct Factor	Detector
	(MHz)	Level	(dBuV/m)	(dB)	(dBuV)	(dB)	Туре
		(dBuV/m)					
* 1	11570.000	61.84	74.00	-12.16	55.09	6.75	РК
2	17355.000	50.87	68.22	-17.35	37.90	12.97	РК

- 1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
- 2. Emission Level = Reading Level + Correct Factor.
- 3. Correct Factor = Antenna factor + Cable loss Amplifier gain.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. The emission levels of other frequencies are very lower than the limit and not show in test report.