FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AS7X-F4

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)			
0.3-3.0	614	1.63	(100)*	6			
3.0-30	1842 / f	4.89 / f	(900 / f)*	6			
30-300	61.4	0.163	1.0	6			
300-1500			F/300	6			
1500-100,000			5	6			

Note: *f* is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2	Result
2.4G WIFI	802.11b&2 437	16±1	17	50.1187	1.7022 (2.31dBi)	0.017	1	Pass
BLE	GFSK&HC H	1±1	2	1.5849	0.8551 (-0.68dBi)	0.0003	1	Pass
EDR	8DPSK&H CH	3±1	4	2.5119	0.8551 (-0.68dBi)	0.0004	1	Pass
5.2GWIFI	802.11ac4 0&5190	12±1	13	19.9526	1.6866 (2.27dBi)	0.0067	1	Pass

S=0.017/1+0.0004/1+0.0067/1=0.0241 < 1, The result is pass