

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Xi'an SuperHii Network Technology Co.,Ltd
Address of applicant: A11804,Xi'an National Digital Publishing Base,NO.996,TianGu 7th Road, High-tech Zone,Xi'an,Shaanxi Province,China

Applicant: Xi'an SuperHii Network Technology Co.,Ltd
Address of applicant: A11804,Xi'an National Digital Publishing Base,NO.996,TianGu 7th Road, High-tech Zone,Xi'an,Shaanxi Province,China

General Description of EUT:

Product Name: Smart Shopping Cart
Brand Name: /
Model No.: Trolley-S600-XXX
Adding Model(s): /
Rated Voltage: Charging Port:DC36V
Battery:DC11.1V
Battery Capacity: 83Wh
Power Adapter: /
FCC ID: 2A5Z3-LST-S02W-W02
Equipment Type: Fixed device

Technical Characteristics of EUT:	
Wi-Fi(5GHz)	
Support Standards:	802.11a, 802.11n(HT20) , 802.11n-HT40, 802.11ac-VHT80
Frequency Range:	5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
RF Output Power:	16.38dBm (Conducted)
Type of Modulation:	BPSK, QPSK,16QAM,64QAM, 256QAM
Quantity of Channels:	15
Type of Antenna:	FPC Antenna
Antenna Gain:	3dBi
Wi-Fi(2.4GHz)	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	15.20dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz

Type of Antenna:	FPC Antenna
Antenna Gain:	3dBi
Bluetooth	
Bluetooth Version:	V4.2
Frequency Range:	2402-2480MHz
RF Output Power:	5.215dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Type of Antenna:	FPC Antenna
Antenna Gain:	3dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Wi-Fi(5GHz)

Maximum Tune-Up output power: 16.5(dBm)

Maximum peak output power at antenna input terminal: 44.67(mW)

Prediction distance: >20(cm)

Prediction frequency: 5240 (MHz)

Antenna gain: 3.0 (dBi)

Directional gain (numeric gain): 2.00

The worst case is power density at prediction frequency at 20cm: 0.0177(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Wi-Fi(2.4GHz)

Maximum Tune-Up output power: 15.5(dBm)

Maximum peak output power at antenna input terminal: 35.48(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 3.0 (dBi)

Directional gain (numeric gain): 2.00

The worst case is power density at prediction frequency at 20cm: 0.0141(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Bluetooth

Maximum Tune-Up output power: 5.5(dBm)

Maximum peak output power at antenna input terminal: 3.55(mW)

Prediction distance: >20(cm)

Prediction frequency: 2441(MHz)

Antenna gain: 3.0 (dBi)

Directional gain (numeric gain): 2.00

The worst case is power density at prediction frequency at 20cm: 0.0014(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Wi-Fi(5GHz), Wi-Fi(2.4GHz) and Bluetooth is the use the same antenna cannot simultaneous transmission.

Result: Pass