

# TEST REPORT

Applicant Name : Zeeva International Limited  
 Address : Suite 1007B, 10th Floor, Exchange Tower, 33 Wang Chiu Road, Kowloon Bay, Hong Kong  
 Report Number : RA221116-54403E-RF  
 FCC ID: 2ADM5-SP-0213

**Test Standard (s)**  
 FCC PART 15.247

## Sample Description

Product Type: BT LED LANTERN SPEAKER  
 Model No.: SP-0213  
 Date Received: 2022-11-16  
 Date of Test: 2022-11-19 to 2022-11-21  
 Report Date: 2022-11-28

|              |       |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

\* In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

*Roger.Ling*

Roger.Ling  
 EMC Engineer

**Approved By:**

*Candy . Li*

Candy Li  
 EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**Shenzhen Accurate Technology Co., Ltd.**

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
 Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

|                                                                                   |           |
|-----------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION</b>                                                        | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)                                | 4         |
| OBJECTIVE                                                                         | 4         |
| TEST METHODOLOGY                                                                  | 4         |
| MEASUREMENT UNCERTAINTY                                                           | 5         |
| TEST FACILITY                                                                     | 5         |
| <b>SYSTEM TEST CONFIGURATION</b>                                                  | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION                                                 | 6         |
| EUT EXERCISE SOFTWARE                                                             | 6         |
| SPECIAL ACCESSORIES                                                               | 6         |
| EQUIPMENT MODIFICATIONS                                                           | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS                                                | 6         |
| BLOCK DIAGRAM OF TEST SETUP                                                       | 7         |
| <b>SUMMARY OF TEST RESULTS</b>                                                    | <b>8</b>  |
| <b>TEST EQUIPMENT LIST</b>                                                        | <b>9</b>  |
| <b>FCC§15.247 (i), §1.1307 (b) &amp; §2.1093 – RF EXPOSURE</b>                    | <b>10</b> |
| <b>FCC §15.203 – ANTENNA REQUIREMENT</b>                                          | <b>11</b> |
| APPLICABLE STANDARD                                                               | 11        |
| ANTENNA CONNECTOR CONSTRUCTION                                                    | 11        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS</b>                              | <b>12</b> |
| APPLICABLE STANDARD                                                               | 12        |
| EUT SETUP                                                                         | 12        |
| EMI TEST RECEIVER SETUP                                                           | 12        |
| TEST PROCEDURE                                                                    | 13        |
| FACTOR & MARGIN CALCULATION                                                       | 13        |
| TEST DATA                                                                         | 13        |
| <b>FCC §15.205, §15.209 &amp; §15.247(d) – RADIATED EMISSIONS</b>                 | <b>16</b> |
| APPLICABLE STANDARD                                                               | 16        |
| EUT SETUP                                                                         | 16        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP                                       | 17        |
| TEST PROCEDURE                                                                    | 17        |
| FACTOR & MARGIN CALCULATION                                                       | 17        |
| TEST DATA                                                                         | 17        |
| <b>FCC §15.247(a) (1)-CHANNEL SEPARATION TEST</b>                                 | <b>23</b> |
| APPLICABLE STANDARD                                                               | 23        |
| TEST PROCEDURE                                                                    | 23        |
| TEST DATA                                                                         | 23        |
| <b>FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH &amp; 99% OCCUPIED BANDWIDTH</b> | <b>26</b> |
| APPLICABLE STANDARD                                                               | 26        |
| TEST PROCEDURE                                                                    | 26        |
| TEST DATA                                                                         | 27        |
| <b>FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST</b>                  | <b>37</b> |
| APPLICABLE STANDARD                                                               | 37        |
| TEST PROCEDURE                                                                    | 37        |

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| TEST DATA .....                                                       | 37        |
| <b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b> | <b>40</b> |
| APPLICABLE STANDARD .....                                             | 40        |
| TEST PROCEDURE .....                                                  | 40        |
| TEST DATA .....                                                       | 40        |
| <b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....</b>        | <b>50</b> |
| APPLICABLE STANDARD .....                                             | 50        |
| TEST PROCEDURE .....                                                  | 50        |
| TEST DATA .....                                                       | 50        |
| <b>FCC §15.247(d) - BAND EDGES TESTING .....</b>                      | <b>56</b> |
| APPLICABLE STANDARD .....                                             | 56        |
| TEST PROCEDURE .....                                                  | 56        |
| TEST DATA .....                                                       | 56        |

---

**GENERAL INFORMATION**

---

**Product Description for Equipment under Test (EUT)**

|                                     |                                                       |
|-------------------------------------|-------------------------------------------------------|
| Product Type                        | BT LED LANTERN SPEAKER                                |
| Tested Model                        | SP-0213                                               |
| UPC                                 | 1922343400691                                         |
| SKU                                 | 7395143                                               |
| Frequency Range                     | 2402~2480MHz                                          |
| Maximum conducted Peak output power | -1.1dBm                                               |
| Modulation Technique                | BDR/EDR( $\pi/4$ -DQPSK)/EDR(8DPSK)                   |
| Antenna Specification*              | Internal Antenna: -1.63dBi(provided by the applicant) |
| Voltage Range                       | DC3.7V from battery or 5V from USB port               |
| Sample number                       | RA221116-54403E-RF-S1 (Assigned by ATC, Shenzhen)     |
| Sample/EUT Status                   | Good condition                                        |

**Objective**

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

**Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

| Parameter                          |                 | Uncertainty            |
|------------------------------------|-----------------|------------------------|
| Occupied Channel Bandwidth         |                 | 5%                     |
| RF Frequency                       |                 | $0.082 \times 10^{-7}$ |
| RF output power, conducted         |                 | 0.73dB                 |
| Unwanted Emission, conducted       |                 | 1.6dB                  |
| AC Power Lines Conducted Emissions |                 | 2.72dB                 |
| Emissions,<br>Radiated             | 30MHz - 1GHz    | 4.28dB                 |
|                                    | 1GHz - 18GHz    | 4.98dB                 |
|                                    | 18GHz - 26.5GHz | 5.06dB                 |
| Temperature                        |                 | 1°C                    |
| Humidity                           |                 | 6%                     |
| Supply voltages                    |                 | 0.4%                   |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 5077A.

---

## SYSTEM TEST CONFIGURATION

---

### Description of Test Configuration

The system was configured for testing in an engineering mode.

### EUT Exercise Software

Software “FCC1.0.2.2”\* was used during testing and the power level was 10\*.

### Special Accessories

N/A.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


| Manufacturer | Description | Model        | Serial Number  |
|--------------|-------------|--------------|----------------|
| HUAWEI       | Adapter     | HW-050100C01 | H779KBK6V19398 |

### External I/O Cable


| Cable Description               | Length(m) | From/Port | To      |
|---------------------------------|-----------|-----------|---------|
| Unshielded Detachable USB Cable | 0.3       | EUT       | Adapter |

## Block Diagram of Test Setup

For conducted emission:



For radiated emission:



---

**SUMMARY OF TEST RESULTS**

---

| FCC Rules                     | Description of Test                               | Result    |
|-------------------------------|---------------------------------------------------|-----------|
| §15.247(i), §1.1307(b)        | RF Exposure                                       | Compliant |
| §15.203                       | Antenna Requirement                               | Compliant |
| §15.207(a)                    | AC Line Conducted Emissions                       | Compliant |
| §15.205, §15.209 & §15.247(d) | Radiated Emissions                                | Compliant |
| §15.247(a)(1)                 | 20 dB Emission Bandwidth & 99% Occupied Bandwidth | Compliant |
| §15.247(a)(1)                 | Channel Separation Test                           | Compliant |
| §15.247(a)(1)(iii)            | Time of Occupancy (Dwell Time)                    | Compliant |
| §15.247(a)(1)(iii)            | Quantity of hopping channel Test                  | Compliant |
| §15.247(b)(1)                 | Peak Output Power Measurement                     | Compliant |
| §15.247(d)                    | Band edges                                        | Compliant |

**TEST EQUIPMENT LIST**

| Manufacturer                                     | Description                  | Model                | Serial Number      | Calibration Date | Calibration Due Date |
|--------------------------------------------------|------------------------------|----------------------|--------------------|------------------|----------------------|
| Conducted Emission Test                          |                              |                      |                    |                  |                      |
| Rohde & Schwarz                                  | EMI Test Receiver            | ESCI                 | 100784             | 2021/12/13       | 2022/12/12           |
| Rohde & Schwarz                                  | L.I.S.N.                     | ENV216               | 101314             | 2021/12/13       | 2022/12/12           |
| Anritsu Corp                                     | 50 Coaxial Switch            | MP59B                | 6100237248         | 2021/12/13       | 2022/12/12           |
| Unknown                                          | RF Coaxial Cable             | No.17                | N0350              | 2021/12/14       | 2022/12/13           |
| Conducted Emission Test Software: e3 19821b (V9) |                              |                      |                    |                  |                      |
| Radiated Emissions Test                          |                              |                      |                    |                  |                      |
| Rohde & Schwarz                                  | Test Receiver                | ESR                  | 102725             | 2021/12/13       | 2022/12/12           |
| Rohde & Schwarz                                  | Spectrum Analyzer            | FSV40                | 101949             | 2021/12/13       | 2022/12/12           |
| SONOMA INSTRUMENT                                | Amplifier                    | 310 N                | 186131             | 2022/11/08       | 2023/11/07           |
| A.H. Systems, inc.                               | Preamplifier                 | PAM-0118P            | 135                | 2022/11/08       | 2023/11/07           |
| Quinstar                                         | Amplifier                    | QLW-184055<br>36-J0  | 15964001002        | 2022/11/08       | 2023/11/07           |
| Schwarzbeck                                      | Bilog Antenna                | VULB9163             | 9163-323           | 2021/07/06       | 2024/07/05           |
| Schwarzbeck                                      | Horn Antenna                 | BBHA9120D            | 9120D-1067         | 2020/01/05       | 2023/01/04           |
| Schwarzbeck                                      | HORN ANTENNA                 | BBHA9170             | 9170-359           | 2020/01/05       | 2023/01/04           |
| Wainwright                                       | High Pass Filter             | WHKX3.6/18<br>G-10SS | 5                  | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.10                | N050               | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.11                | N1000              | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.12                | N040               | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.13                | N300               | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.14                | N800               | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.15                | N600               | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.16                | N650               | 2021/12/14       | 2022/12/13           |
| Radiated Emission Test Software: e3 19821b (V9)  |                              |                      |                    |                  |                      |
| RF Conducted Test                                |                              |                      |                    |                  |                      |
| Rohde & Schwarz                                  | Spectrum Analyzer            | FSV-40               | 101495             | 2021/12/13       | 2022/12/12           |
| Rohde & Schwarz                                  | Open Switch and Control Unit | OSP120 +<br>OSP-B157 | 101244 +<br>100866 | 2021/12/13       | 2022/12/12           |
| WEINSCHTEL                                       | 10dB Attenuator              | 5324                 | AU 3842            | 2021/12/14       | 2022/12/13           |
| Unknown                                          | RF Coaxial Cable             | No.33                | RF-03              | Each time        |                      |

**\* Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC§15.247 (i), §1.1307 (b) & §2.1093 – RF EXPOSURE

### Applicable Standard

According to FCC §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2 – 1-mW test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

### Test Result

For worst case:

| Mode    | Frequency | Maximum Tune-up Conducted Power |      | 1-mW test Exemption |
|---------|-----------|---------------------------------|------|---------------------|
|         | (MHz)     | (dBm)                           | (mW) |                     |
| BDR/EDR | 2402-2480 | 0                               | 1    | Yes                 |

Note: The tune-up power was declared by the applicant.

**Result:** Compliant.

---

**FCC §15.203 – ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**Antenna Connector Construction**

The EUT has one Internal Antenna arrangement, which was permanently attached and the antenna gain is -1.63dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

## Test Data


### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 23°C   |
| Relative Humidity: | 60%    |
| ATM Pressure:      | 101kPa |

*The testing was performed by Lipa Wu on 2022-11-19.*

*EUT operation mode: BT Transmitting*


## AC 120V/60 Hz, Line



Site : Shielding Room  
Condition: Line  
Job No. : RA221116-54403E-RF  
Mode : Charging + BT  
Power : AC 120V 60Hz

|    | Freq  | Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|--------|------------|-------|------------|------------|---------|
|    | MHz   | dB     | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.162 | 9.80   | 33.71      | 43.51 | 55.34      | -11.83     | Average |
| 2  | 0.162 | 9.80   | 44.81      | 54.61 | 65.34      | -10.73     | QP      |
| 3  | 0.169 | 9.80   | 20.20      | 30.00 | 54.99      | -24.99     | Average |
| 4  | 0.169 | 9.80   | 35.14      | 44.94 | 64.99      | -20.05     | QP      |
| 5  | 0.239 | 9.80   | 22.63      | 32.43 | 52.14      | -19.71     | Average |
| 6  | 0.239 | 9.80   | 36.70      | 46.50 | 62.14      | -15.64     | QP      |
| 7  | 0.337 | 9.80   | 15.83      | 25.63 | 49.29      | -23.66     | Average |
| 8  | 0.337 | 9.80   | 32.00      | 41.80 | 59.29      | -17.49     | QP      |
| 9  | 0.557 | 9.81   | 32.34      | 42.15 | 46.00      | -3.85      | Average |
| 10 | 0.557 | 9.81   | 36.03      | 45.84 | 56.00      | -10.16     | QP      |
| 11 | 1.671 | 9.82   | 29.57      | 39.39 | 46.00      | -6.61      | Average |
| 12 | 1.671 | 9.82   | 30.25      | 40.07 | 56.00      | -15.93     | QP      |
| 13 | 2.785 | 9.83   | 32.86      | 42.69 | 46.00      | -3.31      | Average |
| 14 | 2.785 | 9.83   | 34.19      | 44.02 | 56.00      | -11.98     | QP      |
| 15 | 3.896 | 9.84   | 20.76      | 30.60 | 46.00      | -15.40     | Average |
| 16 | 3.896 | 9.84   | 35.22      | 45.06 | 56.00      | -10.94     | QP      |
| 17 | 5.011 | 9.85   | 26.01      | 35.86 | 50.00      | -14.14     | Average |
| 18 | 5.011 | 9.85   | 30.39      | 40.24 | 60.00      | -19.76     | QP      |

## AC 120V/60 Hz, Neutral





Site : Shielding Room  
Condition: Neutral  
Job No. : RA221116-54403E-RF  
Mode : Charging + BT  
Power : AC 120V 60Hz

|    | Freq  | Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|--------|------------|-------|------------|------------|---------|
|    | MHz   | dB     | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.158 | 9.80   | 29.23      | 39.03 | 55.59      | -16.56     | Average |
| 2  | 0.158 | 9.80   | 43.36      | 53.16 | 65.59      | -12.43     | QP      |
| 3  | 0.168 | 9.80   | 23.26      | 33.06 | 55.08      | -22.02     | Average |
| 4  | 0.168 | 9.80   | 36.54      | 46.34 | 65.08      | -18.74     | QP      |
| 5  | 0.236 | 9.80   | 19.55      | 29.35 | 52.22      | -22.87     | Average |
| 6  | 0.236 | 9.80   | 34.43      | 44.23 | 62.22      | -17.99     | QP      |
| 7  | 0.317 | 9.80   | 16.39      | 26.19 | 49.78      | -23.59     | Average |
| 8  | 0.317 | 9.80   | 31.46      | 41.26 | 59.78      | -18.52     | QP      |
| 9  | 0.557 | 9.81   | 33.57      | 43.38 | 46.00      | -2.62      | Average |
| 10 | 0.557 | 9.81   | 37.20      | 47.01 | 56.00      | -8.99      | QP      |
| 11 | 1.674 | 9.82   | 33.17      | 42.99 | 46.00      | -3.01      | Average |
| 12 | 1.674 | 9.82   | 35.46      | 45.28 | 56.00      | -10.72     | QP      |
| 13 | 2.791 | 9.83   | 31.27      | 41.10 | 46.00      | -4.90      | Average |
| 14 | 2.791 | 9.83   | 35.58      | 45.41 | 56.00      | -10.59     | QP      |
| 15 | 3.907 | 9.84   | 28.76      | 38.60 | 46.00      | -7.40      | Average |
| 16 | 3.907 | 9.84   | 34.22      | 44.06 | 56.00      | -11.94     | QP      |
| 17 | 5.021 | 9.89   | 29.38      | 39.27 | 50.00      | -10.73     | Average |
| 18 | 5.021 | 9.89   | 34.13      | 44.02 | 60.00      | -15.98     | QP      |

**FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS****Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

**EUT Setup****Below 1 GHz:****Above 1GHz:**

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Measurement |
|-------------------|---------|-----------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz   | 120 kHz | QP          |
| Above 1 GHz       | 1 MHz   | 3 MHz     | /       | PK          |

For average measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ ,

Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulse, etc.

Average Emission Level=Peak Emission Level+20\*log(Duty cycle)

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform QP/Average measurement.

## Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## Test Data


### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 24 °C  |
| Relative Humidity: | 58 %   |
| ATM Pressure:      | 101kPa |

The testing was performed by Jason Liu on 2022-11-19.

EUT operation mode: BT Transmitting

(Scan with GFSK,  $\pi/4$ -DQPSK, 8DPSK mode at X axis, Y axis, Z axis, the worst case is 8DPSK Mode at Y axis)

**Below 1GHz: 8DPSK, High Channel:****Horizontal**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA221116-54403E-RF

Test Mode: BT Transmitting

|   | Freq    | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|---------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz     | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 49.208  | -9.95  | 31.31         | 21.36  | 40.00         | -18.64        | Peak   |
| 2 | 138.691 | -15.38 | 50.53         | 35.15  | 43.50         | -8.35         | Peak   |
| 3 | 148.767 | -15.34 | 53.10         | 37.76  | 43.50         | -5.74         | QP     |
| 4 | 158.737 | -14.39 | 52.40         | 38.01  | 43.50         | -5.49         | QP     |
| 5 | 161.616 | -14.27 | 54.50         | 40.23  | 43.50         | -3.27         | QP     |
| 6 | 317.562 | -8.59  | 41.46         | 32.87  | 46.00         | -13.13        | Peak   |

## Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : RA221116-54403E-RF  
Test Mode: BT Transmitting

|   | Freq    | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|---------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz     | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 49.057  | -9.96  | 42.61         | 32.65  | 40.00         | -7.35         | QP     |
| 2 | 155.024 | -14.93 | 52.42         | 37.49  | 43.50         | -6.01         | Peak   |
| 3 | 158.320 | -14.45 | 52.29         | 37.84  | 43.50         | -5.66         | QP     |
| 4 | 161.616 | -14.27 | 52.60         | 38.33  | 43.50         | -5.17         | QP     |
| 5 | 480.107 | -5.00  | 40.47         | 35.47  | 46.00         | -10.53        | Peak   |
| 6 | 829.673 | 0.04   | 37.75         | 37.79  | 46.00         | -8.21         | Peak   |

**Above 1GHz (worst case for 8DPSK):**

| Frequency<br>(MHz) | Receiver          |        | Turntable<br>Angle<br>Degree | Rx Antenna    |                | Factor<br>(dB/m) | Absolute<br>Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|------------------------------|---------------|----------------|------------------|-------------------------------|-------------------|----------------|
|                    | Reading<br>(dBuV) | PK/Ave |                              | Height<br>(m) | Polar<br>(H/V) |                  |                               |                   |                |
| Low Channel        |                   |        |                              |               |                |                  |                               |                   |                |
| 2310               | 47.09             | PK     | 235                          | 1.1           | H              | -7.23            | 39.86                         | 74                | -34.14         |
| 2310               | 48.03             | PK     | 103                          | 1.7           | V              | -7.23            | 40.8                          | 74                | -33.2          |
| 2390               | 50.07             | PK     | 0                            | 2.0           | H              | -7.21            | 42.86                         | 74                | -31.14         |
| 2390               | 51.13             | PK     | 223                          | 1.2           | V              | -7.21            | 43.92                         | 74                | -30.08         |
| 4804               | 51.15             | PK     | 157                          | 1.6           | H              | -3.52            | 47.63                         | 74                | -26.37         |
| 4804               | 50.99             | PK     | 138                          | 1.7           | V              | -3.52            | 47.47                         | 74                | -26.53         |
| Middle Channel     |                   |        |                              |               |                |                  |                               |                   |                |
| 4882               | 52.54             | PK     | 235                          | 2.0           | H              | -3.37            | 49.17                         | 74                | -24.83         |
| 4882               | 50.9              | PK     | 57                           | 1.4           | V              | -3.37            | 47.53                         | 74                | -26.47         |
| High Channel       |                   |        |                              |               |                |                  |                               |                   |                |
| 2483.5             | 54.77             | PK     | 352                          | 1.9           | H              | -7.2             | 47.57                         | 74                | -26.43         |
| 2483.5             | 57.26             | PK     | 331                          | 1.4           | V              | -7.2             | 50.06                         | 74                | -23.94         |
| 2500               | 52.81             | PK     | 149                          | 2.0           | H              | -7.18            | 45.63                         | 74                | -28.37         |
| 2500               | 54.42             | PK     | 270                          | 1.5           | V              | -7.18            | 47.24                         | 74                | -26.76         |
| 4960               | 54.17             | PK     | 169                          | 2.2           | H              | -3.01            | 51.16                         | 74                | -22.84         |
| 4960               | 53.14             | PK     | 341                          | 1.8           | V              | -3.01            | 50.13                         | 74                | -23.87         |

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level (Corrected Amplitude) – Limit


The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

**Worst case for  $\pi/4$ -DQPSK, Middle Channel:**

**Horizontal**




**Vertical**




**18-25GHz:** (Pre-Scan plots)

**Worst case for  $\pi/4$ -DQPSK, Middle Channel:**

**Horizontal**



**Vertical**




## FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### Test Procedure

1. Set the EUT in TX mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.



### Test Data

#### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 24°C   |
| Relative Humidity: | 48%    |
| ATM Pressure:      | 101kPa |

The testing was performed by Glenn Jiang on 2022-11-21.

EUT operation mode: Transmitting


Test Result: Compliant.

| Test Mode | Antenna | Channel | Result[MHz] | Limit[MHz]   | Verdict |
|-----------|---------|---------|-------------|--------------|---------|
| DH5       | Ant1    | Hop     | 1           | $\geq 0.636$ | PASS    |
| 2DH5      | Ant1    | Hop     | 1.003       | $\geq 0.879$ | PASS    |
| 3DH5      | Ant1    | Hop     | 1.003       | $\geq 0.866$ | PASS    |


Note: The limit =  $(2/3) * 20\text{dB bandwidth}$

Please refer to the below plots:


## DH5\_Ant1\_Hop



## 2DH5\_Ant1\_Hop



## 3DH5\_Ant1\_Hop



Date: 21.NOV.2022 10:24:34

## FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


### Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not TX continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



**Test Data****Environmental Conditions**

|                           |        |
|---------------------------|--------|
| <b>Temperature:</b>       | 24°C   |
| <b>Relative Humidity:</b> | 48%    |
| <b>ATM Pressure:</b>      | 101kPa |

The testing was performed by Glenn Jiang on 2022-11-21.


EUT operation mode: Transmitting

Test Result: Compliant.

| TestMode | Antenna | Channel | 20db EBW[MHz] | 99% OCCUPIED BANDWIDTH[MHz] | Verdict |
|----------|---------|---------|---------------|-----------------------------|---------|
| DH5      | Ant1    | 2402    | 0.954         | 0.869                       | PASS    |
|          |         | 2441    | 0.954         | 0.872                       | PASS    |
|          |         | 2480    | 0.954         | 0.869                       | PASS    |
| 2DH5     | Ant1    | 2402    | 1.318         | 1.175                       | PASS    |
|          |         | 2441    | 1.318         | 1.175                       | PASS    |
|          |         | 2480    | 1.314         | 1.178                       | PASS    |
| 3DH5     | Ant1    | 2402    | 1.293         | 1.178                       | PASS    |
|          |         | 2441    | 1.296         | 1.181                       | PASS    |
|          |         | 2480    | 1.299         | 1.184                       | PASS    |

Please refer to the below plots:

## 20 dB EMISSION BANDWIDTH\_DH5\_Ant1\_2402




Date: 21.NOV.2022 09:56:16

## 99% OCCUPIED BANDWIDTH\_DH5\_Ant1\_2402




Date: 21.NOV.2022 09:56:33

## 20 dB EMISSION BANDWIDTH\_DH5 \_Ant1\_2441




Date: 21.NOV.2022 10:00:44

## 99% OCCUPIED BANDWIDTH\_DH5 \_Ant1\_2441




Date: 21.NOV.2022 10:01:01


## 20 dB EMISSION BANDWIDTH\_DH5 \_Ant1\_2480



## 99% OCCUPIED BANDWIDTH\_DH5 \_Ant1\_2480



## 20 dB EMISSION BANDWIDTH\_2DH5\_Ant1\_2402




Date: 21.NOV.2022 10:05:26

## 99% OCCUPIED BANDWIDTH\_2DH5\_Ant1\_2402



Date: 21.NOV.2022 10:05:43


## 20 dB EMISSION BANDWIDTH\_2DH5\_Ant1\_2441




## 99% OCCUPIED BANDWIDTH\_2DH5\_Ant1\_2441




## 20 dB EMISSION BANDWIDTH \_2DH5\_Ant1\_2480



## 99% OCCUPIED BANDWIDTH \_2DH5\_Ant1\_2480




## 20 dB EMISSION BANDWIDTH \_3DH5\_Ant1\_2402




Date: 21.NOV.2022 10:09:15

## 99% OCCUPIED BANDWIDTH \_3DH5\_Ant1\_2402




Date: 21.NOV.2022 10:09:32

## 20 dB EMISSION BANDWIDTH \_3DH5\_Ant1\_2441




Date: 21.NOV.2022 10:10:19

## 99% OCCUPIED BANDWIDTH \_3DH5\_Ant1\_2441




Date: 21.NOV.2022 10:10:36

## 20 dB EMISSION BANDWIDTH \_3DH5\_Ant1\_2480



## 99% OCCUPIED BANDWIDTH \_3DH5\_Ant1\_2480




## FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.



### Test Data

#### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 24°C   |
| Relative Humidity: | 48%    |
| ATM Pressure:      | 101kPa |

The testing was performed by Glenn Jiang on 2022-11-21.


EUT operation mode: Transmitting

Test Result: Compliant.

| Test Mode | Antenna | Channel | Result[Num] | Limit[Num] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5       | Ant1    | Hop     | 79          | >=15       | PASS    |
| 2DH5      | Ant1    | Hop     | 79          | >=15       | PASS    |
| 3DH5      | Ant1    | Hop     | 79          | >=15       | PASS    |


Please refer to the below plots:

## DH5\_Ant1\_Hop




Date: 21.NOV.2022 10:14:34

## 2DH5\_Ant1\_Hop



Date: 21.NOV.2022 10:20:13

3DH5\_Ant1\_Hop




Date: 21.NOV.2022 10:25:48

**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

**Test Data****Environmental Conditions**

|                           |        |
|---------------------------|--------|
| <b>Temperature:</b>       | 24°C   |
| <b>Relative Humidity:</b> | 48%    |
| <b>ATM Pressure:</b>      | 101kPa |

The testing was performed by Glenn. Jiang on 2022-11-21.

EUT operation mode: Transmitting

Test Result: Compliant.


| Test Mode | Antenna | Channel | Burst Width [ms] | Total Hops [Num] | Result[s] | Limit[s]   | Verdict |
|-----------|---------|---------|------------------|------------------|-----------|------------|---------|
| DH1       | Ant1    | Hop     | 0.37             | 330              | 0.122     | $\leq 0.4$ | PASS    |
| DH3       | Ant1    | Hop     | 1.62             | 140              | 0.227     | $\leq 0.4$ | PASS    |
| DH5       | Ant1    | Hop     | 2.86             | 110              | 0.315     | $\leq 0.4$ | PASS    |
| 2DH1      | Ant1    | Hop     | 0.38             | 330              | 0.125     | $\leq 0.4$ | PASS    |
| 2DH3      | Ant1    | Hop     | 1.63             | 160              | 0.261     | $\leq 0.4$ | PASS    |
| 2DH5      | Ant1    | Hop     | 2.87             | 130              | 0.373     | $\leq 0.4$ | PASS    |
| 3DH1      | Ant1    | Hop     | 0.38             | 320              | 0.122     | $\leq 0.4$ | PASS    |
| 3DH3      | Ant1    | Hop     | 1.63             | 170              | 0.277     | $\leq 0.4$ | PASS    |
| 3DH5      | Ant1    | Hop     | 2.87             | 130              | 0.373     | $\leq 0.4$ | PASS    |

Note 1: A period time =  $0.4 \times 79 = 31.6(s)$ , Result = Burst Width \* Total Hops


Note 2: Total Hops = Hopping Number in  $3.16s \times 10$

Note 3: Hopping Number in 3.16s = Total of highest signals in 3.16s (Second high signals were other channel)

## DH1\_Ant1\_Hop




Date: 21.NOV.2022 10:16:44




Date: 21.NOV.2022 10:16:49

## DH3\_Ant1\_Hop




Date: 21.NOV.2022 10:16:16




Date: 21.NOV.2022 10:16:21

## DH5\_Ant1\_Hop




Date: 21.NOV.2022 10:15:48




Date: 21.NOV.2022 10:15:53

## 2DH1\_Ant1\_Hop




Date: 21.NOV.2022 10:21:29




Date: 21.NOV.2022 10:21:34

## 2DH3\_Ant1\_Hop




Date: 21.NOV.2022 10:21:03




Date: 21.NOV.2022 10:21:09

## 2DH5\_Ant1\_Hop




Date: 21.NOV.2022 10:20:31




Date: 21.NOV.2022 10:20:37

## 3DH1\_Ant1\_Hop




Date: 21.NOV.2022 10:26:56




Date: 21.NOV.2022 10:27:01

## 3DH3\_Ant1\_Hop




Date: 21.NOV.2022 10:26:31




Date: 21.NOV.2022 10:26:36

## 3DH5\_Ant1\_Hop



Date: 21.NOV.2022 10:26:04



Date: 21.NOV.2022 10:26:09


## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### Test Procedure

1. Place the EUT on a bench and set in TX mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 24°C   |
| Relative Humidity: | 48%    |
| ATM Pressure:      | 101kPa |

The testing was performed by Glenn Jiang on 2022-11-21.


EUT operation mode: Transmitting

Test Result: Compliant.

| Test Mode | Antenna | Channel | Conducted peak output power [dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-----------------------------------|------------|---------|
| DH5       | Ant1    | 2402    | -4.32                             | <=20.97    | PASS    |
|           |         | 2441    | -2.93                             | <=20.97    | PASS    |
|           |         | 2480    | -2.33                             | <=20.97    | PASS    |
| 2DH5      | Ant1    | 2402    | -3.33                             | <=20.97    | PASS    |
|           |         | 2441    | -2.09                             | <=20.97    | PASS    |
|           |         | 2480    | -1.53                             | <=20.97    | PASS    |
| 3DH5      | Ant1    | 2402    | -2.83                             | <=20.97    | PASS    |
|           |         | 2441    | -1.57                             | <=20.97    | PASS    |
|           |         | 2480    | <b>-1.10</b>                      | <=20.97    | PASS    |


Please refer to the below plots:

## DH5\_Ant1\_2402




Date: 21.NOV.2022 09:54:37

## DH5\_Ant1\_2441




Date: 21.NOV.2022 09:54:06

## DH5\_Ant1\_2480




Date: 21.NOV.2022 09:55:01

## 2DH5\_Ant1\_2402




Date: 21.NOV.2022 09:55:23


## 2DH5\_Ant1\_2441



## 2DH5\_Ant1\_2480




## 3DH5\_Ant1\_2402




Date: 21.NOV.2022 09:56:18

## 3DH5\_Ant1\_2441



Date: 21.NOV.2022 09:56:44

3DH5\_Ant1\_2480



Date: 21.NOV.2022 09:57:09


## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in TX mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Data

#### Environmental Conditions

|                    |        |
|--------------------|--------|
| Temperature:       | 24°C   |
| Relative Humidity: | 48%    |
| ATM Pressure:      | 101kPa |


The testing was performed by Glenn Jiang on 2022-11-21.

EUT operation mode: Transmitting

Test Result: Compliant


Please refer to the below plots:

### DH5: Band Edge-Left Side Hopping




Date: 21.NOV.2022 10:12:57

### Single




Date: 21.NOV.2022 09:58:48


### DH5: Band Edge- Right Side Hopping




### Single




### 2DH5: Band Edge-Left Side Hopping



### Single




## 2DH5: Band Edge- Right Side Hopping




Date: 21.NOV.2022 10:22:29

## Single




Date: 21.NOV.2022 10:08:31

3DH5: Band Edge-Left Side Hopping




Date: 21.NOV.2022 10:23:30

Single




Date: 21.NOV.2022 10:09:47

### 3DH5: Band Edge- Right Side Hopping



Date: 21.NOV.2022 10:27:50

### Single



Date: 21.NOV.2022 10:11:48

\*\*\*\*\* END OF REPORT \*\*\*\*\*