



Caution:

Use only with Class 2 power unit for charging.
Utiliser uniquement avec une alimentation de classe 2 pour recharger.
Usar sólo con la unidad de alimentación Clase 2 para recargar.
For wall-calling/under cabinet/shelf mount! Suitable for installation in the Storage Area of a Chiller Case.
Pour mur/plafond/dessous de meuble/vitrine.
Convenit pour une installation dans la zone de rangement d'un placard à vitrines.
Para montaje en pared/rack/diapo armario/vitrinas.
Atención para instalación en zonas de almacenamiento de armario vitrina.
Replace battery with RCA L200A type (RCA L 2V 2400mAh).

Conforms to: UL Std 2108 Certified to CSA Std C22.2 No. 8.0 CAN ICES-005 (B) /NMB-005 (B) This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.FCC ID:F10-L200A

Made in Xxxx.
RCA of Sweden AB, SE - 34181 Årehus
IC60-TVA
© 1999 RCA Systems B.V. 2018



Type No. L200A-NOLVATTEN
XXXXX
Y04 5 V DC 3.2 W Battery input 4.8 V DC
20W AAAA 1.5V XXXXX

