Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\left[\sqrt{f(GHZ)}\right] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	8.93	7.82	8.5±1	9.5	8.91	<5	2.76834	3.00	YES
	2.437	8.91	7.78	8.5±1	9.5	8.91	<5	2.78264	3.00	YES
	2.462	8.4	6.92	8.5±1	9.5	8.91	<5	2.79688	3.00	YES
802.11g	2.412	7.97	6.27	7.5±1	8.5	7.08	<5	2.19897	3.00	YES
	2.437	7.87	6.12	7.5±1	8.5	7.08	<5	2.21033	3.00	YES
	2.462	7.82	6.05	7.5±1	8.5	7.08	<5	2.22164	3.00	YES
802.11n H20	2.412	7.14	5.18	6.5±1	7.5	5.62	<5	1.74670	3.00	YES
	2.437	6.66	4.63	6.5±1	7.5	5.62	<5	1.75573	3.00	YES
	2.462	6.62	4.59	6.5±1	7.5	5.62	<5	1.76471	3.00	YES

Conclusion:

For the max result : 2.79688≤3.0 for 1g SAR, SAR is not required.

Alw Signature:

Date: 2023-05-18

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.