APPLICANT : Ring LLC

EQUIPMENT: Spotlight Cam Pro

BRAND NAME : Ring MODEL NAME : 5E62E9

FCC ID : 2AEUPBHASP001

STANDARD : FCC Part 15 Subpart E §15.407

CLASSIFICATION: (NII) Unlicensed National Information Infrastructure

TEST DATE(S) : Jul. 27, 2022 ~ Jul. 31, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

JasonJia

Approved by: Jason Jia





Report No.: FR1D0812-01G

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Page Number : 1 of 16
Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAR	Y OF TEST RESULT	4
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	5
	1.6	Testing Location	6
	1.7	Test Software	6
	1.8	Applicable Standards	6
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency and Channel	7
	2.2	Test Mode	7
	2.3	Connection Diagram of Test System	8
	2.4	EUT Operation Test Setup	8
3	TEST	RESULT	9
	3.1	Maximum Conducted Output Power Measurement	9
	3.2	Unwanted Emissions Measurement	11
4	LIST	OF MEASURING EQUIPMENT	15
5	UNC	ERTAINTY OF EVALUATION	16
ΑP	PEND	IX A. RADIATED SPURIOUS EMISSION	
ΑP	PEND	X B. DUTY CYCLE PLOTS	
۸D	DENID	IX C SETUD DHOTOGD ADUS	

Report No.: FR1D0812-01G

REVISION HISTORY

Report No. : FR1D0812-01G

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE	
FR1D0812-01G	Rev. 01	Initial issue of report	Oct. 12, 2022	

 Sporton International Inc. (Kunshan)
 Page Number
 : 3 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

SUMMARY OF TEST RESULT

Report No.: FR1D0812-01G

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	3.1 15.407(a) Maximum Conducted Output Power		≤ 30 dBm	Pass	-
3.2	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 9.14 dB at 11650.00 MHz

Note: This is a variant report for 5E62E9, the change note could be referred to 5E62E9_Operational Description of Product Equality Declaration which is exhibit separately. According to the change, the worst cases of conducted power and RSE from original report; all the other test cases are leveraged from original report FR1D0812G.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Report Version : Rev. 01

Page Number

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

: 4 of 16

1 General Description

1.1 Applicant

Ring LLC

12515 Cerise Ave, Hawthorne, CA 90250 USA

1.2 Manufacturer

Goertek Inc.

No.268 Dongfang Road High-Tech Industrial Development District, Weifang Shandong, China

1.3 Product Feature of Equipment Under Test

Product Feature					
Equipment	Spotlight Cam Pro				
Brand Name	Ring				
Model Name	5E62E9				
FCC ID	2AEUPBHASP001				
HW Version	DVT2				
SW Version	1.5.17				
EUT Stage	Identical Prototype				

Report No.: FR1D0812-01G

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification					
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz				
Maximum Output Power	<5745 MHz ~ 5825 MHz> 802.11a : 15.21 dBm / 0.0332 W 802.11n HT20 : 14.97 dBm / 0.0314 W				
Type of Modulation	802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)				
Antenna Type / Gain	Stamping antenna with gain 4.51 dBi				

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

 Sporton International Inc. (Kunshan)
 Page Number
 : 5 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Report No.: FR1D0812-01G

Test Firm	Sporton International Inc. (Kunshan)						
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL: +86-512-57900158 FAX: +86-512-57900958						
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.				
Test Site No.	03CH03-KS TH01-KS	CN1257	314309				

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-KS	AUDIX	E3	6.2009-8-24a

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 Sporton International Inc. (Kunshan)
 Page Number
 : 6 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

Report No.: FR1D0812-01G

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745 5005 MIL	149	5745	161	5805
5745-5825 MHz U-NII-3	153	5765	165	5825
O-IVII-3	157	5785	-	-

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate	
802.11a	6 Mbps	


	Ch. #	U-NII-3:5745-5825 MHz
	CII. #	802.11a
L	Low	-
M	Middle	-
Н	High	165

 Sporton International Inc. (Kunshan)
 Page Number
 : 7 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

: 8 of 16

Page Number

Report No.: FR1D0812-01G

3 Test Result

3.1 Maximum Conducted Output Power Measurement

3.1.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.1.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

- 1. Measurement is performed using a wideband RF power meter.
- 2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
- 3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.1.4 Test Setup



Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Page Number : 9 of 16
Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

Report No.: FR1D0812-01G

3.1.5 Test Result of Maximum Conducted Output Power

	U-NII-3									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	_	Pass/Fail
11a	6Mbps	1	165	5825	0.08	15.21	30.00	4.51	_	Pass
HT20	MCS0	1	165	5825	0.08	14.97	30.00	4.51	_	Pass

Report No.: FR1D0812-01G

: 10 of 16

Sporton International Inc. (Kunshan) Page Number TEL: +86-512-57900158 Report Issued Date: Oct. 12, 2022

Report Version : Rev. 01 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4

3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

Report No.: FR1D0812-01G

3.2.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band: 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBµV/m

d_{Meas} is the measurement distance, in m

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

 Sporton International Inc. (Kunshan)
 Page Number
 : 11 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

3.2.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
 Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW ≥ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
- 2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- 4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- 5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Sporton International Inc. (Kunshan)


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Page Number : 12 of 16
Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

Report No.: FR1D0812-01G


SPURION LAB. 1 CO IV. 1 COL IVOPO

3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Page Number : 13 of 16
Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

Report No.: FR1D0812-01G

3.2.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Report No.: FR1D0812-01G

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.2.6 Test Result of Radiated Band Edges

Please refer to Appendix A.

3.2.7 Duty Cycle

Please refer to Appendix B.

3.2.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix A.

 Sporton International Inc. (Kunshan)
 Page Number
 : 14 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 05, 2021	Jul. 31, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2021	Jul. 31, 2022	Jan. 04, 2023	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Oct. 14, 2021	Jul. 27, 2022	Oct. 13, 2022	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY553705 28	10Hz-44GHz	Oct. 14, 2021	Jul. 27, 2022	Oct. 13, 2022	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 23, 2021	Jul. 27, 2022	Oct. 22, 2022	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-1GHz	Dec. 22, 2021	Jul. 27, 2022	Dec. 21, 2022	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Dec. 24, 2021	Jul. 27, 2022	Dec. 23, 2022	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101115	18GHz~40GHz	Dec. 23, 2021	Jul. 27, 2022	Dec. 22, 2022	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102220	30MHz ~1000MHz	Oct. 14, 2021	Jul. 27, 2022	Oct. 13, 2022	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 05, 2021	Jul. 27, 2022	Jan. 04, 2023	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2082394	1Ghz-18Ghz	Jan. 05, 2021	Jul. 27, 2022	Jan. 04, 2023	Radiation (03CH03-KS)
Amplifier	Keysight	83017A	MY532703 19	1GHz~26.5GHz	Oct. 14, 2021	Jul. 27, 2022	Oct. 13, 2022	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Jul. 27, 2022	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jul. 27, 2022	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jul. 27, 2022	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001 Page Number : 15 of 16
Report Issued Date : Oct. 12, 2022
Report Version : Rev. 01

Report No.: FR1D0812-01G

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Report No.: FR1D0812-01G

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.56 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
of 95% (U = 2UC(y))	

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.0dB
of 95% (U = 2Uc(y))	5.UGB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	5.0dB
of 95% (U = 2Uc(y))	J.VUD

----- THE END -----

 Sporton International Inc. (Kunshan)
 Page Number
 : 16 of 16

 TEL: +86-512-57900158
 Report Issued Date
 : Oct. 12, 2022

 FAX: +86-512-57900958
 Report Version
 : Rev. 01



Appendix A. Radiated Spurious Emission

Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 2	U-NII-3	5.725-5.85	1	802.11a	165	5825	6Mbps	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
2	802.11a	165	11650.00	44.86	54.00	-9.14	V	AVERAGE	Pass	Harmonic

TEL: +86-512-57900158

Sporton International Inc. (Kunshan)

FAX: +86-512-57900958

Page Number

: A1 of A4

2 **Band Edge** Mode U-NII-3_5.725-5.85_802.11a_CH165_5825MHz **ANT** 1 Pol. Horizontal **Fundamental** 130 Level (dBuV/m) 130 Level (dBuV/m) 113.8 113.8 97.5 97.5 81.3 65.0 5G BAND 4 48.8 48.8 32.5 Peak 32.5 16.3 16.3 5825 5850. 5925. , Frequency (MHz) 2200. 7000 Limit Read Ant Cable Preamp Aux APos TPos Frequency (MHz) Freq Level Line Margin Level Factor Loss Factor Factor Remark Limit Read Ant Cable Preamp Aux APos TPos MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB 1 5855.00 55.43 110.90 -55.47 40.55 34.87 11.49 31.48 0.00 deg 304 PEAK Freq Level Line Margin Level Factor Loss Factor Factor 300 5865.63 55.17 107.92 -52.75 40.27 34.88 11.50 31.48 0.00 304 PEAK MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB 5924.00 51.12 69.04 -17.92 36.14 34.93 11.55 31.50 0.00 5946.38 52.50 68.30 -15.80 37.48 34.95 11.57 31.50 0.00 1 5825.00 104.88 122.30 -17.42 90.03 34.85 11.47 31.47 0.00 130 Level (dBuV/m) 113.8 81.3 65.0 48.8 Avg **Blank** 32.5 16.3 1000 2200. 7000 3400. 4600. Frequency (MHz) Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB 1 5825.00 97.26 68.30 28.96 82.41 34.85 11.47 31.47 0.00 300

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958

2 **Band Edge** Mode U-NII-3_5.725-5.85_802.11a_CH165_5825MHz **ANT** 1 Pol. Vertical **Fundamental** 130 Level (dBuV/m) 130 Level (dBuV/m) 113.8 113.8 97.5 97.5 81.3 65.0 48.8 32.5 Peak 32.5 16.3 16.3 5825 5850. 5925. , Frequency (MHz) 2200. 7000 Limit Read Ant Cable Preamp Aux APos TPos Frequency (MHz) Freq Level Line Margin Level Factor Loss Factor Factor Remark Limit Read Ant Cable Preamp Aux APos TPos MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB 1 5854.38 62.27 112.32 -50.05 47.39 34.87 11.49 31.48 0.00 deg 259 PEAK Freq Level Line Margin Level Factor Loss Factor Factor 360 5856.25 62.88 110.55 -47.67 47.99 34.88 11.49 31.48 0.00 259 PEAK MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB 5924.88 51.43 68.39 -16.96 36.45 34.93 11.55 31.50 0.00 259 PEAK 5940.38 53.10 68.30 -15.20 38.10 34.94 11.56 31.50 0.00 1 5825.00 106.25 122.30 -16.05 91.39 34.86 11.48 31.48 0.00 130 Level (dBuV/m) 113.8 81.3 65.0 48.8 Avg **Blank** 32.5 16.3 1000 2200. 7000 3400. 4600. Frequency (MHz) Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB 1 5825.00 99.26 68.30 30.96 84.41 34.85 11.47 31.47 0.00 360 259 AVERAGE

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158 FAX: +86-512-57900958




2 Mode **Harmonic** U-NII-3_5.725-5.85_802.11a_CH165_5825MHz **ANT** 1 Pol. Horizontal Vertical 117 Level (dBuV/m) 117 Level (dBuV/m) 102.4 102.4 87.8 87.8 73.1 73.1 58.5 43.9 43.9 **Peak** 29.3 29.3 Avg 14.6 14.6 0<u></u> 7000 0<u></u> 7000 9200. 15800. 18000 9200. 15800. 18000 Frequency (MHz) Frequency (MHz) Read Ant Cable Preamp Aux APos TPos Limit Read Ant Cable Preamp Aux APos TPos Limit Freq Level Line Margin Level Factor Loss Factor Factor Freq Level Line Margin Level Factor Loss Factor Factor Remark Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB MHz dBuV/m dBuV/m dB dBuV dB/m dB 1 11650.00 54.27 74.00 -19.73 66.43 38.19 16.23 66.58 0.00 1 11650.00 55.95 74.00 -18.05 68.11 38.19 16.23 66.58 0.00 100 126 PEAK 225 PEAK 2 11650.00 43.27 54.00 -10.73 55.42 38.19 16.24 66.58 0.00 2 11650.00 44.86 54.00 -9.14 57.00 38.20 16.24 66.58 0.00

TEL: +86-512-57900158 FAX: +86-512-57900958

Appendix B. Duty Cycle Plots

Band Duty Cycle		T(ms)	1/T(kHz)	VBW Setting
802.11a	98.25	-	-	10Hz

802.11a



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AEUPBHASP001