

---

**FCC ID: 2BEDU-LOVEE**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

GFSK	2.402	1.059	1.28	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.028	1.60	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.138	1.64	2±1	3.00	2.00	<5	0.62843	3.00	YES
$\pi$ /4DQPSK	2.402	1.947	1.57	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.892	1.95	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.982	1.99	2±1	3.00	2.00	<5	0.62843	3.00	YES

**Conclusion:**

For the max result :  $0.62843 \leq \text{FCC Limit } 3.0$  for 1g SAR.