



FEATURES AND BENEFITS

- Quick and easy installation
- Adhesive holds to surface during humidity exposure and hot/cold cycles
- RoHS-compliant
- Patent Number: 9450307
- Can be installed in the following ways:
 - On different non-conductive surfaces and thicknesses
 - On flat or semi-curved surfaces
 - Near metals or the human body

SPECIFICATIONS	
Frequency (MHz)	902-928
Peak Gain (dBi)	-0.1
Average Efficiency (dB)	> -3.6
VSWR (MHz)	< 2.5:1
Impedance (Ω)	50
Polarization	Linear

MECHANICAL SPECIFICATIONS	
Antenna Type	Flexible Planar Inverted F Antenna (FlexPIFA)
Dimensions – mm (inches)	88 x 40 x 6.2 (3.47 x 1.58 x 0.25)
Weight – g (oz.)	11 (0.38)
Color	Clear yellow
Adhesive	3M 100MP
Connector Mating Height (max) – mm	MHF1 (U.FL) 2.5 MHF4L 1.4

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)
Material Substance Compliance	RoHS

CONFIGURATION

PART NUMBER	CABLE LENGTH	CONNECTOR
EFB9020A3S-15MHF1	150 mm	MHF1
EFB9020A3S-15MH4L	150 mm	MHF4L

Note: Specifications are based on the 150mm cable length, standard antenna version with MHF1 / U.FL connector. Varying the cable length or type or connector will cause variations in these antenna specifications.

MECHANICAL DRAWING

Physical Dimensions (in mm) of the EFB9020A with a 150 mm Long Cable




Figure 1: 9-FlexPIFA mechanical drawing of EFB9020A Antenna

FLAT SURFACE ANTENNA MEASUREMENTS

Flat surface measurements were performed with the antenna centered on a 1.5 mm-thick plate of polycarbonate.

VSWR

9-FlexPIFA VSWR - 1.5mm PolyCarbonate




Figure 2: Antenna VSWR measured on a 1.5 mm-thick plate of polycarbonate with a nominal value of 1.56

RETURN LOSS

S11, LOGMAG - 9-FlexPIFA - 1.5mm PolyCarbonate




Figure 3: Antenna Return Loss measured on a 1.5 mm-thick plate of polycarbonate with a nominal value of -16.8dB

ANTENNA CHAMBER TEST SETUP

Antenna measurements such as VSWR and S11 were measured with an Agilent E5071C vector network analyzer. Radiation patterns were measured with a Rohde & Schwarz ZNB8-4PORT vector network analyzer in a Howland Company 3100 chamber equivalent. Phase center is nine inches above the Phi positioner.




Figure 4: Howland Company 3100 Antenna chamber

ANTENNA RADIATION PERFORMANCE

9-FlexPIFA centered on a 1.5 mm-thick plate of polycarbonate




Figure 5: Flat surface setup

EFFICIENCY




Figure 6: Antenna Efficiency measured on a 1.5 mm-thick plate of polycarbonate with a nominal value of -3.4dB across the operating frequency

ANTENNA GAIN





Figure 7: Antenna Gain measured on a 1.5 mm-thick plate of polycarbonate with a nominal value of -0.6dBi across the operating frequency

RADIATION PATTERNS – 2D Plots

2D Plots at 915 MHz



RADIATION PATTERNS – 3D Plots

3D Plots at 915 MHz





Figure 8: Phi polarization, Theta polarization and, and total gain plots – 915 MHz

Rev 5.0 - Initial Production Release



ADDITIONAL ASSISTANCE

Please contact your local Laird Connectivity sales representative or our support team for further assistance:

Support Center <https://www.lairdconnect.com/resources/support>

Phone Americas: +1-800-492-2320
 Europe: +44-1628-858-940
 Hong Kong: +852 2762 4823

Web <https://www.lairdconnect.com/internal-antennas>

Address Laird Connectivity
 50 S. Main Street, Suite 1100
 Akron, OH 44308

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com

© Copyright 2023 Laird Connectivity. All Rights Reserved. Patent pending. Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials or products rests with the end user since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of Sale in effect from time to time, a copy of which will be furnished upon request. Nothing herein provides a license under any Laird Connectivity or any third-party intellectual property right.