




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/12

Job No.:	LP24070228C02-03	Temp:	22.5 (C) / 51 %RH/ 1014
Test Standard:	FCC PART 15B 3M Radiation	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	183.8440	9.08	23.50	32.58	43.50	-10.92	QP	*	
2	235.8164	11.01	19.04	30.05	46.00	-15.95	QP		
3	258.3264	11.25	18.05	29.30	46.00	-16.70	QP		
4	355.4273	14.56	20.23	34.79	46.00	-11.21	QP		
5	426.5210	15.21	18.86	34.07	46.00	-11.93	QP		
6	531.9635	16.86	17.41	34.27	46.00	-11.73	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C -30-1000 RSE\Data :#2





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/12

Job No.:	LP24070228C02-03	Temp:	22.5 (C) / 51 %RH/ 1014
Test Standard:	FCC PART 15B 3M Radiation	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	47.8260	12.56	15.10	27.66	40.00	-12.34	QP		
2	66.0341	9.92	17.24	27.16	40.00	-12.84	QP		
3	71.5805	8.51	19.71	28.22	40.00	-11.78	QP	*	
4	137.4201	6.93	22.26	29.19	43.50	-14.31	QP		
5	213.0150	10.90	18.90	29.80	43.50	-13.70	QP		
6	245.0900	11.18	19.54	30.72	46.00	-15.28	QP		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C -30-1000 RSE\Data :#1



1GHz - 18GHz

Note: The highest waveform in the figure is 2.4GHz Fundamental.




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4995.000	-1.00	43.84	42.84	74.00	-31.16	peak		
2	7120.000	5.72	41.46	47.18	74.00	-26.82	peak		
3	10299.000	8.35	40.81	49.16	74.00	-24.84	peak		
4	5012.000	-0.95	31.73	30.78	54.00	-23.22	AVG		
5	7103.000	5.72	30.09	35.81	54.00	-18.19	AVG		
6	10316.000	8.38	29.90	38.28	54.00	-15.72	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-RSE\Data :#6






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4876.000	-1.01	41.38	40.37	74.00	-33.63	peak		
2	4893.000	-1.00	30.90	29.90	54.00	-24.10	AVG		
3	7392.000	5.60	42.26	47.86	74.00	-26.14	peak		
4	7409.000	5.59	32.46	38.05	54.00	-15.95	AVG	*	
5	10503.000	8.72	41.23	49.95	74.00	-24.05	peak		
6	10503.000	8.72	29.27	37.99	54.00	-16.01	AVG		

Note: Level=Reading+Factor, Over=Level-Limit.
MK.: *Maximum data x: Over limit !: Over margin

File: OB146C-RSE\Data :#5






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2444MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4893.000	-1.00	44.52	43.52	74.00	-30.48	peak		
2	4910.000	-1.01	33.72	32.71	54.00	-21.29	AVG		
3	7069.000	5.74	40.00	45.74	74.00	-28.26	peak		
4	7103.000	5.72	29.71	35.43	54.00	-18.57	AVG		
5	10231.000	8.22	41.06	49.28	74.00	-24.72	peak		
6	10248.000	8.25	29.72	37.97	54.00	-16.03	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-RSE\Data :#4





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.: LP24070228C02-03
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Dongle
Model No.: OB1461C
Test Mode: TX
Remark 1: 2444MHz

Temp: 22.7 (C) / 50 %RH/ 1018
Test Engineer: Kervin
Power Rating: DC 5V
Ant. Polarization: Vertical



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4893.000	-1.00	42.25	41.25	74.00	-32.75	peak		
2	4910.000	-1.01	32.26	31.25	54.00	-22.75	AVG		
3	7086.000	5.73	39.29	45.02	74.00	-28.98	peak		
4	7103.000	5.72	29.24	34.96	54.00	-19.04	AVG		
5	9976.000	7.80	41.11	48.91	74.00	-25.09	peak		
6	9976.000	7.80	28.86	36.66	54.00	-17.34	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-RSE\Data :#3





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.: LP24070228C02-03
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Dongle
Model No.: OB1461C
Test Mode: TX
Remark 1: 2480MHz

Temp: 22.7 (C) / 50 %RH/ 1018
Test Engineer: Kervin
Power Rating: DC 5V
Ant. Polarization: Vertical



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4995.000	-1.00	42.80	41.80	74.00	-32.20	peak		
2	5012.000	-0.95	31.22	30.27	54.00	-23.73	AVG		
3	7052.000	5.75	39.94	45.69	74.00	-28.31	peak		
4	7103.000	5.72	30.04	35.76	54.00	-18.24	AVG		
5	10180.000	8.14	42.27	50.41	74.00	-23.59	peak		
6	10248.000	8.25	29.98	38.23	54.00	-15.77	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-RSE\Data :#2





Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn


Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.: LP24070228C02-03
Test Standard: FCC Class B 3M Radiation Peak(Above 1G)
EUT: Dongle
Model No.: OB1461C
Test Mode: TX
Remark 1: 2480MHz

Temp: 22.7 (C) / 50 %RH/ 1018
Test Engineer: Kervin
Power Rating: DC 5V
Ant. Polarization: **Horizontal**



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	4689.000	-1.02	41.05	40.03	74.00	-33.97	peak		
2	4706.000	-1.02	30.37	29.35	54.00	-24.65	AVG		
3	7052.000	5.75	40.22	45.97	74.00	-28.03	peak		
4	7103.000	5.72	30.00	35.72	54.00	-18.28	AVG		
5	10180.000	8.14	41.23	49.37	74.00	-24.63	peak		
6	10248.000	8.25	30.07	38.32	54.00	-15.68	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-RSE\Data :#1



Appendix B.4: Test Results of Radiated Emissions in Restricted Bands

Low channel




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2390.000	-4.83	40.17	35.34	74.00	-38.66	peak		
2	2390.090	-4.83	29.88	25.05	54.00	-28.95	AVG	*	
3	2400.000	-4.79	39.41	34.62	74.00	-39.38	peak		
4	2400.100	-4.79	29.57	24.78	54.00	-29.22	AVG		

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File: OB146C-BAND\Data :#1






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2403MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2390.000	-4.83	39.98	35.15	74.00	-38.85	peak		
2	2390.090	-4.83	29.96	25.13	54.00	-28.87	AVG		
3	2400.000	-4.79	39.81	35.02	74.00	-38.98	peak		
4	2400.100	-4.79	29.99	25.20	54.00	-28.80	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:Maximum data x:Over limit !:Over margin

File: OB146C-BAND1Data :#2



High channel




Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Horizontal
Test Mode:	TX		
Remark 1:	2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	39.07	34.61	74.00	-39.39	peak		
2	2483.500	-4.46	29.19	24.73	54.00	-29.27	AVG		
3	2485.000	-4.46	39.09	34.63	74.00	-39.37	peak		
4	2485.000	-4.46	29.24	24.78	54.00	-29.22	AVG	*	

Note: Level=Reading+Factor,Over=Level-Limit.
MK.:*:Maximum data x:Over limit !:Over margin

File: OB146C-BANDData :#4






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Radiation Emission

Site: 966 Chamber 1

2024/12/11

Job No.:	LP24070228C02-03	Temp:	22.7 (C) / 50 %RH/ 1018
Test Standard:	FCC Class B 3M Radiation Peak(Above 1G)	Test Engineer:	Kervin
EUT:	Dongle	Power Rating:	DC 5V
Model No.:	OB1461C	Ant. Polarization:	Vertical
Test Mode:	TX		
Remark 1:	2480MHz		



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	41.21	36.75	74.00	-37.25	peak		
2	2483.500	-4.46	29.22	24.76	54.00	-29.24	AVG	*	
3	2485.000	-4.46	38.56	34.10	74.00	-39.90	peak		
4	2485.000	-4.46	29.15	24.69	54.00	-29.31	AVG		

Note: Level=Reading+Factor, Over=Level-Limit.
MK.: *Maximum data x: Over limit !: Over margin

File: OB146C-BAND1Data :#3






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Conduction Emission

Site: Shielded Room 2

Date: 2024/12/3 Time:

Job No.:	LP24070228C02-03	Temp:	23.8(C) / 55 %RH/ 1014
Test Standard:	Conduction(QP)	Test Engineer:	Claire
EUT:	See remark	Power Rating:	AC 120V/60Hz
Model No.:	1) OB1560, 2)OB1461C	Phase:	L1
Test Mode:	Working		
Remark 1:	1) Incase Sculpt Ergonomic Mouse, 2)Dongle		



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	MK.	Remark
1	0.2575	10.76	36.80	47.56	61.51	-13.95	QP		
2	0.2575	10.76	28.04	38.80	51.51	-12.71	AVG	*	
3	0.3930	10.82	32.44	43.26	58.00	-14.74	QP		
4	0.3930	10.82	20.03	30.85	48.00	-17.15	AVG		
5	0.6447	11.00	31.17	42.17	56.00	-13.83	QP		
6	0.6447	11.00	17.51	28.51	46.00	-17.49	AVG		
7	3.5748	11.34	27.15	38.49	56.00	-17.51	QP		
8	3.5748	11.34	12.99	24.33	46.00	-21.67	AVG		
9	7.2073	11.51	31.75	43.26	60.00	-16.74	QP		
10	7.2073	11.51	22.12	33.63	50.00	-16.37	AVG		
11	8.4115	11.51	27.74	39.25	60.00	-20.75	QP		
12	8.4115	11.51	16.22	27.73	50.00	-22.27	AVG		

Note: Level=Reading+Factor,Margin=Level-Limit.
MK.:*Maximum data x:Over limit !:Over margin

File :1) OB1560, 2)OB1461C - RED\Data :#2






Dongguan Lepont Testing Service Co., Ltd.
Room 102, Building 11, No.7 Houjie Science And Technology
Avenue, Houjie, Dongguan, Guangdong, China
Tel.: +86 769 8308 6888 Http://www.lepont.com.cn

Conduction Emission

Site: Shielded Room 2

Date: 2024/12/3 Time:

Job No.:	LP24070228C02-03	Temp:	23.8(C) / 55 %RH/ 1014
Test Standard:	Conduction(QP)	Test Engineer:	Claire
EUT:	See remark	Power Rating:	AC 120V/60Hz
Model No.:	1) OB1560, 2)OB1461C	Phase:	N
Test Mode:	Working		
Remark 1:	1) Incase Sculpt Ergonomic Mouse, 2)Dongle		



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	MK.	Remark
1	0.1663	10.84	42.42	53.26	65.14	-11.88	QP	*	
2	0.1663	10.84	26.85	37.69	55.14	-17.45	AVG		
3	0.2515	10.93	35.58	46.51	61.71	-15.20	QP		
4	0.2515	10.93	27.25	38.18	51.71	-13.53	AVG		
5	0.3964	10.99	30.06	41.05	57.93	-16.88	QP		
6	0.3964	10.99	16.31	27.30	47.93	-20.63	AVG		
7	0.6498	10.96	28.52	39.48	56.00	-16.52	QP		
8	0.6498	10.96	15.31	26.27	46.00	-19.73	AVG		
9	3.0480	10.99	23.27	34.26	56.00	-21.74	QP		
10	3.0480	10.99	13.97	24.96	46.00	-21.04	AVG		
11	10.0721	11.34	29.24	40.58	60.00	-19.42	QP		
12	10.0721	11.34	21.95	33.29	50.00	-16.71	AVG		

Note: Level=Reading+Factor,Margin=Level-Limit.
MK.:*:Maximum data x:Over limit !:Over margin

File :1) OB1560, 2)OB1461C - RED\Data :#1

