



FCC PART 15C TEST REPORT No.I23Z60697-IOT08

for

TCL Communication Ltd.

Tablet PC

8492A

With

FCC ID: 2ACCJB207

Hardware Version: 05

Software Version: KZ12

Issued Date: 2023-06-28

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I23Z60957-IOT08	Rev.0	1st edition	2023-06-28

CONTENTS

1. TEST LABORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	6
1.4. PROJECT DATE	6
1.5. SIGNATURE	6
2. CLIENT INFORMATION.....	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT	8
3.3. INTERNAL IDENTIFICATION OF AE.....	8
4.1. GENERAL DESCRIPTION.....	9
4.2. INTERPRETATION OF THE TEST ENVIRONMENT.....	9
5. REFERENCE DOCUMENTS.....	9
5.1. DOCUMENTS SUPPLIED BY APPLICANT	9
5.2. REFERENCE DOCUMENTS FOR TESTING.....	9
6. TEST RESULTS	10
6.1. SUMMARY OF TEST RESULTS.....	10
6.2. STATEMENTS.....	10
6.3. TEST CONDITIONS	10
7. TEST FACILITIES UTILIZED	11
8. MEASUREMENT UNCERTAINTY	12
8.1. MAXIMUM OUTPUT POWER.....	12
8.2. PEAK POWER SPECTRAL DENSITY	12
8.3. DTS 6-dB SIGNAL BANDWIDTH.....	12
8.4. BAND EDGES COMPLIANCE	12
8.5. TRANSMITTER SPURIOUS EMISSION	12
8.6. AC POWER-LINE CONDUCTED EMISSION	12
ANNEX A: DETAILED TEST RESULTS.....	13
A.1. MEASUREMENT METHOD.....	13
A.2. MAXIMUM OUTPUT POWER.....	14
A.2.1. PEAK OUTPUT POWER-CONDUCTED	14

A.3. PEAK POWER SPECTRAL DENSITY	16
A.4. DTS 6-DB SIGNAL BANDWIDTH	23
A.5. BAND EDGES COMPLIANCE	30
A.6. TRANSMITTER SPURIOUS EMISSION.....	35
A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED	35
A.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED	56
A.7. AC POWER-LINE CONDUCTED EMISSION	69
ANNEX B: EUT PARAMETERS.....	73
ANNEX C: ACCREDITATION CERTIFICATE	73

1. Test Laboratory

1.1.Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

1.2.Testing Location

Location 1:CTTL(Huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China100191

Radiated testing Location:

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
100191, P. R. China


1.3. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.4. Project date

Testing Start Date: 2023-05-26
Testing End Date: 2023-06-28

1.5. Signature



Xie Xiuzhen
(Prepared this test report)



Zheng Wei
(Reviewed this test report)



Pang Shuai
(Approved this test report)

2. Client Information

2.1.Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: +86 755 3661 1621
Fax: +86 755 3661 2000-81722

2.2.Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Telephone: +86 755 3661 1621
Fax: +86 755 3661 2000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Tablet PC
Model name	8492A
FCC ID	2ACCJB207
With WLAN Function	Yes
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	25.54dBm
Power Supply	3.7V

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
UT03a	B4695F5551182EC	05	KZ12
UT24a	B4695F5641182F5	05	KZ12

*EUT ID: is used to identify the test sample in the lab internally.

UT03a is used for Conduction test, UT24a is used for Radiation test.

3.3. Internal Identification of AE

4. AE ID*	Description	SN
AE1	Battery	/
AE2	Charger1	/
AE3	Data Cable	
AE1		
Model	2853B7PL - 2P	
Manufacturer	Gaoyuan	
Capacity(mAh)	6000mAh	
AE2		
Model	CG10A0502000UU	
Manufacturer	JUWEI	
Length of cable	/	
AE3		
Model	JWUB1591-J51R	
Manufacturer	JUWEI	
Length of cable	/	

*AE ID: is used to identify the test sample in the lab internally.

4.1. General Description

The Equipment under Test (EUT) is a model of Tablet PC with integrated antenna and inbuilt battery. It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

4.2. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

5. Reference Documents

5.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

5.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C:	2021
	15.205 Restricted bands of operation;	
	15.209 Radiated emission limits, general requirements;	
ANSI C63.10	15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	2013
	American National Standard of Procedures for Compliance	
	Testing of Unlicensed Wireless Devices	
KDB 558074 D01	Federal Communications Commission Office of Engineering and Technology Laboratory Division	2019
	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON	
	DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	

6. Test Results

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	P
Peak Power Spectral Density	15.247 (e)	/	P
Occupied 6dB Bandwidth	15.247 (a)	/	P
Band Edges Compliance	15.247 (d)	/	P
Transmitter Spurious Emission - Conducted	15.247 (d)	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

6.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	T nom	26°C
Voltage	V nom	3.7V
Humidity	H nom	20-75%

7. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2024-06-05
2	LISN	ENV216	101200	Rohde & Schwarz	1 year	2024-06-29
3	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2024-02-21
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESW44	103144	R&S	1 year	2023-10-25
2	EMI Antenna	VULB 9163	01223	SCHWARZBECK	1 year	2023-07-25
3	EMI Antenna	3115	00167250	ETS-Lindgren	1 year	2023-06-20

※Note: The EMI Antenna with series number of 00167250 did not exceed the CAL.DUE.DATE when used.

8. Measurement Uncertainty

8.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5. Transmitter Spurious Emission

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	4.72dB
$1\text{GHz} \leq f \leq 18\text{GHz}$	4.84dB
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.12dB

8.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB, k=2.

ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

Connect the EUT to the test system as Fig.A.1.1.1 shows.

Set the EUT to the required work mode.

Set the EUT to the required channel.

Set the Vector Signal Analyzer and start measurement.

Record the values. Vector Signal Analyzer




Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements

A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;




Fig.A.1.2.1: Test Setup Diagram for Radiated Measurements

A.2. Maximum Output Power

Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.1

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq$ $[3 \times \text{RBW}]$.
- c) Set span $\geq$ $[3 \times \text{RBW}]$.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

EUT ID: UT03a

A.2.1. Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	21.55	21.98	21.67
802.11g	6	25.05	25.54	24.31

The data rate 1Mbps and 6Mbps are selected as worst condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	24.35	24.71	23.90

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	MCS0	24.45	24.73	24.51

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

The duty cycle of all mode are 100%

Conclusion: Pass

A.3. Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-2013-clause 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to RBW = 3 kHz.
- Set the VBW = 10 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

802.11b/g mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11b	1	Fig.A.3.1	-3.12	P
	6	Fig.A.3.2	-2.43	P
	11	Fig.A.3.3	-3.56	P
802.11g	1	Fig.A.3.4	-7.91	P
	6	Fig.A.3.5	-7.98	P
	11	Fig.A.3.6	-9.42	P

802.11n-HT20 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT20)	1	Fig.A.3.7	-8.93	P
	6	Fig.A.3.8	-6.89	P
	11	Fig.A.3.9	-8.33	P

802.11n-HT40 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT40)	3	Fig.A.3.10	-11.07	P
	6	Fig.A.3.11	-11.71	P
	9	Fig.A.3.12	-11.07	P

Conclusion: Pass

Test graphs as below:




Fig.A.3.1 Power Spectral Density(802.11b,Ch1)




Fig.A.3.2 Power Spectral Density (802.11b, Ch 6)




Fig.A.3.3 Power Spectral Density (802.11b, Ch 11)






Fig.A.3.4 Power Spectral Density (802.11g, Ch 1)




Date: 25.JUN.2023 15:52:57

Fig.A.3.5 Power Spectral Density (802.11g, Ch 6)




Date: 25.JUN.2023 16:01:03

Fig.A.3.6 Power Spectral Density (802.11g, Ch 11)




Date: 25.JUN.2023 16:05:39

Fig.A.3.7 Power Spectral Density (802.11n-HT20, Ch 1)




Date: 25.JUN.2023 16:09:18

Fig.A.3.8 Power Spectral Density (802.11n-HT20, Ch 6)




Date: 25.JUN.2023 16:13:20

Fig.A.3.9 Power Spectral Density (802.11n-HT20, Ch 11)




Date: 25.JUN.2023 16:20:45

Fig.A.3.10 Power Spectral Density (802.11n-HT40, Ch 3)



Date: 25.JUN.2023 16:24:02

Fig.A.3.11 Power Spectral Density (802.11n-HT40, Ch 6)



Date: 25.JUN.2023 16:28:40

Fig.A.3.12 Power Spectral Density (802.11n-HT40, Ch 9)

A.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) = 300 kHz.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

EUT ID: UT03a

Measurement Result:

802.11b/g mode

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11b	1	Fig.A.4.1	8.05	P
	6	Fig.A.4.2	8.03	P
	11	Fig.A.4.3	8.07	P
802.11g	1	Fig.A.4.4	16.10	P
	6	Fig.A.4.5	16.36	P
	11	Fig.A.4.6	15.96	P

802.11n-HT20 mode


Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11n (HT20)	1	Fig.A.4.7	17.36	P
	6	Fig.A.4.8	17.60	P
	11	Fig.A.4.9	16.56	P

802.11n-HT40 mode

Mode	Channel	Occupied 6dB Bandwidth (MHz)		conclusion
802.11n (HT40)	3	Fig.A.4.10	32.51	P
	6	Fig.A.4.11	36.44	P
	9	Fig.A.4.12	33.67	P


Conclusion: Pass

Test graphs as below:




Date: 25.JUN.2023 15:39:06

Fig.A.4.1 Occupied 6dB Bandwidth(802.11b,Ch 1)




Date: 25.JUN.2023 15:41:45

Fig.A.4.2 Occupied 6dB Bandwidth (802.11b, Ch 6)




Date: 25.JUN.2023 15:45:02

Fig.A.4.3 Occupied 6dB Bandwidth (802.11b, Ch 11)




Date: 25.JUN.2023 15:47:32

Fig.A.4.4 Occupied 6dB Bandwidth (802.11g, Ch 1)




Date: 25.JUN.2023 15:51:40

Fig.A.4.5 Occupied 6dB Bandwidth (802.11g, Ch 6)




Date: 25.JUN.2023 15:56:16

Fig.A.4.6 Occupied 6dB Bandwidth (802.11g, Ch 11)




Date: 25.JUN.2023 16:03:53

Fig.A.4.7 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 1)




Date: 25.JUN.2023 16:07:37

Fig.A.4.8 Occupied 6dB Bandwidth (802.11n-HT20, Ch 6)




Date: 25.JUN.2023 16:11:36

Fig.A.4.9 Occupied 6dB Bandwidth (802.11n-HT20, Ch 11)




Date: 25.JUN.2023 16:17:25

Fig.A.4.10 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 3)



Date: 25.JUN.2023 16:22:43

Fig.A.4.11 Occupied 6dB Bandwidth (802.11n-HT40, Ch 6)



Date: 25.JUN.2023 16:27:27

Fig.A.4.12 Occupied 6dB Bandwidth (802.11n-HT40, Ch 9)

A.5. Band Edges Compliance

Method of Measurement: See ANSI C63.10-2013-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 100MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

EUT ID: UT03a

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.A.5.1	P
	11	Fig.A.5.2	P
802.11g	1	Fig.A.5.3	P
	11	Fig.A.5.4	P

802.11n-HT20 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT20)	1	Fig.A.5.5	P
	11	Fig.A.5.6	P

802.11n-HT40 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT40)	3	Fig.A.5.7	P
	9	Fig.A.5.8	P

Conclusion: Pass

Test graphs as below:






Fig.A.5.1 Band Edges (802.11b, Ch 1)




Date: 25.JUN.2023 15:45:46

Fig.A.5.2 Band Edges (802.11b, Ch 11)




Date: 25.JUN.2023 15:48:00

Fig.A.5.3 Band Edges (802.11g, Ch 1)




Date: 25.JUN.2023 15:56:50

Fig.A.5.4 Band Edges (802.11g, Ch 11)




Date: 25.JUN.2023 16:04:21

Fig.A.5.5 Band Edges (802.11n-HT20, Ch 1)




Date: 28.JUN.2023 15:17:42

Fig.A.5.6 Band Edges (802.11n-HT20, Ch 11)



Date: 25.JUN.2023 16:17:58

Fig.A.5.7 Band Edges (802.11n-HT40, Ch 3)


Date: 25.JUN.2023 16:26:57

Fig.A.5.8 Band Edges (802.11n-HT40, Ch 9)

A.6. Transmitter Spurious Emission

A.6.1 Transmitter Spurious Emission – Conducted

Method of Measurement: See ANSI C63.10-2013-clause 11.11

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency
 - b) Set the span to ≥ 1.5 times the DTS bandwidth
 - c) Set the RBW= 100 kHz
 - d) Set the VBW= 300 kHz
 - e) Detector = Peak
 - f) Sweep time = auto couple
 - g) Trace mode = max hold
 - h) Allow trace to fully stabilize
 - i) Use the peak marker function to determine the maximum PSD level
- Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
 - b) Set the RBW = 100 kHz.
 - c) Set the VBW = 300 kHz.
 - d) Detector = peak.
 - e) Sweep time = auto couple.
 - f) Trace mode = max hold.
 - g) Allow trace to fully stabilize.
 - h) Use the peak marker function to determine the maximum amplitude level.
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

EUT ID: UT03a

Measurement Results:

802.11b mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412 GHz	Fig.A.6.1.1	P
		30 MHz ~ 1 GHz	Fig.A.6.1.2	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.3	P
	6	2.437 GHz	Fig.A.6.1.4	P
		30 MHz ~ 1 GHz	Fig.A.6.1.5	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.6	P
	11	2.462 GHz	Fig.A.6.1.7	P
		30 MHz ~ 1 GHz	Fig.A.6.1.8	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.9	P

802.11g mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11g	1	2.412 GHz	Fig.A.6.1.10	P
		30 MHz ~ 1 GHz	Fig.A.6.1.11	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.12	P
	6	2.437 GHz	Fig.A.6.1.13	P
		30 MHz ~ 1 GHz	Fig.A.6.1.14	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.15	P
	11	2.462 GHz	Fig.A.6.1.16	P
		30 MHz ~ 1 GHz	Fig.A.6.1.17	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.18	P

802.11n-HT20 mode


MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	1	2.412 GHz	Fig.A.6.1.19	P
		30 MHz ~ 1 GHz	Fig.A.6.1.20	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.21	P
	6	2.437 GHz	Fig.A.6.1.22	P
		30 MHz ~ 1 GHz	Fig.A.6.1.23	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.24	P
	11	2.462 GHz	Fig.A.6.1.25	P
		30 MHz ~ 1 GHz	Fig.A.6.1.26	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.27	P

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	3	2.422 GHz	Fig.A.6.1.28	P
		30 MHz ~ 1 GHz	Fig.A.6.1.29	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.30	P
	6	2.437 GHz	Fig.A.6.1.31	P
		30 MHz ~ 1 GHz	Fig.A.6.1.32	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.33	P
	9	2.452 GHz	Fig.A.6.1.34	P
		30 MHz ~ 1 GHz	Fig.A.6.1.35	P
		1 GHz ~ 26.5 GHz	Fig.A.6.1.36	P


Conclusion: Pass

Test graphs as below:




Date: 25.JUN.2023 15:40:12

Fig.A.6.1.1 Transmitter Spurious Emission - Conducted (802.11b, Ch1, Center Frequency)




Date: 25.JUN.2023 15:40:36

Fig.A.6.1.2 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 30 MHz-1 GHz)




Date: 25.JUN.2023 15:41:00

Fig.A.6.1.3 Transmitter Spurious Emission - Conducted (802.11b, Ch1, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 15:43:42

Fig.A.6.1.4 Transmitter Spurious Emission - Conducted (802.11b, Ch6, Center Frequency)




Date: 25.JUN.2023 15:44:06

Fig.A.6.1.5 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 30 MHz-1 GHz)




Date: 25.JUN.2023 15:44:30

Fig.A.6.1.6 Transmitter Spurious Emission - Conducted (802.11b, Ch6, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 15:46:16

Fig.A.6.1.7 Transmitter Spurious Emission - Conducted (802.11b, Ch11, Center Frequency)




Date: 25.JUN.2023 15:46:40

Fig.A.6.1.8 Transmitter Spurious Emission - Conducted (802.11b, Ch11, 30 MHz-1 GHz)




Date: 25.JUN.2023 15:47:04

Fig.A.6.1.9 Transmitter Spurious Emission - Conducted (802.11b, Ch11, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 15:50:05

Fig.A.6.1.10 Transmitter Spurious Emission - Conducted (802.11g, Ch1, Center Frequency)




Date: 25.JUN.2023 15:50:29

Fig.A.6.1.11 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 30 MHz-1 GHz)




Date: 25.JUN.2023 15:50:53

Fig.A.6.1.12 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 15:53:22

Fig.A.6.1.13 Transmitter Spurious Emission - Conducted (802.11g, Ch6, Center Frequency)




Date: 25.JUN.2023 15:53:46

Fig.A.6.1.14 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 30 MHz-1 GHz)




Date: 25.JUN.2023 15:54:10

Fig.A.6.1.15 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 16:01:35

Fig.A.6.1.16 Transmitter Spurious Emission - Conducted (802.11g, Ch11, Center Frequency)




Date: 25.JUN.2023 16:02:00

Fig.A.6.1.17 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 30 MHz-1 GHz)




Date: 25.JUN.2023 16:02:23

Fig.A.6.1.18 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 16:06:03

Fig.A.6.1.19 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Date: 25.JUN.2023 16:06:28

Fig.A.6.1.20 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-1 GHz)




Date: 25.JUN.2023 16:06:51

Fig.A.6.1.21 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 16:09:44

Fig.A.6.1.22 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Date: 25.JUN.2023 16:10:08

Fig.A.6.1.23 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-1 GHz)




Date: 25.JUN.2023 16:10:32

Fig.A.6.1.24 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 16:14:58

Fig.A.6.1.25 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Date: 25.JUN.2023 16:15:22

Fig.A.6.1.26 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-1 GHz)




Date: 25.JUN.2023 16:15:46

Fig.A.6.1.27 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 1 GHz-26.5 GHz)




Date: 25.JUN.2023 16:21:11

Fig.A.6.1.28 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Date: 25.JUN.2023 16:21:35

Fig.A.6.1.29 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-1 GHz)




Date: 25.JUN.2023 16:21:59

Fig.A.6.1.30 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 1 GHz-26.5 GHz)




Date: 28.JUN.2023 15:21:55

Fig.A.6.1.31 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Date: 28.JUN.2023 15:22:19

Fig.A.6.1.32 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-1 GHz)




Date: 28.JUN.2023 15:22:42

Fig.A.6.1.33 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 1 GHz-26.5 GHz)




Date: 28.JUN.2023 15:23:14

Fig.A.6.1.34 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)



Date: 28.JUN.2023 15:23:39

Fig.A.6.1.35 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-1 GHz)



Date: 28.JUN.2023 15:24:02

Fig.A.6.1.36 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 1 GHz-26.5 GHz)s

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

EUT ID: UT24a

Measurement results for Set.1:

802.11b mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.31GHz~2.43GHz---L	Fig.A.6.2.1	P
	11	2.45GHz~2.50GHz---H	Fig.A.6.2.2	P

802.11g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	1	2.31GHz~2.43GHz---L	Fig.A.6.2.3	P
	11	2.45GHz~2.50GHz---H	Fig.A.6.2.4	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	1	2.31GHz~2.43GHz---L	Fig.A.6.2.5	P
	11	2.45GHz~2.50GHz---H	Fig.A.6.2.6	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	3	2.31GHz~2.43GHz---L	Fig.A.6.2.7	P
	9	2.45GHz~2.50GHz---H	Fig.A.6.2.8	P

Conclusion: Pass

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea}+A_{Rpl}= P_{Mea}+Cable\ Loss+Antenna\ Factor$

Peak
802.11b

Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17295.500	52.03	-29.50	42.90	38.63	74.00	21.97	V
13614.500	49.44	-31.30	40.90	39.84	74.00	24.56	H
4824.000	48.75	-37.70	33.00	53.45	74.00	25.25	H
12870.000	47.25	-31.90	39.90	39.25	74.00	26.75	H
9749.000	46.30	-34.50	37.80	43.00	74.00	27.70	V
2363.400	56.35	-19.60	28.20	47.75	74.00	17.65	V

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17396.000	51.87	-29.50	43.80	37.57	74.00	22.13	H
14100.000	49.39	-30.20	41.70	37.89	74.00	24.61	V
4873.500	48.77	-37.50	33.40	52.87	74.00	25.23	V
12669.500	47.76	-31.80	39.40	40.16	74.00	26.24	V
9005.000	46.36	-34.70	37.70	43.36	74.00	27.64	V
7422.500	45.20	-35.10	36.60	43.70	74.00	28.80	V

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17367.500	51.28	-28.60	43.40	36.48	74.00	22.72	V
4923.500	50.38	-37.60	33.30	54.68	74.00	23.62	V
13715.000	49.08	-31.00	41.10	38.98	74.00	24.92	H
12914.500	47.87	-31.50	40.00	39.37	74.00	26.13	V
9893.000	45.74	-33.90	37.90	41.74	74.00	28.26	V
2498.200	56.91	-19.70	28.20	48.41	74.00	17.09	H

802.11g

Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17448.500	52.34	-28.50	44.20	36.64	74.00	21.66	H
14083.000	48.81	-30.20	41.70	37.31	74.00	25.19	V
12778.500	47.37	-31.50	39.80	39.07	74.00	26.63	V
7906.500	45.52	-35.20	36.70	44.02	74.00	28.48	V
9430.000	45.34	-33.60	37.90	41.04	74.00	28.66	H
2389.000	68.19	-19.80	28.20	59.79	74.00	5.81	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17480.500	51.55	-29.20	44.50	36.15	74.00	22.45	V
14078.500	49.75	-30.20	41.70	38.25	74.00	24.25	H
12673.500	47.04	-31.90	39.50	39.44	74.00	26.96	V
9033.000	46.52	-34.30	37.80	43.02	74.00	27.48	H
7228.500	45.40	-35.60	36.40	44.60	74.00	28.60	V
4875.000	41.00	-37.50	33.40	45.10	74.00	33.00	V

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
16863.500	51.83	-29.60	40.00	41.43	74.00	22.17	V
14693.000	49.71	-30.00	41.50	38.21	74.00	24.29	V
12769.000	47.25	-31.80	39.60	39.35	74.00	26.75	H
9648.500	46.30	-34.30	37.60	43.00	74.00	27.70	V
7602.500	45.47	-35.60	36.30	44.77	74.00	28.53	H
2485.100	62.44	-19.70	28.20	53.94	74.00	11.56	H

802.11n-HT20

Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17907.000	51.61	-29.40	46.00	35.01	74.00	22.39	V
14086.500	49.25	-30.20	41.70	37.75	74.00	24.75	V
12307.500	47.64	-32.10	39.00	40.74	74.00	26.36	H
9635.000	45.90	-34.30	37.60	42.60	74.00	28.10	V
7311.000	45.78	-35.40	36.60	44.58	74.00	28.22	H
2388.600	70.19	-19.80	28.20	61.79	74.00	3.81	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17392.000	51.87	-29.50	43.80	37.57	74.00	22.13	V
14200.500	48.92	-30.20	41.70	37.42	74.00	25.08	V
12679.000	48.04	-31.90	39.50	40.44	74.00	25.96	H
7544.000	45.39	-35.50	36.30	44.59	74.00	28.61	H
9007.500	45.38	-34.70	37.70	42.38	74.00	28.62	V
4874.500	41.65	-37.50	33.40	45.75	74.00	32.35	V

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17438.000	51.68	-28.50	44.20	35.98	74.00	22.32	H
13726.500	49.20	-31.00	41.10	39.10	74.00	24.80	H
12764.000	47.65	-31.80	39.60	39.75	74.00	26.35	V
8578.500	45.92	-35.00	37.50	43.42	74.00	28.08	V
7222.500	45.16	-35.40	36.20	44.36	74.00	28.84	V
2485.300	66.85	-19.70	28.20	58.35	74.00	7.15	H

802.11n-HT40

Ch3

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17571.000	51.80	-29.20	44.90	36.10	74.00	22.20	V
14101.500	49.57	-30.20	41.70	38.07	74.00	24.43	H
11802.500	47.76	-32.00	39.20	40.56	74.00	26.24	V
9510.000	45.63	-33.80	37.60	41.83	74.00	28.37	V
7321.500	44.99	-35.40	36.60	43.79	74.00	29.01	V
2389.400	68.33	-19.80	28.20	59.93	74.00	5.67	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17810.500	51.36	-29.40	46.00	34.76	74.00	22.64	H
14169.000	49.61	-30.20	41.70	38.11	74.00	24.39	V
12270.000	47.39	-32.50	39.00	40.89	74.00	26.61	H
8727.000	45.74	-34.80	37.90	42.64	74.00	28.26	H
7474.500	45.04	-35.50	36.50	44.04	74.00	28.96	H
4960.000	41.23	-37.40	33.60	45.03	74.00	32.77	V

Ch9

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17460.000	51.94	-28.50	44.20	36.24	74.00	22.06	H
13648.000	48.82	-31.30	40.90	39.22	74.00	25.18	V
12763.500	47.18	-31.80	39.60	39.28	74.00	26.82	H
7317.500	45.60	-35.40	36.60	44.40	74.00	28.40	V
9527.000	45.60	-33.80	37.60	41.80	74.00	28.40	V
2485.100	69.97	-19.70	28.20	61.47	74.00	4.03	H

Average
802.11b
Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
4824.000	46.61	-37.70	33.00	51.31	54.00	7.39	H
17264.500	41.74	-29.30	42.40	28.64	54.00	12.26	H
13713.000	39.71	-31.00	41.10	29.61	54.00	14.29	H
12771.000	37.79	-31.80	39.60	29.89	54.00	16.21	H
7221.000	36.38	-35.40	36.20	35.58	54.00	17.62	H
2388.100	45.31	-19.80	28.20	36.91	54.00	8.69	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
4874.000	46.07	-37.50	33.40	50.17	54.00	7.93	V
17350.000	41.99	-28.60	43.40	27.19	54.00	12.01	H
13724.500	39.55	-31.00	41.10	29.45	54.00	14.45	V
12779.500	37.49	-31.50	39.80	29.19	54.00	16.51	H
7319.500	36.05	-35.40	36.60	34.85	54.00	17.95	V
9226.500	35.86	-34.30	37.60	32.56	54.00	18.14	V

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
4924.000	47.78	-37.60	33.30	52.08	54.00	6.22	V
17438.000	41.92	-28.50	44.20	26.22	54.00	12.08	H
13741.000	39.65	-31.00	41.10	29.55	54.00	14.35	V
12779.500	38.11	-31.50	39.80	29.81	54.00	15.89	V
9418.000	36.36	-33.60	37.90	32.06	54.00	17.64	V
2487.400	45.48	-19.70	28.20	36.98	54.00	8.52	H

802.11g
Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17541.500	41.93	-29.20	44.90	26.23	54.00	12.07	V
14158.000	39.44	-30.80	41.70	28.54	54.00	14.56	V
12761.500	38.11	-31.80	39.60	30.21	54.00	15.89	V
9733.500	36.07	-34.50	37.80	32.77	54.00	17.93	V
7543.500	35.72	-35.50	36.30	34.92	54.00	18.28	V
2389.800	53.14	-19.80	28.20	44.74	54.00	0.86	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17528.500	41.98	-29.20	44.90	26.28	54.00	12.02	H
13745.000	40.20	-31.00	41.10	30.10	54.00	13.80	H
12782.500	37.94	-31.50	39.80	29.64	54.00	16.06	V
9328.500	35.94	-34.10	37.80	32.24	54.00	18.06	V
7224.000	35.88	-35.40	36.20	35.08	54.00	18.12	V
4873.500	32.94	-37.50	33.40	37.04	54.00	21.06	V

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17572.500	42.90	-29.20	44.90	27.20	54.00	11.10	V
14115.500	39.67	-30.80	41.70	28.77	54.00	14.33	H
11303.500	37.73	-32.80	38.70	31.83	54.00	16.27	V
7533.000	36.37	-35.50	36.30	35.57	54.00	17.63	H
8719.000	36.36	-34.80	37.90	33.26	54.00	17.64	V
2485.000	48.52	-19.70	28.20	40.02	54.00	5.48	H

802.11n-HT20
Ch1

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17252.500	41.71	-29.30	42.40	28.61	54.00	12.29	H
14112.500	39.79	-30.80	41.70	28.89	54.00	14.21	V
12877.500	37.67	-31.50	40.00	29.17	54.00	16.33	H
9498.500	36.31	-34.60	37.70	33.21	54.00	17.69	H
7537.500	36.18	-35.50	36.30	35.38	54.00	17.82	H
2390.000	52.79	-19.80	28.20	44.39	54.00	1.21	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17446.000	42.02	-28.50	44.20	26.32	54.00	11.98	V
13693.500	39.81	-31.00	41.00	29.81	54.00	14.19	V
12768.000	37.93	-31.80	39.60	30.03	54.00	16.07	V
9116.500	36.11	-34.30	37.70	32.71	54.00	17.89	H
7550.000	35.92	-35.50	36.30	35.12	54.00	18.08	H
4878.000	32.79	-37.50	33.40	36.89	54.00	21.21	H

Ch11

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17872.000	42.09	-29.40	46.00	25.49	54.00	11.91	H
13681.500	39.59	-31.00	41.00	29.59	54.00	14.41	H
12762.500	37.70	-31.80	39.60	29.80	54.00	16.30	V
9396.000	36.01	-34.10	37.90	32.21	54.00	17.99	V
7313.000	35.71	-35.40	36.60	34.51	54.00	18.29	V
2485.000	48.77	-19.70	28.20	40.27	54.00	5.23	H

802.11n-HT40
Ch3

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17657.500	42.07	-29.50	45.40	26.17	54.00	11.93	H
14099.500	39.60	-30.20	41.70	28.10	54.00	14.40	H
12771.000	38.47	-31.80	39.60	30.57	54.00	15.53	V
9617.500	36.06	-34.30	37.60	32.76	54.00	17.94	H
7318.500	35.57	-35.40	36.60	34.37	54.00	18.43	V
2389.600	51.74	-19.80	28.20	43.34	54.00	2.26	H

Ch6

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17448.000	42.28	-28.50	44.20	26.58	54.00	11.72	V
13785.000	39.60	-30.90	41.20	29.30	54.00	14.40	V
12995.500	37.73	-31.90	40.10	29.53	54.00	16.27	V
9411.500	36.02	-33.60	37.90	31.72	54.00	17.98	V
7330.000	35.50	-35.90	36.60	34.80	54.00	18.50	V
4875.000	31.70	-37.50	33.40	35.80	54.00	22.30	H

Ch9

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17230.500	42.25	-29.30	42.40	29.15	54.00	11.75	H
13712.500	39.65	-31.00	41.00	29.65	54.00	14.35	V
12197.500	37.87	-32.20	38.90	31.27	54.00	16.13	V
8714.500	36.52	-34.80	37.90	33.42	54.00	17.48	V
7330.000	36.10	-35.90	36.60	35.40	54.00	17.90	H
2485.200	50.45	-19.70	28.20	41.95	54.00	3.55	H

Test graphs as below:




Fig.A.6.1.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.31 GHz – 2.43GHz




Fig.A.6.1.2 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.1.3 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.31 GHz - 2.43GHz




Fig.A.6.1.4 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.1.5 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.31 GHz - 2.43GHz




Fig.A.6.1.6 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.1.7 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.31 GHz - 2.43GHz




Fig.A.6.1.8 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz

A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:
WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:

Measurement results for Set.1:

Result for Traffic:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.418000	36.4	2000.0	9.000	On	N	19.7	21.1	57.5	
0.502000	41.8	2000.0	9.000	On	N	19.7	14.2	56.0	
1.166000	31.2	2000.0	9.000	On	N	19.6	24.8	56.0	
1.302000	32.1	2000.0	9.000	On	N	19.6	23.9	56.0	
3.498000	30.3	2000.0	9.000	On	N	19.6	25.7	56.0	
4.486000	32.5	2000.0	9.000	On	N	19.6	23.5	56.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.354000	25.3	2000.0	9.000	On	L1	19.7	23.5	48.9	
0.494000	30.8	2000.0	9.000	On	L1	19.7	15.3	46.1	
1.062000	25.3	2000.0	9.000	On	L1	19.7	20.7	46.0	
1.294000	27.2	2000.0	9.000	On	L1	19.7	18.8	46.0	
3.130000	26.8	2000.0	9.000	On	L1	19.6	19.2	46.0	
4.838000	23.1	2000.0	9.000	On	N	19.6	22.9	46.0	

Measurement results for Set.1:

Result for Idle:




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.422000	37.0	2000.0	9.000	On	N	19.7	20.4	57.4	
0.494000	42.7	2000.0	9.000	On	N	19.7	13.4	56.1	
1.074000	33.5	2000.0	9.000	On	N	19.6	22.5	56.0	
1.478000	32.9	2000.0	9.000	On	N	19.6	23.1	56.0	
3.050000	30.7	2000.0	9.000	On	N	19.6	25.3	56.0	
4.890000	32.5	2000.0	9.000	On	N	19.6	23.5	56.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.314000	23.8	2000.0	9.000	On	N	19.7	26.1	49.9	
0.494000	30.9	2000.0	9.000	On	L1	19.7	15.2	46.1	
0.882000	26.0	2000.0	9.000	On	L1	19.7	20.0	46.0	
1.418000	27.3	2000.0	9.000	On	L1	19.7	18.7	46.0	
3.002000	26.5	2000.0	9.000	On	L1	19.6	19.5	46.0	
4.682000	23.5	2000.0	9.000	On	N	19.6	22.5	46.0	

ANNEX B: EUT parameters

Disclaimer: The antenna gain and worse case provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX C: Accreditation Certificate

United States Department of Commerce National Institute of Standards and Technology   Certificate of Accreditation to ISO/IEC 17025:2017	
NVLAP LAB CODE: 600118-0	
Telecommunication Technology Labs, CAICT Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
Electromagnetic Compatibility & Telecommunications	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).</i>	
2022-10-01 through 2023-09-30 Effective Dates	 For the National Voluntary Laboratory Accreditation Program

END OF REPORT